

BSI-DSZ-CC-0572-2008

for

Infineon Smart Card IC (Security Controller)

SLE66CL187PEM / m2984-a11,

SLE66CL187PE / m2985-a11,

SLE66CL187PES / m2986-a11,

SLE66CL88PEM / m2995-a11,

SLE66CL88PE / m2994-a11,

SLE66CL87PEM / m2992-a11,

SLE66CL87PES / m2993-a11,

SLE66CL87PE / m2991-a11 and

SLE66CL48PE / m2983-a11

all with specific IC dedicated software

from

Infineon Technologies AG

BSI - Bundesamt für Sicherheit in der Informationstechnik, Postfach 20 03 63, D-53133 Bonn
Phone +49 (0)228 99 9582-0, Fax +49 (0)228 9582-5477, Infoline +49 (0)228 99 9582-111



Deutsches



IT-Sicherheitszertifikat

erteilt vom

Bundesamt für Sicherheit in der Informationstechnik

BSI-DSZ-CC-0572-2008

Infineon Smart Card IC (Security Controller)

**SLE66CL187PEM / m2984-a11, SLE66CL187PE / m2985-a11,
SLE66CL187PES / m2986-a11, SLE66CL88PEM / m2995-a11,
SLE66CL88PE / m2994-a11, SLE66CL87PEM / m2992-a11,
SLE66CL87PES / m2993-a11, SLE66CL87PE / m2991-a11 and
SLE66CL48PE / m2983-a11 all with specific IC dedicated software**

from Infineon Technologies AG
PP Conformance: Smartcard IC Platform Protection Profile, Version 1.0,
July 2001, Eurosmart, BSI-PP-0002-2001
Functionality: PP conformant
Common Criteria Teil 2 extended
Assurance: Common Criteria Part 3 conformant
EAL 5 augmented by
ALC_DVS.2, AVA_MSU.3 and AVA_VLA.4



Common Criteria
Recognition
Arrangement
for components up to
EAL 4



The IT product identified in this certificate has been evaluated at an accredited and licensed / approved evaluation facility using the Common Methodology for IT Security Evaluation, Version 2.3 extended by advice of the Certification Body for components beyond EAL 4 and guidance specific for the technology of the product for conformance to the Common Criteria for IT Security Evaluation (CC), Version 2.3 (ISO/IEC 15408:2005).

This certificate applies only to the specific version and release of the product in its evaluated configuration and in conjunction with the complete Certification Report.

The evaluation has been conducted in accordance with the provisions of the certification scheme of the German Federal Office for Information Security (BSI) and the conclusions of the evaluation facility in the evaluation technical report are consistent with the evidence adduced.

This certificate is not an endorsement of the IT product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

Bonn, 25 November 2008

For the Federal Office for Information Security



SOGIS - MRA

Bernd Kowalski
Head of Department

L.S.

This page is intentionally left blank.

Preliminary Remarks

Under the BSIG¹ Act, the Federal Office for Information Security (BSI) has the task of issuing certificates for information technology products.

Certification of a product is carried out on the instigation of the vendor or a distributor, hereinafter called the sponsor.

A part of the procedure is the technical examination (evaluation) of the product according to the security criteria published by the BSI or generally recognised security criteria.

The evaluation is normally carried out by an evaluation facility recognised by the BSI or by BSI itself.

The result of the certification procedure is the present Certification Report. This report contains among others the certificate (summarised assessment) and the detailed Certification Results.

The Certification Results contain the technical description of the security functionality of the certified product, the details of the evaluation (strength and weaknesses) and instructions for the user.

¹ Act setting up the Federal Office for Information Security (BSI-Errichtungsgesetz, BSIG) of 17 December 1990, Bundesgesetzblatt I p. 2834

Contents

- A Certification.....7
 - 1 Specifications of the Certification Procedure.....7
 - 2 Recognition Agreements.....7
 - 2.1 European Recognition of ITSEC/CC - Certificates.....8
 - 2.2 International Recognition of CC - Certificates.....8
 - 3 Performance of Evaluation and Certification.....8
 - 4 Validity of the certification result.....9
 - 5 Publication.....9
- B Certification Results.....11
 - 1 Executive Summary.....12
 - 2 Identification of the TOE.....14
 - 3 Security Policy.....16
 - 4 Assumptions and Clarification of Scope.....16
 - 5 Architectural Information.....16
 - 6 Documentation.....17
 - 7 IT Product Testing.....17
 - 8 Evaluated Configuration.....18
 - 9 Results of the Evaluation.....19
 - 9.1 CC specific results.....19
 - 9.2 Results of cryptographic assessment.....20
 - 10 Obligations and notes for the usage of the TOE.....20
 - 11 Security Target.....20
 - 12 Definitions.....21
 - 12.1 Acronyms.....21
 - 12.2 Glossary.....22
 - 13 Bibliography.....24
- C Excerpts from the Criteria.....27
- D Annexes.....35

A Certification

1 Specifications of the Certification Procedure

The certification body conducts the procedure according to the criteria laid down in the following:

- BSIG²
- BSI Certification Ordinance³
- BSI Schedule of Costs⁴
- Special decrees issued by the Bundesministerium des Innern (Federal Ministry of the Interior)
- DIN EN 45011 standard
- BSI certification: Procedural Description (BSI 7125) [3]
- Common Criteria for IT Security Evaluation (CC), Version 2.3 (ISO/IEC 15408:2005)⁵
- Common Methodology for IT Security Evaluation, Version 2.3
- BSI certification: Application Notes and Interpretation of the Scheme (AIS)
- Advice from the Certification Body on methodology for assurance components above EAL4 (AIS 34)

2 Recognition Agreements

In order to avoid multiple certification of the same product in different countries a mutual recognition of IT security certificates - as far as such certificates are based on ITSEC or CC - under certain conditions was agreed.

² Act setting up the Federal Office for Information Security (BSI-Errichtungsgesetz, BSIG) of 17 December 1990, Bundesgesetzblatt I p. 2834

³ Ordinance on the Procedure for Issuance of a Certificate by the Federal Office for Information Security (BSI-Zertifizierungsverordnung, BSIZertV) of 07 July 1992, Bundesgesetzblatt I p. 1230

⁴ Schedule of Cost for Official Procedures of the Bundesamt für Sicherheit in der Informationstechnik (BSI-Kostenverordnung, BSI-KostV) of 03 March 2005, Bundesgesetzblatt I p. 519

⁵ Proclamation of the Bundesministerium des Innern of 10 May 2006 in the Bundesanzeiger dated 19 May 2006, p. 3730

2.1 European Recognition of ITSEC/CC - Certificates

The SOGIS-Mutual Recognition Agreement (MRA) for certificates based on ITSEC became effective on 3 March 1998.

This agreement was signed by the national bodies of Finland, France, Germany, Greece, Italy, The Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom. This agreement on the mutual recognition of IT security certificates was extended to include certificates based on the CC for all Evaluation Assurance Levels (EAL 1 – EAL 7). The German Federal Office for Information Security (BSI) recognises certificates issued by the national certification bodies of France and the United Kingdom within the terms of this agreement.

The SOGIS-MRA logo printed on the certificate indicates that it is recognised under the terms of this agreement.

2.2 International Recognition of CC - Certificates

An arrangement (Common Criteria Recognition Arrangement) on the mutual recognition of certificates based on the CC Evaluation Assurance Levels up to and including EAL 4 has been signed in May 2000 (CCRA). It includes also the recognition of Protection Profiles based on the CC.

As of February 2007 the arrangement has been signed by the national bodies of: Australia, Austria, Canada, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, India, Israel, Italy, Japan, Republic of Korea, The Netherlands, New Zealand, Norway, Republic of Singapore, Spain, Sweden, Turkey, United Kingdom, United States of America. The current list of signatory nations resp. approved certification schemes can be seen on the web site: <http://www.commoncriteriaportal.org>

The Common Criteria Recognition Arrangement logo printed on the certificate indicates that this certification is recognised under the terms of this agreement.

This evaluation contains the components ALC_DVS.2, AVA_MSU.3, and AVA_VLA.4 that are not mutually recognised in accordance with the provisions of the CCRA. For mutual recognition the EAL4 components of these assurance families are relevant.

3 Performance of Evaluation and Certification

The certification body monitors each individual evaluation to ensure a uniform procedure, a uniform interpretation of the criteria and uniform ratings.

The product Infineon Smart Card IC (Security Controller) SLE66CL187PEM / m2984-a11, SLE66CL187PE / m2985-a11, SLE66CL187PES / m2986-a11, SLE66CL88PEM / m2995-a11, SLE66CL88PE / m2994-a11, SLE66CL87PEM / m2992-a11, SLE66CL87PES / m2993-a11, SLE66CL87PE / m2991-a11 and SLE66CL48PE / m2983-a11 all with specific IC dedicated software have undergone the certification procedure at BSI. This is a re-certification based on BSI-DSZ-CC-0538-2008. Specific results from the evaluation process BSI-DSZ-CC-0538-2008 were re-used.

The evaluation of the product Infineon Smart Card IC (Security Controller) SLE66CL187PEM / m2984-a11, SLE66CL187PE / m2985-a11, SLE66CL187PES / m2986-a11, SLE66CL88PEM / m2995-a11, SLE66CL88PE / m2994-a11, SLE66CL87PEM / m2992-a11, SLE66CL87PES / m2993-a11, SLE66CL87PE / m2991-a11 and SLE66CL48PE / m2983-a11 all with specific IC dedicated software was

conducted by TÜV Informationstechnik GmbH. The evaluation was completed on 18 November 2008. The TÜV Informationstechnik GmbH is an evaluation facility (ITSEF)⁶ recognised by the certification body of BSI.

For this certification procedure the sponsor and applicant is: Infineon Technologies AG

The product was developed by: Infineon Technologies AG

The certification is concluded with the comparability check and the production of this Certification Report. This work was completed by the BSI.

4 Validity of the certification result

This Certification Report only applies to the version of the product as indicated. The confirmed assurance package is only valid on the condition that

- all stipulations regarding generation, configuration and operation, as given in the following report, are observed,
- the product is operated in the environment described, where specified in the following report and in the Security Target.

For the meaning of the assurance levels and the confirmed strength of functions, please refer to the excerpts from the criteria at the end of the Certification Report.

The Certificate issued confirms the assurance of the product claimed in the Security Target at the date of certification. As attack methods may evolve over time, the resistance of the certified version of the product against new attack methods can be re-assessed if required and the sponsor applies for the certified product being monitored within the assurance continuity program of the BSI Certification Scheme. It is recommended to perform a re-assessment on a regular basis.

In case of changes to the certified version of the product, the validity can be extended to the new versions and releases, provided the sponsor applies for assurance continuity (i.e. re-certification or maintenance) of the modified product, in accordance with the procedural requirements, and the evaluation does not reveal any security deficiencies.

5 Publication

The product Infineon Smart Card IC (Security Controller) SLE66CL187PEM / m2984-a11, SLE66CL187PE / m2985-a11, SLE66CL187PES / m2986-a11, SLE66CL88PEM / m2995-a11, SLE66CL88PE / m2994-a11, SLE66CL87PEM / m2992-a11, SLE66CL87PES / m2993-a11, SLE66CL87PE / m2991-a11 and SLE66CL48PE / m2983-a11 all with specific IC dedicated software has been included in the BSI list of the certified products, which is published regularly (see also Internet: <http://www.bsi.bund.de>) and [5]. Further information can be obtained from BSI-Infoline +49 228 9582-111.

Further copies of this Certification Report can be requested from the developer⁷ of the product. The Certification Report may also be obtained in electronic form at the internet address stated above.

⁶ Information Technology Security Evaluation Facility

⁷ Infineon Technologies AG
CCS M PS
Am Campeon 1-12
85579 Neubiberg

This page is intentionally left blank.

B Certification Results

The following results represent a summary of

- the Security Target of the sponsor for the Target of Evaluation,
- the relevant evaluation results from the evaluation facility, and
- complementary notes and stipulations of the certification body.

1 Executive Summary

The Target of Evaluation (TOE) is Infineon Smart Card IC (Security Controller) SLE66CL187PEM / m2984-a11, SLE66CL187PE / m2985-a11, SLE66CL187PES / m2986-a11, SLE66CL88PEM / m2995-a11, SLE66CL88PE / m2994-a11, SLE66CL87PEM / m2992-a11, SLE66CL87PES / m2993-a11, SLE66CL87PE / m2991-a11 and SLE66CL48PE / m2983-a11 all with specific IC dedicated software. This TOE, comprising the group of derivatives listed above, is principally based on the same hardware as the first contactless PE-derivate group comprising the derivatives with their different memory sizes which have successfully passed the EAL5+ evaluation as well. These were the BSI internal processes BSI-DSZ-CC-0399-2006, BSI-DSZ-CC-0430-2007, BSI-DSZ-CC-0482-2007 and also BSI-DSZ-CC-0538-2008. The latter process comprised almost the same hardware in the design step a14 but comes in the current process with an STS update, an enhanced radio interface and some improvements and optimizations. For more details please refer to [6, chapter 1.2].

The ICs consists of a dedicated non standard microprocessor (CPU) with a MMU (Memory Management Unit), several different memories, security logic, a timer, an interrupt-controlled I/O interface, a AIS31 compatible RNG (Random Number Generator), and a checksum module (CRC module) and further components are integrated on the chip too. The TOE's block diagram is shown in Figure 1 of the Security Target [6, chapter 2.1]. The term Smartcard Embedded Software is used in the following for all operating systems and applications stored and executed on the TOE. The TOE is the platform for the Smartcard Embedded Software. The Smartcard Embedded Software itself is not part of the TOE.

This TOE is intended to be used in smart cards for particularly security relevant applications, including high speed security authentication and data encryption. Several security features independently implemented in hardware or controlled by software will be provided to ensure proper operations and integrity and confidentiality of stored data. The TOE is available in nine derivatives differ only in their EEPROM size and the interface configuration. The EEPROM sizes available are 18 kByte, 8 kByte and 4 kByte.

The CPU accesses the memory via the integrated Memory Encryption and Decryption unit (MED). The access rights of the application to the memories can be controlled with the memory management unit (MMU). Errors in the NVM are automatically detected and corrected. Security, sleep mode and interrupt logic as well as the RNG are specially designed for smart card applications. The sleep mode logic (clock stop mode per ISO/IEC 7816-3) is used to reduce the overall power consumption. The timer permits easy implementation of communication protocols such as T=1 and all other time-critical operations. The UART-controlled I/O interface allows the smart card controller and the terminal interface to be operated independently in terms of timing. The virtual PLL (VPLL) unit allows operating all variants with a multiplication factor over the external clock signal or free running with maximum frequency. The RNG does not supply a pseudorandom number sequence, but instead produces genuine random numbers under all conditions. The checksum module allows simple calculation of checksums per ISO 3309 (16 bit CRC).

The module implemented for cryptographic operations is the Cryptographic Unit (DDES) for Dual Key DES calculations. This module is especially designed for chip-card applications with respect to the security and power consumption. The DDES module computes the complete DES algorithm within a few clock cycles and is especially designed to counter attacks like DPA or EMA.

The TOE includes also functionality to calculate single DES operations, but part of the evaluation is the triple-DES operation only.

For more detail please refer to the Security Target [6, chapter 2.1].

The Security Target [6] is the basis for this certification. It is based on the certified Protection Profile Smartcard IC Platform Protection Profile, Version 1.0, July 2001, Eurosmart, BSI-PP-0002-2001 [9].

The TOE Security Assurance Requirements (SAR) are based entirely on the assurance components defined in Part 3 of the Common Criteria (see part C or [1], Part 3 for details). The TOE meets the Assurance Requirements of the Evaluation Assurance Level EAL 5 augmented by ALC_DVS.2 (Sufficiency of security measures), AVA_MSU.3 (validation of analysis) and AVA_VLA.4 (Highly resistant).

The TOE Security Functional Requirements (SFR) relevant for the TOE are outlined in the Security Target [6, chapter 5.1]. They are selected from Common Criteria Part 2 and some of them are newly defined. Thus the TOE is CC part 2 extended.

The Security Functional Requirements (SFR) relevant for the IT-Environment of the TOE are outlined in the Security Target [6, chapter 5.2].

The TOE Security Functional Requirements are implemented by the following TOE Security Functions:

TOE Security Function	Addressed issue
SEF1	Operating state checking
SEF2	Phase management with test mode lock-out
SEF3	Protection against snooping
SEF4	Data encryption and data disguising
SEF5	Random number generation
SEF6	TSF self test
SEF7	Notification of physical attack
SEF8	Memory Management Unit (MMU)
SEF9	Cryptographic support

Table 1: TOE Security Functions

For more details please refer to the Security Target [6, chapter 6].

The claimed TOE's Strength of Functions 'high' (SOF-high) for specific functions as indicated in the Security Target [6, chapter 6] is confirmed. The rating of the strength of functions does not include the cryptoalgorithms suitable for encryption and decryption (see BSIG Section 4, Para. 3, Clause 2). For details see chapter 9 of this report.

The assets to be protected by the TOE are defined in the Security [6, chapter 3.1]. Based on these assets the security environment is defined in terms of assumptions, threats and policies. This is outlined in the Security Target [6, chapter 3.2 to 3.4].

This certification covers the following configurations of the TOE:

- SLE66CL187PEM / m2984-a11 (produced in Dresden),
- SLE66CL187PE / m2985-a11 (produced in Dresden),
- SLE66CL187PES / m2986-a11 (produced in Dresden),

- SLE66CL88PEM / m2995-a11 (produced in Dresden),
- SLE66CL88PE / m2994-a11 (produced in Dresden),
- SLE66CL87PEM / m2992-a11 (produced in Dresden),
- SLE66CL87PES / m2993-a11 (produced in Dresden),
- SLE66CL87PE / m2991-a11 (produced in Dresden),
- SLE66CL48PE / m2983-a11 (produced in Dresden),

For more details please refer to chapter 8

The certification results only apply to the version of the product indicated in the certificate and on the condition that all the stipulations are kept as detailed in this Certification Report. This certificate is not an endorsement of the IT product by the Federal Office for Information Security (BSI) or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT product by BSI or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

2 Identification of the TOE

The Target of Evaluation (TOE) is called:

Infineon Smart Card IC (Security Controller) SLE66CL187PEM / m2984-a11, SLE66CL187PE / m2985-a11, SLE66CL187PES / m2986-a11, SLE66CL88PEM / m2995-a11, SLE66CL88PE / m2994-a11, SLE66CL87PEM / m2992-a11, SLE66CL87PES / m2993-a11, SLE66CL87PE / m2991-a11 and SLE66CL48PE / m2983-a11 all with specific IC dedicated software

The following table outlines the TOE deliverables:

No	Type	Identifier	Release	Form of delivery
1a	HW	SLE66CL187PEM Smart Card IC	GDS-file-ID: m2984-a11 with production line indicator: "2" (Dresden)	Wafer or packaged module
1b	HW	SLE66CL187PE Smart Card IC	GDS-file-ID: m2985-a11 with production line indicator: "2" (Dresden)	Wafer or packaged module
1c	HW	SLE66CL187PES Smart Card IC	GDS-file-ID: m2986-a11 with production line indicator: "2" (Dresden)	Wafer or packaged module
1d	HW	SLE66CL88PEM Smart Card IC	GDS-file-ID: m2995-a11 with production line indicator: "2" (Dresden)	Wafer or packaged module
1e	HW	SLE66CL88PE Smart Card IC	GDS-file-ID: m2994-a11 with production line indicator: "2" (Dresden)	Wafer or packaged module
1f	HW	SLE66CL87PEM Smart Card IC	GDS-file-ID: m2992-a11 with production line indicator: "2" (Dresden)	Wafer or packaged module

No	Type	Identifier	Release	Form of delivery
1g	HW	SLE66CL87PES Smart Card IC	GDS-file-ID: m2993-a11 with production line indicator: "2" (Dresden)	Wafer or packaged module
1h	HW	SLE66CL87PE Smart Card IC	GDS-file-ID: m2991-a11 with production line indicator: "2" (Dresden)	Wafer or packaged module
1i	HW	SLE66CL48PE Smart Card IC	GDS-file-ID: m2983-a11 with production line indicator: "2" (Dresden)	Wafer or packaged module
2	FW	STS Self Test Software (the IC Dedicated Test Software)	V57.09.08	Stored in Test ROM on the IC
3	FW	RMS-E Resource Management System (the IC Dedicated Support Software) [11]	RMS_E V06	Stored in reserved area of User ROM on the IC
4	DOC	Data Book – SLE66C(L) (X)xxxPE(M/S) Security Controller Family incl. the errata sheet [11]	2008-09	Hardcopy and pdf- file
5	DOC	Confidential Errata & Delta Sheet - SLE66C(L)(X)xxxPE(M/S) Controllers - Product and Boundout [12]	2008-10	Hardcopy and pdf- file
6	DOC	Security Programmers' Manual - SLE66C(L)xxxP(E) Controllers [13]	08.07	Hardcopy and pdf- file
7	DOC	Security & Chip Card ICs – SLE66CxxxPE – Instruction Set [14]	07.04	Hardcopy and pdf- file
8	DOC	Chip Card & Security ICs - SLE66CL(X)xxxPE(M/S) – Instruction Set and Special Function Registers – Quick Reference [15]	11.06	Hardcopy and pdf- file
9	DOC	Application Notes [16]..[30]	see lsection 13	Hardcopy and pdf- file

Table 2: Deliverables of the TOE

The TOE is identified by Infineon Smart Card IC (Security Controller) SLE66CL187PEM / m2984-a11, SLE66CL187PE / m2985-a11, SLE66CL187PES / m2986-a11, SLE66CL88PEM / m2995-a11, SLE66CL88PE / m2994-a11, SLE66CL87PEM / m2992-a11, SLE66CL87PES / m2993-a11, SLE66CL87PE / m2991-a11 and SLE66CL48PE / m2983-a11 all with specific IC dedicated software. The TOE is uniquely identified with its chip identification number. This chip identification number is chip specific as the chip type, lot number, wafer, chip coordinates on the wafer, production date, production site (e.g. upper nibble of (08000AH) "2" stands for Infineon's IC fabrication in Dresden/Germany "a") and design step (e.g. "0B" at address (080009H) stands for design step "11") are part of the number. If the TOE gives the user the possibility to read the chip identification number, the corresponding format is defined in the [11, chapter 7.9] and [12, chapter 6.7].

The chip type byte identifies the different versions in the following manner:

- C8 hex for version m2984
- C9 hex for version m2985
- CA hex for version m2986
- CF hex for version m2995

- CE hex for version m2994
- CC hex for version m2992
- CD hex for version m2993
- CB hex for version m2991
- D0 hex for version m2983

The STS is identified by its unique version number which is stored in three additional control bytes of the Chip Identification Number [11, chapter 7.9.1]. The RMS is identified by its unique version number. As the RMS is part of the ROM mask, one can get the RMS version number for a specific chip by using the ROM type bytes and asking the data base system at Infineon Logistic Department. It is also accessible by the operating system function `SleRmsVersion` [11, chapter 6.16.2.1].

The version numbers of the current TOE are listed in Table 2 above.

3 Security Policy

The security policy is expressed by the set of security functional requirements and implemented by the TOE. It covers the following issues:

The security policy of the TOE is to provide basic Security Functions to be used by the smart card operating system and the smart card application thus providing an overall smart card system security. Therefore, the TOE will implement an algorithm to ensure the confidentiality of plain text data by encryption and to support secure authentication protocols and it will provide a random number generator.

As the TOE is a hardware security platform, the security policy of the TOE is also to provide protection against leakage of information (e.g. to ensure the confidentiality of cryptographic keys during Triple-DES cryptographic functions performed by the TOE), against physical probing, against malfunctions, against physical manipulations and against abuse of functionality. Hence the TOE shall

- maintain the integrity and the confidentiality of data stored in the memory of the TOE and
- maintain the integrity, the correct operation and the confidentiality of Security Functions (security mechanisms and associated functions) provided by the TOE.

4 Assumptions and Clarification of Scope

The assumptions defined in the Security Target and some aspects of threats and organisational security policies are not covered by the TOE itself. These aspects lead to specific security objectives to be fulfilled by the TOE-Environment. The following topics are of relevance: Usage of Hardware Platform, Treatment of User Data, Protection during TOE Development and Production, Protection during Packaging, Finishing and Personalisation. Details can be found in the Security Target [6, chapter 4.2].

5 Architectural Information

The TOEs are integrated circuits (IC) providing a platform to a smart card operating system and smart card application software. A top level block diagram and a list of subsystems can be found within the TOE description of the Security Target [6, chapter

2.1]. The complete hardware description and the complete instruction set of the TOE is to be found in the Data Book [11] and other guidance documents delivered to the customer, see table 2.

For the implementation of the TOE Security Functions basically the central processing unit (CPU) with memory management unit (MMU), RAM, ROM, EEPROM, security logic, interrupt module, bus system, Random Number Generator (RNG) and the cryptographic operation of the chip are used. Security measures for physical protection are realised within the layout of the whole circuitry.

The Special Function Registers, the CPU instructions and the various on-chip memories provide the interface to the software using the Security Functions of the TOE.

The TOE IC Dedicated Test Software (STS), stored on the chip, is used for testing purposes during production only and is completely separated from the use of the embedded software by disabling before TOE delivery.

The TOE IC Dedicated Support Software (RMS), stored on the chip, is used for EEPROM programming and Security Function testing. It is stored by the TOE manufacturer in a reserved area of the normal user ROM and can be used by the users embedded software.

The TOE includes also functionality to calculate single DES operations, but part of the evaluation is the Triple-DES operation only.

6 Documentation

The evaluated documentation as outlined in table 2 is being provided with the product to the customer. This documentation contains the required information for secure usage of the TOE in accordance with the Security Target.

Additional obligations and notes for secure usage of the TOE as outlined in chapter 10 of this report have to be followed.

7 IT Product Testing

The tests performed by the developer were divided into six categories:

- Simulation tests: These tests are performed before starting the production to develop the technology for the production and to define the process parameters.
- Qualification tests: These tests are performed after the first production of chips. The tests are performed in test mode. With these tests the influence of temperature, frequency, and voltage on the security functions are tested in detail.
- Verification tests: These tests are performed in normal mode and check the functionality in the end user environment. The results of the qualification and verification tests are the basis on which it is decided, whether the TOE is released to production.
- Security evaluation tests: These tests are performed in normal mode and check the security mechanisms aiming on the security functionality and the effectiveness of the mechanisms. The random numbers are tested as required by AIS 31 and fulfill the criteria.
- Production tests: These tests are performed at each TOE before delivery. The aim of the production tests is to check whether each chip is functioning correctly.

- Penetration Tests: Penetration Tests are performed to find security flaws in the product.

The developer tests cover all Security Functions and all security mechanisms as identified in the functional specification, the high level design and the low level design. Chips from the production site Dresden (see part D, annex A of this report) were used for tests.

The evaluators testing effort can be summarised into the following classes of tests: Module tests, Simulation tests, Emulation tests, Tests in user mode, Tests in test mode and Hardware tests. The evaluators performed independent tests to supplement, augment and to verify the tests performed by the developer by sampling. Besides repeating exactly the developers tests, test parameters were varied and additional analysis was done. With these kind of tests performed in the developer's testing environment the entire security functionality of the TOE was verified. Overall the evaluators have tested the TSF systematically against the functional specification, the high-level design and the low-level design.

The evaluators supplied evidence that the current version of the TOE with production line indicator "2" for Dresden (Germany) provides the Security Functions as specified.

For this re-evaluation the evaluators re-assessed the penetration testing and confirmed the results from the previous certification procedure BSI-DSZ-CC-0538-2008 where they took all Security Functions into consideration. Intensive penetration testing was performed at that time to consider the physical tampering of the TOE using highly sophisticated equipment and expertised know-how. Specific additional penetration attacks were performed in the course of this evaluation.

8 Evaluated Configuration

The SLE66CL187PEX, the SLE66CL88PEX, the SLE66CL87PEX, and the SLE66CL48PE are identically from hardware perspective. The difference is that in the SLE66CL88PEX, the SLE66CL87PEX, and the SLE66CL48PE the memory is blocked to smaller size. All types can be distinguished by a different chip ident. The difference in the memory size does not influence the security of the TOE as neither an asset nor a security enforcing function is affected.

This certification covers the following configurations of the TOE:

- SLE66CL187PEM/m2984-a11,
- SLE66CL187PE/m2985-a11,
- SLE66CL187PES/m2986-a11,
- SLE66CL88PEM/m2995-a11,
- SLE66CL88PE/m2994-a11,
- SLE66CL87PEM/m2992-a11,
- SLE66CL87PES/m2993-a11,
- SLE66CL87PE/m2991-a11,
- SLE66CL48PE/m2983-a11.

All with the specific IC Dedicated Software and with production line indicator "2" for Dresden/Germany. After delivery the TOE only features one fixed configuration (user

mode), which cannot be altered by the user. The TOE was tested in this configuration. All the evaluation and certification results therefore are only effective for this version of the TOE. For all evaluation activities performed in test mode, there was a rationale why the results are valid for the user mode, too.

9 Results of the Evaluation

9.1 CC specific results

The Evaluation Technical Report (ETR) [7] was provided by the ITSEF according to the Common Criteria [1], the Methodology [2], the requirements of the Scheme [3] and all interpretations and guidelines of the Scheme (AIS) [4] as relevant for the TOE.

The Evaluation Methodology CEM [2] was used for those components up to EAL4 extended by advice of the Certification Body for components beyond EAL 4 and guidance specific for the technology of the product [4] (AIS 34).

The following guidance specific for the technology was used:

- The Application of CC to Integrated Circuits
- The Application of Attack Potential to Smartcards
- Functionality classes and evaluation methodology of physical random number generators

(see [4], AIS 25, AIS 26, AIS 31) were used.

As a result of the evaluation the verdict PASS is confirmed for the following assurance components:

- All components of the class ASE
- All components of the EAL 5 package as defined in the CC (see also part C of this report)
- The components ALC_DVS.2 (Sufficiency of security measures), AVA_MSU.3 (validation of analysis) and AVA_VLA.4 (Highly resistant). augmented for this TOE evaluation.
- All components claimed in the Security Target [6, chapter 6] and defined in the CC (see also part C of this report)

As the evaluation work performed for this certification procedure was carried out as a re-evaluation based on the certificate BSI-DSZ-CC-0538-2008, re-use of specific evaluation tasks was possible. The focus of this re-evaluation was on implemented cryptolibrary ECC and RSA2048.

The evaluation has confirmed:

- PP Conformance: Smartcard IC Platform Protection Profile, Version 1.0, July 2001, Eurosmart, BSI-PP-0002-2001 [9]
- for the Functionality: PP conformant
Common Criteria Teil 2 extended
- for the Assurance: Common Criteria Part 3 conformant
EAL 5 augmented by
ALC_DVS.2, AVA_MSU.3 and AVA_VLA.4

- The following TOE Security Functions fulfil the claimed Strength of Function : high
SEF2 – Phase management with test mode lock-out,
SEF3 – Protection against snooping,
SEF4 – Data encryption and data disguising,
SEF5 – Random number generation

In order to assess the strength of function the scheme interpretations AIS 25, 26 and AIS 31 (see [4]) were used. For specific evaluation results regarding the development and production environment see annex B in part D of this report.

The results of the evaluation are only applicable to the TOE as defined in chapter 2 and the configuration as outlined in chapter 8 above.

9.2 Results of cryptographic assessment

The following cryptographic algorithms are used by the TOE to enforce its security policy:

- algorithms for the encryption and decryption: Triple-DES
- This holds for the following security functions: SF9

This security enforcing function SEF9 is introduced to include the cryptographic operation in the scope of the evaluation as the cryptographic function itself is not used from the TOE security policy. On the other hand these functions are of special interest for the use of the hardware as platform for the software. The component is a hardware DES encryption unit. The keys for the cryptographic Triple-DES operations are provided from the Smartcard Embedded Software.

The strength of the cryptographic algorithms was not rated in the course of this evaluation (see BSI Section 4, Para. 3, Clause 2). According to [31] the algorithms are suitable for encryption and decryption. The validity period of each algorithm is mentioned in the official catalogue [31].

10 Obligations and notes for the usage of the TOE

The TOE is delivered to the Smartcard Embedded Software Developer and the Card Manufacturer. The actual end user obtains the TOE from the Card Manufacturer together with the application which runs on the TOE.

The operational documents as outlined in Table 2, deliverables of the TOE, contain necessary information about the usage of the TOE and all security hints therein have to be considered. In addition, the following aspects need to be fulfilled when using the TOE:

All security hints described in the user guidance documentation [11], [13] and the delivered application notes [16]..[30] have to be considered. For secure usage of the TOE the fulfilment of the assumptions about the environment in the Security Target [6] and especially the recommendations of the Security Programmers Manual [13] have to be taken into account.

11 Security Target

For the purpose of publishing, the Security Target [6] of the Target of Evaluation (TOE) is provided within a separate document as Annex A of this report.

12 Definitions

12.1 Acronyms

ACE	Advanced Crypto Engine
API	Application Programming Interface
BSI	Bundesamt für Sicherheit in der Informationstechnik / Federal Office for Information Security, Bonn, Germany
CBC	Cipher Block Chaining
CC	Common Criteria for IT Security Evaluation
CRC	Checksum module
CPU	Central Processing Unit
DES	Data Encryption Standard; symmetric block cipher algorithm
DDC	DES accelerator
DPA	Differential Power Analysis
EAL	Evaluation Assurance Level
ECB	Electrical Code Block
ECC	Elliptic Curve Cryptography
ECDH	Elliptic Curve Diffie-Hellman
ECDSA	Elliptic Curve Digital Signature Algorithm
EEPROM	Electrically Erasable Programmable Read Only Memory
EMA	Electro magnetic analysis
ETR	Evaluation Technical Report
IC	Integrated Circuit
IT	Information Technology
ITSEF	Information Technology Security Evaluation Facility
MED	Memory Encryption and Decryption unit
MMU	Memory Management Unit
PP	Protection Profile
RAM	Random Access Memory
RNG	Random Number Generator
ROM	Read Only Memory
RSA	Rivest, Shamir, Adleman – a public key encryption algorithm
RMS	Resource Management System
SEF	Security Function
SFP	Security Function Policy
SFR	Security Functional Requirement

SOF	Strength of Function
SPA	Simple power analysis
ST	Security Target
STS	Self Test Software
SW	Software
TOE	Target of Evaluation
Triple-DES	Symmetric block cipher algorithm based on the DES
TSC	TSF Scope of Control
TSF	TOE Security Functions
TSP	TOE Security Policy
TSS	TOE Summary Specification
UCP	Unified Channel Programming

12.2 Glossary

Augmentation - The addition of one or more assurance component(s) from CC Part 3 to an EAL or assurance package.

Extension - The addition to an ST or PP of functional requirements not contained in part 2 and/or assurance requirements not contained in part 3 of the CC.

Formal - Expressed in a restricted syntax language with defined semantics based on well-established mathematical concepts.

Informal - Expressed in natural language.

Object - An entity within the TSC that contains or receives information and upon which subjects perform operations.

Protection Profile - An implementation-independent set of security requirements for a category of TOEs that meet specific consumer needs.

Security Function - A part or parts of the TOE that have to be relied upon for enforcing a closely related subset of the rules from the TSP.

Security Target - A set of security requirements and specifications to be used as the basis for evaluation of an identified TOE.

Semiformal - Expressed in a restricted syntax language with defined semantics.

Strength of Function - A qualification of a TOE security function expressing the minimum efforts assumed necessary to defeat its expected security behaviour by directly attacking its underlying security mechanisms.

SOF-basic - A level of the TOE strength of function where analysis shows that the function provides adequate protection against casual breach of TOE security by attackers possessing a low attack potential.

SOF-medium - A level of the TOE strength of function where analysis shows that the function provides adequate protection against straightforward or intentional breach of TOE security by attackers possessing a moderate attack potential.

SOF-high - A level of the TOE strength of function where analysis shows that the function provides adequate protection against deliberately planned or organised breach of TOE security by attackers possessing a high attack potential.

Subject - An entity within the TSC that causes operations to be performed.

Target of Evaluation - An IT product or system and its associated administrator and user guidance documentation that is the subject of an evaluation.

TOE Security Functions - A set consisting of all hardware, software, and firmware of the TOE that must be relied upon for the correct enforcement of the TSP.

TOE Security Policy - A set of rules that regulate how assets are managed, protected and distributed within a TOE.

TSF Scope of Control - The set of interactions that can occur with or within a TOE and are subject to the rules of the TSP.

13 Bibliography

- [1] Common Criteria for Information Technology Security Evaluation, Version 2.3, August 2005
- [2] Common Methodology for Information Technology Security Evaluation (CEM), Evaluation Methodology, Version 2.3, August 2005
- [3] BSI certification: Procedural Description (BSI 7125)
- [4] Application Notes and Interpretations of the Scheme (AIS) as relevant for the TOE.⁸
- [5] German IT Security Certificates (BSI 7148, BSI 7149), periodically updated list published also on the BSI Website
- [6] Security Target, SLE66CL187PEM/m2984-a11, SLE66CL187PE/m2985-a11, SLE66CL187PES/m2986-a11, SLE66CL88PEM/m2995-a11, SLE66CL88PE/m2994-a11, SLE66CL87PEM/m2992-a11, SLE66CL87PES/m2993-a11, SLE66CL87PE/m2991-a11, SLE66CL48PE/m2983-a11, Version 1.1, date 2008-10-22, Infineon AG
- [7] EVALUATION TECHNICAL REPORT (ETR), Version: 2, date: 2008-11-13, ID: 8104918415 / BSI-DSZ-CC-0572. Product: SLE66CL187PEM/m2984-a11, SLE66CL187PE/m2985-a11, SLE66CL187PES/m2986-a11, SLE66CL88PEM/m2995-a11, SLE66CL88PE/m2994-a11, SLE66CL87PEM/m2992-a11, SLE66CL87PES/m2993-a11, SLE66CL87PE/m2991-a11, SLE66CL48PE/m2983-a11, Evaluation Body for IT Security of TÜV Informationstechnik GmbH (confidential document)
- [8] Configuration Management Scope (ACM_SCP), SLE66CL187PEM/m2984-a11, SLE66CL187PE/m2985-a11, SLE66CL187PES/m2986-a11, SLE66CL88PEM/m2995-a11, SLE66CL88PE/m2994-a11, SLE66CL87PEM/m2992-a11, SLE66CL87PES/m2993-a11, SLE66CL87PE/m2991-a11, SLE66CL48PE/m2983-a11, Version 1.1 from 2008-10-22, Infineon AG (confidential document)

⁸ specifically

- AIS 25, Version 3, 6 August 2007, Anwendung der CC auf Integrierte Schaltungen including JIL Document resp. CC Supporting Document
- AIS 26, Version 3, 6 August 2007, Evaluationsmethodologie für in Hardware integrierte Schaltungen including JIL Document resp. CC Supporting Document
- AIS 31, Version 1, 25 Sept. 2001 Funktionalitätsklassen und Evaluationsmethodologie für physikalische Zufallszahlengeneratoren
- AIS 32, Version 1, 2 July 2001, Übernahme international abgestimmter CC-Interpretationen ins deutsche Zertifizierungsschema.
- AIS 34, Version 1.00, 1 June 2004, Evaluation Methodology for CC Assurance Classes for EAL5+
- AIS 35, Version 2.0, 12 November 2007, Öffentliche Fassung des Security Targets (ST-Lite) including JIL Document resp. CC Supporting Document and CCRA policies
- AIS 36, Version 2, 12 November 2007, Kompositionsevaluierung including JIL Document resp. CC Supporting Document
- AIS 38, Version 2.0, 28 September 2007, Reuse of evaluation results

- [9] Smart card IC Platform Protection Profile, Version 1.0, July 2001, BSI registration ID: BSI-PP-0002-2001, developed by Atmel Smart Card ICs, Hitachi Ltd., Infineon Technologies AG, Philips Semiconductors
- [10] ETR FOR COMPOSITE EVALUATION (ETR-COMP), Version: 2, Date: 2008-11-13, ID: 8104918415/BSI-DSZ-CC-0523, Product: SLE66CL187PEM/m2984-a11, SLE66CL187PE/m2985-a11, SLE66CL187PES/m2986-a11, SLE66CL88PEM/ m2995-a11, SLE66CL88PE/m2994-a11, SLE66CL87PEM/m2992-a11, SLE66CL87PES/m2993-a11,SLE66CL87PE/m2991-a11, SLE66CL48PE/ m2983-a11, Evaluation Body for IT Security of TÜV Informationstechnik GmbH (confidential document)
- [11] Data Book – Data Book – SLE66C(L)(X)xxxPE(M/S) Security Controller Family incl. the errata sheet, Version 2008-09, from 2008-09-03, Infineon AG
- [12] Confidential Errata & Delta Sheet - SLE66C(L)(X)xxxPE(M/S) Controllers - Product and Boundout, Version 2008-10 from 2008-10-15, Infineon AG
- [13] Security Programmers' Manual -SLE66C(L)xxxP(E) Controllers, Version 08.07 from 2007-08-14, Infineon AG
- [14] Security & Chip Card ICs – SLE 66CxxxPE – Instruction Set, Version 07.04 from 2004-07, Infineon AG
- [15] Chip Card & Security ICs - SLE66CL(X)xxxPE(M/S) – Instruction Set and Special Function Registers – Quick Reference, Version 11.06 from 2006-11, Infineon AG
- [16] SLE66CL(X)xxxPE(M/S) – Contactless Protocol Type A Type B (source v18092), Version 2008-07 from 2008-07, Infineon AG
- [17] SLE 66CL(X)xxxPE(M/S) - Contactless Card Coil Design Guide, Version 2008-10 from 2008-10, Infineon AG
- [18] SLE 66CL(X)xxxPE(M/S) - Optimized Contactless Energy Performance, Version 2008-09 from 2008-10-06, Infineon AG
- [19] SLE 66CL(X)xxxPE(M/S) - Contactless Performance for Payment Applications, Version 2008-10 from 2008-10-03, Infineon AG
- [20] SLE 66CLXxxxPE - Implementation of Transmission Protocol according to ISO/IEC 14443 Part 3 and 4, Version 2006-02 from 2006-02-23, Infineon AG
- [21] Application Note, SLE66CxxxP, DDES - EC2 Accelerator Version 04.02 from 2004-02, including complementary Application Note SLE 66CxxxPE DDES Accelerator, Version 07.05 from 2005-07, Infineon AG
- [22] Application Note, SLE66CxxxPE, Using MicroSlim NVM (cLib), confidential, Version 05.05 from 2005-05, Infineon AG
- [23] Application Note, SLE66CxxxP/PE, Memory Encryption Decryption confidential, Version 11.04 from 2004-11, Infineon AG
- [24] Application Note, SLE66CxxxPE, MMU-Memory Management Unit (PDF+SW) confidential, Version 12.04 from 2004-12, Infineon AG
- [25] SLE66C(L)xxxPE - Optimized Usage of Data NVM Above 64k, Version 08.05 from 2005-08, Infineon AG
- [26] Application Note, SLE66CxxxP/PE, Testing the RNG, confidential, Version 11.04 from 2004-11, Infineon AG

- [27] Application Note, SLE66CxxxP/PE, Using RNG a.t. FIPS140 (PDF+SW), confidential, Version 02.04 from 2004-02, Infineon AG
- [28] Application Note, SLE66CxxxPE, Using the active shield, confidential, Version 12.04 from 2004-12, Infineon AG
- [29] Application Note, SLE66CxxxPE - UART basic (PDF), Version 02.07 from 2007-02, Infineon AG
- [30] Application Note, SLE66CxxxPE - Static UART (PDF), Version 01.07 from 2007-01, Infineon AG
- [31] Bundesnetzagentur: Bekanntmachung zur elektronischen Signatur nach dem Signaturgesetz und der Signaturverordnung (Übersicht über geeignete Algorithmen), German "Bundesanzeiger Nr. 19", published February 5th, 2008, page 376

C Excerpts from the Criteria

CC Part1:

Conformance results (chapter 7.4)

„The conformance result indicates the source of the collection of requirements that is met by a TOE or PP that passes its evaluation. This conformance result is presented with respect to CC Part 2 (functional requirements), CC Part 3 (assurance requirements) and, if applicable, to a pre-defined set of requirements (e.g., EAL, Protection Profile).

The conformance result consists of one of the following:

- **CC Part 2 conformant** - A PP or TOE is CC Part 2 conformant if the functional requirements are based only upon functional components in CC Part 2.
- **CC Part 2 extended** - A PP or TOE is CC Part 2 extended if the functional requirements include functional components not in CC Part 2.

plus one of the following:

- **CC Part 3 conformant** - A PP or TOE is CC Part 3 conformant if the assurance requirements are based only upon assurance components in CC Part 3.
- **CC Part 3 extended** - A PP or TOE is CC Part 3 extended if the assurance requirements include assurance requirements not in CC Part 3.

Additionally, the conformance result may include a statement made with respect to sets of defined requirements, in which case it consists of one of the following:

- **Package name Conformant** - A PP or TOE is conformant to a pre-defined named functional and/or assurance package (e.g. EAL) if the requirements (functions or assurance) include all components in the packages listed as part of the conformance result.
- **Package name Augmented** - A PP or TOE is an augmentation of a pre-defined named functional and/or assurance package (e.g. EAL) if the requirements (functions or assurance) are a proper superset of all components in the packages listed as part of the conformance result.

Finally, the conformance result may also include a statement made with respect to Protection Profiles, in which case it includes the following:

- **PP Conformant** - A TOE meets specific PP(s), which are listed as part of the conformance result.“

CC Part 3:

Protection Profile criteria overview (chapter 8.2)

“The goal of a PP evaluation is to demonstrate that the PP is complete, consistent, technically sound, and hence suitable for use as a statement of requirements for one or more evaluatable TOEs. Such a PP may be eligible for inclusion within a PP registry.

Assurance Class	Assurance Family
Class APE: Protection Profile evaluation	TOE description (APE_DES)
	Security environment (APE_ENV)
	PP introduction (APE_INT)
	Security objectives (APE_OBJ)
	IT security requirements (APE_REQ)
	Explicitly stated IT security requirements (APE_SRE)

Table 3 - Protection Profile families - CC extended requirements”

Security Target criteria overview (Chapter 8.3)

“The goal of an ST evaluation is to demonstrate that the ST is complete, consistent, technically sound, and hence suitable for use as the basis for the corresponding TOE evaluation.

Assurance Class	Assurance Family
Class ASE: Security Target evaluation	TOE description (ASE_DES)
	Security environment (ASE_ENV)
	ST introduction (ASE_INT)
	Security objectives (ASE_OBJ)
	PP claims (ASE_PPC)
	IT security requirements (ASE_REQ)
	Explicitly stated IT security requirements (ASE_SRE)
	TOE summary specification (ASE_TSS)

Table 5 - Security Target families - CC extended requirements ”

Assurance categorisation (chapter 7.5)

“The assurance classes, families, and the abbreviation for each family are shown in Table 1.

Assurance Class	Assurance Family
ACM: Configuration management	CM automation (ACM_AUT)
	CM capabilities (ACM_CAP)
	CM scope (ACM_SCP)
ADO: Delivery and operation	Delivery (ADO_DEL)
	Installation, generation and start-up (ADO_IGS)
ADV: Development	Functional specification (ADV_FSP)
	High-level design (ADV_HLD)
	Implementation representation (ADV_IMP)
	TSF internals (ADV_INT)
	Low-level design (ADV_LLD)
	Representation correspondence (ADV_RCR)
	Security policy modeling (ADV_SPM)
AGD: Guidance documents	Administrator guidance (AGD_ADM)
	User guidance (AGD_USR)
ALC: Life cycle support	Development security (ALC_DVS)
	Flaw remediation (ALC_FLR)
	Life cycle definition (ALC_LCD)
	Tools and techniques (ALC_TAT)
ATE: Tests	Coverage (ATE_COV)
	Depth (ATE_DPT)
	Functional tests (ATE_FUN)
	Independent testing (ATE_IND)
AVA: Vulnerability assessment	Covert channel analysis (AVA_CCA)
	Misuse (AVA_MSU)
	Strength of TOE security functions (AVA_SOF)
	Vulnerability analysis (AVA_VLA)

Table 1: Assurance family breakdown and mapping”

Evaluation assurance levels (chapter 11)

“The Evaluation Assurance Levels (EALs) provide an increasing scale that balances the level of assurance obtained with the cost and feasibility of acquiring that degree of assurance. The CC approach identifies the separate concepts of assurance in a TOE at the end of the evaluation, and of maintenance of that assurance during the operational use of the TOE.

It is important to note that not all families and components from CC Part 3 are included in the EALs. This is not to say that these do not provide meaningful and desirable assurances. Instead, it is expected that these families and components will be considered for augmentation of an EAL in those PPs and STs for which they provide utility.”

Evaluation assurance level (EAL) overview (chapter 11.1)

“Table 6 represents a summary of the EALs. The columns represent a hierarchically ordered set of EALs, while the rows represent assurance families. Each number in the resulting matrix identifies a specific assurance component where applicable.

As outlined in the next section, seven hierarchically ordered evaluation assurance levels are defined in the CC for the rating of a TOE's assurance. They are hierarchically ordered inasmuch as each EAL represents more assurance than all lower EALs. The increase in assurance from EAL to EAL is accomplished by substitution of a hierarchically higher assurance component from the same assurance family (i.e. increasing rigour, scope, and/or depth) and from the addition of assurance components from other assurance families (i.e. adding new requirements).

These EALs consist of an appropriate combination of assurance components as described in chapter 7 of this Part 3. More precisely, each EAL includes no more than one component of each assurance family and all assurance dependencies of every component are addressed.

While the EALs are defined in the CC, it is possible to represent other combinations of assurance. Specifically, the notion of “augmentation” allows the addition of assurance components (from assurance families not already included in the EAL) or the substitution of assurance components (with another hierarchically higher assurance component in the same assurance family) to an EAL. Of the assurance constructs defined in the CC, only EALs may be augmented. The notion of an “EAL minus a constituent assurance component” is not recognised by the standard as a valid claim. Augmentation carries with it the obligation on the part of the claimant to justify the utility and added value of the added assurance component to the EAL. An EAL may also be extended with explicitly stated assurance requirements.

Assurance Class	Assurance Family	Assurance Evaluation Assurance Level Components							by
		EAL1	EAL2	EAL3	EAL4	EAL5	EAL6	EAL7	
Configuration management	ACM_AUT				1	1	2	2	
	ACM_CAP	1	2	3	4	4	5	5	
	ACM_SCP			1	2	3	3	3	
Delivery and operation	ADO_DEL		1	1	2	2	2	3	
	ADO_IGS	1	1	1	1	1	1	1	
Development	ADV_FSP	1	1	1	2	3	3	4	
	ADV_HLD		1	2	2	3	4	5	
	ADV_IMP				1	2	3	3	
	ADV_INT					1	2	3	
	ADV_LLD				1	1	2	2	
	ADV_RCR	1	1	1	1	2	2	3	
	ADV_SPM				1	3	3	3	
Guidance documents	AGD_ADM	1	1	1	1	1	1	1	
	AGD_USR	1	1	1	1	1	1	1	
Life cycle support	ALC_DVS			1	1	1	2	2	
	ALC_FLR								
	ALC_LCD				1	2	2	3	
	ALC_TAT				1	2	3	3	
Tests	ATE_COV		1	2	2	2	3	3	
	ATE_DPT			1	1	2	2	3	
	ATE_FUN		1	1	1	1	2	2	
	ATE_IND	1	2	2	2	2	2	3	
Vulnerability assessment	AVA_CCA					1	2	2	
	AVA_MSU			1	2	2	3	3	
	AVA_SOF		1	1	1	1	1	1	
	AVA_VLA		1	1	2	3	4	4	

Table 6: Evaluation assurance level summary”

Evaluation assurance level 1 (EAL1) - functionally tested (chapter 11.3)

“Objectives

EAL1 is applicable where some confidence in correct operation is required, but the threats to security are not viewed as serious. It will be of value where independent assurance is required to support the contention that due care has been exercised with respect to the protection of personal or similar information.

EAL1 provides an evaluation of the TOE as made available to the customer, including independent testing against a specification, and an examination of the guidance documentation provided. It is intended that an EAL1 evaluation could be successfully conducted without assistance from the developer of the TOE, and for minimal outlay.

An evaluation at this level should provide evidence that the TOE functions in a manner consistent with its documentation, and that it provides useful protection against identified threats.”

Evaluation assurance level 2 (EAL2) - structurally tested (chapter 11.4)

“Objectives

EAL2 requires the co-operation of the developer in terms of the delivery of design information and test results, but should not demand more effort on the part of the developer than is consistent with good commercial practice. As such it should not require a substantially increased investment of cost or time.

EAL2 is therefore applicable in those circumstances where developers or users require a low to moderate level of independently assured security in the absence of ready availability of the complete development record. Such a situation may arise when securing legacy systems, or where access to the developer may be limited.”

Evaluation assurance level 3 (EAL3) - methodically tested and checked (chapter 11.5)

“Objectives

EAL3 permits a conscientious developer to gain maximum assurance from positive security engineering at the design stage without substantial alteration of existing sound development practices.

EAL3 is applicable in those circumstances where developers or users require a moderate level of independently assured security, and require a thorough investigation of the TOE and its development without substantial re-engineering.”

Evaluation assurance level 4 (EAL4) - methodically designed, tested, and reviewed
(chapter 11.6)**“Objectives**

EAL4 permits a developer to gain maximum assurance from positive security engineering based on good commercial development practices which, though rigorous, do not require substantial specialist knowledge, skills, and other resources. EAL4 is the highest level at which it is likely to be economically feasible to retrofit to an existing product line.

EAL4 is therefore applicable in those circumstances where developers or users require a moderate to high level of independently assured security in conventional commodity TOEs and are prepared to incur additional security-specific engineering costs.”

Evaluation assurance level 5 (EAL5) - semiformally designed and tested (chapter 11.7)**“Objectives**

EAL5 permits a developer to gain maximum assurance from security engineering based upon rigorous commercial development practices supported by moderate application of specialist security engineering techniques. Such a TOE will probably be designed and developed with the intent of achieving EAL5 assurance. It is likely that the additional costs attributable to the EAL5 requirements, relative to rigorous development without the application of specialised techniques, will not be large.

EAL5 is therefore applicable in those circumstances where developers or users require a high level of independently assured security in a planned development and require a rigorous development approach without incurring unreasonable costs attributable to specialist security engineering techniques.”

Evaluation assurance level 6 (EAL6) - semiformally verified design and tested
(chapter 11.8)**“Objectives**

EAL6 permits developers to gain high assurance from application of security engineering techniques to a rigorous development environment in order to produce a premium TOE for protecting high value assets against significant risks.

EAL6 is therefore applicable to the development of security TOEs for application in high risk situations where the value of the protected assets justifies the additional costs.”

Evaluation assurance level 7 (EAL7) - formally verified design and tested (chapter 11.9)**“Objectives**

EAL7 is applicable to the development of security TOEs for application in extremely high risk situations and/or where the high value of the assets justifies the higher costs. Practical application of EAL7 is currently limited to TOEs with tightly focused security functionality that is amenable to extensive formal analysis.”

Strength of TOE security functions (AVA_SOF) (chapter 19.3)**“Objectives**

Even if a TOE security function cannot be bypassed, deactivated, or corrupted, it may still be possible to defeat it because there is a vulnerability in the concept of its underlying security mechanisms. For those functions a qualification of their security behaviour can be made using the results of a quantitative or statistical analysis of the security behaviour of these mechanisms and the effort required to overcome them. The qualification is made in the form of a strength of TOE security function claim.”

Vulnerability analysis (AVA_VLA) (chapter 19.4)**“Objectives**

Vulnerability analysis is an assessment to determine whether vulnerabilities identified, during the evaluation of the construction and anticipated operation of the TOE or by other methods (e.g. by flaw hypotheses), could allow users to violate the TSP.

Vulnerability analysis deals with the threats that a user will be able to discover flaws that will allow unauthorised access to resources (e.g. data), allow the ability to interfere with or alter the TSF, or interfere with the authorised capabilities of other users.”

“Application notes

A vulnerability analysis is performed by the developer in order to ascertain the presence of security vulnerabilities, and should consider at least the contents of all the TOE deliverables including the ST for the targeted evaluation assurance level. The developer is required to document the disposition of identified vulnerabilities to allow the evaluator to make use of that information if it is found useful as a support for the evaluator's independent vulnerability analysis.”

“Independent vulnerability analysis goes beyond the vulnerabilities identified by the developer. The main intent of the evaluator analysis is to determine that the TOE is resistant to penetration attacks performed by an attacker possessing a low (for AVA_VLA.2 Independent vulnerability analysis), moderate (for AVA_VLA.3 Moderately resistant) or high (for AVA_VLA.4 Highly resistant) attack potential.”

D Annexes

List of annexes of this certification report

Annex A: Security Target provided within a separate document.

Annex B: Evaluation results regarding development
and production environment

37

This page is intentionally left blank.

Annex B of Certification Report BSI-DSZ-CC-0572-2008

Evaluation results regarding development and production environment



The IT product Infineon Smart Card IC (Security Controller) SLE66CL187PEM / m2984-a11, SLE66CL187PE / m2985-a11, SLE66CL187PES / m2986-a11, SLE66CL88PEM / m2995-a11, SLE66CL88PE / m2994-a11, SLE66CL87PEM / m2992-a11, SLE66CL87PES / m2993-a11, SLE66CL87PE / m2991-a11 and SLE66CL48PE / m2983-a11 all with specific IC dedicated software (Target of Evaluation, TOE) has been evaluated at an accredited and licensed / approved evaluation facility using the Common Methodology for IT Security Evaluation, Version 2.3 extended by advice of the Certification Body for components beyond EAL 4 and guidance specific for the technology of the product for conformance to the Common Criteria for IT Security Evaluation (CC), Version 2.3 (ISO/IEC 15408:2005).

As a result of the TOE certification, dated 25 November 2008, the following results regarding the development and production environment apply. The Common Criteria assurance requirements

- **ACM – Configuration management (i.e. ACM_AUT.1, ACM_CAP.4, ACM_SCP.3),**
- **ADO – Delivery and operation (i.e. ADO_DEL.2, ADO_IGS.1) and**
- **ALC – Life cycle support (i.e. ALC_DVS.2, ALC_LCD.2, ALC_TAT.2),**

are fulfilled for the development and production sites of the TOE listed below:

Site	Address	Function
Altis-Toppan	Toppan Photomask, Inc. European Technology Center Boulevard John Kennedy 224 91105 Corbeil Essonnes France	Mask Center
Amkor	Amkor Technology Philippines Km. 22 East Service Rd. South Superhighway Muntinlupa City 1702 Philippines Amkor Technology Philippines 119 North Science Avenue Laguna Technopark, Binan Laguna 4024 Philippines	Module Mounting
Augsburg	Infineon Technologies AG Alter Postweg 101 86159 Augsburg Germany	Development

Site	Address	Function
Bangkok	Smartrac Technology, 142 Moo 1 Hi-Tech industrial Estate, Ban Laean, Bang, Pa-In Phra na korn Si Ayatthaya, 13160 Thailand	Inlay Antenna Mounting
Bukarest	Infineon Technologies Romania Blvd. Dimitrie Pompeiu Nr. 6, Sector 2 020335 Bucharest, Romania	Development
Dresden	Infineon Technologies Dresden GmbH & Co. OHG Königsbrücker Str. 180 01099 Dresden, Germany	Production
Dresden-Toppan	Toppan Photomask, Inc Rähnitzer Allee 9 01109 Dresden, Germany	Mask Center
Erfurt	Assa Abloy Identification Technologies GmbH (former Sokymat GmbH) In den Weiden 4b, 99099 Erfurt	Module Mounting with Inlay Antenna Mounting
Graz / Villach / Klagenfurt	Infineon Technologies Austria AG Development Center Graz Babenbergerstr. 10 8020 Graz, Austria Infineon Technologies Austria AG Siemensstr. 2 9500 Villach, Austria Infineon Technologies Austria AG Lakeside B05 9020 Klagenfurt, Austria	Development
Großostheim	Infineon Technology AG, DCE, Kühne & Nagel Stockstädter Strasse 10 - Building 8A 63762 Großostheim, Germany	Distribution Center
Hayward	Kuehne & Nagel 30805 Santana Street Hayward, CA 94544 U.S.A.	Distribution Center
Lustenau	New Logic Technologies AG, - A Wipro Company, Millenium Park 6, 6890 Lustenau, Austria	Development
Munich	Infineon Technologies AG Am Campeon 1-12 85579 Neubiberg, Germany Infineon Technologies AG Otto-Hahn-Ring 6 81739 München (Perlach), Germany	Development
Regensburg-West	Infineon Technologies AG Wernerwerkstraße 2 93049 Regensburg, Germany Smartrac Technology GmbH, Wernerwerkstraße 2 93049 Regensburg, Germany	Module Mounting Inlay Antenna Mounting, Distribution Center

Site	Address	Function
Singapore	Exel Singapore Pte Ltd DHL Exel Supply Chian 81, ALPS Avenue Singapore 498803	Distribution Center
Singapore Kallang	Infineon Technologies AG 168 Kallang Way Singapore 349253	Module Mounting
Tokyo	Kintetsu World Express, Inc. Tokyo Import Logistics Center Narita Terminal Tokyo, Japan	Distribution Center
Wuxi	Infineon Technologies (Wuxi) Co. Ltd. No. 118, Xing Chuang San Lu Wuxi-Singapore Industrial Park Wuxi 214028, Jiangsu, P.R. China	Module Mounting, Distribution Center

Table 3: Production Sites

The chip versions of the TOE are manufactured in Infineons IC fabrication in Dresden, Germany, indicated by the first nibble of the batch number which gives the production line indicator "2".

For the sites listed above, the requirements have been specifically applied in accordance with the Security Target [6]. The evaluators verified, that the threats, security objectives and requirements for the TOE life cycle phases up to delivery (as stated in the Security Target [6]) are fulfilled by the procedures of these sites.

This page is intentionally left blank.