# **Certification Report**

# BSI-DSZ-CC-0774-2011

for

# Renesas Cryptographic Library v5126 on Renesas RS47X security integrated circuit Version 01

from

**Renesas Electronics Corporation** 

BSI - Bundesamt für Sicherheit in der Informationstechnik, Postfach 20 03 63, D-53133 Bonn Phone +49 (0)228 99 9582-0, Fax +49 (0)228 9582-5477, Infoline +49 (0)228 99 9582-111

Certification Report V1.0 CC-Zert-327 V4.52





#### BSI-DSZ-CC-0774-2011

#### Renesas Cryptographic Library

v5126 on Renesas RS47X security integrated circuit Version 01

from Renesas Electronics Corporation

PP Conformance: Security IC Platform Protection Profile, Version

1.0, 15 June 2007, BSI-CC-PP-0035-2007

PP conformant plus product specific extensions Functionality:

Common Criteria Part 2 extended

Assurance: Common Criteria Part 3 conformant

EAL 5 augmented by ALC\_DVS.2, AVA\_VAN.5



Common Criteria Recognition Arrangement for components up to

EAL 4



The IT product identified in this certificate has been evaluated at an approved evaluation facility using the Common Methodology for IT Security Evaluation (CEM), Version 3.1 extended by advice of the Certification Body for components beyond EAL 5 and guidance specific for the technology of the product for conformance to the Common Criteria for IT Security Evaluation (CC), Version 3.1.

This certificate applies only to the specific version and release of the product in its evaluated configuration and in conjunction with the complete Certification Report.

The evaluation has been conducted in accordance with the provisions of the certification scheme of the German Federal Office for Information Security (BSI) and the conclusions of the evaluation facility in the evaluation technical report are consistent with the evidence adduced.

This certificate is not an endorsement of the IT product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

Bonn, 22 September 2011 For the Federal Office for Information Security



Bernd Kowalski **Head of Department**  L.S.

This page is intentionally left blank.

# **Preliminary Remarks**

Under the BSIG¹ Act, the Federal Office for Information Security (BSI) has the task of issuing certificates for information technology products.

Certification of a product is carried out on the instigation of the vendor or a distributor, hereinafter called the sponsor.

A part of the procedure is the technical examination (evaluation) of the product according to the security criteria published by the BSI or generally recognised security criteria.

The evaluation is normally carried out by an evaluation facility recognised by the BSI or by BSI itself.

The result of the certification procedure is the present Certification Report. This report contains among others the certificate (summarised assessment) and the detailed Certification Results.

The Certification Results contain the technical description of the security functionality of the certified product, the details of the evaluation (strength and weaknesses) and instructions for the user.

-

Act on the Federal Office for Information Security (BSI-Gesetz - BSIG) of 14 August 2009, Bundesgesetzblatt I p. 2821

# **Contents**

A Certification	7
1 Specifications of the Certification Procedure	7
2 Recognition Agreements	7
2.1 European Recognition of ITSEC/CC – Certificates (SOGIS-MRA	
2.2 International Recognition of CC – Certificates (CCRA)	8
3 Performance of Evaluation and Certification	8
4 Validity of the Certification Result	9
5 Publication	9
B Certification Results	10
1 Executive Summary	11
2 Identification of the TOE	12
3 Security Policy	13
4 Assumptions and Clarification of Scope	13
5 Architectural Information	14
6 Documentation	14
7 IT Product Testing	14
8 Evaluated Configuration	15
9 Results of the Evaluation	16
9.1 CC specific results	16
9.2 Results of cryptographic assessment	17
10 Obligations and Notes for the Usage of the TOE	17
11 Security Target	18
12 Definitions	18
12.1 Acronyms	18
12.2 Glossary	
13 Bibliography	20
C Excerpts from the Criteria	23
D Anneyes	22

#### A Certification

# 1 Specifications of the Certification Procedure

The certification body conducts the procedure according to the criteria laid down in the following:

- BSIG<sup>2</sup>
- BSI Certification Ordinance<sup>3</sup>
- BSI Schedule of Costs<sup>4</sup>
- Special decrees issued by the Bundesministerium des Innern (Federal Ministry of the Interior)
- DIN EN 45011 standard
- BSI certification: Procedural Description (BSI 7125) [3]
- Common Criteria for IT Security Evaluation (CC), Version 3.1<sup>5</sup> [1]
- Common Methodology for IT Security Evaluation, Version 3.1 [2]
- BSI certification: Application Notes and Interpretation of the Scheme (AIS) [4]

# 2 Recognition Agreements

In order to avoid multiple certification of the same product in different countries a mutual recognition of IT security certificates - as far as such certificates are based on ITSEC or CC - under certain conditions was agreed.

# 2.1 European Recognition of ITSEC/CC – Certificates (SOGIS-MRA)

The SOGIS-Mutual Recognition Agreement (SOGIS-MRA) Version 3 became effective in April 2010. It defines the recognition of certificates for IT-Products at a basic recognition level and in addition at higher recognition levels for IT-Products related to certain technical domains only.

The basic recognition level includes Common Criteria (CC) Evaluation Assurance Levels EAL1 to EAL4 and ITSEC Evaluation Assurance Levels E1 to E3 (basic). For higher recognition levels the technical domain Smart card and similar Devices has been defined. It includes assurance levels beyond EAL4 resp. E3 (basic). In Addition, certificates issued for Protection Profiles based on Common Criteria are part of the recognition agreement.

Act on the Federal Office for Information Security (BSI-Gesetz - BSIG) of 14 August 2009, Bundesgesetzblatt I p. 2821

Ordinance on the Procedure for Issuance of a Certificate by the Federal Office for Information Security (BSI-Zertifizierungsverordnung, BSIZertV) of 07 July 1992, Bundesgesetzblatt I p. 1230

Schedule of Cost for Official Procedures of the Bundesamt für Sicherheit in der Informationstechnik (BSI-Kostenverordnung, BSI-KostV) of 03 March 2005, Bundesgesetzblatt I p. 519

Proclamation of the Bundesministerium des Innern of 12 February 2007 in the Bundesanzeiger dated 23 February 2007, p. 3730

As of September 2011 the new agreement has been signed by the national bodies of Austria, Finland, France, Germany, Italy, The Netherlands, Norway, Spain, Sweden and the United Kingdom. Details on recognition and the history of the agreement can be found at <a href="https://www.bsi.bund.de/zertifizierung">https://www.bsi.bund.de/zertifizierung</a>.

The SOGIS-MRA logo printed on the certificate indicates that it is recognised under the terms of this agreement by the nations listed above.

### 2.2 International Recognition of CC – Certificates (CCRA)

An arrangement (Common Criteria Recognition Arrangement) on the mutual recognition of certificates based on the CC Evaluation Assurance Levels up to and including EAL 4 has been signed in May 2000 (CCRA). It includes also the recognition of Protection Profiles based on the CC.

As of September 2011 the arrangement has been signed by the national bodies of: Australia, Austria, Canada, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, India, Israel, Italy, Japan, Republic of Korea, Malaysia, The Netherlands, New Zealand, Norway, Pakistan, Republic of Singapore, Spain, Sweden, Turkey, United Kingdom, United States of America. The current list of signatory nations and approved certification schemes can be seen on the web site: <a href="http://www.commoncriteriaportal.org">http://www.commoncriteriaportal.org</a>

The Common Criteria Recognition Arrangement logo printed on the certificate indicates that this certification is recognised under the terms of this agreement by the nations listed above.

This evaluation contains the components ADV\_FSP.5, ADV\_INT.2, ADV\_TDS.4, ALC\_CMS.5, ALC\_DVS.2, ALC\_TAT.2, ATE\_DPT.3 and AVA\_VAN.5 that are not mutually recognised in accordance with the provisions of the CCRA. For mutual recognition the EAL4 components of these assurance families are relevant.

#### 3 Performance of Evaluation and Certification

The certification body monitors each individual evaluation to ensure a uniform procedure, a uniform interpretation of the criteria and uniform ratings.

The product Renesas Cryptographic Library v5126 on Renesas RS47X security integrated circuit Version 01 has undergone the certification procedure at BSI.

The evaluation of the product Renesas Cryptographic Library v5126 on Renesas RS47X security integrated circuit Version 01 was conducted by T-Systems GEI GmbH. The evaluation was completed on 22 September 2011. The T-Systems GEI GmbH is an evaluation facility (ITSEF)<sup>6</sup> recognised by the certification body of BSI.

For this certification procedure the sponsor and applicant is: Renesas Electronics Corporation.

The product was developed by: Renesas Electronics Corporation.

The certification is concluded with the comparability check and the production of this Certification Report. This work was completed by the BSI.

٠

<sup>&</sup>lt;sup>6</sup> Information Technology Security Evaluation Facility

# 4 Validity of the Certification Result

This Certification Report only applies to the version of the product as indicated. The confirmed assurance package is only valid on the condition that

- all stipulations regarding generation, configuration and operation, as given in the following report, are observed,
- the product is operated in the environment described, where specified in the following report and in the Security Target.

For the meaning of the assurance levels please refer to the excerpts from the criteria at the end of the Certification Report.

The Certificate issued confirms the assurance of the product claimed in the Security Target at the date of certification. As attack methods evolve over time, the resistance of the certified version of the product against new attack methods needs to be re-assessed. Therefore, the sponsor should apply for the certified product being monitored within the assurance continuity program of the BSI Certification Scheme (e.g. by a re-certification). Specifically, if results of the certification are used in subsequent evaluation and certification procedures, in a system integration process or if a user's risk management needs regularly updated results, it is recommended to perform a re-assessment on a regular e.g. annual basis.

In case of changes to the certified version of the product, the validity can be extended to the new versions and releases, provided the sponsor applies for assurance continuity (i.e. re-certification or maintenance) of the modified product, in accordance with the procedural requirements, and the evaluation does not reveal any security deficiencies.

### 5 Publication

The product Renesas Cryptographic Library v5126 on Renesas RS47X security integrated circuit Version 01 has been included in the BSI list of the certified products, which is published regularly (see also Internet: <a href="https://www.bsi.bund.de">https://www.bsi.bund.de</a> and [5]). Further information can be obtained from BSI-Infoline +49 228 9582-111.

Further copies of this Certification Report can be requested from the developer<sup>7</sup> of the product. The Certification Report may also be obtained in electronic form at the internet address stated above.

Japan

Renesas Electronics Corporation
 5-20-1 Jousuihon-cho, Kodaira-shi
 Tokyo 187-8588

# **B** Certification Results

The following results represent a summary of

- the Security Target of the sponsor for the Target of Evaluation,
- the relevant evaluation results from the evaluation facility, and
- complementary notes and stipulations of the certification body.

# 1 Executive Summary

The Target of Evaluation (TOE) is the Renesas Cryptographic Library v5126 running on the RS47X. The Renesas Cryptographic Library (RCL) provides cryptographic services using the RS47X hardware. The TOE is intended for use in a range of high security applications, including high speed secure authentication, data encryption or electronic signature. The RCL is intended to be used as crypto library by the Security IC Embedded Software.

The Security Target [6] is the basis for this certification. It is based on the certified Protection Profile Security IC Platform Protection Profile, Version 1.0, 15 June 2007, BSI-CC-PP-0035-2007 [7].

The TOE Security Assurance Requirements (SAR) are based entirely on the assurance components defined in Part 3 of the Common Criteria (see part C or [1], Part 3 for details). The TOE meets the assurance requirements of the Evaluation Assurance Level EAL 5 augmented by ALC DVS.2, AVA VAN.5.

The TOE Security Functional Requirements (SFR) relevant for the TOE are outlined in the Security Target [6] and [8], chapter 6.1. They are selected from Common Criteria Part 2 and some of them are newly defined. Thus the TOE is CC Part 2 extended.

The TOE Security Functional Requirements are implemented by the following TOE Security Functionalities:

TOE Security Functionality	Addressed issue
SF.RCL-LeakProtect	In addition to the measures provided by the hardware, the RCL provides additional measures to protect against leakage of information from the IC.
SF.RNG	The RCL provides a pseudo random number generator and includes functions to generate seeds usind the HW RNG and also to run the on-line test of the HW RNG.
SF.DES	The RCL provides single block (ECB), CBC and OFB mode DES using the hardware platform DES coprocessor.
SF.AES	The RCL provides single block (ECB), CBC and OFB mode AES using the hardware platform AES coprocessor.
SF.MMCopro	The hardware platform of the composite TOE provides a co- processor that carries out modular multiplication. The RCL provides an implementation of the RSA and RSA CRT using the MMC and provides secure key generation for the RSA and RSA CRT.
SF.Hash	The RCL provides implementations of the hash functions SHA-224, SHA-256, SHA-384 and SHA-512.

Table 1: TOE Security Functionalities

For more details please refer to the Security Target [6] and [8], chapter 7.

The assets to be protected by the TOE are defined in the Security Target [6] and [8], chapter 3.1. Based on these assets the TOE Security Problem is defined in terms of Assumptions, Threats and Organisational Security Policies. This is outlined in the Security Target [6] and [8], chapter 3.2 to 3.4.

This certification covers the following configurations of the TOE: Renesas Cryptographic Library v5126 running on the RS47X integrated circuit Version 01. For details refer to chapter 8.

The vulnerability assessment results as stated within this certificate do not include a rating for those cryptographic algorithms and their implementation suitable for encryption and decryption (see BSIG Section 9, Para. 4, Clause 2).

The certification results only apply to the version of the product indicated in the certificate and on the condition that all the stipulations are kept as detailed in this Certification Report. This certificate is not an endorsement of the IT product by the Federal Office for Information Security (BSI) or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT product by BSI or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

### 2 Identification of the TOE

The Target of Evaluation (TOE) is called:

#### **Renesas Cryptographic Library**

v5126 on Renesas RS47X security integrated circuit Version 01

The following table outlines the TOE deliverables:

No	Туре	Identifier	Release	Form of Delivery
1	HW	Renesas RS47X integrated circuit	version 01	Wafer or packaged module
2	SW	IC Dedicated Test Software	20981	Included in RS47X test ROM
		Test ROM Software		
3	SW	RNG on-line test software	1.4	Hardcopy: provided as a part of [14]
4	SW	AES/DES library for RS-4		Electronic Data
		consists of		
		RS4_LL.lib,	4658	
		RS4_LL.txt,	4658	
		and RS4_LL.h	4658	
5	DOC	Hardware Manual [15]	1.10	Electronic Data/Hardcopy
6	DOC	User Guidance [14]	1.3	Electronic Data/Hardcopy
7	DOC	Option List [16]	1.3	Electronic Data/Hardcopy
8	SW	Renesas Cryptographic Library running on the RS47X	5126	Electronic Data
9	DOC	Renesas Cryptographic Library User's Manual [13]	1.20	Electronic Data/Hardcopy

Table 2: Deliverables of the TOE

The hardware platform is labelled according to the availability of the optional contactless protocols Type-B and Type-F and considering the selection of the built-in capacitance

between both antenna contact pads (LA-LB) which are optional modules selected in [16] by the user.

The security functionality of the TOE is not influenced by the delivery forms.

The commercial type name is the name of the TOE along with the selected contactless protocols option, the package code, and with the customer specific ROM code (the Security IC Embedded Software) of the TOE. The commercial type name is built as shown in Table 3:

Product Name	Type-A or Type-F	ROM code	Package code	Built-in capacitance
RS47X	A for Type-A C for Type-F	A number between 0 – 99 (unique for each ROM)	package code (two or three ASCII characters)	1 or space

Table 3: Meaning of the commercial type names of the TOE

The hardware part of the TOE is identified with the information stored at the first 20 bytes of the EEPROM address range. Option List for Smart Card Microcomputer (for RS47X) describes the information for identification of the TOE. In addition the hardware version can be identified by the nameplate on the surface of the die.

The RCL has the version number 5126. The section 2.4.5 of [13] lists the check sums of the TOE's components that have to be verified when they are integrated into the hardware platform.

# 3 Security Policy

The security policy of the TOE is to provide basic security functions to be used by the smart card operating system and the smart card application thus providing an overall smart card system security. Therefore, the TOE will implement cryptographic algorithms and will provide a random number generation of appropriate quality.

As the TOE is a hardware security platform with Cryptographic Library, the security policy of the TOE is also to provide protection against leakage of information (e.g. to ensure the confidentiality of cryptographic keys during cryptographic functions performed by the TOE), against physical probing, against malfunctions, against physical manipulations and against abuse of functionality. Hence the TOE shall:

- maintain the integrity and the confidentiality of data stored in the memory of the TOE and
- maintain the integrity, the correct operation and the confidentiality of security functions (security mechanisms and associated functions) provided by the TOE.

# 4 Assumptions and Clarification of Scope

The Assumptions defined in the Security Target and some aspects of Threats and organisational Security Policies are not covered by the TOE itself. These aspects lead to specific security objectives to be fulfilled by the TOE-Environment. The following topics are of relevance:

- Usage of Hardware Platform
- Treatment of User Data

- Protection during Packaging, Finishing and Personalisation
- Injected Data Support
- Usage of Kex-dependent Functions

Details can be found in the Security Target [6] and [8], chapter 4.2.

#### 5 Architectural Information

The Renesas Renesas RS47X integrated circuit version 01 is an integrated circuit providing a hardware platform for a Security IC Embedded Software. A top level block diagram and a list of subsystems can be found within the TOE description of the "RS47X Version 01 Security Target", [6] and [8]. The complete hardware description and the complete instruction set of the Renesas Renesas RS47X integrated circuit version 01 can be found in the "RS47X User's Manual", [14] and publicly available "H8S/2600 Series, H8S/2000 Series Software Manual, Revision 4.00", [17].

The implementation of the TOE Security Functionality basically consists of the components 32-bit CPU, DES/3DES co-processor, AES co-processor, Random Number Generator, system control logic, and security circuitry implemented in the analogue circuitry as well as in the random logic circuitries, that include security sensors. The contactless interface detects the related contactless communication protocols automatically. The security measures for physical protection are realized within the layout of the whole circuitry.

Beside the security functionalities, the TOE is equipped with the CRC coprocessor, the contactless interface circuitry, the UART, the interval timers, the pseudo-random number generator, the modular multiplication coprocessor, and the watchdog timer. Although those modules are required for the functionality of the TOE, the security of the TOE does not depend on those modules.

The smart card embedded support software "DES/AES Library of RS-4" is delivered as object code to the customer, who has to use the library when triple-DES or AES are required.

#### 6 Documentation

The evaluated documentation as outlined in table 2 is being provided with the product to the customer. This documentation contains the required information for secure usage of the TOE in accordance with the Security Target.

Additional obligations and notes for secure usage of the TOE as outlined in chapter 10 of this report have to be followed.

# 7 IT Product Testing

The tests performed by the developer can be divided into the following categories:

- tests which are performed in a simulation environment with different tools for the analogue circuitries and for the digital parts of the TOE,
- characterisation and verification tests to release the hardware platform for production including tests with different operating conditions as well as special verification tests for security features of the hardware,

functional tests at the end of the production process using IC Dedicated Test Software.
 These tests are executed for every chip to check its correct functionality as a last step of phase 3,

- design tool checks (layout versus schematic), and
- verification tests carried out to verify the functionality and quality of the related property

Additional tests are carried out when the module production (COT) is completed, however the tests are limited to confirm the functionality after the COT production. The developer tests cover all TSFIs as identified in the functional specification as well as in the test documentation.

The evaluators repeated the tests of the developer by sampling. A test protocol of the tests provided by the developer was verified. In addition the evaluators performed independent tests to supplement, augment and to verify the tests performed by the developer. The tests of the evaluators comprise special tests and examination of the hardware platform using open samples.

The evaluation provides evidence that the actual version of the TOE provides the TOE Security Functionality as specified by the developer. The test results confirm the correct implementation of the TOE Security Functionality.

For penetration testing the evaluators took all TOE Security Functionality into consideration. Extensive penetration testing was performed to test the security mechanisms used to provide the Security Services and Security Features. The tests for the hardware platform comprise the use of bespoke equipment and expert knowledge. The penetration tests considered both the physical tampering of the hardware platform and attacks which do not modify the hardware platform physically. The support of attacks by reverse engineering was also considered. The test of the hardware platform comprises attacks that must be averted by the combination of the hardware platform and the Security IC Embedded Software as well as attacks against the hardware platform directly. In addition side channel analysis was performed for the DES/3DES and AES co-processor including the supporting software DES/AES Library for RS-4 and the RCL.

# 8 Evaluated Configuration

The TOE is Renesas' Cryptographic Library v5126 running on Renesas' certified product hardware platform (RS47X) without any Security IC Embedded Software. The hardware platform Renesas RS47X integrated circuit version 01 was certified under the certification-ID BSI-DSZ-CC-0705-2011 (see [19]). The TOE is intended to be used by the secure application software (Security IC Embedded Software), which is not in scope of the evaluation, however responsible for the proper use of the TOE. The hardware platform requires the implementation of the RNG on-line test software, which is implemented as a security functionality of the TOE. The hardware platform includes the "DES/AES Library for RS-4", that is also implemented in the TOE. The RCL on RS47X serves supports the development of Security IC Embedded Software.

#### 9 Results of the Evaluation

#### 9.1 CC specific results

The Evaluation Technical Report (ETR) [9] was provided by the ITSEF according to the Common Criteria [1], the Methodology [2], the requirements of the Scheme [3] and all interpretations and guidelines of the Scheme (AIS) [4] as relevant for the TOE.

The Evaluation Methodology CEM [2] was used for those components up to EAL5 extended by advice of the Certification Body for components beyond EAL 5 and guidance specific for the technology of the product [4] (AIS 34).

The following guidance specific for the technology was used:

- Supporting Document Mandatory Technical Document, The Application of CC to Integrated Circuits
- Supporting Document Mandatory Technical Document, Application of Attack Potential to Smartcards
- Supporting Document Guidance, Smartcard Evaluation (see [4], AIS 25, AIS 26, AIS 37).

For RNG assessment the scheme interpretations AIS 20 and AIS 31 were used (see [4]).

To support composite evaluations according to AIS 36 the document ETR for composite evaluation [10] was provided and approved. This document provides details of this platform evaluation that have to be considered in the course of a composite evaluation on top.

The assurance refinements outlined in the Security Target were followed in the course of the evaluation of the TOE.

As a result of the evaluation the verdict PASS is confirmed for the following assurance components:

- All components of the EAL 5 package including the class ASE as defined in the CC (see also part C of this report)
- The components ALC\_DVS.2, AVA\_VAN.5 augmented for this TOE evaluation.

As the evaluation work performed for this certification procedure was carried out as a reevaluation based on the certificate BSI-DSZ-CC-0735-2011, re-use of specific evaluation tasks was possible. The focus of this re-evaluation was on vulnerability analysis, testing and penetration testing.

The evaluation has confirmed:

• PP Conformance: Security IC Platform Protection Profile,

Version 1.0, 15 June 2007, BSI-CC-PP-0035-2007 [10]

• for the Functionality: PP conformant plus product specific extensions

Common Criteria Part 2 extended

• for the Assurance: Common Criteria Part 3 conformant

EAL 5 augmented by ALC DVS.2, AVA VAN.5

For specific evaluation results regarding the development and production environment see annex B in part D of this report.

The results of the evaluation are only applicable to the TOE as defined in chapter 2 and the configuration as outlined in chapter 8 above.

#### 9.2 Results of cryptographic assessment

The vulnerability assessment results as stated within this certificate do not include a rating for those cryptographic algorithms and their implementation suitable for encryption and decryption (see BSIG Section 9, Para. 4, Clause 2). This holds for:

the TOE Security functionality SF.DES, SF.AES, SF.Hash and SF.MMCopro

The strength of the cryptographic algorithms was not rated in the course of this certification procedure (see BSIG Section 4, Para. 3, Clause 2). But Cryptographic Functionalities with a security level of 80 bits or lower can no longer be regarded as secure against attacks with high attack potential without considering the application context. Therefore for this functionalities it shall be checked whether the related crypto operations are appropriate for the intended system. Some further hints and guidelines can be derived from the 'Technische Richtlinie BSI TR-02102' (<a href="https://www.bsi.bund.de">https://www.bsi.bund.de</a>).

The Cryptographic Functionalities 2-key Triple DES (2TDES) and RSA 1024 provided by the TOE achieves a security level of maximum 80 Bits (in general context).

# 10 Obligations and Notes for the Usage of the TOE

The documents as outlined in table 2 contain necessary information about the usage of the TOE and all security hints therein have to be considered. In addition all aspects of Assumptions, threats and policies as outlined in the Security Target not covered by the TOE itself need to be fulfilled by the operational environment of the TOE.

The customer or user of the product shall consider the results of the certification within his system risk management process. In order for the evolution of attack methods and techniques to be covered, he should define the period of time until a re-assessment for the TOE is required and thus requested from the sponsor of the certificate.

The limited validity for the usage of cryptograhic algorithms as outlined in chapter 9 has to be considered by the user and his system risk management process.

Some security measures are partly implemented in the hardware and require additional configuration or control or measures to be implemented by the IC Dedicated Support Software or Embedded Software.

For this reason the TOE includes guidance documentation (see table 2) which contains guidelines for the developer of the IC Dedicated Support Software and Embedded Software on how to securely use the microcontroller chip and which measures have to be implemented in the software in order to fulfil the security requirements of the Security Target of the TOE.

In the course of the evaluation of the composite product or system it must be examined if the required measures have been correctly and effectively implemented by the software. Additionally, the evaluation of the composite product or system must also consider the evaluation results as outlined in the document ETR for composite evaluation [10].

If the user decides to use other software countermeasures instead of the DES/AES Library for RS-4 or the RCL, the composite evaluator is required to evaluate the resistance of the algorithms against SCA and DFA. The other smart card embedded support software "RNG online-test Software" is printed out in [14]. The user is required to implement the software.

# 11 Security Target

For the purpose of publishing, the Security Target [8] of the Target of Evaluation (TOE) is provided within a separate document as Annex A of this report. It is a sanitised version of the complete Security Target [6] used for the evaluation performed. Sanitisation was performed according to the rules as outlined in the relevant CCRA policy (see AIS 35 [4])

#### 12 Definitions

## 12.1 Acronyms

**3DES** Triple Data Encryption Standard **AES** Advanced Encryption Standard

AIS Application Notes and Interpretations of the Scheme

BSI Bundesamt für Sicherheit in der Informationstechnik / Federal Office for

Information Security, Bonn, Germany

**BSIG** BSI-Gesetz / Act on the Federal Office for Information Security

CBC Cipher Block Chaining. A mode of DES & AES encryption

CCRA Common Criteria Recognition ArrangementCC Common Criteria for IT Security Evaluation

**CEM** Common Methodology for Information Technology Security Evaluation

**COT** Chip on Tape

CPU Central processing unit

DES Data Encryption Standard

EAL Evaluation Assurance Level

**ECB** Electronic Codebook. A mode of DES & AES encryption. **EEPROM** Electrically Erasable Programmable Read-Only Memory

**ETR** Evaluation Technical Report

**HW** Hardware

IT Information Technology

ITSEC Information Technology Security Evaluation Criteria
ITSEF Information Technology Security Evaluation Facility

MMC Modular Multiplication Coprocessor

**PP** Protection Profile

**RCL** Renesas Cryptographic Library

**ROM** Read-Only Memory

**SAR** Security Assurance Requirement

**SFP** Security Function Policy

**SFR** Security Functional Requirement

**ST** Security Target

**SW** Software

**TOE** Target of Evaluation

**TSF** TOE Security Functionalities

**UART** Universal Asynchronous Receiver Transmitter

### 12.2 Glossary

**Augmentation** - The addition of one or more requirement(s) to a package.

**Extension** - The addition to an ST or PP of functional requirements not contained in part 2 and/or assurance requirements not contained in part 3 of the CC.

**Formal** - Expressed in a restricted syntax language with defined semantics based on well-established mathematical concepts.

Informal - Expressed in natural language.

**Object** - An passive entity in the TOE, that contains or receives information, and upon which subjects perform operations.

**Protection Profile** - An implementation-independent statement of security needs for a TOE type.

**Security Target** - An implementation-dependent statement of security needs for a specific identified TOE.

**Semiformal** - Expressed in a restricted syntax language with defined semantics.

**Subject** - An active entity in the TOE that performs operations on objects.

**Target of Evaluation** - A set of software, firmware and/or hardware possibly accompanied by guidance.

**TOE Security Functionality** - combined functionality of all hardware, software, and firmware of a TOE that must be relied upon for the correct enforcement of the SFRs

#### 13 **Bibliography**

[1] Common Criteria for Information Technology Security Evaluation, Version 3.1,

- Part 1: Introduction and general model, Revision 3, July 2009
- Part 2: Security functional components, Revision 3, July 2009
- Part 3: Security assurance components, Revision 3, July 2009
- [2] Common Methodology for Information Technology Security Evaluation (CEM), Evaluation Methodology, Version 3.1, Rev. 3, July 2009
- BSI certification: Procedural Description (BSI 7125) [3]
- Application Notes and Interpretations of the Scheme (AIS) as relevant for the TOE<sup>8</sup>. [4]
- [5] German IT Security Certificates (BSI 7148), periodically updated list published also in the BSI Website
- [6] Security Target BSI-DSZ-CC-0774-2011, Version 5524, 21.07.2011, RCL on RS47X Version 01 Security Target, Renesas Europe Ltd. (confidential document)
- [7] Security IC Platform Protection Profile, Version 1.0, 15 June 2007, BSI-CC-PP-0035-2007
- [8] Security Target BSI-DSZ-CC-0774-2011, Version 1.1, 21.7.2011, RCL on RS47X Version 01 Security Target Public Version, Renesas Europe Ltd. (sanitised public document)
- [9] Evaluation Technical Report BSI-DSZ-CC-0774, Version 1.0. 19.09.2011, T-Systems GEI GmbH, (confidential document)
- [10] ETR for composite evaluation according to AIS 36 for the Product Renesas RS47X integrated circuit version 01, Version 1.0, 22.7.2011, T-Systems GEI GmbH (confidential document)

#### 8specifically

- AIS 20, Version 1, 2. December 1999, Funktionalitätsklassen und Evaluationsmethodologie für deterministische Zufallszahlengeneratoren
- AIS 25, Version 7, 30.6.2011, Anwendung der CC auf Integrierte Schaltungen including JIL Document and CC Supporting Document
- AIS 26, Version 8, 08.6.2011, Evaluationsmethodologie für in Hardware integrierte Schaltungen including JIL Document and CC Supporting Document
- AIS 31, Version 1, 25 Sept. 2001 Funktionalitätsklassen und Evaluationsmethodologie für physikalische Zufallszahlengeneratoren
- AIS 32, Version 6, 3 August 2010, CC-Interpretationen im deutschen Zertifizierungsschema
- AIS 34, Version 3, 3 September 2009, Evaluation Methodology for CC Assurance Classes for EAL5+ (CCv2.3 & CCv3.1) and EAL6 (CCv3.1)
- AIS 35, Version 2.0, 12 November 2007, Öffentliche Fassung des Security Targets (ST-Lite) including JIL Document and CC Supporting Document and CCRA policies
- AIS 36, Version 3, 19 October 2010, Kompositionsevaluierung including JIL Document and CC Supporting Document
- AIS 38, Version 2.0, 28 September 2007, Reuse of evaluation results

[11] RCL on RS-4 Generic Configuration List, Version 5523, Date: 21.07.2011, Document Number D008710\_ALC, Renesas Electronics Europe Ltd. (confidential document)

- [12] RCL on RS47X-CC-VER, Version 5530, Document Number D008710\_VER, Renesas Electronics Europe Ltd., 21.07.2011 (confidential document)
- [13] Renesas Cryptographic Library (RCL), User's Manual: Software, Renesas Secure Microcomputer RS-4 Series, Version 5126 (RCL2.1), Rev.1.20, CM\_Doc\_ID: 5317, Renesas Electronics Corporation, 22.03.2011
- [14] RS-4 dual-way Series User Guidance Manual, Revision 1.4, Renesas Electronics Corporation, July 2011
- [15] RS47X User's Manual: Hardware, Renesas Secure Microcomputer RS-4 Series, Rev. 1.10, Renesas Electronics Corporation, September 14, 2010
- [16] Option List for Smart Card Microcomputer (for RS47X), Revision 1.1, Rev. 14985, Renesas Electronics Corporation, 24 June 2011
- [17] H8S/2600 Series, H8S/2000 Series Software Manual, Revision 4.00, Renesas Technology Corp., 24 February 2006
- [18] Certification Report BSI-DSZ-CC-0735-2011 for Renesas RS47X integrated circuit version 01 from Renesas Electronics Corp., 21 July 2011, Federal Office for Information Security
- [19] Certification Report BSI-DSZ-CC-0705-2011 for Renesas Cryptographic Library v5126 running on the RS46X from Renesas Electronics Corp., 20 July 2011, Federal Office for Information Security

This page is intentionally left blank.

# **C** Excerpts from the Criteria

CC Part1:

**Conformance Claim** (Release 3 = chapter 10.4)

"The conformance claim indicates the source of the collection of requirements that is met by a PP or ST that passes its evaluation. This conformance claim contains a CC conformance claim that:

- describes the version of the CC to which the PP or ST claims conformance.
- describes the conformance to CC Part 2 (security functional requirements) as either:
  - CC Part 2 conformant A PP or ST is CC Part 2 conformant if all SFRs in that PP or ST are based only upon functional components in CC Part 2, or
  - CC Part 2 extended A PP or ST is CC Part 2 extended if at least one SFR in that PP or ST is not based upon functional components in CC Part 2.
- describes the conformance to CC Part 3 (security assurance requirements) as either:
  - CC Part 3 conformant A PP or ST is CC Part 3 conformant if all SARs in that PP or ST are based only upon assurance components in CC Part 3, or
  - CC Part 3 extended A PP or ST is CC Part 3 extended if at least one SAR in that PP or ST is not based upon assurance components in CC Part 3.

Additionally, the conformance claim may include a statement made with respect to packages, in which case it consists of one of the following:

- Package name Conformant A PP or ST is conformant to a pre-defined package (e.g. EAL) if:
  - the SFRs of that PP or ST are identical to the SFRs in the package, or
  - the SARs of that PP or ST are identical to the SARs in the package.
- Package name Augmented A PP or ST is an augmentation of a predefined package if:
  - the SFRs of that PP or ST contain all SFRs in the package, but have at least one additional SFR or one SFR that is hierarchically higher than an SFR in the package.
  - the SARs of that PP or ST contain all SARs in the package, but have at least one additional SAR or one SAR that is hierarchically higher than an SAR in the package.

Note that when a TOE is successfully evaluated to a given ST, any conformance claims of the ST also hold for the TOE. A TOE can therefore also be e.g. CC Part 2 conformant.

Finally, the conformance claim may also include two statements with respect to Protection Profiles:

- PP Conformant A PP or TOE meets specific PP(s), which are listed as part of the conformance result.
- Conformance Statement (Only for PPs) This statement describes the manner in which PPs or STs must conform to this PP: strict or demonstrable. For more information on this Conformance Statement, see Annex D."

#### CC Part 3:

#### Class APE: Protection Profile evaluation (chapter 10)

"Evaluating a PP is required to demonstrate that the PP is sound and internally consistent, and, if the PP is based on one or more other PPs or on packages, that the PP is a correct instantiation of these PPs and packages. These properties are necessary for the PP to be suitable for use as the basis for writing an ST or another PP.

Assurance Class	Assurance Components				
Class APE: Protection Profile evaluation	APE_INT.1 PP introduction				
	APE_CCL.1 Conformance claims				
	APE_SPD.1 Security problem definition				
	APE_OBJ.1 Security objectives for the operational environment APE_OBJ.2 Security objectives				
	APE_ECD.1 Extended components definition				
	APE_REQ.1 Stated security requirements APE_REQ.2 Derived security requirements				

APE: Protection Profile evaluation class decomposition"

### Class ASE: Security Target evaluation (chapter 11)

"Evaluating an ST is required to demonstrate that the ST is sound and internally consistent, and, if the ST is based on one or more PPs or packages, that the ST is a correct instantiation of these PPs and packages. These properties are necessary for the ST to be suitable for use as the basis for a TOE evaluation."

Assurance Class	Assurance Components				
	ASE_INT.1 ST introduction				
	ASE_CCL.1 Conformance claims				
Class ASE: Security	ASE_SPD.1 Security problem definition				
Target evaluation	ASE_OBJ.1 Security objectives for the operational environment ASE_OBJ.2 Security objectives				
	ASE_ECD.1 Extended components definition				
	ASE_REQ.1 Stated security requirements ASE_REQ.2 Derived security requirements				
	ASE_TSS.1 TOE summary specification ASE_TSS.2 TOE summary specification with architectural design summary				

ASE: Security Target evaluation class decomposition

# **Security assurance components** (chapter 7)

"The following Sections describe the constructs used in representing the assurance classes, families, and components."

The following table shows the assurance class decomposition.

Assurance Class	Assurance Components			
ADV: Development	ADV_ARC.1 Security architecture description			
	ADV_FSP.1 Basic functional specification ADV_FSP.2 Security-enforcing functional specification ADV_FSP.3 Functional specification with complete summary ADV_FSP.4 Complete functional specification ADV_FSP.5 Complete semi-formal functional specification with additional error information ADV_FSP.6 Complete semi-formal functional specification with additional formal specification			
	ADV_IMP.1 Implementation representation of the TSF ADV_IMP.2 Implementation of the TSF			
	ADV_INT.1 Well-structured subset of TSF internals ADV_INT.2 Well-structured internals ADV_INT.3 Minimally complex internals			
	ADV_SPM.1 Formal TOE security policy model			
	ADV_TDS.1 Basic design ADV_TDS.2 Architectural design ADV_TDS.3 Basic modular design ADV_TDS.4 Semiformal modular design ADV_TDS.5 Complete semiformal modular design ADV_TDS.6 Complete semiformal modular design with formal high-level design presentation			

<sup>&</sup>quot;Each assurance class contains at least one assurance family."

<sup>&</sup>quot;Each assurance family contains one or more assurance components."

Assurance Class	Assurance Components					
AGD:	AGD_OPE.1 Operational user guidance					
Guidance documents	AGD_PRE.1 Preparative procedures					
	ALC_CMC.1 Labelling of the TOE ALC_CMC.2 Use of a CM system ALC_CMC.3 Authorisation controls ALC_CMC.4 Production support, acceptance procedures and automation ALC_CMC.5 Advanced support					
ALC: Life cycle support	ALC_CMS.1 TOE CM coverage ALC_CMS.2 Parts of the TOE CM coverage ALC_CMS.3 Implementation representation CM coverage ALC_CMS.4 Problem tracking CM coverage ALC_CMS.5 Development tools CM coverage					
	ALC_DEL.1 Delivery procedures					
	ALC_DVS.1 Identification of security measures ALC_DVS.2 Sufficiency of security measures					
	ALC_FLR.1 Basic flaw remediation ALC_FLR.2 Flaw reporting procedures ALC_FLR.3 Systematic flaw remediation					
	ALC_LCD.1 Developer defined life-cycle model ALC_LCD.2 Measurable life-cycle model					
	ALC_TAT.1 Well-defined development tools ALC_TAT.2 Compliance with implementation standards ALC_TAT.3 Compliance with implementation standards - all parts					
	ATE_COV.1 Evidence of coverage ATE_COV.2 Analysis of coverage ATE_COV.3 Rigorous analysis of coverage					
ATE: Tests	ATE_DPT.1 Testing: basic design ATE_DPT.2 Testing: security enforcing modules ATE_DPT.3 Testing: modular design ATE_DPT.4 Testing: implementation representation					
	ATE_FUN.1 Functional testing ATE_FUN.2 Ordered functional testing					
	ATE_IND.1 Independent testing – conformance ATE_IND.2 Independent testing – sample ATE_IND.3 Independent testing – complete					
AVA: Vulnerability assessment	AVA_VAN.1 Vulnerability survey AVA_VAN.2 Vulnerability analysis AVA_VAN.3 Focused vulnerability analysis AVA_VAN.4 Methodical vulnerability analysis AVA_VAN.5 Advanced methodical vulnerability analysis					

Assurance class decomposition

#### **Evaluation assurance levels** (chapter 8)

"The Evaluation Assurance Levels (EALs) provide an increasing scale that balances the level of assurance obtained with the cost and feasibility of acquiring that degree of assurance. The CC approach identifies the separate concepts of assurance in a TOE at the end of the evaluation, and of maintenance of that assurance during the operational use of the TOE.

It is important to note that not all families and components from CC Part 3 are included in the EALs. This is not to say that these do not provide meaningful and desirable assurances. Instead, it is expected that these families and components will be considered for augmentation of an EAL in those PPs and STs for which they provide utility."

#### Evaluation assurance level (EAL) overview (chapter 8.1)

"Table 1 represents a summary of the EALs. The columns represent a hierarchically ordered set of EALs, while the rows represent assurance families. Each number in the resulting matrix identifies a specific assurance component where applicable.

As outlined in the next Section, seven hierarchically ordered evaluation assurance levels are defined in the CC for the rating of a TOE's assurance. They are hierarchically ordered inasmuch as each EAL represents more assurance than all lower EALs. The increase in assurance from EAL to EAL is accomplished by substitution of a hierarchically higher assurance component from the same assurance family (i.e. increasing rigour, scope, and/or depth) and from the addition of assurance components from other assurance families (i.e. adding new requirements).

These EALs consist of an appropriate combination of assurance components as described in Chapter 7 of this CC Part 3. More precisely, each EAL includes no more than one component of each assurance family and all assurance dependencies of every component are addressed.

While the EALs are defined in the CC, it is possible to represent other combinations of assurance. Specifically, the notion of "augmentation" allows the addition of assurance components (from assurance families not already included in the EAL) or the substitution of assurance components (with another hierarchically higher assurance component in the same assurance family) to an EAL. Of the assurance constructs defined in the CC, only EALs may be augmented. The notion of an "EAL minus a constituent assurance component" is not recognised by the standard as a valid claim. Augmentation carries with it the obligation on the part of the claimant to justify the utility and added value of the added assurance component to the EAL. An EAL may also be augmented with extended assurance requirements.

Assurance Class	Assurance Family	Assurance Components by Evaluation Assurance Level						
		EAL1	EAL2	EAL3	EAL4	EAL5	EAL6	EAL7
Development	ADV_ARC		1	1	1	1	1	1
	ADV_FSP	1	2	3	4	5	5	6
	ADV_IMP				1	1	2	2
	ADV_INT					2	3	3
	ADV_SPM						1	1
	ADV_TDS		1	2	3	4	5	6
Guidance	AGD_OPE	1	1	1	1	1	1	1
Documents	AGD_PRE	1	1	1	1	1	1	1
Life cycle	ALC_CMC	1	2	3	4	4	5	5
Support	ALC_CMS	1	2	3	4	5	5	5
	ALC_DEL		1	1	1	1	1	1
	ALC_DVS			1	1	1	2	2
	ALC_FLR							
	ALC_LCD			1	1	1	1	2
	ALC_TAT				1	2	3	3
Security Target	ASE_CCL	1	1	1	1	1	1	1
Evaluation	ASE_ECD	1	1	1	1	1	1	1
	ASE_INT	1	1	1	1	1	1	1
	ASE_OBJ	1	2	2	2	2	2	2
	ASR_REQ	1	2	2	2	2	2	2
	ASE_SPD		1	1	1	1	1	1
	ASE_TSS	1	1	1	1	1	1	1
Tests	ATE_COV		1	2	2	2	3	3
	ATE_DPT			1	1	3	3	4
	ATE_FUN		1	1	1	1	2	2
	ATE_IND	1	2	2	2	2	2	3
Vulnerability assessment	AVA_VAN	1	2	2	3	4	5	5

Table 1: Evaluation assurance level summary"

### Evaluation assurance level 1 (EAL1) - functionally tested (chapter 8.3)

### "Objectives

EAL1 is applicable where some confidence in correct operation is required, but the threats to security are not viewed as serious. It will be of value where independent assurance is required to support the contention that due care has been exercised with respect to the protection of personal or similar information.

EAL1 requires only a limited security target. It is sufficient to simply state the SFRs that the TOE must meet, rather than deriving them from threats, OSPs and assumptions through security objectives.

EAL1 provides an evaluation of the TOE as made available to the customer, including independent testing against a specification, and an examination of the guidance documentation provided. It is intended that an EAL1 evaluation could be successfully conducted without assistance from the developer of the TOE, and for minimal outlay.

An evaluation at this level should provide evidence that the TOE functions in a manner consistent with its documentation."

### Evaluation assurance level 2 (EAL2) - structurally tested (chapter 8.4)

#### "Objectives

EAL2 requires the co-operation of the developer in terms of the delivery of design information and test results, but should not demand more effort on the part of the developer than is consistent with good commercial practise. As such it should not require a substantially increased investment of cost or time.

EAL2 is therefore applicable in those circumstances where developers or users require a low to moderate level of independently assured security in the absence of ready availability of the complete development record. Such a situation may arise when securing legacy systems, or where access to the developer may be limited."

# **Evaluation assurance level 3 (EAL3) - methodically tested and checked** (chapter 8.5) "Objectives

EAL3 permits a conscientious developer to gain maximum assurance from positive security engineering at the design stage without substantial alteration of existing sound development practises.

EAL3 is applicable in those circumstances where developers or users require a moderate level of independently assured security, and require a thorough investigation of the TOE and its development without substantial re-engineering."

# Evaluation assurance level 4 (EAL4) - methodically designed, tested, and reviewed (chapter 8.6)

"Objectives

EAL4 permits a developer to gain maximum assurance from positive security engineering based on good commercial development practises which, though rigorous, do not require substantial specialist knowledge, skills, and other resources. EAL4 is the highest level at which it is likely to be economically feasible to retrofit to an existing product line.

EAL4 is therefore applicable in those circumstances where developers or users require a moderate to high level of independently assured security in conventional commodity TOEs and are prepared to incur additional security-specific engineering costs."

# **Evaluation assurance level 5 (EAL5) - semiformally designed and tested** (chapter 8.7) "Objectives

EAL5 permits a developer to gain maximum assurance from security engineering based upon rigorous commercial development practises supported by moderate application of specialist security engineering techniques. Such a TOE will probably be designed and developed with the intent of achieving EAL5 assurance. It is likely that the additional costs attributable to the EAL5 requirements, relative to rigorous development without the application of specialised techniques, will not be large.

EAL5 is therefore applicable in those circumstances where developers or users require a high level of independently assured security in a planned development and require a rigorous development approach without incurring unreasonable costs attributable to specialist security engineering techniques."

# Evaluation assurance level 6 (EAL6) - semiformally verified design and tested (chapter 8.8)

"Objectives

EAL6 permits developers to gain high assurance from application of security engineering techniques to a rigorous development environment in order to produce a premium TOE for protecting high value assets against significant risks.

EAL6 is therefore applicable to the development of security TOEs for application in high risk situations where the value of the protected assets justifies the additional costs."

# Evaluation assurance level 7 (EAL7) - formally verified design and tested (chapter 8.9)

"Objectives

EAL7 is applicable to the development of security TOEs for application in extremely high risk situations and/or where the high value of the assets justifies the higher costs. Practical application of EAL7 is currently limited to TOEs with tightly focused security functionality that is amenable to extensive formal analysis."

#### Class AVA: Vulnerability assessment (chapter 16)

"The AVA: Vulnerability assessment class addresses the possibility of exploitable vulnerabilities introduced in the development or the operation of the TOE."

## Vulnerability analysis (AVA\_VAN) (chapter 16.1)

### "Objectives

Vulnerability analysis is an assessment to determine whether potential vulnerabilities identified, during the evaluation of the development and anticipated operation of the TOE or by other methods (e.g. by flaw hypotheses or quantitative or statistical analysis of the security behaviour of the underlying security mechanisms), could allow attackers to violate the SFRs.

Vulnerability analysis deals with the threats that an attacker will be able to discover flaws that will allow unauthorised access to data and functionality, allow the ability to interfere with or alter the TSF, or interfere with the authorised capabilities of other users."

This page is intentionally left blank

# **D** Annexes

# List of annexes of this certification report

Annex A: Security Target provided within a separate document.

Annex B: Evaluation results regarding development

and production environment

This page is intentionally left blank.

# Annex B of Certification Report BSI-DSZ-CC-0774-2011

# Evaluation results regarding development and production environment



The IT product Renesas Cryptographic Library, v5126 on Renesas RS47X security integrated circuit Version 01 (Target of Evaluation, TOE) has been evaluated at an approved evaluation facility using the Common Methodology for IT Security Evaluation (CEM), Version 3.1 extended by advice of the Certification Body for components beyond EAL 5 and guidance specific for the technology of the product for conformance to the Common Criteria for IT Security Evaluation (CC), Version 3.1.

As a result of the TOE certification, dated 22 September 2011, the following results regarding the development and production environment apply. The Common Criteria assurance requirements ALC – Life cycle support (i.e. ALC\_CMC.4, ALC\_CMS.5, ALC\_DEL.1, ALC\_DVS.2, ALC\_LCD.1, ALC\_TAT.2)

are fulfilled for the development and production sites of the TOE listed below:

- a) Renesas Electronics Corporation, 5-20-1, Jousuihon-cho, Kodaira-shi, Tokyo 187-8588, Japan (development and customer support)
- b) Renesas Electronics Europe Ltd., Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5FH, U.K. (development, testing and customer support)
- c) Renesas Electronics Corporation Naka Factory, 751 Horiguchi, Hitachinakashi, Ibaraki 312-0034, Japan (semiconductor factory)
- d) Dai Nippon Printing Co., Ltd., 2-2-1 Fukuoka, Fujimino-shi, Saitama 356-8507, Japan (mask shop)
- e) Renesas Electronics Corporation Kofu site, 4617 Nishiyahata, Kai-shi, Yamanashi 400-0117, Japan (test center)
- f) Toyo Electronics Co., Ltd., 2781-1, Shimosone-cho, Kofu-shi, Yamanashi, 400-1508, Japan (test center)
- g) Renesas Musashi Engineering Service Co., Ltd., 5-22-1 Jousuihon-cho, Kodaira-shi, Tokyo 187-8522, Japan (ROM handling)
- h) MTEX Matsumura Corp., 2-2-2 Kitamachi, Obanazawa-shi, Yamagata 999-4231, Japan (module assembly)
- i) The Apollo Electronics Co., Ltd., 610 Shimoimasuwa, Minami-alps-shi, Yamanashi, 400-0212, Japan (back grinding)
- j) Enzan Factory Co., Ltd., 276 Enzanshimoozo, Koshu-shi, Yamanashi, 404-0043, Japan (wafer dicing)
- k) Renesas Electronics Europe GmbH, Karl-Hammerschmidt-Str. 42, 85609 Aschheim-Dornach, Germany (development and testing)

For the sites listed above, the requirements have been specifically applied in accordance with the Security Target [6]. The evaluators verified, that the threats, security objectives and requirements for the TOE life cycle phases up to delivery (as stated in the Security Target [6] and [8]) are fulfilled by the procedures of these sites.