



**HP LaserJet Enterprise M506 Printer Series, Color
LaserJet Enterprise M553 Printer Series,
LaserJet Enterprise M604 Printer Series, LaserJet
Enterprise M605 Printer Series, and LaserJet
Enterprise M606 Printer Series Firmware with
Jetdirect Inside Security Target**

Version:	2.0
Status:	Final
Last Update:	2015-09-28

Trademarks

The following term is a trademark of atsec information security corporation in the United States, other countries, or both:

- atsec®

The following terms are trademarks of The Institute of Electrical and Electronics Engineers, Incorporated in the United States, other countries, or both:

- 2600.2™
- IEEE®

The following term is a trademark of Massachusetts Institute of Technology (MIT) in the United States, other countries, or both:

- Kerberos™

The following terms are trademarks of Microsoft Corporation in the United States, other countries, or both:

- Microsoft®
- Windows®

The following term is a trademark of SafeNet, Inc. in the United States, other countries, or both:

- SafeNet®

Legal Notices

This document is provided AS IS with no express or implied warranties. Use the information in this document at your own risk.

This document may be reproduced or distributed in any form without prior permission provided the copyright notice is retained on all copies. Modified versions of this document may be freely distributed provided that they are clearly identified as such, and this copyright is included intact.

Revision History

Revision	Date	Author(s)	Changes to Previous Revision
2.0	2015-09-28	Gerardo Colunga (HP Inc.), Scott Chapman (atsec)	Final ST.

Table of Contents

1	Introduction.....	8
1.1	Security Target Identification	8
1.2	TOE Identification.....	8
1.3	TOE Type.....	8
1.4	TOE Overview.....	8
1.4.1	Required and optional non-TOE hardware, software, and firmware.....	9
1.4.2	Intended method of use.....	10
1.5	TOE Description.....	11
1.5.1	TOE architecture	11
1.5.2	TOE security functionality (TSF) summary.....	15
1.5.2.1	Auditing	15
1.5.2.2	Cryptography.....	15
1.5.2.3	Identification and authentication	15
1.5.2.4	Data protection and access control.....	17
1.5.2.5	Protection of the TSF.....	18
1.5.2.6	TOE access protection	19
1.5.2.7	Trusted channel communication and certificate management.....	19
1.5.2.8	User and access management	19
1.5.3	TOE boundaries	19
1.5.3.1	Physical.....	19
1.5.3.2	Logical.....	20
1.5.3.3	Evaluated configuration	20
1.5.4	Security policy model	21
1.5.4.1	Subjects/Users	21
1.5.4.2	Objects.....	22
1.5.4.3	SFR package functions.....	24
1.5.4.4	SFR package attributes	24
2	CC Conformance Claim	25
2.1	Protection Profile tailoring and additions.....	25
2.1.1	IEEE Std 2600.2-2009; "2600.2-PP, Protection Profile for Hardcopy Devices, Operational Environment B" (with NIAP CCEVS Policy Letter #20) ([PP2600.2]).....	25
2.1.2	SFR Package for Hardcopy Device Document Storage and Retrieval (DSR) Functions ([PP2600.2-DSR])	29
2.1.3	SFR Package for Hardcopy Device Print Functions ([PP2600.2-PRT]).....	29
2.1.4	SFR Package for Hardcopy Device Shared-medium Interface Functions ([PP2600.2-SMI])	29
3	Security Problem Definition	31
3.1	Introduction	31
3.2	Threat Environment.....	31
3.2.1	Threats countered by the TOE	31
3.3	Assumptions.....	32
3.3.1	Environment of use of the TOE	32
3.3.1.1	Physical.....	32
3.3.1.2	Personnel.....	32
3.3.1.3	Connectivity.....	32
3.4	Organizational Security Policies	32
3.4.1	Included in the PP2600.2 protection profile.....	32
3.4.2	In addition to the PP2600.2 protection profile.....	33
4	Security Objectives	34
4.1	Objectives for the TOE.....	34
4.2	Objectives for the Operational Environment.....	34
4.3	Security Objectives Rationale	35
4.3.1	Coverage.....	35
4.3.2	Sufficiency.....	37

5	Extended Components Definition	44
5.1	Class FPT: Protection of the TSF	44
5.1.1	Restricted forwarding of data to external interfaces (FDI)	44
5.1.1.1	FPT_FDI_EXP.1 - Restricted forwarding of data to external interfaces	44
6	Security Requirements	45
6.1	TOE Security Functional Requirements	45
6.1.1	Security audit (FAU)	48
6.1.1.1	Audit data generation (FAU_GEN.1)	48
6.1.1.2	User identity association (FAU_GEN.2)	49
6.1.2	Cryptographic support (FCS)	49
6.1.2.1	Cryptographic key generation (FCS_CKM.1)	49
6.1.2.2	Cryptographic key distribution (FCS_CKM.2)	50
6.1.2.3	Cryptographic operation (FCS_COP.1-ipsec)	50
6.1.2.4	Cryptographic operation (FCS_COP.1-job)	51
6.1.3	User data protection (FDP)	51
6.1.3.1	Common access control SFP (FDP_ACC.1-cac)	51
6.1.3.2	TOE function access control SFP (FDP_ACC.1-tfac)	52
6.1.3.3	Common access control functions (FDP_ACF.1-cac)	52
6.1.3.4	TOE function access control functions (FDP_ACF.1-tfac)	53
6.1.3.5	Subset residual information protection (FDP_RIP.1)	53
6.1.4	Identification and authentication (FIA)	53
6.1.4.1	Authentication failure handling (FIA_AFL.1)	53
6.1.4.2	Local user attribute definition (FIA_ATD.1)	55
6.1.4.3	Verification of secrets (FIA_SOS.1)	55
6.1.4.4	Timing of Control Panel authentication (FIA_UAU.1)	55
6.1.4.5	IPsec authentication before any action (FIA_UAU.2)	55
6.1.4.6	Control Panel protected authentication feedback (FIA_UAU.7)	55
6.1.4.7	Timing of Control Panel identification (FIA_UID.1)	56
6.1.4.8	IPsec identification before any action (FIA_UID.2)	56
6.1.4.9	User-subject binding (FIA_USB.1)	56
6.1.5	Security management (FMT)	56
6.1.5.1	Management of authentication security functions behavior (FMT_MOF.1)	56
6.1.5.2	Management of Permission Set security attributes (FMT_MSA.1-perm)	57
6.1.5.3	Management of TOE function security attributes (FMT_MSA.1-tfac)	57
6.1.5.4	Management of TSF data (FMT_MTD.1-auth)	57
6.1.5.5	Management of TSF data (FMT_MTD.1-users)	57
6.1.5.6	Specification of management functions (FMT_SMF.1)	57
6.1.5.7	Security roles (FMT_SMR.1)	58
6.1.6	Protection of the TSF (FPT)	58
6.1.6.1	Restricted forwarding of data to external interfaces (FPT_FDI_EXP.1)	58
6.1.6.2	Reliable time stamps (FPT_STM.1)	58
6.1.6.3	TSF testing (FPT_TST.1)	58
6.1.7	TOE access (FTA)	59
6.1.7.1	Control Panel TSF-initiated termination (FTA_SSL.3)	59
6.1.8	Trusted path/channels (FTP)	59
6.1.8.1	Inter-TSF trusted channel (FTP_ITC.1)	59
6.2	Security Functional Requirements Rationale	59
6.2.1	Coverage	59
6.2.2	Sufficiency	62
6.2.3	Security requirements dependency analysis	68
6.2.4	Internal consistency and mutual support of SFRs	71
6.3	Security Assurance Requirements	71
6.4	Security Assurance Requirements Rationale	73
7	TOE Summary Specification	74
7.1	TOE Security Functionality	74
7.1.1	Auditing	74
7.1.2	Cryptography	74
7.1.3	Identification and authentication (I&A)	75
7.1.3.1	Control Panel I&A	75
7.1.3.2	IPsec I&A	77

7.1.4	Data protection and access control	78
7.1.4.1	Permission Sets	78
7.1.4.2	Job PINs.....	78
7.1.4.3	Job Encryption Passwords	79
7.1.4.4	Common access control	79
7.1.4.5	TOE function access control.....	79
7.1.4.6	Residual information protection	80
7.1.5	Protection of the TSF	80
7.1.5.1	Restricted forwarding of data to external interfaces	80
7.1.5.2	TSF self-testing	81
7.1.5.3	Reliable timestamps	81
7.1.6	TOE access protection	81
7.1.6.1	Inactivity timeout.....	81
7.1.7	Trusted channel communication and certificate management	81
7.1.8	User and access management.....	83
8	Abbreviations, Terminology and References	85
8.1	Abbreviations	85
8.2	Terminology	87
8.3	References.....	88

List of Tables

Table 1: TOE Reference.....	9
Table 2: IPsec user mappings to allowed network protocols	16
Table 3: Users	21
Table 4: User Data	22
Table 5: TSF Data	23
Table 6: TSF Data Listing.....	24
Table 7: SFR package functions	24
Table 8: SFR package attributes.....	24
Table 9: SFR mappings between 2600.2 and the ST	28
Table 10: SFR mappings of non-PP2600.2 SFRs and the ST (in the ST, but not required by or hierarchical to SFRs in PP2600.2)	29
Table 11: SFR mappings between 2600.2-DSR and the ST	29
Table 12: SFR mappings between 2600.2-PRT and the ST.....	29
Table 13: SFR mappings between 2600.2-SMI and the ST.....	30
Table 14: Mapping of security objectives to threats and policies	36
Table 15: Mapping of security objectives for the Operational Environment to assumptions, threats and policies.....	37
Table 16: Sufficiency of objectives countering threats	39
Table 17: Sufficiency of objectives holding assumptions.....	41
Table 18: Sufficiency of objectives enforcing Organizational Security Policies	43
Table 19: Security functional requirements for the TOE	48
Table 20: Auditable events	49
Table 21: Cryptographic key generation	49
Table 22: Cryptographic key distribution	50
Table 23: Cryptographic operations	51
Table 24: Cryptographic operations	51
Table 25: Common Access Control SFP.....	52
Table 26: Simplified Account Lockout for each sign in method.....	55
Table 27: Mapping of security functional requirements to security objectives	62
Table 28: Security objectives for the TOE rationale.....	68
Table 29: TOE SFR dependency analysis	71
Table 30: Security assurance requirements.....	73
Table 31: Trusted channel connections	82

List of Figures

Figure 1: HCD physical diagram	11
Figure 2: HCD logical diagram	15

1 Introduction

1.1 Security Target Identification

Title: HP LaserJet Enterprise M506 Printer Series, Color LaserJet Enterprise M553 Printer Series, LaserJet Enterprise M604 Printer Series, LaserJet Enterprise M605 Printer Series, and LaserJet Enterprise M606 Printer Series Firmware with Jetdirect Inside Security Target

Version: 2.0

Status: Final

Date: 2015-05-06

Sponsor: HP Inc.

Developer: HP Inc.

Certification Body: CSEC

Certification ID: CSEC2015002

Keywords: HP Inc., HP, Color LaserJet, LaserJet, M506, M553, M604, M605, M606, hardcopy device, HCD, printer, Jetdirect Inside.

1.2 TOE Identification

The TOE is the HP LaserJet Enterprise M506 Printer Series, Color LaserJet Enterprise M553 Printer Series, LaserJet Enterprise M604 Printer Series, LaserJet Enterprise M605 Printer Series, and LaserJet Enterprise M606 Printer Series Firmware with Jetdirect Inside.

1.3 TOE Type

The TOE type is the internal firmware providing the functionality of a network printer.

1.4 TOE Overview

The TOE models are network printers designed to be shared by many client computers and users. These products are designed to meet the requirements of the [PP2600.2] protection profile in conjunction with [CCEVS-PL20] in the environment defined by these two documents (the Policy Letter modifies the requirements and environment).

The TOE contains functions for storing print jobs and printing print jobs received from networked computers. These hardcopy devices (HCDs), as they are called in [PP2600.2], are self-contained units that include processors, memory, networking, a storage drive, and a print engine. The operating system, web servers, and Control Panel applications (i.e., applications that run internally on the HCD) reside within the firmware of the HCD.

The TOE is the contents of the firmware with the exception of the operating system and the QuickSec cryptographic library (used by IPsec), which are part of the Operational Environment.

The printer models for which the firmware is evaluated are listed in the following table along with the evaluated firmware version numbers for each model:

Printer (HCD) Model	TOE Firmware Version
LaserJet Enterprise M506 Printer Series (M506n, M506dn, M506x)	System Firmware version: 2305076_518482 Jetdirect Inside version: JSI23500060
Color LaserJet Enterprise M553 Printer Series (M553n, M553dn, M553dh, M553x)	System Firmware version: 2305076_518484 Jetdirect Inside version: JSI23500060
LaserJet Enterprise M604 Printer Series (M604n, M604dn)	System Firmware version: 2305076_518485 Jetdirect Inside version: JSI23500060
LaserJet Enterprise M605 Printer Series (M605n, M605dn, M605dh, M605x)	System Firmware version: 2305076_518485 Jetdirect Inside version: JSI23500060
LaserJet Enterprise M606 Printer Series (M606dn, M606x)	System Firmware version: 2305076_518485 Jetdirect Inside version: JSI23500060

Table 1: TOE Reference

Each model provides the following security features:

- Auditing
- Cryptography
- Identification and authentication
- Data protection and access control
- Protection of the TSF (restricted forwarding, TSF self-testing, timestamps)
- TOE access protection (inactivity timeout)
- Trusted channel communication and certificate management
- User and access management

1.4.1 Required and optional non-TOE hardware, software, and firmware

The following *required* firmware components are considered part of the Operational Environment:

- Operating system (included in the firmware)
- QuickSec cryptographic library module (included in the firmware)

The hardware portion of the HP printer models is considered part of the Operational Environment. The TOE is evaluated on all of the HP printer models defined in [Table 1](#) and *requires* one of these models in order to run in the evaluated configuration.

The following *required* components are part of the Operational Environment:

- DNS server
- NTP server
- Syslog server

- WINS server
- One administrative client computer network connected to the TOE in the role of an Administrative Computer

The following *optional* components are part of the Operational Environment:

- HP Print Drivers, including the HP Universal Print Driver, for client computers (for submitting print job requests from client computers)
- HP Web Jetadmin administrative tool
- Windows domain controller/Kerberos server
- LDAP server
- Client computers network connected to the TOE in a non-administrative computer role
- SMB server for administrative backup and restore of customer-specific configuration settings and TSF data (local user account data)
- SMTP gateway
- Web browser

1.4.2 Intended method of use

[PP2600.2] is defined for a commercial information processing environment in which a moderate level of document security, network security, and security assurance are required.

The TOE is intended to be used in non-hostile, networked environments where TOE users have direct physical access to the HCDs for printing. The physical environment should be reasonably controlled and/or monitored where physical tampering of the HCDs would be evident and noticed.

The TOE can be connected to multiple client computers via a local area network using HP's Jetdirect Inside in the evaluated configuration. The evaluated configuration uses secure network mechanisms for communication between the network computers and the TOE. The TOE is managed by one designated administrative computer. The TOE is not intended to be connected to the Internet.

The evaluated configuration contains a built-in user identification and authentication database (a.k.a. sign in method) used for Local Device Sign In that is part of the TOE. It also supports a Windows domain controller (via Kerberos) for a feature called Windows Sign In and a Lightweight Directory Access Protocol (LDAP) authentication server for a feature called LDAP Sign In to identify and authenticate users. The Windows domain controller and LDAP server are part of the Operational Environment.

The evaluated configuration supports the optional HP Web Jetadmin administrative tool for managing the TOE. This tool uses the Hypertext Transfer Protocol (HTTP), Hypertext Markup Language (HTML), Simple Object Access Protocol (SOAP), Extensible Markup Language (XML), Open Extensibility Platform device layer (OXPD) Web Services, WS-* Web Services, and Simple Network Management Protocol (SNMP) to communicate to the TOE. (The Web Jetadmin administrative tool is part of the Operational Environment.) The evaluated configuration also supports the Embedded Web Server (EWS) interface for managing the TOE using a web browser over HTTP. (Web browsers are part of the Operational Environment.)

The Universal Serial Bus (USB) ports are disabled in the evaluated configuration.

At the top of this figure is the Administrative Computer which connects to the TOE using Internet Protocol Security (IPsec) with X.509v3 certificates for both mutual authentication and for protection of data from disclosure and alteration. This computer can administer the TOE using the following interfaces over the IPsec connection:

- Embedded Web Server (EWS)
- Simple Network Management Protocol (SNMP)
- Web Services:
 - Open Extensibility Platform device (OXPd) Web Services
 - WS-* Web Services

The HTTP-based EWS administrative interface allows administrators to remotely manage the features of the TOE using a web browser.

The Web Services allow administrators to manage the TOE using HP's Web Jetadmin application, which is part of the Operational Environment. The TOE supports both HP's Open Extensibility Platform device (OXPd) Web Services and certain WS-* Web Services (conforming to the WS-* standards defined by w3.org) accessed via the Simple Object Access Protocol (SOAP) and Extensible Markup Language (XML).

The SNMP network interface allows administrators to remotely manage the TOE using external SNMP-based administrative applications like the HP Web Jetadmin administrative tool.

Printer Job Language (PJL) is used in a non-administrative capacity by the Administrative Computer. The Administrative Computer uses PJL to send print jobs to the TOE as well as to receive job status. In general, PJL supports password protected administrative commands, but in the evaluated configuration these commands are disabled. For the purposes of this Security Target, we define the PJL Interface as PJL data sent to port 9100.

The TOE protects all network communications with Internet Protocol Security (IPsec), which is part of the embedded Jetdirect Inside firmware. Though IPsec supports multiple authentication methods, in the evaluated configuration, both ends of the IPsec connection are authenticated using X.509v3 certificates. An identity certificate for the TOE must be created outside the TOE, signed by a Certificate Authority (CA), and imported (added) into the TOE with the Certificate Authority's CA certificate.

Because IPsec authenticates the computers (IPsec authenticates the computer itself; IPsec does not authenticate the individual users of the computer), access to the Administrative Computer should be restricted to TOE administrators only.

The TOE distinguishes between the Administrative Computer and Network Client Computers by using IP addresses, IPsec, and the embedded Jetdirect Inside's internal firewall. In the evaluated configuration, the number of Administrative Computers used to manage the TOE is limited to one and the Device Administrator Password must be set.

The evaluated configuration supports the following SNMP versions:

- SNMPv1 read-only
- SNMPv2c read-only
- SNMPv3

Network Client Computers connect to the TOE using IPsec with X.509v3 certificates to protect the communication and to mutually authenticate. These client computers can send print jobs to the TOE using the PJL Interface as well as receive job status.

The TOE protects stored jobs with either a 4-digit Job PIN or by accepting (and storing) an encrypted job from a client computer. Both protection mechanisms are optional by default and are mutually exclusive of each other if used. In the evaluated configuration, every job must either be assigned a 4-digit Job PIN or be an encrypted job.

The TOE supports the Server Message Block (SMB) protocol. SMB is used by administrators to backup and restore customer-specific configuration settings and TSF data (local user account data). (It does not backup job files.) Only administrators can access the SMB through the TOE. The connection is protected using IPsec.

The TOE can send email alert messages to administrator-specified email addresses. In addition, the TOE's AutoSend feature can send automated emails regarding product configuration and printer supplies to HP. The TOE supports protected communications between the TOE and Simple Mail Transfer Protocol (SMTP) gateways. It uses IPsec with X.509v3 certificates to protect the communications and to mutually authenticate with the SMTP gateway. The TOE can only protect unencrypted email up to the SMTP gateway. It is the responsibility of the Operational Environment to protect emails from the SMTP gateway to the email's destination. Also, the TOE can only send emails; it does not accept inbound emails.

Each HCD contains a user interface called the Control Panel. The Control Panel is the physical interface that a user uses to communicate with the TOE when physically using the HCD. Model numbers that end with "n", "dn", or "dh" have a Control Panel with a 4-line LCD non-touchscreen display. Model numbers that end with "x" have a Control Panel with a 4.3-inch LCD touchscreen display. Each Control Panel has an "Easy Access" USB port which is disabled in the evaluated configuration. Each Control Panel also has a set of physical buttons whose quantities and functions vary between models. Users use the Control Panel to sign in to the TOE and perform functions such as accessing and printing stored print jobs. When a user signs in at the Control Panel, a Permission Set is associated with that user's session which determines the functions the user is permitted to perform.

The Control Panel supports both local and remote sign in methods. The local sign in method is called Local Device Sign In which supports individual user accounts. The user account information is maintained in the Local Device Sign In database within the TOE. The remote sign in methods are called LDAP Sign In and Windows Sign In (Kerberos). The TOE uses IPsec with X.509v3 certificates to protect both the LDAP and Kerberos communications.

The Print Engine in [Figure 1](#) converts electronic format into hardcopy.

All printer models contain a nonvolatile mass storage device (a.k.a. storage drive) that resides in the Operational Environment. The storage drive contains a section called Job Storage which is a user-visible file system where stored print jobs are stored/held. Depending on the printer model number, the storage drive is either an:

- Embedded MultiMediaCard (eMMC), or
- HP High Performance Secure Hard Disk

If the printer model contains an eMMC, all jobs in Job Storage are automatically deleted when the HCD is power-cycled. If the printer model contains an HP High Performance Secure Hard Disk, the jobs can persist across power-cycles or can be deleted, depending on how the administrator configures the TOE and on the job type. (Job types are discussed in [section 1.5.4.2](#).)

The TOE supports the auditing of security relevant functions by generating and forwarding audit records to a remote syslog server. The TOE uses IPsec with X.509v3 certificates to protect the communications between the TOE and the syslog server and to mutually authenticate the TOE and syslog server.

The Jetdirect Inside Firmware and HCD System Firmware components comprise the firmware on the system. They are shown as two separate components but they both share the same operating system (OS). The operating system is part of the Operational Environment. Both firmware components also contain an Embedded Web Server (EWS).

The Jetdirect Inside firmware includes SNMP, IPsec, a firewall, and the management functions for managing these network-related features. The Jetdirect Inside firmware also provides the network stack and drivers controlling the TOE's Ethernet interface.

The HCD System Firmware controls the overall functions of the TOE from the Control Panel to the storage drive to the print jobs.

Figure 2 shows the HCD boundary in grey and the firmware (TOE) boundary in blue (the TOE being comprised of the HCD System firmware and the Jetdirect Inside firmware excluding the underlying operating system and the QuickSec cryptographic library). The Jetdirect Inside firmware provides the network connectivity and network device drivers used by the HCD System firmware. The HCD System firmware and Jetdirect Inside firmware share the same operating system (which is part of the Operational Environment). The HCD System firmware also includes internal Control Panel applications that drive the functions of the TOE. Both firmware components work together to provide the security functionality defined in this document for the TOE.




Figure 2: HCD logical diagram

1.5.2 TOE security functionality (TSF) summary

1.5.2.1 Auditing

The TOE performs auditing of security relevant functions. Both the Jetdirect Inside and HCD System firmware generate audit records. The TOE connects and sends audit records to a syslog server for long-term storage and audit review. (The syslog server is part of the Operational Environment.)

1.5.2.2 Cryptography

The TOE uses IPsec to protect its communications channels. The QuickSec cryptographic library, which is part of the Operational Environment, is used to supply the cryptographic algorithms for IPsec. See [section 1.5.2.7](#) for more information.

The TOE supports the decrypting of print jobs encrypted using the Job Encryption Password. The decryption algorithm used by the TOE for this is included in the TOE. See [section 1.5.2.4](#) for more information.

Cryptography outside the scope of the TOE

This section exists to inform the reader that the HCD contains other cryptography that is outside the scope of the TOE, is **not** part of this evaluation, and is **not** used to fulfill any of the [PP2600.2] requirements.

The HP High Performance Secure Hard Disk provides hardware-based cryptography and persistent storage to securely manage sensitive print data. Data on this drive is encrypted and the encryption key is locked to the device. The cryptographic functionality is transparent to the TOE and to the user. Not all printer models in this evaluation contain this drive. The printer models that do not, instead contain an eMMC.

The eMMCs are encrypted under the control of the TOE using the HCD's hardware. Each time the TOE is power-cycled, the cryptographic keys are destroyed and new keys generated to encrypt the drive. Because of this, the jobs in Job Storage are effectively erased upon power-cycling the HCD.

1.5.2.3 Identification and authentication

Control Panel I&A

All HCDs have a Control Panel used to select a function (a.k.a. Control Panel application) to be performed, such as Retrieve from Device Memory. The Control Panel supports both local and remote sign in methods.

The mechanism for the local sign in method, which is part of the TOE firmware, is called:

- Local Device Sign In

Remote sign in methods used by the TOE are:

- LDAP Sign In
- Windows Sign In (via Kerberos)

For successful remote authentication, Control Panel users must enter their username and password as defined by the remote sign in method.

All users must sign in before being presented with the home screen allowing access to Control Panel applications. Prior to signing in, the TOE can be configured to display a Welcome message on which the user must press "OK" before the user can access the sign in screen. At the sign in screen, the user may get help on various printer functions or select a sign in method prior to signing in. The sign in method selections are:

- Local Device Sign In:
 - Administrator Access Code
 - User Access Code
- LDAP Sign In (if configured and enabled)
- Windows Sign In (if configured and enabled)

When users sign in through the Control Panel, the TOE displays asterisks or dots (depending on the model number) for each character of a PIN, Access Code, or password typed to prevent onlookers from viewing another user's authentication data. The TOE also contains a mechanism called Simplified Account Lockout that slows Control Panel authentication attempts when multiple unsuccessful authentication attempts occur.

IPsec I&A

Client computers can connect to the TOE to submit print jobs and to manage the TOE. The TOE uses IPsec to identify and mutually authenticate client computers that attempt to connect to the TOE.

The client computers that connect to the TOE are considered IPsec users and are classified as either Network Client Computers or the Administrative Computer. The TOE uses IP addresses to identify these users and X.509v3 certificates to authenticate the users. The IP address of a connecting client computer must be defined to the TOE's IPsec firewall in order for the computer to be considered authorized to access the TOE. Any client computer not defined to the TOE's IPsec/Firewall is considered unauthorized and is blocked by the firewall from accessing the TOE.

The TOE uses IPsec/Firewall address templates, service templates, and rules to map IP addresses to network service protocols. An address template contains one or more IP addresses. A service template contains one or more allowed network service protocols. A rule contains a mapping of an address template to a service template. Through the rules, an administrator determines the User Role of the client computers (i.e., the administrator determines which client computer is the Administrative Computer and which client computers are the Network Client Computers). In the evaluated configuration, the IPsec/firewall only allows the Administrative Computer to connect to all interfaces supported by the TOE. The Network Client Computers are limited to just the PjL Interface (TCP port 9100). [Table 2](#) shows the mapping of IPsec users to their allowed network protocols.

IPsec user	Allowed network protocol access
Administrative Computer (U.ADMINISTRATOR)	EWS (HTTP), OXPd, WS-*, SNMP, PjL
Network Client Computer (U.NORMAL)	PjL (TCP port 9100 only)

Table 2: IPsec user mappings to allowed network protocols

Because IPsec mutual authentication is performed at the computer level, not the user level, the computer allowed by the firewall to access the TOE via EWS, OXPd, WS-*, and SNMP must itself be the Administrative Computer. This means that non-TOE administrative users should not be allowed to logon to the Administrative Computer because every user of the Administrative Computer is potentially a TOE administrator.

IPsec is configured to use X.509v3 certificates via the Internet Key Exchange (IKE) protocols IKEv1 and IKEv2 in the evaluated configuration.

In addition, the TOE can contact many types of trusted IT products using IPsec and mutual authentication over the interfaces specified in [section 1.5.4.1](#). The TOE contacts these computers either to send data to them (e.g., send email notification to the SMTP Gateway) or to request information from them (e.g.,

authenticate a user using LDAP). The TOE mutually authenticates these servers via IPsec prior to sending data or requesting information from them.

1.5.2.4 Data protection and access control

Permission Sets

Each Control Panel application requires one or more permissions in order to execute it. These permissions are defined in Permission Sets (a.k.a. Control Panel User Roles). The applied Permission Set can be a combination of various Permission Sets associated with a user. The default Permission Sets in the evaluated configuration are:

- Device Administrator (assigned to U.ADMINISTRATOR)
- Device User (assigned to U.NORMAL)

The TOE includes a Device Guest Permission Set, but it has no enabled permissions in the evaluated configuration.

Additional (custom) Permission Sets can be created and applied by the administrator in the evaluated configuration.

In the evaluated configuration, the Device Administrator Permission Set has more permissions enabled than the Device User Permission Set. This translates into U.ADMINISTRATORS users being able to access more functionality, specifically administrative functionality, than U.NORMAL users.

Permission Set data is stored in the TOE and managed via EWS and WS-* Web Services.

Job PINs

Users control access to print jobs that they place on the TOE by assigning Job PINs to these jobs (required in the evaluated configuration). Job PINs must be 4 digits in length. Job PINs limit access to these jobs while they reside on the TOE and allow users to control when the jobs are printed so that physical access to the hard copies can be controlled.

Job Encryption Password

The TOE can store and decrypt encrypted stored print jobs received from a client computer which has the HP Universal Print Driver installed. A stored print job is first encrypted by the client computer using a user-specified Job Encryption Password. The job is then sent encrypted to the TOE and stored encrypted by the TOE. To decrypt the job, a Control Panel user must enter the correct Job Encryption Password used to encrypt the job.

Common access control

The TOE protects each print job in Job Storage from non-administrative users through the use of a user identifier and a Job PIN or through the use of just a Job Encryption Password. The user identifier for a print job received from a client computer is either automatically assigned by that client computer or assigned by the user sending the print job from the client computer. Every print job in Job Storage is assigned either a Job PIN or a Job Encryption Password by the user at job creation time.

The default rules for a non-administrative (U.NORMAL) user for accessing a print job in Job Storage are:

- if the job is Job PIN protected:
 - the job owner (i.e., the authenticated user who matches the job's user identifier) can access the job without supplying the Job PIN
 - any non-owner authenticated user who supplies the correct Job PIN can access the job
- if the job is Job Encryption Password protected, any authenticated user who supplies the correct Job Encryption Password can access the job

A Control Panel administrator (U.ADMINISTRATOR) user has a permission in their Permission Set that allows the administrator to delete a print job in Job Storage.

TOE function access control

For Control Panel users, the TOE controls access to Control Panel applications (e.g., Retrieve from Device Memory) using Permission Sets and, optionally, sign-in methods (authentication databases). Permission Sets act as User Roles to determine if the user can perform a function controlled by permissions.

Each Control Panel application requires the user to have one or more specific permissions in their session Permission Set in order to access that application. In addition, the TOE's administrator can map sign in methods to each Control Panel application and require the user to be authenticated to that sign in method in order to access that application. The individual applications only check and enforce permissions. They do not check the sign in methods. Instead, the TOE enforces the sign in method requirement at the time that the user signs in to the TOE by removing permissions from the user's session Permission Set for each application in which the user's sign in method does not match the sign in method required by the TOE. By removing the permissions required by each non-matching application, the TOE limits the set of applications that the user can access.

Administrators can change/modify the sign in method mapped to each application. In addition, the TOE contains a function that allows administrators to select if the sign in method application mappings are enforced or ignored by the TOE. This function is called "Allow users to choose alternate sign-in methods." When this function is disabled, the TOE enforces the "sign in method to application" mappings and prunes (reduces) the user's session Permission Set accordingly. When this function is enabled, the sign in method mappings are ignored by the TOE and the user's session Permission Set remains unchanged.

For IPsec users, the TOE uses the IPsec/Firewall to control access to the supported network service protocols. The IPsec/Firewall contains the IP addresses of authorized client computers grouped into address templates and the network service protocols grouped into service templates. The administrator maps an address template to a service template using an IPsec/Firewall rule. Service templates, therefore, act as the User Roles. IP addresses of computers not contained in a rule are denied access to the TOE.

Residual information protection

The TOE protects deleted objects by making them unavailable to TOE users via the TOE's interfaces. This prevents TOE users from attempting to recover deleted objects of other users via the TOE interfaces.

1.5.2.5 Protection of the TSF

Restricted forwarding of data to external interfaces

The TOE disallows the forwarding of data received from an External Interface to the Shared-medium Interface.

TSF self-testing

The TOE contains a suite of self tests to test specific security functionality of the TOE. It contains data integrity checks for testing specific TSF Data of the TOE and for testing the stored TOE executables.

Reliable timestamps

The TOE contains a system clock that is used to generate reliable timestamps. In the evaluated configuration, the TOE synchronizes the system clock with a Network Time Protocol (NTP) server.

1.5.2.6 TOE access protection

Inactivity timeout

The Control Panel supports an inactivity timeout in case users forget to logout of the Control Panel after logging in.

1.5.2.7 Trusted channel communication and certificate management

The TOE supports IPsec to protect data being transferred over the Shared-medium Interface. IPsec uses IP addresses and X.509v3 certificates to identify and authenticate the Network Client Computers and Administrative Computers as well as other trusted IT products to which the TOE connects (e.g., syslog server, NTP server, SMTP gateway).

The TOE uses several cryptographic algorithms with IPsec. These cryptographic algorithms, supplied by the QuickSec cryptographic library, are all part of the Operational Environment, but the TOE controls the usage of these algorithms. Also, the TOE uses a software-based random number generator in the Operational Environment when creating symmetric encryption keys used as communications session keys and secret keys used during data integrity verification.

In addition, the TOE provides certificate management functions used to manage (add, replace, delete) X.509v3 certificates.

1.5.2.8 User and access management

The TOE provides management capabilities for managing its security functionality. The TOE supports the following roles:

- administrators (U.ADMINISTRATOR)
- users (U.NORMAL)

Administrators have the authority to manage the security functionality of the TOE and to manage users. Users can only manage user data that they have access to on the TOE.

1.5.3 TOE boundaries

1.5.3.1 Physical

The physical boundary of the TOE is the programs and data stored in the firmware of the HCD (except for the embedded operating system and the QuickSec cryptographic library) and the English-language guidance documentation.

It is typical for an HCD, and thus the TOE, to be shared by many users and for those users to have direct physical access to the HCD. By design, users have easy access to some of the hardware features, such as the Control Panel, the paper input trays, the paper output trays, and the power button. But other features such as the processor, volatile memory, and storage drive are located inside the HCD in the formatter cage. The formatter cage can be secured to the HCD chassis using a combination lock, thus, restricting normal user access to the components inside the cage.

Because of the restricted access to the storage drive, the drive is considered a non-removable non-volatile storage device from the perspective of [PP2600.2].

Due to the physical accessibility of the HCDs, they must be used in non-hostile environments. Physical access should be controlled and/or monitored.

QuickSec version 5.1 ([QuickSec51]) library implements the TOE's IPsec including the IPsec/Firewall. QuickSec includes a cryptographic library. Although the IPsec implementation in QuickSec is in the TOE

boundary, the QuickSec cryptographic library used by QuickSec for all IPsec cryptography is part of the Operational Environment. QuickSec is developed and tested by SafeNet, Inc.

Regarding the SMTP gateway, the TOE can only provide protection of sent emails to the device with which the TOE has the IPsec connection (i.e., the TOE only provides protection between the TOE and SMTP gateway). After that point, the Operational Environment must provide the remaining protection necessary to transfer the email from the SMTP gateway to the email's addressee(s).

1.5.3.2 Logical

The security functionality provided by the TOE has been described above and includes:

- Auditing
- Cryptography
- Identification and authentication
- Data protection and access control
- Protection of the TSF (restricted forwarding, TSF self-testing, timestamps)
- TOE access protection (inactivity timeout)
- Trusted channel communication and certificate management
- User and access management

1.5.3.3 Evaluated configuration

The following items will need to be adhered to in the evaluated configuration:

- Device Administrator Password must be set as per `P.ADMIN.PASSWORD`
- Only one Administrative Computer is used to manage the TOE
- HP and third party applications cannot be installed on the TOE
- All print jobs must be assigned a Job PIN or encrypted with a password
- Type A and B USB ports must be disabled
- Remote Firmware Upgrade through any means other than EWS (e.g., PjL) and USB must be disabled
- Jetdirect Inside management via telnet and FTP must be disabled
- Jetdirect XML Services must be disabled
- File System External Access must be disabled
- IPsec authentication using X.509v3 certificates must be enabled (IPsec authentication using Kerberos or Pre-Shared Key is not supported)
- IPsec Authentication Headers (AH) must be disabled
- Full Authentication must be enabled (this disables the Guest account)
- SNMP support limited to:
 - SNMPv1 read-only
 - SNMPv2c read-only
 - SNMPv3

- The Service PIN, used by a customer support engineer to access functions available to HP support personnel, must be disabled
- Near Field Communication (NFC) must be disabled
- Wireless Direct Print must be disabled
- PjL device access commands must be disabled
- When using Windows Sign In, the Windows domain must reject Microsoft NT LAN Manager (NTLM) connections
- Display Names for the Local Device Sign In method users and user names for the LDAP and Windows Sign In method users must only contain the characters defined in `P.USERNAME.CHARACTER_SET`
- Remote Control-Panel use is disallowed per `P.REMOTE_PANEL.DISALLOWED`

1.5.4 Security policy model

This section describes the security policy model for the TOE. Much of the terminology in this section comes from [PP2600.2] and is duplicated here so that readers won't have to read [PP2600.2] to understand the terminology used in the rest of this Security Target document.

1.5.4.1 Subjects/Users

Users are entities that are external to the TOE and which interact with the TOE. TOE users are defined in Table 3.

Designation	Definition	
U.USER	Any authorized User. Authorized Users are U.ADMINISTRATOR and U.NORMAL.	
	Designation	Definition
	U.NORMAL	A User who is authorized to perform User Document Data processing functions of the TOE.
U.ADMINISTRATOR	A User who has been specifically granted the authority to manage some portion or all of the TOE and whose actions may affect the TOE security policy (TSP). A password must be set for all U.ADMINISTRATOR accounts in the evaluated configuration.	

Table 3: Users

For the purpose of clarity in this Security Target, the following distinctions are made:

- **Control Panel users** – U.NORMAL and U.ADMINISTRATOR users who physically access the TOE's Control Panel.
 - **Security attributes:** User Role (defined by Permission Set) and User Identifier
- **IPsec users:**

- **Network Client Computers** – Computers (U.NORMAL entities) that can successfully authenticate to the TOE's PJI Interface (TCP port 9100) using IPsec and mutual authentication. The TOE will accept print jobs from any user of a client computer where the client computer has successfully authenticated with the TOE.
 - **Security attributes:** User Role (defined by IPsec/Firewall service template) and User Identifier (defined by IP address)
- **Administrative Computers** – Computers (U.ADMINISTRATOR entities) that can successfully authenticate to the TOE's administrative interfaces (e.g., EWS/HTTP, OXPd, WS-*, SNMP) using IPsec and mutual authentication. An Administrative Computer may also connect to the TOE as a Network Client Computer (i.e., the Administrative Computer can send print jobs as a U.NORMAL user through the PJI Interface on port 9100).
 - **Security attributes:** User Role (defined by IPsec/Firewall service template) and User Identifier (defined by IP address)

1.5.4.2 Objects

Objects are passive entities in the TOE that contain or receive information, and upon which Subjects perform Operations. Objects are equivalent to TOE Assets. There are three types of Objects:

- User Data
- TSF Data
- Functions

User Data

User Data are data created by and for Users and do not affect the operation of the TOE Security Functionality (TSF). This type of data is comprised of two objects:

- User Document Data
- User Function Data

Designation	Definition
D.DOC	User Document Data consists of the information contained in a user's document. This includes the original document itself in hardcopy or electronic form, image data, or residually-stored data created by the HCD while processing an original document and printed hardcopy output.
D.FUNC	User Function Data are the information about a user's document or job to be processed by the TOE.

Table 4: User Data

User Data objects include:

- **Print job types that use Job Storage:**
 - **Personal jobs** – Print jobs from a client computer that are stored in Job Storage. In the evaluated configuration, such jobs must be PIN protected with a Job PIN. These jobs are held until the user logs in to the Control Panel and releases the job. For PIN protected stored jobs, the user must be the job owner or know the Job PIN (or have administrator privileges) in order to delete the job. These jobs are automatically deleted after printing or if the HCD is turned off or after an administrator specified time interval. If the HCD has an

HP High Performance Secure Hard Disk, the administrator can configure the TOE to retain these jobs after reboot.

- **Stored jobs** – Print jobs such as a personnel form, time sheet, or calendar from a client computer that are stored indefinitely on the TOE and reprinted. In the evaluated configuration, such jobs must be PIN protected with a Job PIN. For PIN protected stored jobs, the user must be the job owner or know the Job PIN (or have administrator privileges) in order to delete the job. If the HCD has an eMMC, these jobs are automatically deleted when the HCD is power-cycled.
- **Encrypted stored print jobs** – Print jobs like those described above but that require higher than normal protection (for example, documents containing company or employee confidential information). These jobs will be assigned a password by the submitter when submitted to the TOE. The user must know the password of the job in order to print or delete it. The administrator may delete it without knowing the password. If the HCD has eMMC, these jobs are automatically deleted when the HCD is power-cycled.

Ownership of a print job sent from a client computer is defined as the username associated with the job when it is submitted to the TOE. The username is specified outside of the TOE, in the Operational Environment, so it can neither be confirmed nor denied by the TOE.

TSF Data

TSF Data are data created by and for the TOE and that might affect the operation of the TOE. This type of data is comprised of two components: TSF Protected Data and TSF Confidential Data.

Designation	Definition
D.CONF	TSF Confidential Data are assets for which either disclosure or alteration by a user who is neither an administrator nor the owner of the data would have an effect on the operational security of the TOE.
D.PROT	TSF Protected Data are assets for which alteration by a user who is neither an administrator nor the owner of the data would have an effect on the operational security of the TOE, but for which disclosure is acceptable.

Table 5: TSF Data

The following table lists the TSF Data and the data designations.

TSF Data	D.CONF	D.PROT
Audit records	X	
Cryptographic keys and certificates	X	
Device and network configuration settings (including IPsec/Firewall rules and templates)		X
Job data including Job PINs	X	
PJL protocol excluding the job data and Job PINs		X

TSF Data	D.CONF	D.PROT
Permission Sets		X
System time		X
User and Administrator identification data		X
User and Administrator authentication data	X	

Table 6: TSF Data Listing

1.5.4.3 SFR package functions

Functions perform processing, storage, and transmission of data. The following [PP2600.2]-defined functions apply to this Security Target.

Designation	Definition
F.DSR	Document storage and retrieval: a function in which a document is stored during one job and retrieved during one or more subsequent jobs
F.PRT	Printing: a function in which electronic document input is converted to physical document output
F.SMI	Shared-medium interface: a function that transmits or receives User Data or TSF Data over a communications medium which, in conventional practice, is or can be simultaneously accessed by multiple users, such as wired network media and most radio-frequency wireless media

Table 7: SFR package functions

1.5.4.4 SFR package attributes

When a function is performing processing, storage, or transmission of data, the identity of the function is associated with that particular data as a security attribute. The following [PP2600.2]-defined attributes apply to this Security Target.

Designation	Definition
+DSR	Indicates data that is associated with a document storage and retrieval job.
+PRT	Indicates data that is associated with a print job.
+SMI	Indicates data that is transmitted or received over a shared-medium interface.

Table 8: SFR package attributes

2 CC Conformance Claim

This Security Target is CC Part 2 extended and CC Part 3 conformant, with a claimed Evaluation Assurance Level of EAL2, augmented by ALC_FLR.2.

This Security Target claims conformance to the following Protection Profiles and PP packages, if any:

- [PP2600.2]: IEEE Std 2600.2-2009; "2600.2-PP, Protection Profile for Hardcopy Devices, Operational Environment B" (with NIAP CCEVS Policy Letter #20). Version 1.0 as of December 2009; demonstrable conformance.
- [PP2600.2-DSR]: SFR Package for Hardcopy Device Document Storage and Retrieval (DSR) Functions. Version 1.0 as of December 2009; demonstrable conformance.
- [PP2600.2-PRT]: SFR Package for Hardcopy Device Print Functions. Version 1.0 as of December 2009; demonstrable conformance.
- [PP2600.2-SMI]: SFR Package for Hardcopy Device Shared-medium Interface Functions. Version 1.0 as of December 2009; demonstrable conformance.

Common Criteria [CC] version 3.1 revision 4 is the basis for this conformance claim.

2.1 Protection Profile tailoring and additions

2.1.1 IEEE Std 2600.2-2009; "2600.2-PP, Protection Profile for Hardcopy Devices, Operational Environment B" (with NIAP CCEVS Policy Letter #20) ([PP2600.2])

In this Security Target, [PP2600.2] has been modified to conform with the NIAP CCEVS Policy Letter #20 ([CCEVS-PL20]).

Although the HCDs in this Security Target contain a nonvolatile mass storage device (i.e., a storage drive), this device is considered an internal, built-in component of the HCDs and, therefore, constitutes a non-removable nonvolatile storage device from the perspective of [PP2600.2] and [CCEVS-PL20]. Because no removable nonvolatile storage devices exist in the HCDs, this Security Target does **not** claim conformance to "2600.2-NVS SFR Package for Hardcopy Device Nonvolatile Storage Functions, Operational Environment B" contained in [PP2600.2].

The following tables provide the mappings of and rationale for how the SFRs in this Security Target map to the SFRs in the protection profile [PP2600.2]. The term "n/a" means "not applicable". The term "common" is used to refer to that portion of [PP2600.2] to which all TOEs must conform (i.e., the portions not labeled as packages).

[PP2600.2] SFR	Maps to ST SFR(s)	Iteration	Hierarchical substitution	Rationale
FAU_GEN.1	FAU_GEN.1			The ST's FAU_GEN.1 combines the contents of FAU_GEN.1 from the common [PP2600.2] and FAU_GEN.1 from the [PP2600.2] SMI SFR package.
FAU_GEN.2	FAU_GEN.2			n/a

[PP2600.2] SFR	Maps to ST SFR(s)	Iteration	Hierarchical substitution	Rationale
FDP_ACC.1(a)	FDP_ACC.1-cac			The ST's FDP_ACC.1-cac combines the contents of the FDP_ACC.1(a) from the common [PP2600.2] and the FDP_ACC.1's from the [PP2600.2] packages claimed by the ST. The iteration name was changed from "(a)" to "-cac" (Common Access Control) for better understandability when reading the ST.
FDP_ACC.1(b)	FDP_ACC.1-tfac			The iteration name was changed from "(b)" to "-tfac" (TOE Function Access Control) for better understandability when reading the ST.
FDP_ACF.1(a)	FDP_ACF.1-cac			The ST's FDP_ACF.1-cac combines the contents of the FDP_ACF.1(a) from the common [PP2600.2] and the FDP_ACF.1's from the [PP2600.2] packages claimed by the ST. The iteration name was changed from "(a)" to "-cac" (Common Access Control) for better understandability when reading the ST.
FDP_ACF.1(b)	FDP_ACF.1-tfac			The iteration name was changed from "(b)" to "-tfac" (TOE Function Access Control) for better understandability when reading the ST.
FDP_RIP.1	FDP_RIP.1			n/a
FIA_ATD.1	FIA_ATD.1			n/a
FIA_UAU.1	FIA_UAU.1			The TOE's Control Panel supports authentication (FIA_UAU.1).
	FIA_UAU.2		X	The TOE supports IPsec authentication (FIA_UAU.2) which complies with the more restrictive FIA_UAU.2.
FIA_UID.1	FIA_UID.1			The TOE's Control Panel supports identification (FIA_UID.1).

[PP2600.2] SFR	Maps to ST SFR(s)	Iteration	Hierarchical substitution	Rationale
	FIA_UID.2		X	The TOE supports IPsec identification (FIA_UID.2) which complies with the more restrictive FIA_UID.2.
FIA_USB.1	FIA_USB.1			n/a
FMT_MSA.1(a)	FMT_MSA.1-perm	X		FMT_MSA.1(a) iteration name is different to better reflect the security attributes involved because this SFR is shared with another access control policy.
FMT_MSA.1(b)	FMT_MSA.1-perm and FMT_MSA.1-tfac	X		FMT_MSA.1(b) was further iterated because the operations on the security attributes differ.
FMT_MSA.3(a)	None			FMT_MSA.3(a) was omitted because the security attributes do not have default values in the evaluated configuration.
FMT_MSA.3(b)	None			FMT_MSA.3(b) was omitted because the security attributes do not have default values in the evaluated configuration.
FMT_MTD.1.1(a)	FMT_MTD.1-auth			The iteration name was changed from "(a)" to "-auth" (TSF Data associated with authorization) for better understandability when reading the ST.
FMT_MTD.1.1(b)	FMT_MTD.1-users			The iteration name was changed from "(b)" to "-users" (TSF Data associated with users) for better understandability when reading the ST.
FMT_SMF.1	FMT_SMF.1			n/a
FMT_SMR.1	FMT_SMR.1			n/a

[PP2600.2] SFR	Maps to ST SFR(s)	Iteration	Hierarchical substitution	Rationale
FPT_STM.1	FPT_STM.1			Because the TOE is configured to use NTP along with its internal time source, both A.SERVICES.RELIABLE and OE.SERVICES.RELIABLE apply.
FPT_TST.1	FPT_TST.1			n/a
FTA_SSL.3	FTA_SSL.3			n/a

Table 9: SFR mappings between 2600.2 and the ST

These SFRs in the Security Target are not required by and do not map to the protection profile [PP2600.2].

[PP2600.2] SFR	Maps to ST SFR(s)	Iteration	Hierarchical substitution	Rationale
None	FCS_CKM.1			FCS_CKM.1 specifies the types of cryptographic keys generated by the TOE for use with AES and HMAC in IPsec.
None	FCS_CKM.2			FCS_CKM.2 specifies the cryptographic key distribution methods used by the TOE in IKEv1 and IKEv2 in IPsec.
None	FCS_COP.1-ipsec	X		FCS_COP.1-ipsec specifies the AES encryption and decryption algorithm, the RSA decryption algorithm, and the HMAC algorithms used by the TOE in IPsec.
None	FCS_COP.1-job	X		FCS_COP.1-job specifies the AES decryption algorithm used by the TOE for decrypting encrypted print jobs.
None	FIA_AFL.1			The TOE slows the number of unsuccessful Control Panel authentication attempts made over a period of time. Recommended by [PP2600.2] APPLICATION NOTE 38.
None	FIA_SOS.1			FIA_SOS.1 specifies the Job PIN strength of certain authorization mechanisms used by the TOE.

[PP2600.2] SFR	Maps to ST SFR(s)	Iteration	Hierarchical substitution	Rationale
None	FIA_UAU.7			The TOE masks Job PINs, Access Codes, and passwords. Recommended by [PP2600.2] APPLICATION NOTE 38.
None	FMT_MOF.1	X		The TOE allows administrators to allow or disallow users from choosing an alternate sign in method differing from the administrator-selected method.

Table 10: SFR mappings of non-PP2600.2 SFRs and the ST (in the ST, but not required by or hierarchical to SFRs in PP2600.2)

2.1.2 SFR Package for Hardcopy Device Document Storage and Retrieval (DSR) Functions ([PP2600.2-DSR])

The following table shows how the SFRs in this SFR package map to the SFRs in the Security Target.

[PP2600.2-DSR] SFR	Maps to ST SFR(s)	Iteration	Hierarchical substitution	Rationale
FDP_ACC.1	FDP_ACC.1-cac	X		See rationale for FDP_ACC.1(a).
FDP_ACF.1	FDP_ACF.1-cac	X		See rationale for FDP_ACF.1(a).

Table 11: SFR mappings between 2600.2-DSR and the ST

2.1.3 SFR Package for Hardcopy Device Print Functions ([PP2600.2-PRT])

The following table shows how the SFRs in this SFR package map to the SFRs in the Security Target.

[PP2600.2-PRT] SFR	Maps to ST SFR(s)	Iteration	Hierarchical substitution	Rationale
FDP_ACC.1	FDP_ACC.1-cac	X		See rationale for FDP_ACC.1(a).
FDP_ACF.1	FDP_ACF.1-cac	X		See rationale for FDP_ACF.1(a).

Table 12: SFR mappings between 2600.2-PRT and the ST

2.1.4 SFR Package for Hardcopy Device Shared-medium Interface Functions ([PP2600.2-SMI])

The following table shows how the SFRs in this SFR package map to the SFRs in the Security Target.

[PP2600.2-SMI] SFR	Maps to ST SFR(s)	Iteration	Hierarchical substitution	Rationale
FAU_GEN.1	FAU_GEN.1			The ST's FAU_GEN.1 combines the contents of FAU_GEN.1 from the common [PP2600.2] and FAU_GEN.1 from the [PP2600.2] SMI SFR package.
FPT_FDI_EXP.1	FPT_FDI_EXP.1			n/a
FTP_ITC.1	FTP_ITC.1			[CCEVS-PL20] modifies FTP_ITC.1.3.

Table 13: SFR mappings between 2600.2-SMI and the ST

3 Security Problem Definition

3.1 Introduction

The statement of TOE security environment describes the security aspects of the environment in which the TOE is intended to be used and the manner in which it is expected to be deployed.

To this end, the statement of TOE security environment identifies the list of assumptions made on the Operational Environment (including physical and procedural measures) and the intended method of use of the product, defines the threats that the product is designed to counter, and the organizational security policies with which the product is designed to comply.

3.2 Threat Environment

This security problem definition addresses threats posed by four categories of threat agents:

- a) Persons who are not permitted to use the TOE who may attempt to use the TOE
- b) Persons who are authorized to use the TOE who may attempt to use TOE functions for which they are not authorized.
- c) Persons who are authorized to use the TOE who may attempt to access data in ways for which they not authorized.
- d) Persons who unintentionally cause a software malfunction that may expose the TOE to unanticipated threats.

The threats and policies defined in this Security Target address the threats posed by these threat agents.

The threat agents are assumed to originate from a well-managed user community in a non-hostile working environment. Therefore, the product protects against threats of security vulnerabilities that might be exploited in the intended environment for the TOE with low level of expertise and effort. The TOE protects against straightforward or intentional breach of TOE security by attackers possessing a Basic attack potential.

3.2.1 Threats countered by the TOE

T.DOC.DIS

User Document Data may be disclosed to unauthorized persons.

T.DOC.ALT

User Document Data may be altered by unauthorized persons.

T.FUNC.ALT

User Function Data may be altered by unauthorized persons.

T.PROT.ALT

TSF Protected Data may be altered by unauthorized persons.

T.CONF.DIS

TSF Confidential Data may be disclosed to unauthorized persons.

T.CONF.ALT

TSF Confidential Data may be altered by unauthorized persons.

3.3 Assumptions

3.3.1 Environment of use of the TOE

3.3.1.1 Physical

A.ACCESS.MANAGED

The TOE is located in a restricted or monitored environment that provides protection from unmanaged access to the physical components and data interfaces of the TOE.

A.ADMIN.PC.SECURE

The administrative computer is in a physically secured and managed environment and only the authorized administrator has access to it.

A.USER.PC.POLICY

User computers are configured and used in conformance with the organization's security policies.

3.3.1.2 Personnel

A.USER.TRAINING

TOE Users are aware of the security policies and procedures of their organization, and are trained and competent to follow those policies and procedures.

A.ADMIN.TRAINING

Administrators are aware of the security policies and procedures of their organization, are trained and competent to follow the manufacturer's guidance and documentation, and correctly configure and operate the TOE in accordance with those policies and procedures.

A.ADMIN.TRUST

Administrators do not use their privileged access rights for malicious purposes.

3.3.1.3 Connectivity

A.SERVICES.RELIABLE

When the TOE uses any of the network services SMB, DNS, Kerberos, LDAP, NTP, SMTP, syslog, and/or WINS, these services provide reliable information and responses to the TOE.

3.4 Organizational Security Policies

3.4.1 Included in the PP2600.2 protection profile

P.USER.AUTHORIZATION

To preserve operational accountability and security, Users will be authorized to use the TOE only as permitted by the TOE Owner.

P.SOFTWARE.VERIFICATION

To detect corruption of the executable code in the TSF, procedures will exist to self-verify executable code in the TSF.

P.AUDIT.LOGGING

To preserve operational accountability and security, records that provide an audit trail of TOE use and security-relevant events will be created, maintained, and protected from unauthorized disclosure or alteration, and will be reviewed by authorized personnel.

P.INTERFACE.MANAGEMENT

To prevent unauthorized use of the external interfaces of the TOE, operation of those interfaces will be controlled by the TOE and its IT environment.

3.4.2 In addition to the PP2600.2 protection profile

P.ADMIN.PASSWORD

To restrict access to administrative tasks, the Device Administrator Password will be set in the evaluated configuration so that it is required to perform security-relevant actions through EWS (HTTP), WS-* Web Services, and at the Control Panel.

P.USERNAME.CHARACTER_SET

To prevent ambiguous user names in the TOE's audit trail, the Display Names of the Local Device Sign In method users and the user names of the LDAP and Windows Sign In method users must only contain ASCII printable characters except for the double quote (22 hex) and single quote (27 hex) characters (i.e., allowed ASCII characters in hexadecimal: 20, 21, 23 - 26, 28 - 7E).

P.REMOTE_PANEL.DISALLOWED

To preserve operational accountability and security, administrators must not use the Remote Control-Panel feature.

4 Security Objectives

4.1 Objectives for the TOE

O.AUDIT.LOGGED

The TOE shall create and maintain a log of TOE use and security-relevant events, and prevent its unauthorized disclosure or alteration.

O.CONF.NO_ALT

The TOE shall protect TSF Confidential Data from unauthorized alteration.

O.CONF.NO_DIS

The TOE shall protect TSF Confidential Data from unauthorized disclosure.

O.DOC.NO_ALT

The TOE shall protect User Document Data from unauthorized alteration.

O.DOC.NO_DIS

The TOE shall protect User Document Data from unauthorized disclosure.

O.FUNC.NO_ALT

The TOE shall protect User Function Data from unauthorized alteration.

O.INTERFACE.MANAGED

The TOE shall manage the operation of external interfaces in accordance with security policies.

O.PROT.NO_ALT

The TOE shall protect TSF Protected Data from unauthorized alteration.

O.SOFTWARE.VERIFIED

The TOE shall provide procedures to self-verify executable code in the TSF.

O.USER.AUTHORIZED

The TOE shall require identification and authentication of Users, and shall ensure that Users are authorized in accordance with security policies before allowing them to use the TOE.

4.2 Objectives for the Operational Environment

OE.ADMIN.PC.SECURE

The TOE Owner shall locate the Administrative Computer in a physically secured and managed environment and allow only authorized personnel access to it.

OE.ADMIN.TRAINED

The TOE Owner shall ensure that TOE Administrators are aware of the security policies and procedures of their organization; have the training, competence, and time to follow the manufacturer's guidance and documentation; and correctly configure and operate the TOE in accordance with those policies and procedures.

OE.ADMIN.TRUSTED

The TOE Owner shall establish trust that TOE Administrators will not use their privileged access rights for malicious purposes.

OE.AUDIT.REVIEWED

The TOE Owner shall ensure that audit logs are reviewed at appropriate intervals for security violations or unusual patterns of activity.

OE.AUDIT_ACCESS.AUTHORIZED

If audit records generated by the TOE are exported from the TOE to another trusted IT product, the TOE Owner shall ensure that those records can be accessed in order to detect potential security violations, and only by authorized persons.

OE.AUDIT_STORAGE.PROTECTED

If audit records are exported from the TOE to another trusted IT product, the TOE Owner shall ensure that those records are protected from unauthorized access, deletion and modifications.

OE.INTERFACE.MANAGED

The IT environment shall provide protection from unmanaged access to TOE external interfaces.

OE.PHYSICAL.MANAGED

The TOE shall be placed in a secure or monitored area that provides protection from unmanaged physical access to the TOE.

OE.SERVICES.RELIABLE

When the TOE uses any of the network services SMB, DNS, Kerberos, LDAP, NTP, SMTP, syslog, and/or WINS, these services shall provide reliable information and responses to the TOE.

OE.USER.AUTHORIZED

The TOE Owner shall grant permission to Users to be authorized to use the TOE according to the security policies and procedures of their organization.

OE.USER.PC.POLICY

The TOE Owner shall create a set of security policies to which user computers will conform.

OE.USER.TRAINED

The TOE Owner shall ensure that Users are aware of the security policies and procedures of their organization, and have the training and competence to follow those policies and procedures.

OE.USERNAME.CHARACTER_SET

The Display Names of all Local Device Sign In method users and the user names of all LDAP and Windows Sign In method users shall only contain ASCII printable characters except for the double quote (22 hex) and single quote (27 hex) characters (i.e., allowed ASCII characters in hexadecimal: 20, 21, 23 - 26, 28 - 7E).

4.3 Security Objectives Rationale

4.3.1 Coverage

The following table provides a mapping of TOE objectives to threats and policies, showing that each objective counters or enforces at least one threat or policy, respectively.

Objective	Threats / OSPs
O.AUDIT.LOGGED	P.AUDIT.LOGGING
O.CONF.NO_ALT	T.CONF.ALT

Objective	Threats / OSPs
O.CONF.NO_DIS	T.CONF.DIS
O.DOC.NO_ALT	T.DOC.ALT
O.DOC.NO_DIS	T.DOC.DIS
O.FUNC.NO_ALT	T.FUNC.ALT
O.INTERFACE.MANAGED	P.INTERFACE.MANAGEMENT
O.PROT.NO_ALT	T.PROT.ALT
O.SOFTWARE.VERIFIED	P.SOFTWARE.VERIFICATION
O.USER.AUTHORIZED	T.DOC.DIS T.DOC.ALT T.FUNC.ALT T.PROT.ALT T.CONF.DIS T.CONF.ALT P.USER.AUTHORIZATION

Table 14: Mapping of security objectives to threats and policies

The following table provides a mapping of the objectives for the Operational Environment to assumptions, threats and policies, showing that each objective holds, counters or enforces at least one assumption, threat or policy, respectively.

Objective	Assumptions / Threats / OSPs
OE.ADMIN.PC.SECURE	A.ADMIN.PC.SECURE
OE.ADMIN.TRAINED	A.ADMIN.TRAINING P.ADMIN.PASSWORD P.REMOTE_PANEL.DISALLOWED
OE.ADMIN.TRUSTED	A.ADMIN.TRUST
OE.AUDIT.REVIEWED	P.AUDIT.LOGGING
OE.AUDIT_ACCESS.AUTHORIZED	P.AUDIT.LOGGING
OE.AUDIT_STORAGE.PROTECTED	P.AUDIT.LOGGING
OE.INTERFACE.MANAGED	P.INTERFACE.MANAGEMENT

Objective	Assumptions / Threats / OSPs
OE.PHYSICAL.MANAGED	A.ACCESS.MANAGED
OE.SERVICES.RELIABLE	A.SERVICES.RELIABLE
OE.USER.AUTHORIZED	T.DOC.DIS T.DOC.ALT T.FUNC.ALT T.PROT.ALT T.CONF.DIS T.CONF.ALT P.USER.AUTHORIZATION
OE.USER.PC.POLICY	A.USER.PC.POLICY
OE.USER.TRAINED	A.USER.TRAINING
OE.USERNAME.CHARACTER_SET	P.USERNAME.CHARACTER_SET

Table 15: Mapping of security objectives for the Operational Environment to assumptions, threats and policies

4.3.2 Sufficiency

The following rationale provides justification that the security objectives are suitable to counter each individual threat and that each security objective tracing back to a threat, when achieved, actually contributes to the removal, diminishing or mitigation of that threat:

Threat	Rationale for security objectives
T.DOC.DIS	<p>The threat:</p> <ul style="list-style-type: none"> User Document Data may be disclosed to unauthorized persons. <p>is countered by:</p> <ul style="list-style-type: none"> O.DOC.NO_DIS which protects D.DOC from unauthorized disclosure. O.USER.AUTHORIZED which establishes user identification and authentication as the basis for authorization. OE.USER.AUTHORIZED which establishes responsibility of the TOE Owner to appropriately grant authorization.
T.DOC.ALT	<p>The threat:</p> <ul style="list-style-type: none"> User Document Data may be altered by unauthorized persons.

Threat	Rationale for security objectives
	<p>is countered by:</p> <ul style="list-style-type: none"> • O.DOC.NO_ALT which protects D.DOC from unauthorized alteration. • O.USER.AUTHORIZED which establishes user identification and authentication as the basis for authorization. • OE.USER.AUTHORIZED which establishes responsibility of the TOE Owner to appropriately grant authorization.
T.FUNC.ALT	<p>The threat:</p> <ul style="list-style-type: none"> • User Function Data may be altered by unauthorized persons. <p>is countered by:</p> <ul style="list-style-type: none"> • O.FUNC.NO_ALT which protects D.FUNC from unauthorized alteration. • O.USER.AUTHORIZED which establishes user identification and authentication as the basis for authorization. • OE.USER.AUTHORIZED which establishes responsibility of the TOE Owner to appropriately grant authorization.
T.PROT.ALT	<p>The threat:</p> <ul style="list-style-type: none"> • TSF Protected Data may be altered by unauthorized persons. <p>is countered by:</p> <ul style="list-style-type: none"> • O.PROT.NO_ALT which protects D.PROT from unauthorized alteration. • O.USER.AUTHORIZED which establishes user identification and authentication as the basis for authorization. • OE.USER.AUTHORIZED which establishes responsibility of the TOE Owner to appropriately grant authorization.
T.CONF.DIS	<p>The threat:</p> <ul style="list-style-type: none"> • TSF Confidential Data may be disclosed to unauthorized persons. <p>is countered by:</p> <ul style="list-style-type: none"> • O.CONF.NO_DIS which protects D.CONF from unauthorized disclosure.

Threat	Rationale for security objectives
	<ul style="list-style-type: none"> • O.USER.AUTHORIZED which establishes user identification and authentication as the basis for authorization. • OE.USER.AUTHORIZED which establishes responsibility of the TOE Owner to appropriately grant authorization.
T.CONF.ALT	<p>The threat:</p> <ul style="list-style-type: none"> • TSF Confidential Data may be altered by unauthorized persons. <p>is countered by:</p> <ul style="list-style-type: none"> • O.CONF.NO_ALT which protects D.CONF from unauthorized alteration. • O.USER.AUTHORIZED which establishes user identification and authentication as the basis for authorization. • OE.USER.AUTHORIZED which establishes responsibility of the TOE Owner to appropriately grant authorization.

Table 16: Sufficiency of objectives countering threats

The following rationale provides justification that the security objectives for the environment are suitable to cover each individual assumption, that each security objective for the environment that traces back to an assumption about the environment of use of the TOE, when achieved, actually contributes to the environment achieving consistency with the assumption, and that if all security objectives for the environment that trace back to an assumption are achieved, the intended usage is supported:

Assumption	Rationale for security objectives
A.ACCESS.MANAGED	<p>The assumption:</p> <ul style="list-style-type: none"> • The TOE is located in a restricted or monitored environment that provides protection from unmanaged access to the physical components and data interfaces of the TOE. <p>is upheld by:</p> <ul style="list-style-type: none"> • OE.PHYSICAL.MANAGED which establishes a protected physical environment for the TOE.
A.ADMIN.PC.SECURE	<p>The assumption:</p> <ul style="list-style-type: none"> • The administrative computer is in a physically secured and managed environment and only the authorized administrator has access to it. <p>is upheld by:</p> <ul style="list-style-type: none"> • OE.ADMIN.PC.SECURE which establishes the responsibility of the TOE owner to locate the administrative computer in a physically secured and managed environment and allow only authorized personnel access.

Assumption	Rationale for security objectives
A.USER.PC.POLICY	<p>The assumption:</p> <ul style="list-style-type: none"> • User computers are configured and used in conformance with the organization's security policies. <p>is upheld by:</p> <ul style="list-style-type: none"> • OE.USER.PC.POLICY which establishes the responsibility of the TOE owner to create a set of security policies to which user computers will conform.
A.USER.TRAINING	<p>The assumption:</p> <ul style="list-style-type: none"> • TOE Users are aware of the security policies and procedures of their organization, and are trained and competent to follow those policies and procedures. <p>is upheld by:</p> <ul style="list-style-type: none"> • OE.USER.TRAINED which establishes responsibility of the TOE Owner to provide appropriate User training.
A.ADMIN.TRAINING	<p>The assumption:</p> <ul style="list-style-type: none"> • Administrators are aware of the security policies and procedures of their organization, are trained and competent to follow the manufacturer's guidance and documentation, and correctly configure and operate the TOE in accordance with those policies and procedures. <p>is upheld by:</p> <ul style="list-style-type: none"> • OE.ADMIN.TRAINED which establishes responsibility of the TOE Owner to provide appropriate Administrator training.
A.ADMIN.TRUST	<p>The assumption:</p> <ul style="list-style-type: none"> • Administrators do not use their privileged access rights for malicious purposes. <p>is upheld by:</p> <ul style="list-style-type: none"> • OE.ADMIN.TRUSTED which establishes responsibility of the TOE Owner to have a trusted relationship with Administrators.
A.SERVICES.RELIABLE	<p>The assumption:</p> <ul style="list-style-type: none"> • When the TOE uses any of the network services SMB, DNS, Kerberos, LDAP, NTP, SMTP, syslog, and/or WINS, these services provide reliable information and responses to the TOE. <p>is upheld by:</p> <ul style="list-style-type: none"> • OE.SERVICES.RELIABLE which, when the TOE uses the network services SMB, DNS, Kerberos, LDAP, NTP, SMTP, syslog, and/or

Assumption	Rationale for security objectives
	WINS, establishes that these services provide reliable information and responses to the TOE.

Table 17: Sufficiency of objectives holding assumptions

The following rationale provides justification that the security objectives are suitable to cover each individual organizational security policy, that each security objective that traces back to an OSP, when achieved, actually contributes to the implementation of the OSP, and that if all security objectives that trace back to an OSP are achieved, the OSP is implemented:

OSP	Rationale for security objectives
P.USER.AUTHORIZATION	<p>The OSP:</p> <ul style="list-style-type: none"> • To preserve operational accountability and security, Users will be authorized to use the TOE only as permitted by the TOE Owner. <p>is enforced by:</p> <ul style="list-style-type: none"> • O.USER.AUTHORIZED which establishes user identification and authentication as the basis for authorization to use the TOE. • OE.USER.AUTHORIZED which establishes responsibility of the TOE Owner to appropriately grant authorization.
P.SOFTWARE.VERIFICATION	<p>The OSP:</p> <ul style="list-style-type: none"> • To detect corruption of the executable code in the TSF, procedures will exist to self-verify executable code in the TSF. <p>is enforced by:</p> <ul style="list-style-type: none"> • O.SOFTWARE.VERIFIED which provides procedures to self-verify executable code in the TSF.
P.AUDIT.LOGGING	<p>The OSP:</p> <ul style="list-style-type: none"> • To preserve operational accountability and security, records that provide an audit trail of TOE use and security-relevant events will be created, maintained, and protected from unauthorized disclosure or alteration, and will be reviewed by authorized personnel. <p>is enforced by:</p> <ul style="list-style-type: none"> • O.AUDIT.LOGGED which creates and maintains a log of TOE use and security-relevant events, and prevents unauthorized disclosure or alteration.

OSP	Rationale for security objectives
	<ul style="list-style-type: none"> • OE.AUDIT_STORAGE.PROTECTED which protects exported audit records from unauthorized access, deletion and modifications. • OE.AUDIT_ACCESS.AUTHORIZED which establishes responsibility of the TOE Owner to provide appropriate access to exported audit records. • OE.AUDIT.REVIEWED which establishes responsibility of the TOE Owner to ensure that audit logs are appropriately reviewed.
P.INTERFACE.MANAGEMENT	<p>The OSP:</p> <ul style="list-style-type: none"> • To prevent unauthorized use of the external interfaces of the TOE, operation of those interfaces will be controlled by the TOE and its IT environment. <p>is enforced by:</p> <ul style="list-style-type: none"> • O.INTERFACE.MANAGED which manages the operation of external interfaces in accordance with security policies. • OE.INTERFACE.MANAGED which establishes a protected environment for TOE external interfaces.
P.ADMIN.PASSWORD	<p>The OSP:</p> <ul style="list-style-type: none"> • To restrict access to administrative tasks, the Device Administrator Password will be set in the evaluated configuration so that it is required to perform security-relevant actions through EWS (HTTP), WS-* Web Services, and at the Control Panel. <p>is enforced by:</p> <ul style="list-style-type: none"> • OE.ADMIN.TRAINED which establishes responsibility of the TOE Owner to provide appropriate Administrator training.
P.USERNAME.CHARACTER_SET	<p>The OSP:</p> <ul style="list-style-type: none"> • To prevent ambiguous user names in the TOE's audit trail, the Display Names of the Local Device Sign In method users and the user names of the LDAP and Windows Sign In method users must only contain ASCII printable characters except for the double quote (22 hex) and single quote (27 hex) characters (i.e., allowed ASCII characters in hexadecimal: 20, 21, 23 - 26, 28 - 7E). <p>is enforced by:</p> <ul style="list-style-type: none"> • OE.USERNAME.CHARACTER_SET which establishes that the Display Names of all Local Device Sign In users and the user names of all LDAP and Windows Sign In methods users shall only contain ASCII printable

OSP	Rationale for security objectives
	characters except for the double quote (22 hex) and single quote (27 hex) characters (i.e., allowed ASCII characters in hexadecimal: 20, 21, 23 - 26, 28 - 7E).
P.REMOTE_PANEL.DISALLOWED	<p>The OSP:</p> <ul style="list-style-type: none"> • To preserve operational accountability and security, administrators must not use the Remote Control-Panel feature. <p>is enforced by:</p> <ul style="list-style-type: none"> • OE.ADMIN_TRAINED which establishes responsibility of the TOE Owner to provide appropriate Administrator training.

Table 18: Sufficiency of objectives enforcing Organizational Security Policies

5 Extended Components Definition

[PP2600.2-SMI] defines the following extended component:

- FPT_FDI_EXP.1: Restricted forwarding of data to external interfaces

5.1 Class FPT: Protection of the TSF

This section describes the functional requirements for the restrictions of forwarding of data to external interfaces. This extended component is defined in [PP2600.2-SMI].

5.1.1 Restricted forwarding of data to external interfaces (FDI)

Family behaviour

This family defines requirements for the TSF to restrict direct forwarding of information from one external interface to another external interface.

Many products receive information on specific external interfaces and are intended to transform and process this information before it is transmitted on another external interface. However, some products may provide the capability for attackers to misuse external interfaces to violate the security of the TOE or devices that are connected to the TOE's external interfaces. Therefore, direct forwarding of unprocessed data between different external interfaces is forbidden unless explicitly allowed by an authorized administrative role. The family FPT_FDI_EXP has been defined to specify this kind of functionality.

Component levelling

FPT_FDI_EXP.1 Restricted forwarding of data to external interfaces provides for the functionality to require TSF controlled processing of data received over defined external interfaces before these data are sent out on another external interface. Direct forwarding of data from one external interface to another one requires explicit allowance by an authorized administrative role.

Management: FPT_FDI_EXP.1

There are no management activities foreseen.

Audit: FPT_FDI_EXP.1

There are no audit events foreseen.

5.1.1.1 FPT_FDI_EXP.1 - Restricted forwarding of data to external interfaces

Hierarchical to: No other components.

Dependencies: No dependencies.

FPT_FDI_EXP.1.1 The TSF shall provide the capability to restrict data received on [assignment: *list of external interfaces*] from being forwarded without further processing by the TSF to [assignment: *list of external interfaces*].

6 Security Requirements

6.1 TOE Security Functional Requirements

The following table shows the security functional requirements for the TOE, and the operations performed on the components according to CC part 2: iteration (Iter.), refinement (Ref.), assignment (Ass.) and selection (Sel.).

Security functional group	Security functional requirement	Base security functional component	Source	Operations			
				Iter.	Ref.	Ass.	Sel.
FAU - Security audit	FAU_GEN.1 Audit data generation		PP2600.2	No	No	Yes	Yes
	FAU_GEN.2 User identity association		PP2600.2	No	No	No	No
FCS - Cryptographic support	FCS_CKM.1 Cryptographic key generation		CC Part 2	No	Yes	Yes	No
	FCS_CKM.2 Cryptographic key distribution		CC Part 2	No	Yes	Yes	No
	FCS_COP.1-ipsec Cryptographic operation	FCS_COP.1	CC Part 2	Yes	Yes	Yes	No
	FCS_COP.1-job Cryptographic operation	FCS_COP.1	CC Part 2	Yes	No	Yes	No
FDP - User data protection	FDP_ACC.1-cac Common access control SFP	FDP_ACC.1	PP2600.2	Yes	No	Yes	No
	FDP_ACC.1-tfac TOE function access control SFP	FDP_ACC.1	PP2600.2	Yes	No	Yes	No
	FDP_ACF.1-cac Common access control functions	FDP_ACF.1	PP2600.2	Yes	No	Yes	No
	FDP_ACF.1-tfac TOE function access control functions	FDP_ACF.1	PP2600.2	Yes	No	Yes	No

Security functional group	Security functional requirement	Base security functional component	Source	Operations			
				Iter.	Ref.	Ass.	Sel.
	FDP_RIP.1 Subset residual information protection		PP2600.2	No	No	Yes	Yes
FIA - Identification and authentication	FIA_AFL.1 Authentication failure handling		CC Part 2	No	No	Yes	Yes
	FIA_ATD.1 Local user attribute definition		PP2600.2	No	No	Yes	No
	FIA_SOS.1 Verification of secrets		CC Part 2	No	No	Yes	No
	FIA_UAU.1 Timing of Control Panel authentication		PP2600.2	No	Yes	Yes	No
	FIA_UAU.2 IPsec authentication before any action		CC Part 2	No	Yes	No	No
	FIA_UAU.7 Control Panel protected authentication feedback		CC Part 2	No	Yes	Yes	No
	FIA_UID.1 Timing of Control Panel identification		PP2600.2	No	Yes	Yes	No
	FIA_UID.2 IPsec identification before any action		CC Part 2	No	Yes	No	No
	FIA_USB.1 User-subject binding		PP2600.2	No	Yes	Yes	No
FMT - Security management	FMT_MOF.1 Management of authentication security functions behavior		CC Part 2	No	No	Yes	Yes

Security functional group	Security functional requirement	Base security functional component	Source	Operations			
				Iter.	Ref.	Ass.	Sel.
	FMT_MSA.1-perm Management of Permission Set security attributes	FMT_MSA.1	PP2600.2	Yes	No	Yes	Yes
	FMT_MSA.1-tfac Management of TOE function security attributes	FMT_MSA.1	PP2600.2	Yes	No	Yes	Yes
	FMT_MTD.1-auth Management of TSF data	FMT_MTD.1	PP2600.2	Yes	No	Yes	Yes
	FMT_MTD.1-users Management of TSF data	FMT_MTD.1	PP2600.2	Yes	No	Yes	Yes
	FMT_SMF.1 Specification of management functions		PP2600.2	No	No	Yes	No
	FMT_SMR.1 Security roles		PP2600.2	No	No	Yes	No
FPT - Protection of the TSF	FPT_FDI_EXP.1 Restricted forwarding of data to external interfaces		PP2600.2-SMI	No	No	Yes	No
	FPT_STM.1 Reliable time stamps		PP2600.2	No	No	No	No
	FPT_TST.1 TSF testing		PP2600.2	No	No	Yes	Yes
FTA - TOE access	FTA_SSL.3 Control Panel TSF-initiated termination		PP2600.2	No	Yes	Yes	No
FTP - Trusted path/channels	FTP_ITC.1 Inter-TSF trusted channel		PP2600.2-SMI	No	Yes	Yes	Yes

Table 19: Security functional requirements for the TOE

6.1.1 Security audit (FAU)

6.1.1.1 Audit data generation (FAU_GEN.1)

FAU_GEN.1.1 The TSF shall be able to generate an audit record of the following auditable events:

- a) Start-up and shutdown of the audit functions; and
- b) All auditable events for the **not specified** level of audit; and
- c) **All Auditable Events as each is defined for its Audit Level (if one is specified) for the Relevant SFR in Table 20 ; none.**

FAU_GEN.1.2 The TSF shall record within each audit record at least the following information:

- a) Date and time of the event, type of event, subject identity (if applicable), and the outcome (success or failure) of the event; and
- b) For each audit event type, based on the auditable event definitions of the functional components included in the PP/ST, **for each Relevant SFR listed in Table 20: (1) information as defined by its Audit Level (if one is specified), and (2) all Additional Information (if any is required); none.**

Auditable event	Relevant SFR(s)	Audit level	Additional information	[PP2600.2]
Both successful and unsuccessful use of the authentication mechanism	FIA_UAU.1, FIA_UAU.2	Basic	None required	Yes: Common
Both successful and unsuccessful use of the identification mechanism	FIA_UID.1, FIA_UID.2	Basic	Attempted user identity, if available	Yes: Common
Use of the management functions	FMT_SMF.1	Minimum	None required	Yes: Common
Modifications to the group of users that are part of a role	FMT_SMR.1	Minimum	None required	Yes: Common
Changes to the time	FPT_STM.1	Minimum	None required	Yes: Common
Failure of the trusted channel functions	FTP_ITC.1	Minimum	None required	Yes: SMI

Termination of an interactive session by the session termination mechanism	FTA_SSL.3	Minimum	None required	No
--	-----------	---------	---------------	----

Table 20: Auditable events

6.1.1.2 User identity association (FAU_GEN.2)

FAU_GEN.2.1 For audit events resulting from actions of identified users, the TSF shall be able to associate each auditable event with the identity of the user that caused the event.

6.1.2 Cryptographic support (FCS)

6.1.2.1 Cryptographic key generation (FCS_CKM.1)

FCS_CKM.1.1 The *QuickSec cryptographic library in the Operational Environment* TSF shall generate cryptographic keys in accordance with a specified cryptographic key generation algorithm **defined in Table 21** and specified cryptographic key sizes **defined in Table 21** that meet the following: **the standards defined in Table 21**.

Protocol	Key generation algorithm	Key sizes (in bits)	Standards
IPsec	AES	128, 192, 256	[RFC4301] Security Architecture for the Internet Protocol
	HMAC-SHA1-96	96	[RFC2404] The Use of HMAC-SHA-1-96 within ESP and AH; [RFC4301] Security Architecture for the Internet Protocol; [RFC4894] Use of Hash Algorithms in Internet Key Exchange (IKE) and IPsec
	HMAC-SHA-256-128	256	[RFC4868] Using HMAC-SHA-256, HMAC-SHA-384, and HMAC-SHA-512 with IPsec
	HMAC-SHA-384-196	384	
	HMAC-SHA-512-256	512	

Table 21: Cryptographic key generation

Application Note: Key generation for **FCS_CKM.1** is implemented with the SSH random number generator described in section 29.5.3 (pages 1044-1045) of [QuickSec51].

6.1.2.2 Cryptographic key distribution (FCS_CKM.2)

FCS_CKM.2.1 The *QuickSec cryptographic library in the Operational Environment TSE* shall distribute cryptographic keys in accordance with a specified cryptographic key distribution method **defined in Table 22** that meets the following: **the standards defined in Table 22.**

Protocol	Key distribution method	Standards
IPsec	IKEv1	[RFC2409] The Internet Key Exchange (IKE); [RFC4109] Algorithms for Internet Key Exchange version 1 (IKEv1)
	IKEv2	[RFC4306] Diffie-Hellman key agreement method defined for the IKEv2 protocol; [RFC4718] IKEv2 Clarifications and Implementation Guidelines

Table 22: Cryptographic key distribution

6.1.2.3 Cryptographic operation (FCS_COP.1-ipsec)

FCS_COP.1.1 The *QuickSec cryptographic library in the Operational Environment TSE* shall perform **the operations defined in Table 23** in accordance with a specified cryptographic algorithm **defined in Table 23** and cryptographic key sizes **defined in Table 23** that meet the following: **the standards defined in Table 23.**

Protocol	Operations	Algorithm	Key sizes (in bits)	Standards
IPsec	Asymmetric decryption	RSA	1024, 2048, 4096	[PKCS1v1.5] Public-Key Cryptography Standard (PKCS) #1: RSA Encryption Standard
	Symmetric encryption and decryption	AES (CBC mode)	128, 192, 256	[FIPS197] Advanced Encryption Standard; [SP800-38A] Recommendation for Block Cipher Modes of Operation: Methods and Techniques
	Data authentication	HMAC-SHA-96	96	[RFC2104] HMAC: Keyed-Hashing for Message Authentication
			256	[RFC4868] Using HMAC-SHA-256, HMAC-SHA-384, and HMAC-SHA-512 with IPsec
384				

		HMAC-SHA-512-256	512	
--	--	------------------	-----	--

Table 23: Cryptographic operations

6.1.2.4 Cryptographic operation (FCS_COP.1-job)

FCS_COP.1.1 The TSF shall perform the operations defined in Table 24 in accordance with a specified cryptographic algorithm defined in Table 24 and cryptographic key sizes defined in Table 24 that meet the following: the standards defined in Table 24.

Protocol	Operations	Algorithm	Key sizes (in bits)	Standards
Print job	Symmetric decryption	AES (CBC mode)	256	[FIPS197] Advanced Encryption Standard; [SP800-38A] Recommendation for Block Cipher Modes of Operation

Table 24: Cryptographic operations

6.1.3 User data protection (FDP)

6.1.3.1 Common access control SFP (FDP_ACC.1-cac)

FDP_ACC.1.1 The TSF shall enforce the Common Access Control SFP in Table 25 on the list of users as subjects, objects, and operations among subjects and objects covered by the Common Access Control SFP in Table 25.

Object	Operation(s)	Subject	Access control rules	[PP2600.2] section
D.FUNC	Modify, Delete	U.NORMAL	For print jobs in Job Storage with the Job PIN attribute set: From the Control Panel, subjects must be the job owner or know the Job PIN or have the appropriate Job Storage permission in their Permission Set to delete the job; otherwise, delete access is denied. D.FUNC for Stored Jobs cannot be modified by any user, including U.ADMINISTRATOR. For encrypted stored print jobs: From the Control Panel, subjects must know the job's Job Encryption Password or have the appropriate Job Storage permission in their Permission Set to delete D.FUNC; otherwise, delete access is denied.	Common

D.DOC	Delete	U.NORMAL	For print jobs in Job Storage with the Job PIN attribute set: From the Control Panel, subjects must be the job owner or know the Job PIN or have the appropriate Job Storage permission in their Permission Set to delete the job; otherwise, delete access is denied. For encrypted stored print jobs: From the Control Panel, subjects must know the job's Job Encryption Password or have the appropriate Job Storage permission in their Permission Set to delete D.DOC; otherwise, delete access is denied.	Common
D.DOC+DSR D.DOC+PRT	Read	U.NORMAL	For print jobs in Job Storage with the Job PIN attribute set: Subjects must be the job owner or know the Job PIN to read the object; otherwise, read access is denied. For encrypted stored print jobs: Subjects must know the job's Job Encryption Password to read the object, otherwise, read access is denied.	DSR, PRT

Table 25: Common Access Control SFP

6.1.3.2 TOE function access control SFP (FDP_ACC.1-tfac)

FDP_ACC.1.1 The TSF shall enforce the **TOE Function Access Control SFP** on users as subjects, TOE functions as objects, and the right to use the functions as operations.

6.1.3.3 Common access control functions (FDP_ACF.1-cac)

FDP_ACF.1.1 The TSF shall enforce the **Common Access Control SFP** in **Table 25** to objects based on the following: **the list of users as subjects and objects controlled under the Common Access Control SFP in Table 25, and for each, the indicated security attributes in Table 25.**

FDP_ACF.1.2 The TSF shall enforce the following rules to determine if an operation among controlled subjects and controlled objects is allowed: **rules specified in the Common Access Control SFP in Table 25 governing access among controlled users as subjects and controlled objects using controlled operations on controlled objects.**

FDP_ACF.1.3 The TSF shall explicitly authorise access of subjects to objects based on the following additional rules:

- **U.ADMINISTRATOR can delete any D.DOC without providing a Job PIN or Job Encryption Password.**

FDP_ACF.1.4 The TSF shall explicitly deny access of subjects to objects based on the following additional rules: **none**.

6.1.3.4 TOE function access control functions (FDP_ACF.1-tfac)

FDP_ACF.1.1 The TSF shall enforce the **TOE Function Access Control SFP** to objects based on the following: **users and the following TOE functions and security attributes**:

- **Users: Control Panel users;**
Functions: F.DSR, F.PRT, F.SMI;
Security attributes:
 - **User Role as defined by the user's Permission Set**
 - **Association of a sign in method to a Control Panel application**
- **Users: Network Client Computers, Administrative Computer;**
Functions: F.DSR, F.PRT, F.SMI;
Security attributes:
 - **User Role as defined by the user's IPsec/Firewall service templates.**

Application Note: *The "Allow users to choose alternate sign-in methods" function affects the sign in processing behavior of Control Panel users, but is considered a function instead of a security attribute and, thus, not listed under "security attributes" above.*

FDP_ACF.1.2 The TSF shall enforce the following rules to determine if an operation among controlled subjects and controlled objects is allowed:

- **The user is explicitly authorized by U.ADMINISTRATOR to use a function**
- **A Network Client Computer that is authorized to use the TOE is automatically authorized to use the functions F.DSR, F.PRT, F.SMI.**

FDP_ACF.1.3 The TSF shall explicitly authorize access of subjects to objects based on the following additional rules: **the user acts in the role U.ADMINISTRATOR, none**.

FDP_ACF.1.4 The TSF shall explicitly deny access of subjects to objects based on the following additional rules: **none**.

6.1.3.5 Subset residual information protection (FDP_RIP.1)

FDP_RIP.1.1 The TSF shall ensure that any previous information content of a resource is made unavailable upon the **deallocation of the resource from** the following objects: **D.DOC**.

6.1.4 Identification and authentication (FIA)

6.1.4.1 Authentication failure handling (FIA_AFL.1)

FIA_AFL.1.1 The TSF shall detect when **the Number for the specified Sign In method in Table 26** of unsuccessful authentication attempts occur related to **the Event for the same Sign In method in Table 26**.

FIA_AFL.1.2 When the defined number of unsuccessful authentication attempts has been met, the TSF shall perform the Action for the same Sign In method in Table 26.

Application Note: Multiple unsuccessful authentication attempts using the same authentication data are counted as just one unsuccessful authentication attempt by the sign in methods. For example, assuming the LDAP Sign In method has zero unsuccessful authentication attempts, if the same user types the same incorrect password into the LDAP Sign In method seven times in a row, the sign in method will only count it as one unsuccessful authentication attempt.

Sign In method	Number	Event	Action
Local Device Sign In: Administrator Access Code	6	the latest successful authentication for the Administrator Access Code	insert a 10 second delay between each Administrator Access Code authentication attempt until: <ul style="list-style-type: none"> • a successful Administrator Access Code authentication occurs, or • 5 minutes elapses after the last failed Administrator Access Code authentication
Local Device Sign In: User Access Code	6	the last successful authentication for User Access Code sign in method (i.e., per method, not per Access Code)	insert a 10 second delay between all User Access Code authentication attempts until: <ul style="list-style-type: none"> • any successful User Access Code authentication occurs, or • 5 minutes elapses after the last failed authentication of all User Access Codes
LDAP Sign In	6	the last successful authentication for the indicated LDAP Sign In user	insert a 10 second delay between authentication attempts of the indicated user until: <ul style="list-style-type: none"> • a successful authentication of the indicated user occurs, or • 5 minutes elapses after the last failed authentication attempt of the indicated user
Windows Sign In	6	the last successful authentication for the indicated Windows Sign In user	insert a 10 second delay between authentication attempts of the indicated user until: <ul style="list-style-type: none"> • a successful authentication of indicated user occurs, or • 5 minutes elapses after the last failed authentication attempt of the indicated user

Table 26: Simplified Account Lockout for each sign in method

6.1.4.2 Local user attribute definition (FIA_ATD.1)

FIA_ATD.1.1 The TSF shall maintain the following list of security attributes belonging to individual users:

- **Control Panel users:**
 - **User Identifier (Access Code and Display Name) for Local Device Sign In**
 - **User Role (defined by Permission Set)**
- **IPsec users:**
 - **User Identifier (defined by IP address)**
 - **User Role (defined by IPsec/Firewall service template)**

Application Note: *The LDAP and Windows Sign In method security attributes belonging to individual users are not in FIA_ATD.1 because these attributes are "maintained" independently by the LDAP server and Windows domain controller, respectively, which are part of the Operational Environment.*

6.1.4.3 Verification of secrets (FIA_SOS.1)

FIA_SOS.1.1 The TSF shall provide a mechanism to verify that secrets meet **the requirement: Job PINs shall be 4 digits.**

6.1.4.4 Timing of Control Panel authentication (FIA_UAU.1)

FIA_UAU.1.1 The TSF shall allow **viewing of the Control Panel help screens and selection of a sign in method** on behalf of the *Control Panel* user to be performed before the user is authenticated.

FIA_UAU.1.2 The TSF shall require each *Control Panel* user to be successfully authenticated before allowing any other TSF-mediated actions on behalf of that user.

6.1.4.5 IPsec authentication before any action (FIA_UAU.2)

FIA_UAU.2.1 The TSF shall require each *Network Client Computer, Administrative Computer, and trusted IT product connection user* to be successfully authenticated before allowing any other TSF-mediated actions on behalf of that *connection user*.

6.1.4.6 Control Panel protected authentication feedback (FIA_UAU.7)

FIA_UAU.7.1 The TSF shall provide only **asterisk characters (models with 4.3-inch LCD touchscreen) or dot characters (models with 4-line LCD non-touchscreen) for each**

- **Access Code digit typed**

- **Authentication password character typed**
- **Job PIN digit typed**

to the user while the *Control Panel* authentication is in progress.

Application Note: *Job PINs are not used for authentication, but the digits are masked when entered.*

6.1.4.7 Timing of Control Panel identification (FIA_UID.1)

FIA_UID.1.1 The TSF shall allow **viewing of the Control Panel help screens and selection of a sign in method** on behalf of the *Control Panel* user to be performed before the user is identified.

FIA_UID.1.2 The TSF shall require each *Control Panel* user to be successfully identified before allowing any other TSF-mediated actions on behalf of that user.

6.1.4.8 IPsec identification before any action (FIA_UID.2)

FIA_UID.2.1 The TSF shall require each *Network Client Computer, Administrative Computer, and trusted IT product connection user* to be successfully identified before allowing any other TSF-mediated actions on behalf of that *connection user*.

6.1.4.9 User-subject binding (FIA_USB.1)

FIA_USB.1.1 The TSF shall associate the following user security attributes with subjects acting on the behalf of that user: **User Identifier (Display Name for Local Device Sign In, user name for both LDAP Sign In and Windows Sign In, IP address for IPsec) and User Role.**

FIA_USB.1.2 The TSF shall enforce the following rules on the initial association of user security attributes with subjects acting on behalf of users: **If "Allow users to choose alternate sign-in methods" is disabled, the user's session Permission Set will be reduced to exclude the permissions of applications whose sign in method does not match the sign in method used by the user to sign in.**

FIA_USB.1.3 The TSF shall enforce the following rules governing changes to the user security attributes ~~associated~~ with the subjects acting on the behalf of users: **none.**

6.1.5 Security management (FMT)

6.1.5.1 Management of authentication security functions behavior (FMT_MOF.1)

FMT_MOF.1.1 The TSF shall restrict the ability to **enable, disable** the functions **"Allow users to choose alternate sign-in methods"** for **Control Panel applications** to **U.ADMINISTRATOR.**

6.1.5.2 Management of Permission Set security attributes (FMT_MSA.1-perm)

FMT_MSA.1.1 The TSF shall enforce the **Common Access Control SFP in Table 25 and TOE Function Access Control SFP** to restrict the ability to **modify, create, delete** the security attributes **Permission Sets and Permission Set associations** to **U.ADMINISTRATOR**.

Application Note: *The rule applies to all the Permission Sets except the Device Administrator and Device User. These default Permission Sets cannot be created, renamed or deleted. In addition, the permissions in Device Administrator Permission Set cannot be modified.*

6.1.5.3 Management of TOE function security attributes (FMT_MSA.1-tfac)

FMT_MSA.1.1 The TSF shall enforce the **TOE Function Access Control SFP** to restrict the ability to **perform the following operations on** the security attributes

- **IPsec/Firewall service templates (defining IPsec User Roles): create, modify, delete operations**
- **Association of a sign in method to a Control Panel application: modify operation**

to **U.ADMINISTRATOR**.

6.1.5.4 Management of TSF data (FMT_MTD.1-auth)

FMT_MTD.1.1 The TSF shall restrict the ability to **perform operations specified below for** the

- **IPsec CA X.509v3 certificate: add, replace, delete operations**
- **IPsec identity X.509v3 certificate: replace operation**
- **IPsec/Firewall address templates and rules for IPsec users: create, modify, delete operations**
- **IPsec/Firewall address templates, service templates, and rules for trusted IT products: create, modify, delete operations**

to **U.ADMINISTRATOR**.

6.1.5.5 Management of TSF data (FMT_MTD.1-users)

FMT_MTD.1.1 The TSF shall restrict the ability to **modify, delete, initialize** the **Device User Accounts** to **U.ADMINISTRATOR**.

6.1.5.6 Specification of management functions (FMT_SMF.1)

FMT_SMF.1.1 The TSF shall be capable of performing the following management functions:

- **IPsec/Firewall rules, address templates, and service templates management (FMT_MSA.1-tfac, FMT_MTD.1-auth)**
- **IPsec X.509v3 certificate management (FMT_MTD.1-auth)**
- **Local Device Sign In data (Access Code) management (FMT_MTD.1-users)**

- **Permission Set management (FMT_MSA.1-perm)**
- **Sign in method association management (FMT_MOF.1, FMT_MSA.1-tfac).**

6.1.5.7 Security roles (FMT_SMR.1)

FMT_SMR.1.1 The TSF shall maintain the roles **U.ADMINISTRATOR, U.NORMAL.**

FMT_SMR.1.2 The TSF shall be able to associate users with roles.

6.1.6 Protection of the TSF (FPT)

6.1.6.1 Restricted forwarding of data to external interfaces (FPT_FDI_EXP.1)

FPT_FDI_EXP.1.1 The TSF shall provide the capability to restrict data received on **any external Interface** from being forwarded without further processing by the TSF to any **Shared-medium Interface.**

6.1.6.2 Reliable time stamps (FPT_STM.1)

FPT_STM.1.1 The TSF shall be able to provide reliable time stamps.

6.1.6.3 TSF testing (FPT_TST.1)

FPT_TST.1.1 The TSF shall run a suite of self tests **at the request of the authorised user** to demonstrate the correct operation of

- **System Clock - Timestamp verification**
- **Local Device Sign In - User Access Code verification**
- **LDAP Sign In - LDAP Settings verification**
- **Windows Sign In (via Kerberos) - Windows Settings verification.**

FPT_TST.1.2 The TSF shall provide authorised users with the capability to verify the integrity of

- **Local Device Sign In database**
- **Device Administrator Password**
- **User and administrator authentication configuration data (including Permission Sets and sign-in method assigned to top-level Control Panel application).**

FPT_TST.1.3 The TSF shall provide authorised users with the capability to verify the integrity of **stored TSF executable code.**

6.1.7 TOE access (FTA)

6.1.7.1 Control Panel TSF-initiated termination (FTA_SSL.3)

- FTA_SSL.3.1
- The TSF shall terminate ~~an~~ a *Control Panel* interactive session after a **20 seconds of user inactivity**.

6.1.8 Trusted path/channels (FTP)

6.1.8.1 Inter-TSF trusted channel (FTP_ITC.1)

FTP_ITC.1.1 The TSF shall provide a communication channel between itself and another trusted IT product that is logically distinct from other communication channels and provides assured identification of its end points and protection of the ~~channel~~ *communicated* data from modification or disclosure.

FTP_ITC.1.2 The TSF shall permit **the TSF, another trusted IT product** to initiate communication via the trusted channel.

FTP_ITC.1.3 The TSF shall initiate communication via the trusted channel for **communication of D.DOC, D.FUNC, D.PROT, and D.CONF over any Shared-medium Interface**.

6.2 Security Functional Requirements Rationale

6.2.1 Coverage

The following table provides a mapping of SFR to the security objectives, showing that each security functional requirement addresses at least one security objective.

Security functional requirements	Objectives
FAU_GEN.1	O.AUDIT.LOGGED
FAU_GEN.2	O.AUDIT.LOGGED
FCS_CKM.1	O.CONF.NO_ALT, O.CONF.NO_DIS, O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT, O.PROT.NO_ALT
FCS_CKM.2	O.CONF.NO_ALT, O.CONF.NO_DIS, O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT, O.PROT.NO_ALT

Security functional requirements	Objectives
FCS_COP.1-ipsec	O.CONF.NO_ALT, O.CONF.NO_DIS, O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT, O.PROT.NO_ALT
FCS_COP.1-job	O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT
FDP_ACC.1-cac	O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT
FDP_ACC.1-tfac	O.USER.AUTHORIZED
FDP_ACF.1-cac	O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT
FDP_ACF.1-tfac	O.USER.AUTHORIZED
FDP_RIP.1	O.DOC.NO_DIS
FIA_AFL.1	O.USER.AUTHORIZED
FIA_ATD.1	O.USER.AUTHORIZED
FIA_SOS.1	O.USER.AUTHORIZED
FIA_UAU.1	O.INTERFACE.MANAGED, O.USER.AUTHORIZED
FIA_UAU.2	O.INTERFACE.MANAGED, O.USER.AUTHORIZED
FIA_UAU.7	O.CONF.NO_DIS

Security functional requirements	Objectives
FIA_UID.1	O.AUDIT.LOGGED, O.CONF.NO_ALT, O.CONF.NO_DIS, O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT, O.INTERFACE.MANAGED, O.PROT.NO_ALT, O.USER.AUTHORIZED
FIA_UID.2	O.AUDIT.LOGGED, O.CONF.NO_ALT, O.CONF.NO_DIS, O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT, O.INTERFACE.MANAGED, O.PROT.NO_ALT, O.USER.AUTHORIZED
FIA_USB.1	O.USER.AUTHORIZED
FMT_MOF.1	O.PROT.NO_ALT
FMT_MSA.1-perm	O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT, O.USER.AUTHORIZED
FMT_MSA.1-tfac	O.USER.AUTHORIZED
FMT_MTD.1-auth	O.CONF.NO_ALT, O.CONF.NO_DIS, O.PROT.NO_ALT
FMT_MTD.1-users	O.CONF.NO_ALT, O.CONF.NO_DIS, O.PROT.NO_ALT
FMT_SMF.1	O.CONF.NO_ALT, O.CONF.NO_DIS, O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT, O.PROT.NO_ALT

Security functional requirements	Objectives
FMT_SMR.1	O.CONF.NO_ALT, O.CONF.NO_DIS, O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT, O.PROT.NO_ALT, O.USER.AUTHORIZED
FPT_FDI_EXP.1	O.INTERFACE.MANAGED
FPT_STM.1	O.AUDIT.LOGGED
FPT_TST.1	O.SOFTWARE.VERIFIED
FTA_SSL.3	O.INTERFACE.MANAGED, O.USER.AUTHORIZED
FTP_ITC.1	O.CONF.NO_ALT, O.CONF.NO_DIS, O.DOC.NO_ALT, O.DOC.NO_DIS, O.FUNC.NO_ALT, O.PROT.NO_ALT

Table 27: Mapping of security functional requirements to security objectives

6.2.2 Sufficiency

The following rationale provides justification for each security objective for the TOE, showing that the security functional requirements are suitable to meet and achieve the security objectives:

Security objectives	Rationale
O.AUDIT.LOGGED	<p>The objective:</p> <ul style="list-style-type: none"> • The TOE shall create and maintain a log of TOE use and security-relevant events, and prevent its unauthorized disclosure or alteration. <p>is met by:</p> <ul style="list-style-type: none"> • FAU_GEN.1 which enforces audit policies by requiring logging of relevant events. • FAU_GEN.2 which enforces audit policies by requiring logging of information associated with audited events. • FIA_UID.1 and FIA_UID.2 which support audit policies by associating user identity with events

Security objectives	Rationale
	<ul style="list-style-type: none"> • FPT_STM.1 which supports audit policies by requiring time stamps associated with events.
O.CONF.NO_ALT	<p>The objective:</p> <ul style="list-style-type: none"> • The TOE shall protect TSF Confidential Data from unauthorized alteration. <p>is met by:</p> <ul style="list-style-type: none"> • FCS_CKM.1 which specifies the type of cryptographic keys generated by the TOE for use with HMAC algorithms in IPsec. • FCS_CKM.2 which specifies the cryptographic key distribution methods used by the TOE in IKEv1 and IKEv2 in IPsec. • FCS_COP.1-ipsec which specifies the RSA decryption algorithms and HMAC algorithms used by the TOE. • FIA_UID.1 and FIA_UID.2 which support access control and security roles by requiring user identification. • FMT_MTD.1-auth and FMT_MTD.1-users which enforce protection by restricting access. • FMT_SMF.1 which supports control of security attributes by requiring functions to control attributes. • FMT_SMR.1 which supports control of security attributes by requiring security roles. • FTP_ITC.1 which enforces protection by requiring the use of trusted channels for communication of data over Shared-medium Interfaces.
O.CONF.NO_DIS	<p>The objective:</p> <ul style="list-style-type: none"> • The TOE shall protect TSF Confidential Data from unauthorized disclosure. <p>is met by:</p> <ul style="list-style-type: none"> • FCS_CKM.1 which specifies the type of cryptographic keys generated by the TOE for use with AES in IPsec. • FCS_CKM.2 which specifies the cryptographic key distribution methods used by the TOE in IKEv1 and IKEv2 in IPsec. • FCS_COP.1-ipsec which specifies the AES encryption/decryption algorithms and the RSA decryption algorithms used by the TOE in IPsec. • FIA_UAU.7 which masks the display of certain passwords and PINs during authentication. • FIA_UID.1 and FIA_UID.2 which support access control and security roles by requiring user identification.

Security objectives	Rationale
	<ul style="list-style-type: none"> • FMT_MTD.1-auth and FMT_MTD.1-users which enforce protection by restricting access. • FMT_SMF.1 which supports control of security attributes by requiring functions to control attributes. • FMT_SMR.1 which supports control of security attributes by requiring security roles. • FTP_ITC.1 which enforces protection by requiring the use of trusted channels for communication of data over Shared-medium Interfaces.
O.DOC.NO_ALT	<p>The objective:</p> <ul style="list-style-type: none"> • The TOE shall protect User Document Data from unauthorized alteration. <p>is met by:</p> <ul style="list-style-type: none"> • FCS_CKM.1 which specifies the type of cryptographic keys generated by the TOE for use with HMAC algorithms in IPsec. • FCS_CKM.2 which specifies the cryptographic key distribution methods used by the TOE in IKEv1 and IKEv2 in IPsec. • FCS_COP.1-ipsec which specifies the RSA decryption algorithms used by the TOE and the HMAC algorithms used by the TOE in IPsec. • FCS_COP.1-job which specifies the AES decryption algorithm used by the TOE to process encrypted jobs. • FDP_ACC.1-cac which enforces protection by establishing an access control policy. • FDP_ACF.1-cac which supports access control policy by providing access control function. • FIA_UID.1 and FIA_UID.2 which support access control and security roles by requiring user identification. • FMT_MSA.1-perm which supports access control function by enforcing control of security attributes. • FMT_SMF.1 which supports control of security attributes by requiring functions to control attributes. • FMT_SMR.1 which supports control of security attributes by requiring security roles. • FTP_ITC.1 which enforces protection by requiring the use of trusted channels for communication of data over Shared-medium Interfaces.
O.DOC.NO_DIS	<p>The objective:</p>

Security objectives	Rationale
	<ul style="list-style-type: none"> • The TOE shall protect User Document Data from unauthorized disclosure. <p>is met by:</p> <ul style="list-style-type: none"> • FCS_CKM.1 which specifies the type of cryptographic keys generated by the TOE for use with AES in IPsec. • FCS_CKM.2 which specifies the cryptographic key distribution methods used by the TOE in IKEv1 and IKEv2 in IPsec. • FCS_COP.1-ipsec which specifies the AES encryption/decryption algorithms and the RSA decryption algorithms used by the TOE in IPsec. • FCS_COP.1-job which specifies the AES decryption algorithm used by the TOE to process encrypted jobs. • FDP_ACC.1-cac which enforces protection by establishing an access control policy. • FDP_ACF.1-cac which supports access control policy by providing access control function. • FDP_RIP.1 which enforces protection by making residual data unavailable. • FIA_UID.1 and FIA_UID.2 which support access control and security roles by requiring user identification. • FMT_MSA.1-perm which supports access control function by enforcing control of security attributes. • FMT_SMF.1 which supports control of security attributes by requiring functions to control attributes. • FMT_SMR.1 which supports control of security attributes by requiring security roles. • FTP_ITC.1 which enforces protection by requiring the use of trusted channels for communication of data over Shared-medium Interfaces.
O.FUNC.NO_ALT	<p>The objective:</p> <ul style="list-style-type: none"> • The TOE shall protect User Function Data from unauthorized alteration. <p>is met by:</p> <ul style="list-style-type: none"> • FCS_CKM.1 which specifies the type of cryptographic keys generated by the TOE for use with HMAC algorithms in IPsec. • FCS_CKM.2 which specifies the cryptographic key distribution methods used by the TOE in IKEv1 and IKEv2 in IPsec. • FCS_COP.1-ipsec which specifies the RSA decryption algorithms used by the TOE and the HMAC algorithms used by the TOE in IPsec.

Security objectives	Rationale
	<ul style="list-style-type: none"> • FDP_ACC.1-cac which enforces protection by establishing an access control policy. • FDP_ACF.1-cac which supports access control policy by providing access control function. • FIA_UID.1 and FIA_UID.2 which support access control and security roles by requiring user identification. • FMT_MSA.1-perm which supports access control function by enforcing control of security attributes. • FMT_SMF.1 which supports control of security attributes by requiring functions to control attributes. • FMT_SMR.1 which supports control of security attributes by requiring security roles. • FTP_ITC.1 which enforces protection by requiring the use of trusted channels for communication of data over Shared-medium Interfaces.
O.INTERFACE.MANAGED	<p>The objective:</p> <ul style="list-style-type: none"> • The TOE shall manage the operation of external interfaces in accordance with security policies. <p>is met by:</p> <ul style="list-style-type: none"> • FIA_UAU.1 and FIA_UAU.2 which enforce management of external interfaces by requiring user authentication. • FIA_UID.1 and FIA_UID.2 which enforce management of external interfaces by requiring user identification. • FPT_FDI_EXP.1 which enforces management of external interfaces by requiring (as needed) administrator control of data transmission from external Interfaces to Shared-medium Interfaces. • FTA_SSL.3 which enforces management of external interfaces by terminating inactive sessions.
O.PROT.NO_ALT	<p>The objective:</p> <ul style="list-style-type: none"> • The TOE shall protect TSF Protected Data from unauthorized alteration. <p>is met by:</p> <ul style="list-style-type: none"> • FCS_CKM.1 which specifies the type of cryptographic keys generated by the TOE for use with HMAC algorithms in IPsec. • FCS_CKM.2 which specifies the cryptographic key distribution methods used by the TOE in IKEv1 and IKEv2 in IPsec. • FCS_COP.1-ipsec which specifies the RSA decryption algorithm and the HMAC algorithms used by the TOE in IPsec.

Security objectives	Rationale
	<ul style="list-style-type: none"> • FIA_UID.1 and FIA_UID.2 which support access control and security roles by requiring user identification. • FMT_MOF.1 which specifies the roles that can manage the selection of sign in methods. • FMT_MTD.1-auth and FMT_MTD.1-users which enforce protection by restricting access. • FMT_SMF.1 which supports control of security attributes by requiring functions to control attributes. • FMT_SMR.1 which supports control of security attributes by requiring security roles. • FTP_ITC.1 which enforces protection by requiring the use of trusted channels for communication of data over Shared-medium Interfaces.
O.SOFTWARE.VERIFIED	<p>The objective:</p> <ul style="list-style-type: none"> • The TOE shall provide procedures to self-verify executable code in the TSF. <p>is met by:</p> <ul style="list-style-type: none"> • FPT_TST.1 which enforces verification of software by requiring the TOE include self-tests.
O.USER.AUTHORIZED	<p>The objective:</p> <ul style="list-style-type: none"> • The TOE shall require identification and authentication of Users, and shall ensure that Users are authorized in accordance with security policies before allowing them to use the TOE. <p>is met by:</p> <ul style="list-style-type: none"> • FDP_ACC.1-tfac which enforces authorization by establishing an access control policy. • FDP_ACF.1-tfac which supports access control policy by providing access control function. • FIA_AFL.1 which slows the number of unsuccessful Control Panel authentication attempts made over a period of time. • FIA_ATD.1 which supports authorization by associating security attributes with users. • FIA_SOS.1 which specifies the password/PIN strength of certain authentication mechanisms. • FIA_UAU.1 and FIA_UAU.2 which enforce authorization by requiring user authentication. • FIA_UID.1 and FIA_UID.2 which enforce authorization by requiring user identification.

Security objectives	Rationale
	<ul style="list-style-type: none"> • FIA_USB.1 which enforces authorization by distinguishing subject security attributes associated with User Roles. • FMT_MSA.1-perm and FMT_MSA.1-tfac which support access control function by enforcing control of security attributes. • FMT_SMR.1 which supports authorization by requiring security roles. • FTA_SSL.3 which enforces authorization by terminating inactive sessions.

Table 28: Security objectives for the TOE rationale

6.2.3 Security requirements dependency analysis

The following table demonstrates the dependencies of SFRs modeled in CC Part 2 and how the SFRs for the TOE resolve those dependencies:

Security functional requirement	Dependencies	Resolution
FAU_GEN.1	FPT_STM.1	FPT_STM.1
FAU_GEN.2	FAU_GEN.1	FAU_GEN.1
	FIA_UID.1	FIA_UID.1
FCS_CKM.1	[FCS_CKM.2 or FCS_COP.1]	FCS_CKM.2 FCS_COP.1-ipsec
	FCS_CKM.4	This dependency is unresolved. The generated keys are not formally destroyed. The object reuse mechanisms of the operating system prevent their use except in the intended context.
FCS_CKM.2	[FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1]	FCS_CKM.1
	FCS_CKM.4	This dependency is unresolved. The distributed symmetric keys are not formally destroyed. The object reuse mechanisms in the operating system prevent their use except in the intended context.
FCS_COP.1-ipsec	[FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1]	FCS_CKM.1

Security functional requirement	Dependencies	Resolution
	FCS_CKM.4	This dependency is unresolved. The keys used for encryption, decryption, and data authentication are not formally destroyed. The object reuse mechanisms in the operating system prevent their use except in the intended context.
FCS_COP.1-job	[FDP_ITC.1 or FDP_ITC.2 or FCS_CKM.1]	This dependency is unresolved. The Client Computer encrypts the print job prior to sending the print job to the TOE using an AES 256-bit key derived from the user's Job Encryption Password. The TOE requires the Control Panel user to reenter the same Job Encryption Password so that the TOE can derive the same AES 256-bit key in order to decrypt the print job.
	FCS_CKM.4	This dependency is unresolved. The key used for decryption is not formally destroyed. The object reuse mechanisms in the operating system prevent their use except in the intended context.
FDP_ACC.1-cac	FDP_ACF.1	FDP_ACF.1-cac
FDP_ACC.1-tfac	FDP_ACF.1	FDP_ACF.1-tfac
FDP_ACF.1-cac	FDP_ACC.1	FDP_ACC.1-cac
	FMT_MSA.3	This dependency is unresolved. The Job PIN, Job Encryption Password, and Permission Sets do not have default values and do not allow for the specification of alternative initial values.
FDP_ACF.1-tfac	FDP_ACC.1	FDP_ACC.1-tfac
	FMT_MSA.3	This dependency is unresolved. The IP service templates, associations of sign in method to a Control Panel application, and Permission Sets do not have default values and do not allow for the specification of alternative initial values.
FDP_RIP.1	No dependencies.	
FIA_AFL.1	FIA_UAU.1	FIA_UAU.1
FIA_ATD.1	No dependencies.	
FIA_SOS.1	No dependencies.	

Security functional requirement	Dependencies	Resolution
FIA_UAU.1	FIA_UID.1	FIA_UID.1
FIA_UAU.2	FIA_UID.1	FIA_UID.2
FIA_UAU.7	FIA_UAU.1	FIA_UAU.1
FIA_UID.1	No dependencies.	
FIA_UID.2	No dependencies.	
FIA_USB.1	FIA_ATD.1	FIA_ATD.1
FMT_MOF.1	FMT_SMR.1	FMT_SMR.1
	FMT_SMF.1	FMT_SMF.1
FMT_MSA.1-perm	[FDP_ACC.1 or FDP_IFC.1]	FDP_ACC.1-cac FDP_ACC.1-tfac
	FMT_SMR.1	FMT_SMR.1
	FMT_SMF.1	FMT_SMF.1
FMT_MSA.1-tfac	[FDP_ACC.1 or FDP_IFC.1]	FDP_ACC.1-tfac
	FMT_SMR.1	FMT_SMR.1
	FMT_SMF.1	FMT_SMF.1
FMT_MTD.1-auth	FMT_SMR.1	FMT_SMR.1
	FMT_SMF.1	FMT_SMF.1
FMT_MTD.1-users	FMT_SMR.1	FMT_SMR.1
	FMT_SMF.1	FMT_SMF.1
FMT_SMF.1	No dependencies.	
FMT_SMR.1	FIA_UID.1	FIA_UID.1
FPT_FDI_EXP.1	FMT_SMR.1	FMT_SMR.1

Security functional requirement	Dependencies	Resolution
	FMT_SMF.1	FMT_SMF.1
FPT_STM.1	No dependencies.	
FPT_TST.1	No dependencies.	
FTA_SSL.3	No dependencies.	
FTP_ITC.1	No dependencies.	

Table 29: TOE SFR dependency analysis

6.2.4 Internal consistency and mutual support of SFRs

6.3 Security Assurance Requirements

The security assurance requirements for the TOE are the Evaluation Assurance Level 2 components as specified in [CC] part 3, augmented by ALC_FLR.2.

The following table shows the Security assurance requirements, and the operations performed on the components according to CC part 3: iteration (Iter.), refinement (Ref.), assignment (Ass.) and selection (Sel.).

Security assurance class	Security assurance requirement	Source	Operations			
			Iter.	Ref.	Ass.	Sel.
ADV Development	ADV_ARC.1 Security architecture description	CC Part 3	No	No	No	No
	ADV_FSP.2 Security-enforcing functional specification	CC Part 3	No	No	No	No
	ADV_TDS.1 Basic design	CC Part 3	No	No	No	No
AGD Guidance documents	AGD_OPE.1 Operational user guidance	CC Part 3	No	No	No	No
	AGD_PRE.1 Preparative procedures	CC Part 3	No	No	No	No
ALC Life-cycle support	ALC_CMC.2 Use of a CM system	CC Part 3	No	No	No	No

Security assurance class	Security assurance requirement	Source	Operations			
			Iter.	Ref.	Ass.	Sel.
	ALC_CMS.2 Parts of the TOE CM coverage	CC Part 3	No	No	No	No
	ALC_DEL.1 Delivery procedures	CC Part 3	No	No	No	No
	ALC_FLR.2 Flaw reporting procedures	CC Part 3	No	No	No	No
ASE Security Target evaluation	ASE_INT.1 ST introduction	CC Part 3	No	No	No	No
	ASE_CCL.1 Conformance claims	CC Part 3	No	No	No	No
	ASE_SPD.1 Security problem definition	CC Part 3	No	No	No	No
	ASE_OBJ.2 Security objectives	CC Part 3	No	No	No	No
	ASE_ECD.1 Extended components definition	CC Part 3	No	No	No	No
	ASE_REQ.2 Derived security requirements	CC Part 3	No	No	No	No
	ASE_TSS.1 TOE summary specification	CC Part 3	No	No	No	No
ATE Tests	ATE_COV.1 Evidence of coverage	CC Part 3	No	No	No	No
	ATE_FUN.1 Functional testing	CC Part 3	No	No	No	No
	ATE_IND.2 Independent testing - sample	CC Part 3	No	No	No	No
AVA Vulnerability assessment	AVA_VAN.2 Vulnerability analysis	CC Part 3	No	No	No	No

Table 30: Security assurance requirements

6.4 Security Assurance Requirements Rationale

The evaluation assurance level has been chosen to match a Basic attack potential commensurate with the threat environment that is experienced by typical consumers of the TOE and commensurate with [PP2600.2]. In addition, the evaluation assurance level has been augmented with ALC_FLR.2 commensurate with the augmented flaw remediation capabilities offered by the developer beyond those required by the evaluation assurance level and commensurate with [PP2600.2].

7 TOE Summary Specification

7.1 TOE Security Functionality

The following section explains how the security functions are implemented by the TOE. The different TOE security functions cover the various SFR classes.

The primary security features of the TOE are:

- Auditing
- Cryptography
- Identification and authentication
- Data protection and access control
- Protection of the TSF
- TOE access protection
- Trusted channel communication and certificate management
- User and access management

7.1.1 Auditing

The TOE performs auditing of security relevant functions. The TOE connects and sends audit records to a syslog server (part of the Operational Environment) for long-term storage and audit review. The records sent to the syslog server by the TOE are only those generated by the TOE while the syslog server has an established connection with the TOE. If the connection between the TOE and syslog server breaks and is later reestablished, only records generated by the TOE after the connection is reestablished are sent to the syslog server. Both the Jetdirect Inside and HCD System firmware generate audit records.

The types of records generated by the TOE are specified in section 6.1.1.1. Each record includes the date and time of the event, type of event, subject identity (if applicable), and the outcome (success or failure) of the event. Events resulting from actions of identified users are associated with the identity of the user that caused the event.

The subject identity used in the audit record is formed in the following manner. For Local Device Sign In, the subject's identity contains the user's Display Name prefixed with "LOCAL". For LDAP Sign In, the subject's identity contains the user's LDAP user name prefixed with either the LDAP server's host name or IP address then a backslash. For Windows Sign In, the subject's identity contains the user's Windows domain name and Windows user name separated by a "\". For IPsec, the subject's identity is the user's IP address.

The time source used for the audit record timestamps is discussed in section 7.1.5.3.

This section maps to the following SFRs:

- FAU_GEN.1
- FAU_GEN.2

7.1.2 Cryptography

The TOE uses IPsec to protect its communications channels. The QuickSec cryptographic library, which is part of the Operational Environment, is used to supply the cryptographic algorithms for IPsec. See section 7.1.7 for more information.

The TOE supports the decrypting of print jobs encrypted using the Job Encryption Password. The decryption code used by the TOE is included in the TOE. See [section 7.1.4.3](#) for more information.

7.1.3 Identification and authentication (I&A)

The TOE supports multiple Control Panel sign in methods, both local and remote methods. It also supports IPsec identification and mutual authentication.

The following interfaces support I&A:

- Control Panel
- IPsec

7.1.3.1 Control Panel I&A

The Control Panel interface supports both local and remote sign in methods. The following sign in methods are allowed with the evaluated configuration:

- Local sign in method:
 - Local Device Sign In
- Remote sign in methods:
 - LDAP Sign In
 - Windows Sign In (via Kerberos)

(The servers for the remote sign in methods are part of the Operational Environment.)

The Control Panel also allows both non-administrative users (U.NORMAL) and administrative users (U.ADMINISTRATOR) to sign in. Prior to sign in, the Control Panel allows users to select a sign in method, sign in to the TOE, or get help on various printer functions.

The TOE contains a local user database for defining non-administrative (U.NORMAL, by default) device user and administrative (U.ADMINISTRATOR) device user accounts used to support the Local Device Sign In mechanism. Each device user account contains the following security attributes:

- Access Code (8 digits)
- Display Name
- Permission Set

The Access Code is a number that serves as both the login user identifier and the authentication secret. Each user's Access Code is unique from all other Local Device users. In the evaluated configuration, the Access Code length must be 8 digits, which is the largest length for an Access Code allowed by the TOE. The length of the Access Code is manually enforced by the administrator.

The one exception is the Local Device Administrator Access Code, also known as the Device Administrator Password. While stored on the device, this password can be as long as 16 characters and composed of letters, numbers, and special characters. The Device Administrator Password can also be used to sign in to EWS or the Web Services interface from a remote computer in addition to signing in at the Control Panel.

The Display Name is a unique name assigned to the account by the administrator. This name is a security attribute because it is used in audit records to identify the user. (The Access Code is not written in the audit records.)

The Permission Set defines/determines a user's access to many of the TOE's functions. Permission Sets are discussed in more detail in [section 7.1.4.1](#).

Like Local Device Sign In, the remote sign in methods are only used by the Control Panel. The TOE receives authentication credentials from the Control Panel users and passes the credentials to the remote sign in method. The remote sign in method returns an authentication decision to the TOE. This decision is then enforced by the TOE by granting or denying access to the Control Panel user.

In the case of LDAP, the user name and password entered at the Control Panel are used to bind to the LDAP server. The user must have a valid and active LDAP account in order to successfully bind using this method.

In the case of Kerberos, the user name and password entered at the Control Panel are used to authenticate with the Windows domain controller. The user must have a valid and active Windows domain account in order to successfully bind using this method.

When a user successfully logs in to the Control Panel, the Permission Set associated with that user is bound to that user instance and defines the user's User Role.

When users authenticate through the Control Panel, the TOE displays an asterisk character (models with 4.3-inch LCD touchscreen) or a dot character (models with 4-line LCD non-touchscreen) for each character of a PIN, Access Code, or password typed to prevent onlookers from viewing another user's authentication data. (Job PINs are not authentication data, but the Job PIN is masked.)

The TOE contains a feature called Simplified Account Lockout to help protect against brute-force attacks at the Control Panel. Each Control Panel sign in method performs its Simplified Account Lockout independent of the other Control Panel sign in methods.

The Administrator Access Code method inserts a 10 second delay between each Administrator Access Code authentication attempt upon reaching 6 failed attempts. It keeps inserting the delay until either:

- a valid Administrator Access Code is entered, or
- 5 minutes elapses after the last failed Administrator Access Code authentication attempt.

The User Access Code method inserts a 10 second delay between each User Access Code authentication attempt upon reaching 6 failed attempts. The failed attempts count cumulative for the entire method, not per Access Code. It keeps inserting the delay until either:

- a valid User Access Code is entered, or
- 5 minutes elapses after all failed User Access Code authentication attempts.

The LDAP Sign In method inserts a 10 second delay between each authentication attempt by the same LDAP user upon reaching 6 failed attempts. It keeps inserting the delay until either:

- the indicated LDAP user successfully authenticates, or
- 5 minutes elapses after the last failed authentication attempt by the indicated LDAP user.

Like the LDAP Sign In method, the Windows Sign In method inserts a 10 second delay between each authentication attempt by the same Windows user upon reaching 6 failed attempts. It keeps inserting the delay until either:

- the indicated Windows user successfully authenticates, or
- 5 minutes elapses after the last failed authentication attempt by the indicated Windows user.

Multiple unsuccessful authentication attempts using the same authentication data are counted as just one unsuccessful authentication attempt by the sign in methods. For example, assuming the LDAP Sign In method has zero unsuccessful authentication attempts, if the same user types the same incorrect password into the LDAP Sign In method seven times in a row, the sign in method will only count it as one unsuccessful authentication attempt.

This section maps to the following SFRs:

- FIA_AFL.1
- FIA_ATD.1 (Access Code, User Role)
- FIA_UAU.1
- FIA_UAU.7
- FIA_UID.1
- FIA_USB.1
- FMT_SMR.1

7.1.3.2 IPsec I&A

The TOE uses IPsec to identify and mutually authenticate the following user types:

- Administrative Computer (U.ADMINISTRATOR)
- Network Client Computers (U.NORMAL)

IPsec uses IP addresses and X.509v3 certificates via the IKE protocols (IKEv1 and IKEv2) to identify and authenticate, respectively, a client computer. The TOE contains an X.509v3 identity certificate and an X.509v3 CA certificate to use for the IPsec mutual authentication. The TOE does not maintain individual X.509v3 certificates of its client computers.

The User Identity of a client computer is its IP address. The TOE's internal firewall maintains lists (IPsec/Firewall address templates) of IP addresses of client computers that can connect to the TOE as a Network Client Computer and as the Administrative Computer. If a client computer has an unrecognized IP address that is not defined in the IPsec/Firewall as either the Administrative Computer or a Network Client Computer, then the client computer is not allowed to connect to the TOE. Similarly, if the client computer presents an invalid or unknown (unrecognized CA) X.509v3 certificate, the IPsec mutual authentication mechanism will fail.

The TOE also uses IP addresses and X.509v3 certificates via the IKE protocols to connect to and identify other trusted IT products. See [section 7.1.7](#) for more details.

The TOE supports the following versions of the IKE protocol:

- IKEv1 ([RFC2409] and [RFC4109])
- IKEv2 ([RFC4306] and [RFC4718])

Mutual identification and authentication must be completed before any tasks can be performed by a Network Client Computer or an Administrative Computer.

The service templates define the User Role of a client computer. The following service templates are used to define the TOE's User Roles for IPsec users:

- All Services (U.ADMINISTRATOR)
- Client Computers (U.NORMAL)

The All Services service template is provided with the TOE. The Client Computers service template is created by the administrator as part of the TOE's configuration guidance.

Both the Administrative Computer and the Network Client Computers can access the PjL Interface on port 9100, but only the Administrative Computer can access the EWS (HTTP) interface, Web Services interface (OXPD and WS-*), and SNMP interface.

IP address management is discussed in [section 7.1.4.5](#). Certificate management is discussed in [section 7.1.7](#).

This section maps to the following SFRs:

- FIA_ATD.1
- FIA_UAU.2
- FIA_UID.2
- FIA_USB.1
- FMT_SMR.1

7.1.4 Data protection and access control

7.1.4.1 Permission Sets

For Control Panel users, the TOE uses a user's User Role (as determined by each user's Permission Set) to determine a user's access to many TOE functions. Only U.ADMINISTRATOR can create, modify, and delete Permission Sets. In addition, only U.ADMINISTRATOR can create, modify, and delete the Permission Set associations to users. By default, the TOE includes the following Permission Sets:

- Device Administrator (U.ADMINISTRATOR)
- Device User (U.NORMAL)

These default Permission Sets cannot be created, renamed or deleted. In addition, the permissions in Device Administrator cannot be modified.

Permissions in a Permission Set include permissions as high-level as executing the Retrieve from Device Memory application. They also include more granular permissions that control administrative functions like the ability to delete any Job Storage job. Each permission in a Permission Set has two possible values: allowed and disallowed.

This section maps to the following SFRs:

- FMT_MSA.1-perm
- FMT_SMF.1

7.1.4.2 Job PINs

Users can control access to each print job that they place under the TOE's control by assigning a Job PIN to each job. A Job PIN limits access to a stored print job while the job resides under the TOE's control and allows a user to control when the job is printed so that physical access to the hard copies can be controlled by the user. A Job PIN must be 4 digits (0000-9999) in length. Only one Job PIN is permitted per job.

A Job PIN can only be assigned to a job at job creation time. They cannot be assigned after the job already resides under the TOE's control. A user assigns a Job PIN to a print job at the client computer. The Job PIN is embedded in the print job by the client computer prior to sending the print job to the TOE. Once the TOE receives a print job containing a Job PIN, the TOE enforces the Job PIN embedded in that job.

Once a Job PIN is set on a job and the job resides under the TOE's control, the Job PIN cannot be modified or deleted (i.e., the TOE does not provide the ability to manage Job PINs).

A job with a Job Encryption Password cannot be assigned a Job PIN.

This section maps to the following SFRs:

- FIA_SOS.1

7.1.4.3 Job Encryption Passwords

The TOE can store and decrypt encrypted stored print jobs received from a client computer. A stored print job is first encrypted by the client computer using a user-specified Job Encryption Password and AES-256 in CBC mode. The job is then sent encrypted to the TOE and stored encrypted by the TOE. To decrypt the job, a Control Panel user must enter the correct Job Encryption Password used to encrypt the job. The decryption algorithm is included in the TOE. Only one Job Encryption Password is permitted per job.

A Job Encryption Password can only be assigned to a job at job creation time. A user assigns a Job Encryption Password to a print job via the client computer. Once a Job Encryption Password is set on a job, it cannot be changed or removed. In addition, a job with a Job Encryption Password cannot be assigned a Job PIN.

Because the encryption of a job is controlled by the Operational Environment, not the TOE, the TOE has no control over the character composition and complexity of the Job Encryption Password chosen by the user. With that said, printer models numbers that end with “n”, “dn”, or “dh” can only decrypt jobs with Job Encryption Passwords containing 4 to 12 digits. All other printer model numbers can decrypt jobs with Job Encryption Passwords containing 4 to 32 alphanumeric characters.

This section maps to the following SFRs:

- `FCS_COP.1-job`

7.1.4.4 Common access control

The TOE protects each print job in Job Storage from non-administrative users through the use of a user identifier and a Job PIN or through the use of a Job Encryption Password. The user identifier for a print job received from a client computer is either assigned by that client computer or assigned by the user sending the print job from the client computer. Every print job in Job Storage is assigned either a Job PIN or a Job Encryption Password by the user at job creation time. If the TOE receives a print job from a client computer without either a Job PIN or a Job Encryption Password, the TOE cancels the job.

The User Role, as defined by the user's Permission Set, defines each user's access. The default rules for a non-administrative U.NORMAL User Role for accessing a print job in Job Storage are:

- if the job is Job PIN protected:
 - the job owner (i.e., the authenticated user who matches the job's user identifier) can access (read/delete D.DOC) the job without supplying the Job PIN
 - any non-owner authenticated user who supplies the correct Job PIN can access (read/delete D.DOC) the job
- if the job is Job Encryption Password protected, any authenticated user who supplies the correct Job Encryption Password can access (read/delete D.DOC) the job

By default, a Control Panel administrator (U.ADMINISTRATOR) has a permission in their Permission Set that allows them to delete Job Storage jobs (D.DOC).

This section maps to the following SFRs:

- `FDP_ACC.1-cac`
- `FDP_ACF.1-cac`

7.1.4.5 TOE function access control

The TOE controls Control Panel access to TOE functions through the use of Permission Sets. The home screen sign in process assigns the Permission Set to the authenticated user's session. This session Permission Set becomes the user's User Role. Access to each TOE device function is configurable in a Permission Set by an administrator. A user can perform any function permitted in the session Permission

Set. Control Panel applications (e.g., Retrieve from Device Memory) use the user's Permission Set to determine which of the application's functions should be allowed or disallowed for the user. A Control Panel user can perform the [PP2600.2] functions of F.DSR, F.PRT and F.SMI as determined by the user's Permission Set.

Each Control Panel application requires the user to have one or more specific permissions in their session Permission Set in order to access that application. In addition, the TOE's administrator can map sign in methods to each Control Panel application and require the user to be authenticated to that sign in method in order to access that application. The individual applications only check and enforce permissions. They do not check the sign in methods. Instead, the TOE enforces the sign in method requirement at the time that the user signs in to the TOE by removing permissions from the user's session Permission Set for each application in which the user's sign in method does not match the sign in method required by the TOE. By removing the permissions required by each non-matching application, the TOE limits the set of applications that the user can access.

Administrators can change/modify the sign in method mapped to each application. In addition, the TOE provides the feature "Allow users to choose alternate sign-in methods" which allows administrators to select if the sign in method application mappings are enforced or ignored by the TOE. It is a function in the configuration settings which can be configured through the EWS (HTTP) or WS-* web services. When this function is disabled, the TOE enforces the "sign in method to application" mappings and prunes (reduces) the user's session Permission Set accordingly. When this function is enabled, the sign in method mappings are ignored by the TOE and the user's session Permission Set remains unchanged.

For IPsec users, the TOE uses the IPsec/Firewall to control access to the supported network service protocols. The IPsec/Firewall contains the IP addresses of authorized client computers grouped into address templates and the network service protocols grouped into service templates. The administrator maps an address template to a service template using an IPsec/Firewall rule. Service templates, therefore, act as the User Roles for IPsec users. IP addresses of computers not contained in a rule are denied access to the TOE. The [PP2600.2] functions available to an authorized client computer are F.DSR, F.PRT, and F.SMI.

This section maps to the following SFRs:

- FDP_ACC.1-tfac
- FDP_ACF.1-tfac

7.1.4.6 Residual information protection

When the TOE deletes an object defined in section 6.1.3.5, the contents of the object are no longer available to TOE users.

This section maps to the following SFR:

- FDP_RIP.1

7.1.5 Protection of the TSF

7.1.5.1 Restricted forwarding of data to external interfaces

The TOE does not allow forwarding of data to an external interface. The TOE contains only one external interface in the evaluated configuration and that interface is the Shared-medium Interface.

This section maps to the following SFR:

- FPT_FDI_EXP.1

7.1.5.2 TSF self-testing

The EWS interface allows an administrator (U.ADMINISTRATOR) to execute a set of correct operations tests, TSF Data integrity tests, and integrity tests of TSF executable code. The specific security related tests available to the administrator are listed in [FPT_TST.1](#). In some cases, the tests have pre-requisites that must be met prior to execution in order to receive valid results. For example, the LDAP Settings verification test requires LDAP Sign In to be configured and enabled prior to executing the test. The tests that may be available during self-test include:

- Timestamp verification (verify a Network Time Server is configured and responding and system clock is incrementing)
- Device User Access Code verification
- LDAP Settings verification
- Windows Setting verification

This section maps to the following SFR:

- [FPT_TST.1](#)

7.1.5.3 Reliable timestamps

The TOE contains a system clock that is used to generate reliable timestamps. Only administrators can manage the system clock.

The administrator must configure the device to synchronize the system clock via a Network Time Protocol (NTP) server.

This section maps to the following SFR:

- [FPT_STM.1](#)

7.1.6 TOE access protection

The following session termination mechanisms are supported by the TOE:

- Inactivity timeout

7.1.6.1 Inactivity timeout

The TOE supports an inactivity timeout for Control Panel sessions. If a logged in user is inactive for longer than the specified period, the user is automatically logged off of the system. The inactivity period is managed by the administrator via EWS (HTTP) or WS-* web services. Only one inactivity period setting exists per TOE.

This section maps to the following SFR:

- [FTA_SSL.3](#)

7.1.7 Trusted channel communication and certificate management

Shared-medium communications (i.e., Ethernet) between the TOE and other trusted IT products use a trusted channel mechanism to protect the communications from disclosure and modification. The TOE also ensures the cryptographic operations are validated during policy processing such as validating digital signatures or encrypting and decrypting data. The following table provides a list of the mechanism(s) used to protect these channels and the channels protected by the mechanism(s).

Secure protocol	Network channel	Initiated by
IPsec	Email connections (SMTP gateway)	TOE
	EWS (HTTP) connections (including web browser & certificate upload)	Administrative Computer
	Windows domain controller (Kerberos) connections	TOE
	LDAP server connections	TOE
	NTP connections	TOE
	PJL connections	Administrative Computer & Network Client Computer
	SMB connections	TOE
	SNMP connections	Administrative Computer
	Syslog server connections	TOE
	Web Services connections (OXPd & WS-*)	Administrative Computer

Table 31: Trusted channel connections

The TOE uses IPsec as means to provide trusted channel communications. IPsec uses X.509v3 certificates, the ESP, ISAKMP, IKEv1, and IKEv2 protocols, and the cryptographic algorithms listed below to protect communications.

The cryptographic functions used by IPsec are implemented in the QuickSec cryptographic library version 5.1 ([QuickSec51]) which is produced by SafeNet, Inc. The QuickSec cryptographic library is part of the Operational Environment, not the TOE. The TOE prepares the data and invokes the appropriate cryptographic functions, but the code in the QuickSec cryptographic library performs the processing and calculations required. SafeNet, Inc. performs regular and rigorous developer testing of the implementation of the cryptographic algorithms in the QuickSec cryptographic library.

In the evaluated configuration, the supported IPsec cryptographic algorithms are:

- RSA 1024-bit and 2048-bit (Operational Environment)
- AES-128, AES-192, and AES-256 in CBC mode (Operational Environment)
- HMAC-SHA1-96 (Operational Environment)
- HMAC-SHA-256-128 (Operational Environment)
- HMAC-SHA-384-196 (Operational Environment)
- HMAC-SHA-512-256 (Operational Environment)

IPsec is conformant to the MUST/MUST NOT requirements of the following IETF RFCs:

- [RFC4301] and [RFC4894] for IPsec
- [RFC4303] for ESP
- [RFC4306] for ISAKMP
- [RFC4109] and [RFC4894] for IKEv1
- [RFC4306], [RFC4718], and [RFC4894] for IKEv2.

The TOE maintains X.509v3 certificates for IPsec in the certificate store:

- One network identity certificate
- One or more Certificate Authority (CA) certificates

The EWS (HTTP) and WS-* interfaces allow administrators to manage these X.509v3 certificates used by IPsec.

When the TOE is first powered on, it generates a self-signed identity certificate to use for network identity. In the evaluated configuration, the use of a self-signed identity certificate generated by the TOE for network identity is not permitted. The administrator must import a CA-signed identity certificate and private key and designate this certificate for network identity usage. The TOE requires a network identity certificate to always exist; therefore, it allows the administrator to replace the network identity certificate used by IPsec.

The TOE uses a copy of the self-signed identity certificate it generates when first powered on as a CA certificate (self-signed) and comes with other CA certificates pre-installed. The administrator must obtain a CA certificate from the Operational Environment and install this certificate when setting up the evaluated configuration. The TOE allows the administrator to add, replace, and delete CA certificates used by IPsec.

This section maps to the following SFRs:

- FCS_CKM.1
- FCS_CKM.2
- FCS_COP.1-ipsec
- FMT_MTD.1-auth
- FMT_SMF.1
- FTP_ITC.1

7.1.8 User and access management

The TOE supports the following roles:

- Administrators (U.ADMINISTRATOR)
- Users (U.NORMAL)

Administrators maintain and configure the TOE and Operational Environment. Users perform the standard print functions on the system.

In addition, the TOE performs many security management functions.

Only administrators can configure the list of Network Client Computers and the Administrative Computer that are allowed to connect to the TOE and the list of other trusted IT products to which the TOE will connect. Administrators do this by creating, modifying, and deleting IPsec/Firewall address templates, service templates, and rules via the TOE. Similarly, only administrators can create, modify, and delete address templates, service templates, and rules via the TOE for trusted IT products.

For each Control Panel application, an administrator can modify the association of a sign in method to an application. (For example, the administrator can associate LDAP Sign In method to the Retrieve from

Device Memory application). In addition, administrators control whether or not a Control Panel user must use the administrator-selected sign in method associated with the applications in order to access that application. This latter feature is controlled through the "Allow users to choose alternate sign-in methods" function.

Administrators can initialize, modify, and delete Device User Accounts in the Local Device Sign In database.

It's worth noting that although the following security attributes are enforced by the TOE, the TOE does not provide functionality to manage these attributes (i.e., the TOE cannot add, change, delete, or query these attributes on an existing job) and the TOE does not provide default values for these attributes; therefore, there are no management SFRs specified in this ST for these security attributes:

- Job Encryption Password - The job is encrypted by the Operational Environment. The TOE does not provide a mechanism to change or delete the password on the job.
- Job PIN - A print job's Job PIN is set by the Operational Environment (i.e., Client Computer). The TOE does not provide a mechanism to change or delete a Job PIN from a print job.

This section maps to the following SFRs:

- FMT_MOF.1
- FMT_MSA.1-tfac
- FMT_MTD.1-auth
- FMT_MTD.1-users
- FMT_SMF.1
- FMT_SMR.1

8 Abbreviations, Terminology and References

8.1 Abbreviations

AES

Advanced Encryption Standard

AH

Authentication Header (IPsec)

ASCII

American Standard Code for Information Interchange

CA

Certificate Authority

CBC

Cipher Block Chaining

SMB

Server Message Block

DNS

Domain Name System

eMMC

embedded MMC

ESP

Encapsulating Security Payload (IPsec)

EWS

Embedded Web Server

HCD

Hardcopy Device

HMAC

Hashed Message Authentication Code

HTML

Hypertext Markup Language

HTTP

Hypertext Transfer Protocol

IEEE

Institute of Electrical and Electronics Engineers, Inc.

IKE

Internet Key Exchange (IPsec)

IP

Internet Protocol

IPsec

Internet Protocol Security

ISAKMP

Internet Security Association Key Management Protocol (IPsec)

LCD

Liquid Crystal Display

LDAP

Lightweight Directory Access Protocol

MAC

Message Authentication Code

MMC

MultiMediaCard

NFC

Near Field Communication

NTLM

Microsoft NT LAN Manager

NTP

Network Time Protocol

OSP

Open Extensibility Platform

OSPd

OSP device layer

PIN

Personal Identification Number

PJL

Printer Job Language

PRF

Pseudo-random Function

SFR

Security Functional Requirement

SHA

Secure Hash Algorithm

SMB

Server Message Block

SMTP

Simple Mail Transfer Protocol

SNMP

Simple Network Management Protocol

SOAP

Simple Object Access Protocol

SSD

Solid-State Drive

SSH

Secure Shell

TOE

Target of Evaluation

USB

Universal Serial Bus

WINS

Windows Internet Name Service

XML

Extensible Markup Language

8.2 Terminology

This section contains definitions of technical terms that are used with a meaning specific to this document. Terms defined in the [CC] are not reiterated here, unless stated otherwise.

Administrative User

This term refers to a user with administrative control of the TOE.

Authentication Data

This includes the Access Code and/or password for each user of the product.

Control Panel Application

An application that resides in the firmware and is selectable by the user via the Control Panel.

Device Administrator Password

The password used to restrict access to administrative tasks via EWS, WS-*, and the Control Panel. This password is also required to associate a user with the Administrator role. In product documentation, it may also be referred to as the Local Device Administrator Password, Local Device Administrator Access Code, the Device Password, or the Administrator Password.

External Interface

A non-hardcopy interface where either the input is being received from outside the TOE or the output is delivered to a destination outside the TOE.

Hardcopy Device (HCD)

This term generically refers to the product models in this Security Target.

Near Field Communication (NFC)

Proximity (within a few inches) radio communication between two or more devices.

Shared-medium Interface

Mechanism for transmitting or receiving data that uses wired or wireless network or non-network electronic methods over a communications medium which, in conventional practice, is or can be simultaneously accessed by multiple users.

User Security Attributes

Defined by functional requirement FIA_ATD.1, every user is associated with one or more security attributes which allow the TOE to enforce its security functions on this user.

Wireless Direct Print

Feature that enables Wi-Fi capable devices (for example: smart phones, tablets, or computers) to establish a direct peer-to-peer wireless connection with the printer to submit print jobs.

8.3 References

CC Common Criteria for Information Technology Security Evaluation

Version 3.1R4

Date September 2012

Location <http://www.commoncriteriaportal.org/files/ccfiles/CCPART1V3.1R4.pdf>

Location <http://www.commoncriteriaportal.org/files/ccfiles/CCPART2V3.1R4.pdf>

Location <http://www.commoncriteriaportal.org/files/ccfiles/CCPART3V3.1R4.pdf>

CCEVS-PL20 NIAP CCEVS Policy Letter #20

Date 2010-11-15

Location http://www.niap-ccevs.org/Documents_and_Guidance/ccevs/policy-ltr-20.pdf

FIPS197 Advanced Encryption Standard

Date 2001-11-26

Location <http://csrc.nist.gov/publications/fips/fips197/fips-197.pdf>

PKCS1v1.5 Public-Key Cryptography Standard (PKCS) #1: RSA Encryption Standard

Author(s) RSA Laboratories

Version 1.5

Date November 1993

PP2600.2 IEEE Std 2600.2-2009; "2600.2-PP, Protection Profile for Hardcopy Devices, Operational Environment B" (with NIAP CCEVS Policy Letter #20)

Version 1.0

Date December 2009

Location http://www.niap-ccevs.org/pp/pp_hcd_eal2_v1.0.pdf

PP2600.2-DSR SFR Package for Hardcopy Device Document Storage and Retrieval (DSR) Functions

Version 1.0

Date December 2009

Location http://www.niap-ccevs.org/pp/pp_hcd_eal2_v1.0.pdf

PP2600.2-PRT SFR Package for Hardcopy Device Print Functions

Version 1.0

Date December 2009

Location http://www.niap-ccevs.org/pp/pp_hcd_eal2_v1.0.pdf

PP2600.2-SMI SFR Package for Hardcopy Device Shared-medium Interface Functions

Version 1.0

Date December 2009

Location http://www.niap-ccevs.org/pp/pp_hcd_eal2_v1.0.pdf

QuickSec51 QuickSec 5.1 Toolkit Reference Manual

Author(s) SafeNet, Inc.

Version 1.0

Date December 2009

RFC2104 HMAC: Keyed-Hashing for Message Authentication

Author(s) H. Krawczyk, M. Bellare, R. Canetti

Date 1997-02-01

Location <http://www.ietf.org/rfc/rfc2104.txt>

RFC2404 The Use of HMAC-SHA-1-96 within ESP and AH

Author(s) C. Madson, R. Glenn

Date 1998-11-01

Location <http://www.ietf.org/rfc/rfc2404.txt>

RFC2409 The Internet Key Exchange (IKE)

Author(s) D. Harkins, D. Carrel

Date 1998-11-01

Location <http://www.ietf.org/rfc/rfc2409.txt>

RFC4109 Algorithms for Internet Key Exchange version 1 (IKEv1)

Author(s) P. Hoffman

Date 2005-05-01

Location <http://www.ietf.org/rfc/rfc4109.txt>

RFC4301 Security Architecture for the Internet Protocol

Author(s) S. Kent, K. Seo

Date 2005-12-01

Location <http://www.ietf.org/rfc/rfc4301.txt>

RFC4303 IP Encapsulating Security Payload (ESP)

Author(s) S. Kent

Date 2005-12-01

Location <http://www.ietf.org/rfc/rfc4303.txt>

RFC4306 Internet Key Exchange (IKEv2) Protocol

Author(s) C. Kaufman

Date 2005-12-01

Location <http://www.ietf.org/rfc/rfc4306.txt>

RFC4718 IKEv2 Clarifications and Implementation Guidelines

Author(s) P. Eronen, P. Hoffman

Date 2006-10-01

Location <http://www.ietf.org/rfc/rfc4718.txt>

RFC4868 Using HMAC-SHA-256, HMAC-SHA-384, and HMAC-SHA-512 with IPsec

Author(s) S. Kelly, S. Frankel

Date 2007-05-01

Location <http://www.ietf.org/rfc/rfc4868.txt>

RFC4894 Use of Hash Algorithms in Internet Key Exchange (IKE) and IPsec

Author(s) P. Hoffman

Date 2007-05-01

Location <http://www.ietf.org/rfc/rfc4894.txt>

SP800-38A Recommendation for Block Cipher Modes of Operation: Methods and Techniques

Author(s) Morris Dworkin

Version NIST Special Publication 800-38A 2001 Edition

Date December 2001

Location <http://csrc.nist.gov/publications/nistpubs/800-38a/sp800-38a.pdf>