

***U.S. Government Protection Profile for
Database Management Systems***



Information Assurance

Version 1.3

December 24, 2010

Protection Profile Title:

- 1 U.S. Government Protection Profile for Database Management Systems

Criteria Version:

- 2 This Protection Profile “US Government Protection Profile for Database Management Systems” (PP) was updated using Version 3.1 of the Common Criteria (CC).
- 3 Any issue that may arise when claiming compliance with this PP can be resolved using the observation report (OR) and observation decision (OD) process.
- 4 Further information, including the status and updates of this protection profile can be found on the CCEVS website: <http://www.niap-ccevs.org/cc-scheme/pp/>. Comments on this document should be directed to ppcomments@missi.ncsc.mil. The email should include the title of the document, the page, the section number, the paragraph number, and the detailed comment and recommendation.

5 Table of Contents

1	Introduction to the Protection Profile.....	5
1.1	PP Identification.....	5
1.2	Overview of the Protection Profile	5
1.3	Conventions	5
1.4	Glossary of Terms.....	6
1.5	Document Organization	6
2	TOE Description	8
2.1	Product Type.....	8
2.2	TOE Definition	9
2.3	General TOE Security Functionality	10
2.4	TOE Operational Environment	11
3	Security Environment.....	14
3.1	Threats.....	14
3.2	Organizational Security Policies.....	15
3.3	Assumptions.....	16
4	Security Objectives	18
4.1	TOE Security Objectives	18
4.2	Environment Security Objectives	19
5	IT Security Requirements	20
5.1	TOE Security Functional Requirements	20
5.2	TOE Security Assurance Requirements.....	31
6	Rationale	42
6.1	Rationale for TOE Security Objectives	42
6.2	Rationale for the Security Objectives and Security Functional Requirements for the Environment.....	49
6.3	Rationale for TOE Security Requirements	51
6.4	Rationale for Assurance Requirements.....	59
6.5	Rationale for Satisfying all Dependencies	59
6.6	Rationale for Extended Requirements	62
7	Appendices.....	65
A	References.....	66
B	Glossary	67
C	Acronyms	70
D	Reserved.....	71
E	Refinements	72

List of Tables

Table 1 Applicable Threats	14
Table 3 Applicable Policies	15
Table 4 Policies Not Applicable to the TOE	16
Table 5 Applicable Assumptions	16
Table 6 Security Objectives	18
Table 7 Environmental Security Objectives	19
Table 8 Security Functional Requirements	20
Table 9 Auditable Events	22
Table 11 Assurance Requirements	31
Table 13 Rationale for TOE Security Objectives	42
Table 14 Rationale for IT Environmental Objectives	49
Table 15 Rationale for TOE Security Requirements	51
Table 16 Rationale for IT Environment Requirements	58
Table 17 Functional Requirement Dependencies	59
Table 19 Assurance Requirement Dependencies	61
Table 20 Rationale for Extended Requirements	62

1 INTRODUCTION TO THE PROTECTION PROFILE

1.1 PP Identification

- 6 Title: U.S. Government Protection Profile for Database Management Systems
- 7 Sponsor: National Security Agency (NSA)
- 8 CC Version: Common Criteria (CC) Version 3.1
- 9 PP Version: 1.3
- 10 **Evaluation Assurance Level:** EAL2+: ADV_ARC.1, ADV_FSP.2, ADV_TDS.1, AGD_OPE.1, AGD_PRE.1, ALC_CMC.2, ALC_CMS.2, ALC_DEL.1, ALC_FLR.2, ATE_COV.1, ATE_FUN.1, ATE_IND.2, AVA_VAN.2
- 11 Keywords: database management system, DBMS, COTS, commercial security, access control, discretionary access control, DAC, CC EAL2 augmented.

1.2 Overview of the Protection Profile

- 12 The “U.S. Government Protection Profile for Database Management Systems” specifies security requirements for a commercial-off-the-shelf (COTS) database system. A product compliant with this Protection Profile includes, but is not limited to, a DBMS server and may be evaluated as a software only application layered on an underlying system (i.e., operating system, hardware, network services and/or custom software) and is usually embedded as a component of a larger system within an operational environment. This profile establishes the requirements necessary to achieve the security objectives of the Target of Evaluation (TOE) and its environment.
- 13 Conformant products provide access control based on user identity and/or group membership (e.g., Discretionary Access Control (DAC)) and generation of audit records for security relevant events. Authorized users, including authorized administrators, of the TOE generally are trusted not to attempt to circumvent access controls implemented by the TOE to gain access to data for which they are not authorized.
- 14 STs that claim conformance to this PP shall meet a minimum standard of demonstrable-PP conformance as defined in section D3 of Common Criteria part 1.

1.3 Conventions

- 15 Except for replacing United Kingdom spelling with American spelling, the notation, formatting, and conventions used in this PP are consistent with version 2.1 of the CC. Selected presentation choices are discussed here to aid the PP reader.

- 16 The CC allows several operations to be performed on functional requirements; *refinement*, *selection*, *assignment*, and *iteration* are defined in paragraph 148 of Part 1 of the CC. Each of these operations is used in this PP.
- 17 The **refinement** operation is used to add detail to a requirement, and thus further restricts a requirement. Refinement of security requirements is denoted by **bold text**.
- 18 The **selection** operation is used to select one or more options provided by the CC in stating a requirement. Selections that have been made by the PP authors are denoted by *italicized text*, selections to be filled in by the Security Target (ST) author appear in square brackets with an indication that a selection is to be made, [selection:], and are not italicized.
- 19 The **assignment** operation is used to assign a specific value to an unspecified parameter, such as the length of a password. Assignments that have been made by the PP authors are denoted by showing the value in square brackets, [Assignment_value], assignments to be filled in by the ST author appear in square brackets with an indication that an assignment is to be made [assignment:].
- 20 The **iteration** operation is used when a component is repeated with varying operations. Iteration is denoted by showing the iteration number in parenthesis following the component identifier, (iteration_number).
- 21 As this PP was sponsored, in part by National Security Agency (NSA), National Information Assurance Partnership (NIAP) interpretations are used and are presented with the NIAP interpretation number as part of the requirement identifier (e.g., **FAU_GEN.1-NIAP-0410** for Audit data generation).
- 22 The CC paradigm also allows protection profile and security target authors to create their own requirements. Such requirements are termed ‘extended requirements’ and are permitted if the CC does not offer suitable requirements to meet the authors’ needs. **Extended requirements** must be identified and are required to use the CC class/family/component model in articulating the requirements. In this PP, extended requirements will be indicated with the “_(EXT)” following the component name.
- 23 Application Notes are provided to help the developer, either to clarify the intent of a requirement, identify implementation choices, or to define “pass-fail” criteria for a requirement. For those components where Application Notes are appropriate, the Application Notes will follow the requirement component.

1.4 Glossary of Terms

- 24 See Appendix B for the Glossary.

1.5 Document Organization

- 25 Section 1 provides the introductory material for the protection profile.

- 26 Section 2 describes the Target of Evaluation in terms of its envisaged usage and connectivity.
- 27 Section 3 defines the expected TOE security environment in terms of the threats to its security, the security assumptions made about its use, and the security policies that must be followed.
- 28 Section 4 identifies the security objectives derived from these threats and policies.
- 29 Section 5 identifies and defines the security functional requirements from the CC that must be met by the TOE in order for the functionality-based objectives to be met. This section also identifies the security assurance requirements for EAL2 augmented.
- 30 Section 6 provides a rationale to demonstrate that the Information Technology Security Objectives satisfy the policies and threats. Arguments are provided for the coverage of each policy and threat. The section then explains how the set of requirements are complete relative to the objectives, and that each security objective is addressed by one or more component requirement. Arguments are provided for the coverage of each objective.
- 31 Section 7, Appendices, includes the appendices that accompany the PP and provides clarity and/or explanation for the reader.
- 32 Appendix A, References, provides background material for further investigation by users of the PP.
- 33 Appendix B, Glossary, provides a listing of definitions of terms.
- 34 Appendix C, Acronyms, provides a listing of acronyms used throughout the document.
- 35 Appendix D, reserved.
- 36 Appendix E, Refinements, identifies the refinements that were made to CC requirements where text is deleted from a requirement.

2 TOE DESCRIPTION

2.1 Product Type

- 37 The product type of the Target of Evaluation (TOE) described in this Protection Profile (PP) is a database management system (DBMS). The DBMS will have the capability to limit TOE access to authorized users, enforce Discretionary Access Controls on objects under the control of the database management system based on user and/or group authorizations, and to provide user accountability via audit of users' actions.
- 38 A DBMS is a computerized repository that stores information and allows authorized users to retrieve and update that information. A DBMS may be a single-user system, in which only one user may access the DBMS at a given time, or a multi-user system, in which many users may access the DBMS simultaneously.
- 39 A DBMS supports two major types of users:
- Users who interact with the DBMS to observe and/or modify data objects for which they have authorization to access; and
 - Authorized administrators who implement and manage the various information-related policies of an organization (e.g., access, integrity, consistency, availability) on the databases that they manage and/or own
- 40 A DBMS stores, and controls access to, two types of data:
- The first type is the user data that the DBMS maintains and protects. User data may consist of the following:
 - a) The user data stored in or as database objects;
 - b) The definitions of user databases and database objects, commonly known as DBMS metadata; and
 - c) User-developed queries, functions, or procedures that the DBMS maintains for users.
 - The second type is the DBMS data (e.g., configuration parameters, user security attributes, transaction log, audit instructions and records) that the DBMS maintains and uses to operate the DBMS.
- 41 Most commercial DBMSs have the following major components:
- The DBMS server application that performs the following functions:
 - a) Controlling users' accesses to user data and DBMS data;

- b) Interacting with, and possibly supplementing portions of, the underlying operating system to retrieve and present the data that are under the DBMS's management;
 - c) Indexing data values to their physical locations for quick retrievals based on a value or range of values;
 - d) Executing pre-written programs (i.e., utilities) to perform common tasks like database backup, recovery, loading, and copying;
 - e) Supporting mechanisms that enable concurrent database access (e.g., locks);
 - f) Assisting recovery of user data and DBMS data (e.g., transaction log); and
 - g) Tracking operations performed by users.
- A data model with which the DBMS data structures and organization can be conceptualized (e.g., hierarchical, object-oriented, relational data models) and DBMS objects defined.
 - High-level language(s) or interfaces that allow authorized users to define database constructs; access and modify user or DBMS data; present user or DBMS data; and perform operations on those data.
- 42 A DBMS specification is the proper document in which to identify the detailed requirements for the DBMS manager/server functions listed above (and any additional DBMS functions). This PP identifies the requirements for the security functions that the DBMS performs in addition to, or as part of, those DBMS manager/server functions.

2.2 TOE Definition

- 43 The TOE consists of at least one instance of the DBMS server application with its associated guidance documentation and the interfaces to the external IT entities with which the DBMS interacts.
- 44 This PP does not dictate a specific architecture. The architecture of the TOE can be a distributed or a non-distributed. The TOE data may reside on a single host or be distributed among several hosts. If the TOE is a distributed architecture, the TOE may depend on the IT environment to provide adequate protection, whether through physical or cryptographic means, to transmit user and DBMS data between the components comprising the TOE. The vendor will have to identify and describe the TOE architecture that they will evaluate.
- 45 The external IT entities with which the DBMS may interact—if they are outside the TOE—include the following:
- Client applications that allow users to interface with the DBMS server;
 - The host operating system (host OS) on which the TOE has been installed;

- The networking, printing, data-storage, and other devices and services with which the host OS may interact on behalf of the DBMS or the DBMS user; and
 - The other IT products such as application servers, web servers, authentication servers, audit servers, and transaction processors with which the DBMS may interact to perform a DBMS function or a security function.
- 46 If the host OS is outside the TOE, the DBMS must specify the host OS on which it must reside to provide the desired degree of security feature integration. However, the goals of confidentiality, integrity and availability for the TOE must be met by the total package: the DBMS and the external IT entities with which it interacts. In all cases, the TOE must be installed and administered in accordance with the TOE installation and administration instructions.

2.3 General TOE Security Functionality

- 47 A DBMS evaluated against this PP will provide the following security services either completely or in cooperation with the IT environment.
- 48 Security services that must be provided by the TOE:
- Discretionary Access Control (DAC) which controls access to objects based on the identity of the subjects or groups to which the subjects and objects belong, and which allows authorized users to specify how the objects that they control are protected.
 - Audit Capture is the function that creates information on all auditable events.
 - Authorized administration role to allow authorized administrators to configure the policies for discretionary access control, identification and authentication, and auditing. The TOE must enforce the authorized administration role.
- 49 Security services that must be provided by the IT environment:
- Identification and Authentication (I&A) by which users are uniquely identified and authenticated before they are authorized to access information stored on the DBMS.
 - Audit Storage is the service that stores records for all security-relevant operations that users perform on user and DBMS data.
 - Audit Review service that allows the authorized administrator to review stored audit records in order to detect potential and actual security violations.
- 50 However, a compliant DBMS will not be able to provide the following:
- physical protection mechanisms and the administrative procedures for using them.

- mechanisms to ensure the complete availability of the data residing on the DBMS. The DBMS can provide simultaneous access to data to make the data available to more than one person at a given time, and it can enforce DBMS resource allocation limits to prevent users from monopolizing a DBMS service/resource. However, it cannot detect or prevent the unavailability that may occur because of a physical or environmental disaster, a storage device failure, or a hacker attack on the underlying operating system. For such threats to availability, the environment must provide the required countermeasures.
- mechanisms to ensure that users properly secure the data that they retrieve from the DBMS. The security procedures of the organization(s) that use and manage the DBMS must define users' data retrieval, storage, and disposition responsibilities.
- mechanisms to ensure that authorized administrators wisely use DAC. Although the DBMS can support an access control policy by which users and/or groups are granted access only to the data that they need to perform their jobs, it cannot completely ensure that authorized administrators who are able to set access controls will do so prudently.

2.4 TOE Operational Environment

2.4.1 Enclave

- 51 The term "enclave" further characterizes the environment in which the TOE is intended to operate. An enclave is under the control of a single authority and has a homogeneous security policy, including personnel and physical security, to protect it from other environments. An enclave can be specific to an organization or a mission and it may contain multiple networks. Enclaves may be logical, such as an operational area network, or be based on physical location and proximity. Any local and external elements that access resources within the enclave must satisfy the policy of the enclave.
- 52 The DBMS is expected to interact with other IT products that reside in the host OS, in the IT environment in which the host computer and host OS reside, and outside that environment but inside the enclave. The IT and non-IT mechanisms used for secure exchanges of information between the DBMS and such products are expected to be administratively determined and coordinated. Similarly, the IT and non-IT mechanisms for negotiating or translating the DAC policy involved in such exchanges are expected to be resolved by the organizations involved.

2.4.2 TOE Architectures

- 53 This PP does not dictate a specific architecture. A TOE compliant with this PP may be evaluated and may operate in several architectures, including but not limited to one or more of the following:
- A stand-alone system running the DBMS server application;

- A stand-alone system running the DBMS server and DBMS client(s) and serving one online user at a given time;
- A network of systems communicating with several distributed DBMS servers simultaneously;
- A network of workstations or terminals running DBMS clients and communicating with a DBMS server simultaneously; these devices may be hardwired to the host computer or be connected to it by means of local or wide-area networks;
- A network of workstations communicating with one or more application servers, which in turn interact with the DBMS on behalf of the workstation users or other subjects (e.g., a DBMS server interacting with a transaction processor that manages user requests); and
- A network of workstations communicating with several distributed DBMS servers simultaneously, the DBMS servers may all be within a single local area network, or they may be distributed geographically.

54 This PP allows each of these architectures to be supported as well as others. A possible architecture is an enclave in which DBMS users access the TOE via a local area network (LAN) and possibly using a dial-up connection. Users in other enclaves will access the LAN and the host computers and servers on it by way of one or more boundary protection mechanisms (e.g., a firewall) and then through a communications server or router to the LAN. Depending on the particular enclave configuration and the DBMS access policy that it supports, all users (both inside and outside the enclave) may then access an application server, which either connects the TOE user to the enclave computer on which the TOE operates or manages the complete user/DBMS session.

2.4.3 TOE Administration

55 Authorized administrators of the TOE will have capabilities that are commensurate with their assigned administrative roles. There may be one or more administrative roles. The TOE developers will establish some roles for their products. If the security target allows it, the administrators of the system may establish other roles. This PP defines one necessary administrator role (authorized administrator) and allows the DBMS developer or ST writer to define more. When the DBMS is established, the ability to segment roles and assign capabilities with significant freedom regarding the number of roles and their responsibilities must also exist. Of course, the very ability to establish and assign roles will be a privileged function.

3 SECURITY ENVIRONMENT

- 56 The security environment for the functions addressed by this specification includes threats, security policies, and usage assumptions, as discussed below.
- 57 This is a Protection Profile (PP) for a Data Base Management System (DBMS). A DBMS in the context of this PP is a device composed of hardware and software.
- 58 While the functionality that the TOE is obligated to implement (in response to the described threat environment) is discussed in detail in later sections, it is useful to give a brief description here. Compliant TOEs will provide security functionality that addresses threats to the TOE and implements policies that are imposed by law or regulation. Compliant TOEs must protect communications to and between elements of a distributed TOE. The TOE must offer identification and authentication services that support the composition of moderate complex passwords or passphrases, and make these services available locally (that is, a local logon) as well as remotely (remote login). The TOE must also offer auditing of a set of events that are associated with security-relevant activity on the TOE, although these events will be stored on a device that is distinct from the TOE.
- 59 It is intended that the set of requirements in this PP is limited in scope in order to promote quicker, less costly evaluations that provide some value to end users. STs that include a large amount of additional functionality (and requirements) are discouraged.

3.1 Threats

The following threats, are addressed by the TOE, and should be read in conjunction with the threat rationale, Section 6.1. There are *other threats that the TOE does not address (e.g., malicious developer inserting a backdoor into the TOE) and it is up to a site to determine how these types of threats apply to its environment.*

Table 1 Applicable Threats

Threat	Definition
T. ACCIDENTAL_ADMIN_ERROR	An administrator may incorrectly install or configure the TOE resulting in ineffective security mechanisms.
T.MASQUERADE	A user or process may masquerade as another entity in order to gain unauthorized access to data or TOE resources

Threat	Definition
T.POOR_DESIGN	Unintentional errors in requirements specification or design of the TOE may occur, leading to flaws that may be exploited by a casually mischievous user or program.
T.POOR_IMPLEMENTATION	Unintentional errors in implementation of the TOE design may occur, leading to flaws that may be exploited by a casually mischievous user or program.
T.POOR_TEST	Lack of or insufficient tests to demonstrate that all TOE security functions operate correctly (including in a fielded TOE) may result in incorrect TOE behavior being discovered thereby causing potential security vulnerabilities.
T.RESIDUAL_DATA	A user or process may gain unauthorized access to data through reallocation of TOE resources from one user or process to another.
T.TSF_COMPROMISE	A malicious user or process may cause configuration data to be inappropriately accessed (viewed, modified or deleted).
T.UNAUTHORIZED_ACCESS	A user may gain unauthorized access to user data for which they are not authorized according to the TOE security policy.
T.UNIDENTIFIED_ACTIONS	Failure of the authorized administrator to identify and act upon unauthorized actions may occur.

3.2 Organizational Security Policies

60 An organizational security policy is a set of rules, practices, and procedures imposed by an organization to address its security needs

Table 2 Applicable Policies

Policy	Definition
P.ACCOUNTABILITY	The authorized users of the TOE shall be held accountable for their actions within the TOE.

Policy	Definition
P.ROLES	The TOE shall provide an authorized administrator role for secure administration of the TOE. This role shall be separate and distinct from other authorized users.

Table 3 Policies Not Applicable to the TOE

Policy Name	Policy Definition	Rationale for NOT Including this Policy
P.ACCESS_BANNER	The TOE shall display an initial banner describing restrictions of use, legal agreements, or any other appropriate information to which users consent by accessing the system.	This policy is not applicable to the TOE due to the absence of a client interface that is capable of displaying an access banner.
P.CRYPTOGRAPHY	Only NIST FIPS validate cryptography (methods and implementations) are acceptable for key management.	This policy is not applicable to the TOE due to the absence of cryptographic requirements for the TOE.

3.3 Assumptions

61 This section contains assumptions regarding the IT environment in which the TOE will reside.

Table 4 Applicable Assumptions

Assumption	Definition
A.NO_EVIL	Administrators are non-hostile, appropriately trained, and follow all administrator guidance.
A.NO_GENERAL_PURPOSE	There are no general-purpose computing capabilities (e.g., compilers or user applications) available on DBMS servers, other than those services necessary for the operation, administration and support of the DBMS.

Assumption	Definition
A.PHYSICAL	It is assumed that appropriate physical security is provided within the domain for the value of the IT assets protected by the TOE and the value of the stored, processed, and transmitted information.

4 SECURITY OBJECTIVES

- 62 This section identifies the security objectives of the TOE and its supporting environment. The security objectives identify the responsibilities of the TOE and its environment in meeting the security needs.

4.1 TOE Security Objectives

Table 5 Security Objectives

Objective Name	Objective Definition
O.ACCESS_HISTORY	The TOE will store and retrieve information (to authorized users) related to previous attempts to establish a session.
O.ADMIN_GUIDANCE	The TOE will provide administrators with the necessary information for secure management.
O.ADMIN_ROLE	The TOE will provide authorized administrator roles to isolate administrative actions.
O.AUDIT_GENERATION	The TOE will provide the capability to detect and create records of security relevant events associated with users.
O.CONFIGURATION_IDENTIFICATION	The configuration of the TOE is fully identified in a manner that will allow implementation errors to be identified and corrected with the TOE being redistributed promptly.
O.DOCUMENTED_DESIGN	The design of the TOE is adequately and accurately documented.
O.INTERNAL_TOE_DOMAINS	The TSF will maintain internal domains for separation of data and queries belonging to concurrent users.
O.MANAGE	The TOE will provide all the functions and facilities necessary to support the authorized administrators in their management of the security of the TOE, and restrict these functions and facilities from unauthorized use.

Objective Name	Objective Definition
O.MEDIATE	The TOE must protect user data in accordance with its security policy.
O.PARTIAL_FUNCTIONAL_TEST	The TOE will undergo some security functional testing that demonstrates that the TSF satisfies some of its security functional requirements.
O.PARTIAL_SELF_PROTECTION	The TSF will maintain a domain for its own execution that protects itself and its resources from external interference, tampering, or unauthorized disclosure through its own interfaces.
O.RESIDUAL_INFORMATION	The TOE will ensure that any information contained in a protected resource within its Scope of Control is not released when the resource is reallocated.
O.TOE_ACCESS	The TOE will provide mechanisms that control a user's logical access to the TOE.
O.VULNERABILITY_ANALYSIS	The TOE will undergo some vulnerability analysis to demonstrate that the design and implementation of the TOE does not contain any obvious flaws.

4.2 Environment Security Objectives

Table 6 Environmental Security Objectives

Environmental Objective Name	Environmental Objective Definition
OE.NO_EVIL	Sites using the TOE shall ensure that authorized administrators are non-hostile, appropriately trained and follow all administrator guidance.
OE.NO_GENERAL_PURPOSE	There will be no general-purpose computing capabilities (e.g., compilers or user applications) available on DMBS servers, other than those services necessary for the operation, administration and support of the DBMS.
OE.PHYSICAL	Physical security will be provided within the domain for the value of the IT assets protected by the TOE and the value of the stored, processed, and transmitted information.

5 IT SECURITY REQUIREMENTS

5.1 TOE Security Functional Requirements

- 63 This section defines the functional requirements for the TOE. Functional requirements in this PP were drawn directly from Part 2 of the CC, or were based on Part 2 of the CC, including the use of NIAP and extended components. These requirements are relevant to supporting the secure operation of the TOE.

Table 7 Security Functional Requirements

Functional Components	
FAU_GEN.1-NIAP-0410	Audit data generation
FAU_GEN_(EXT).2	User and/or group identity association
FAU_SEL.1-NIAP-0407	Selective audit
FDP_ACC.1	Subset access control
FDP_ACF.1-NIAP-0407	Security attribute based access control
FDP_RIP.1	Subset residual information protection
FIA_ATD.1	User attribute definition
FMT_MOF.1	Management of security functions behavior
FMT_MSA.1	Management of security attributes
FMT_MSA_(EXT).3	Static attribute initialization
FMT_MTD.1	Management of TSF data
FMT_REV.1(1)	Revocation (user attributes)
FMT_REV.1(2)	Revocation (subject, object attributes)
FMT_SMF.1	Specification of management functions
FMT_SMR.1	Security roles
FPT_TRC_(EXT).1	Internal TSF consistency

Functional Components	
FTA_MCS.1	Basic limitation on multiple concurrent sessions
FTA_TAH_(EXT).1	TOE access history
FTA_TSE.1	TOE session establishment

5.1.1 Security Audit (FAU)

5.1.1.1 Audit data generation (FAU_GEN.1-NIAP-0410)

Hierarchical to: No other components.

Dependencies: FPT_STM.1 Reliable time stamps

FAU_GEN.1.1-NIAP-0410 **Refinement:** The TSF shall be able to generate an audit record of the following auditable events:

- a) Start-up and shutdown of the audit functions;
- b) All auditable events for the *minimum* level of audit **listed in Table 8**;
- c) **[Start-up and shutdown of the DBMS;**
- d) **Use of special permissions (e.g., those often used by authorized administrators to circumvent access control policies); and**
- e) [selection: [assignment: events at a minimal level of audit introduced by the inclusion of additional SFRs determined by the ST author], [assignment: events commensurate with a minimal level of audit introduced by the inclusion of extended requirements determined by the ST author], “no additional events”].

64 *Application Note: For the selection, the ST author should choose one or both of the assignments (as detailed in the following paragraphs), or select “no additional events”.*

65 *Application Note: For the first assignment, the ST author augments the table (or lists explicitly) the audit events associated with the minimal level of audit for any SFRs that the ST author includes that are not included in this PP.*

66 *Application Note: Likewise, if the ST author includes extended requirements not contained in this PP, the corresponding audit events must be added in the second assignment. Because “minimal” audit is not defined for such requirements, the ST author will need to determine a set of events that are commensurate with the type of information that is captured at the minimal level for similar requirements.*

67 *Application Note: If no additional (CC or extended) SFRs are included, or if additional SFRs are included that do not have “minimal” audit associated with them then it is acceptable to assign “no additional events” in this item.*

FAU_GEN.1.2-NIAP-0410 The TSF shall record within each audit record at least the following information:

- a) Date and time of the event, type of event, subject identity (if applicable), and the outcome (success or failure) of the event; and
- b) For each audit event type, based on the auditable event definitions of the functional components included in the PP/ST, [information specified in column three of Table 8 below].

68 *Application Note: In column 3 of the table below, “Audit Record Contents” is used to designate data that should be included in the audit record if it “makes sense” in the context of the event, that generates the record. If no other information is required (other than that listed in item a) above) for a particular auditable event type, then an assignment of “none” is acceptable.*

Table 8 Auditable Events

Security Functional Requirement	Auditable Event(s)	Additional Audit Record Contents	
FAU_GEN.1-NIAP-0410	None		
FAU_GEN_(EXT).2	None		
FAU_SEL.1-NIAP-0407	All modifications to the audit configuration that occur while the audit collection functions are operating	The identity of the authorized administrator that made the change to the audit configuration	
FDP_ACC.1	None		
FDP_ACF.1-NIAP-0407	Successful requests to perform an operation on an object covered by the SFP		The identity of the subject performing the operation
FDP_RIP.1	None		
FIA_ATD.1	None		
FMT_MOF.1	None		

Security Functional Requirement	Auditable Event(s)	Additional Audit Record Contents
FMT_MSA.1	None	
FMT_MSA_(EXT).3	None	
FMT_MTD.1	None	
FMT_REV.1(1)	Unsuccessful revocation of security attributes	Identity of individual attempting to revoke security attributes
FMT_REV.1(2)	Unsuccessful revocation of security attributes	Identity of individual attempting to revoke security attributes
FMT_SMF.1	Use of the management functions	Identity of the administrator performing these functions
FMT_SMR.1	Modifications to the group of users that are part of a role	Identity of authorized administrator modifying the role definition
FPT_TRC_(EXT).1	Restoring consistency	
FTA_MCS.1	Rejection of a new session based on the limitation of multiple concurrent sessions	
FTA_TAH_(EXT).1	None	
FTA_TSE.1	Denial of a session establishment due to the session establishment mechanism	Identity of the individual attempting to establish a session

5.1.1.2 User and/or group identity association (FAU_GEN_(EXT).2)

FAU_GEN_(EXT).2.1 For audit events resulting from actions of identified users and/or identified groups, the TSF shall be able to associate each auditable event with the identity of the user and/or group that caused the event.

5.1.1.3 Selective audit (FAU_SEL.1-NIAP-0407)

Hierarchical to: No other components.

Dependencies: FAU_GEN.1 Audit data generation

FMT_MTD.1 Management of TSF data

FAU_SEL.1.1-NIAP-0407 **Refinement:** The TSF shall **allow only the administrator** to include or exclude auditable events from the set of audited events based on the following attributes:

- a) *user identity and/or group identity,*
- b) *event type,*
- c) *object identity,*
- d) [selection: “subject identity”, “host identity”, “none”];
- e) [success of auditable security events;
- f) failure of auditable security events; and
- g) [selection: [assignment: list of additional criteria that audit selectivity is based upon], “no additional criteria”].]

69 *Application Note: “event type” is to be defined by the ST author; the intent is to be able to include or exclude classes of audit events.*

70 *Application Note: The intent of this requirement is to capture enough audit data to allow the administrator to perform their task, not necessarily to capture only the needed audit data. In other words, the DBMS does not necessarily need to include or exclude auditable events based on all attributes at any given time.*

5.1.2 User data protection (FDP)

5.1.2.1 Subset access control (FDP_ACC.1)

Hierarchical to: No other components.

Dependencies: FDP_ACF.1 Security attribute based access control

FDP_ACC.1.1 The TSF shall enforce the [Discretionary Access Control policy] on [all subjects, all DBMS-controlled objects and all operations among them].

5.1.2.2 Security attribute based access control (FDP_ACF.1-NIAP-0407)

71 *Interp Note: The following element was modified per CCIMB Interpretation 103.*

Hierarchical to: No other components.

Dependencies: FDP_ACC.1 Subset access control

FMT_MSA.3 Static attribute initialization

FDP_ACF.1.1-NIAP-0407 The TSF shall enforce the [Discretionary Access Control policy] to objects based on the following:

- [the authorized user identity and/or group membership associated with a subject;
- access operations implemented for DBMS-controlled objects; and
- object identity].

72 *Application Note: DBMS-controlled objects may be implementation-specific objects that are presented to authorized users at the user interface to the DBMS. They may include, but are not limited to tables, records, files, indexes, views, constraints, stored queries, and metadata. Data structures that are not presented to authorized users at the DBMS user interface, but are used internally are internal TSF data structures. Internal TSF data structures are not controlled according to the rules specified in FDP_ACF.1-NIAP-0407.*

FDP_ACF.1.2-NIAP-0407 **Refinement:** The TSF shall enforce the following rules to determine if an operation among controlled subjects and **DBMS**-controlled objects is allowed:

□ **The Discretionary Access Control policy mechanism shall, either by explicit authorized user/group action or by default, provide that database management system controlled objects are protected from unauthorized access according to the following ordered rules:**

[selection:

- a) If the requested mode of access is denied to that authorized user, deny access;
- b) If the requested mode of access is permitted to that authorized user, permit access;
- c) If the requested mode of access is denied to every group of which the authorized user is a member, deny access;
- d) If the requested mode of access is permitted to any group of which the authorized user is a member, grant access;
- e) Else, deny access,

OR

- a) [If the requested mode of access is denied to that authorized user, deny access;

- b) If the requested mode of access is denied to [**selection: every, any**] group of which the authorized user is a member, deny access;
 - c) If the requested mode of access is permitted to that authorized user, permit access;
 - d) If the requested mode of access is permitted to any group of which the authorized user is a member, grant access;
 - e) Else, deny access
-].

Application Note: The deny mode of access may be implicit.

Application Note: Rules need to include user IDs if the DBMS implements user IDs. Likewise, rules need to include group IDs if the DBMS implements group IDs.

Application Note: The first option, where the user ID deny and the user ID permit appear before any group permissions are checked, is the preferred selection.

FDP_ACF.1.3-NIAP-0407 **Refinement:** The TSF shall explicitly authorize access of subjects to **DBMS-controlled** objects based on the following additional rules: [selection: assignment: rules, based on security attributes, that explicitly authorize access of subjects to objects], “no additional rules”].

73 *Application Note: This element allows specifications of additional rules for authorized administrators to bypass the Discretionary Access Control policy for system management or maintenance (e.g., system backup).*

FDP_ACF.1.4-NIAP-0407 The TSF shall explicitly deny access of subjects to objects based on the following rules: [selection: [assignment: rules, based on security attributes, that explicitly deny access of subjects to objects], “no additional explicit denial rules”].

5.1.2.3 Subset residual information protection (FDP_RIP.1)

Hierarchical to: No other components.

Dependencies: No dependencies

FDP_RIP.1.1 The TSF shall ensure that any previous information content of a resource is made unavailable upon the *allocation of the resource to* [assignment: list of objects].

5.1.3 Identification and authentication (FIA)

5.1.3.1 User attribute definition (FIA_ATD.1)

Hierarchical to: No other components.

Dependencies: No dependencies.

FIA_ATD.1.1 The TSF shall maintain the following list of security attributes belonging to individual users:

- [Database user identifier and/or group memberships;
- Security-relevant database roles; and
- [assignment: list of security attributes]].

74 *Application Note: The intent of this requirement is to specify the TOE security attributes that the TOE utilizes to determine access. These attributes may be controlled by the environment or by the TOE itself.*

5.1.4 Security management (FMT)

5.1.4.1 Management of security functions behavior (FMT_MOF.1)

Hierarchical to: No other components.

Dependencies: FMT_SMR.1 Security roles
FMT_SMF.1 Specification of Management Functions

FMT_MOF.1.1 The TSF shall restrict the ability to *disable and enable* the functions [relating to the specification of events to be audited] to [authorized administrators].

5.1.4.2 Management of security attributes (FMT_MSA.1)

Hierarchical to: No other components.

Dependencies: FDP_ACC.1 Subset access control, or
FDP_IFC.1 Subset information flow control]
FMT_SMR.1 Security roles
FMT_SMF.1 Specification of Management Functions

FMT_MSA.1.1 **Refinement:** The TSF shall enforce the [Discretionary Access Control policy] to restrict the ability to [*manage*] **all** the security attributes to [authorized administrators].

75 *Application Note: The ST author should ensure that all attributes identified in FIA_ATD.1 are adequately managed and protected.*

5.1.4.3 Static attribute initialization (FMT_MSA_(EXT).3)

76 *Interp Note: The following element is changed because of Interpretations 201 and 202.*

FMT_MSA_(EXT).3.1 The TSF shall enforce the [Discretionary Access Control policy] to provide *restrictive* default values for security attributes that are used to enforce the SFP.

Application Note: This requirement applies to new container objects at the top-level (e.g., tables). When lower-level objects are create (e.g., rows, cells), these may inherit the permissions of the top-level objects by default. In other words, the permissions of the 'child' objects can take the permissions of the 'parent' objects by default.

5.1.4.4 Management of TSF data (FMT_MTD.1)

Hierarchical to: No other components.

Dependencies: FMT_SMR.1 Security roles

FMT_SMF.1 Specification of Management Functions

FMT_MTD.1.1 The TSF shall restrict the ability to [*include or exclude*] the [auditable events] to [authorized administrators].

5.1.4.5 Revocation (FMT_REV.1(1))

Hierarchical to: No other components.

Dependencies: FMT_SMR.1 Security roles

FMT_REV.1.1(1) The TSF shall restrict the ability to revoke security attributes associated with the *users* within the TSC to [the authorized administrator].

FMT_REV.1.2(1) The TSF shall enforce the rules [assignment: specification of revocation rules].

5.1.4.6 Revocation (FMT_REV.1(2))

FMT_REV.1.1(2) The TSF shall restrict the ability to revoke security attributes associated with the *objects* within the TSC to [the authorized administrator and database users as allowed by the Discretionary Access Control policy].

FMT_REV.1.2(2) The TSF shall enforce the rules [assignment: specification of revocation rules].

5.1.4.7 Specification of Management Functions (FMT_SMF.1)

Hierarchical to: No other components.

Dependencies: No dependencies

FMT_SMF.1.1 The TSF shall be capable of performing the following security management functions: [assignment: list of security management functions to be provided by the TSF].

5.1.4.8 Security roles (FMT_SMR.1)

Hierarchical to: No other components.

Dependencies: FIA_UID.1 Timing of identification

FMT_SMR.1.1 **Refinement:** The TSF shall maintain the roles:

- [authorized administrator]; **and**
- **[assignment: additional authorized identified roles].**

FMT_SMR.1.2 The TSF shall be able to associate users with roles.

77 *Application Note: This requirement identifies a minimum set of management roles. A ST or operational environment may contain a finer-grain decomposition of roles that correspond to the roles identified here (e.g., database non-administrative user or database operator). The ST writer may change the names of the roles identified above but the “new” roles must still perform the functions that the FMT requirements in this PP have defined.*

5.1.5 Protection of the TOE Security Functions (FPT)

78 *Application Note: The security domain boundary in the first element is TSF domain and its intent is to protect the TSF from untrusted subjects at the TSFIs. The security domain boundary in the second element covers the complete TOE Scope of Control and its intent is to maintain separation between any subjects within the TOE Scope of Control.*

5.1.5.1 Internal TSF consistency (FPT_TRC_(EXT).1)

FPT_TRC_(EXT).1.1 The TSF shall ensure that TSF data is consistent between parts of the TOE by providing a mechanism to bring inconsistent TSF data into a consistent state in a timely manner.

79 *Application Note: In general, it is impossible to achieve complete, constant consistency of TSF data that is distributed to remote portions of a TOE because distributed portions of the*

TSF may be active at different times or disconnected from one another. This requirement attempts to address this situation in a practical manner by acknowledging that there will be TSF data inconsistencies but that they will be corrected without undue delay. For example, a TSF could provide timely consistency through periodic broadcast of TSF data to all TSF nodes maintaining replicated TSF data. Another example approach is for the TSF to provide a mechanism to explicitly probe remote TSF nodes for inconsistencies and respond with action to correct the identified inconsistencies.

80 *Application Note: This requirement is trivially met if the TOE does not contain physically separated components.*

5.1.6 Toe Access (FTA)

5.1.6.1 Basic limitation on multiple concurrent sessions (FTA_MCS.1)

Hierarchical to: No other components.

Dependencies: FIA_UID.1 Timing of identification

FTA_MCS.1.1 The TSF shall restrict the maximum number of concurrent sessions that belong to the same user.

FTA_MCS.1.2 **Refinement:** The TSF shall enforce, by default, a limit of [**selection:** [assignment: default number], “**an admin configurable number of**”]sessions per user.

5.1.6.2 TOE access history (FTA_TAH_(EXT).1)

Hierarchical to: No other components.

Dependencies: No dependencies.

FTA_TAH_(EXT).1.1 Upon successful session establishment, the TSF shall store and retrieve the *date and time* of the last successful session establishment to the user.

FTA_TAH_(EXT).1.2 Upon successful session establishment, the TSF shall store and retrieve the *date and time* of the last unsuccessful attempt to session establishment and the number of unsuccessful attempts since the last successful session establishment.

5.1.6.3 TOE session establishment (FTA_TSE.1)

Hierarchical to: No other components.

Dependencies: No dependencies.

FTA_TSE.1.1 **Refinement:** The TSF shall be able to deny session establishment based on [attributes that can be set explicitly by authorized administrator(s), including user identity

and/or group identity, time of day, day of the week], **and [assignment: list of additional attributes]**].

5.2 TOE Security Assurance Requirements

81 All of the assurance requirements included in Evaluated Assurance Level (EAL) 2 augmented with the following additions:

- ALC_FLR.2: Flaw remediation

82 The following is a list of the assurance requirements needed for this protection profile:.

Assurance Class	Assurance Components	Assurance Components Description
Development	ADV_ARC.1	Architectural Design with domain separation and non-bypassability
	ADV_FSP.2	Security-enforcing Functional Specification
	ADV_TDS.1	Basic design
Guidance Documents	AGD_OPE.1	Operational user guidance
	AGD_PRE.1	Preparative User guidance
Life Cycle Support	ALC_CMC.2	Use of a CM system
	ALC_CMS.2	Parts of the TOE CM coverage
	ALC_DEL.1	Delivery procedures
	ALC_FLR.2	Flaw Reporting Procedures
Tests	ATE_COV.1	Evidence of coverage
	ATE_FUN.1	Functional testing
	ATE_IND.2	Independent testing - conformance
Vulnerability Assessment	AVA_VAN.2	Vulnerability analysis

Table 9 Assurance Requirements

5.2.1 Class ADV: Development

5.2.1.1 ADV_ARC.1 Security architecture description

Dependencies: ADV_FSP.1 Basic functional specification
 ADV_TDS.1 Basic design

Developer action elements:

- ADV_ARC.1.1D The developer shall design and implement the TOE so that the security features of the TSF cannot be bypassed.
- ADV_ARC.1.2D The developer shall design and implement the TSF so that it is able to protect itself from tampering by untrusted active entities.
- ADV_ARC.1.3D The developer shall provide a security architecture description of the TSF.

Content and presentation elements:

- ADV_ARC.1.1C The security architecture description shall be at a level of detail commensurate with the description of the SFR-enforcing abstractions described in the TOE design document.
- ADV_ARC.1.2C The security architecture description shall describe the security domains maintained by the TSF consistently with the SFRs.
- ADV_ARC.1.3C The security architecture description shall describe how the TSF initialization process is secure.
- ADV_ARC.1.4C The security architecture description shall demonstrate that the TSF protects itself from tampering.
- ADV_ARC.1.5C The security architecture description shall demonstrate that the TSF prevents bypass of the SFR-enforcing functionality.

Evaluator action elements:

- ADV_ARC.1.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

5.2.1.2 ADV_FSP.2 Security-enforcing functional specification

Dependencies: ADV_TDS.1 Basic design

Developer action elements:

- ADV_FSP.2.1D The developer shall provide a functional specification.

ADV_FSP.2.2D The developer shall provide a tracing from the functional specification to the SFRs.

Content and presentation elements:

ADV_FSP.2.1C The functional specification shall completely represent the TSF.

ADV_FSP.2.2C The functional specification shall describe the purpose and method of use for all TSFI.

ADV_FSP.2.3C The functional specification shall identify and describe all parameters associated with each TSFI.

ADV_FSP.2.4C For each SFR-enforcing TSFI, the functional specification shall describe the SFR-enforcing actions associated with the TSFI.

ADV_FSP.2.5C For SFR-enforcing TSFIs, the functional specification shall describe direct error messages resulting from processing associated with the SFR-enforcing actions.

ADV_FSP.2.6C The tracing shall demonstrate that the SFRs trace to TSFIs in the functional specification.

Evaluator action elements:

ADV_FSP.2.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

ADV_FSP.2.2E The evaluator *shall determine* that the functional specification is an accurate and complete instantiation of the SFRs.

5.2.1.3 ADV_TDS.1 Basic design

Dependencies: ADV_FSP.2 Security-enforcing functional specification

Developer action elements:

ADV_TDS.1.1D The developer shall provide the design of the TOE.

ADV_TDS.1.2D The developer shall provide a mapping from the TSFI of the functional specification to the lowest level of decomposition available in the TOE design.

Content and presentation elements:

ADV_TDS.1.1C The design shall describe the structure of the TOE in terms of subsystems.

- ADV_TDS.1.2C The design shall identify all subsystems of the TSF.
- ADV_TDS.1.3C The design shall describe the behavior of each SFR-supporting or SFR-non-interfering TSF subsystem in sufficient detail to determine that it is not SFR-enforcing.
- ADV_TDS.1.4C The design shall summarize the SFR-enforcing behavior of the SFR-enforcing subsystems.
- ADV_TDS.1.5C The design shall provide a description of the interactions among SFR-enforcing subsystems of the TSF, and between the SFR-enforcing subsystems of the TSF and other subsystems of the TSF.
- ADV_TDS.1.6C The mapping shall demonstrate that all behavior described in the TOE design is mapped to the TSFIs that invoke it.

Evaluator action elements:

- ADV_TDS.1.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.
- ADV_TDS.1.2E The evaluator *shall determine* that the design is an accurate and complete instantiation of all security functional requirements.

5.2.2 Class AGD: Guidance documents

5.2.2.1 AGD_OPE.1 Operational user guidance

Dependencies: ADV_FSP.1 Basic functional specification

Developer action elements:

- AGD_OPE.1.1D The developer shall provide operational user guidance.

Content and presentation elements:

- AGD_OPE.1.1C The operational user guidance shall describe, for each user role, the user-accessible functions and privileges that should be controlled in a secure processing environment, including appropriate warnings.
- AGD_OPE.1.2C The operational user guidance shall describe, for each user role, how to use the available interfaces provided by the TOE in a secure manner.
- AGD_OPE.1.3C The operational user guidance shall describe, for each user role, the available functions and interfaces, in particular all security parameters under the control of the user, indicating secure values as appropriate.

- AGD_OPE.1.4C The operational user guidance shall, for each user role, clearly present each type of security-relevant event relative to the user-accessible functions that need to be performed, including changing the security characteristics of entities under the control of the TSF.
- AGD_OPE.1.5C The operational user guidance shall identify all possible modes of operation of the TOE (including operation following failure or operational error), their consequences and implications for maintaining secure operation.
- AGD_OPE.1.6C The operational user guidance shall, for each user role, describe the security measures to be followed in order to fulfill the security objectives for the operational environment as described in the ST.
- AGD_OPE.1.7C The operational user guidance shall be clear and reasonable.

Evaluator action elements:

- AGD_OPE.1.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

5.2.2.2 AGD_PRE.1 Preparative procedures

Dependencies: No dependencies.

Developer action elements:

- AGD_PRE.1.1D The developer shall provide the TOE including its preparative procedures.

Content and presentation elements:

- AGD_PRE.1.1C The preparative procedures shall describe all the steps necessary for secure acceptance of the delivered TOE in accordance with the developer's delivery procedures.
- AGD_PRE.1.2C The preparative procedures shall describe all the steps necessary for secure installation of the TOE and for the secure preparation of the operational environment in accordance with the security objectives for the operational environment as described in the ST.

Evaluator action elements:

- AGD_PRE.1.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.
- AGD_PRE.1.2E The evaluator shall apply the preparative procedures to confirm that the TOE can be prepared securely for operation.

5.2.3 Class ALC: Life-cycle support

5.2.3.1 ALC_CMC.2 Use of a CM system

Dependencies: ALC_CMS.1 TOE CM coverage

Developer action elements:

ALC_CMC.2.1D The developer shall provide the TOE and a reference for the TOE.

ALC_CMC.2.2D The developer shall provide the CM documentation.

ALC_CMC.2.3D The developer shall use a CM system.

Content and presentation elements:

ALC_CMC.2.1C The TOE shall be labeled with its unique reference.

ALC_CMC.2.2C The CM documentation shall describe the method used to uniquely identify the configuration items.

ALC_CMC.2.3C The CM system shall uniquely identify all configuration items.

Evaluator action elements:

ALC_CMC.2.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

5.2.3.2 ALC_CMS.2 Parts of the TOE CM coverage

Dependencies: No dependencies.

Developer action elements:

ALC_CMS.2.1D The developer shall provide a configuration list for the TOE.

Content and presentation elements:

ALC_CMS.2.1C The configuration list shall include the following: the TOE itself; the evaluation evidence required by the SARs; and the parts that comprise the TOE.

ALC_CMS.2.2C The configuration list shall uniquely identify the configuration items.

ALC_CMS.2.3C For each TSF relevant configuration item, the configuration list shall indicate the developer of the item.

Evaluator action elements:

ALC_CMS.2.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

5.2.3.3 ALC_DEL.1 Delivery procedures

Dependencies: No dependencies.

Developer action elements:

ALC_DEL.1.1D The developer shall document procedures for delivery of the TOE or parts of it to the consumer.

ALC_DEL.1.2D The developer shall use the delivery procedures.

Content and presentation elements:

ALC_DEL.1.1C The delivery documentation shall describe all procedures that are necessary to maintain security when distributing versions of the TOE to the consumer.

Evaluator action elements:

ALC_DEL.1.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

5.2.3.4 ALC_FLR.2 Flaw reporting procedures

Dependencies: No dependencies.

Developer action elements:

ALC_FLR.2.1D The developer shall document flaw remediation procedures addressed to TOE developers.

ALC_FLR.2.2D The developer shall establish a procedure for accepting and acting upon all reports of security flaws and requests for corrections to those flaws.

ALC_FLR.2.3D The developer shall provide flaw remediation guidance addressed to TOE users.

Content and presentation elements:

- ALC_FLR.2.1C The flaw remediation procedures documentation shall describe the procedures used to track all reported security flaws in each release of the TOE.
- ALC_FLR.2.2C The flaw remediation procedures shall require that a description of the nature and effect of each security flaw be provided, as well as the status of finding a correction to that flaw.
- ALC_FLR.2.3C The flaw remediation procedures shall require that corrective actions be identified for each of the security flaws.
- ALC_FLR.2.4C The flaw remediation procedures documentation shall describe the methods used to provide flaw information, corrections and guidance on corrective actions to TOE users.
- ALC_FLR.2.5C The flaw remediation procedures shall describe a means by which the developer receives from TOE users reports and enquiries of suspected security flaws in the TOE.
- ALC_FLR.2.6C The procedures for processing reported security flaws shall ensure that any reported flaws are remediated and the remediation procedures issued to TOE users.
- ALC_FLR.2.7C The procedures for processing reported security flaws shall provide safeguards that any corrections to these security flaws do not introduce any new flaws.
- ALC_FLR.2.8C The flaw remediation guidance shall describe a means by which TOE users report to the developer any suspected security flaws in the TOE.

Evaluator action elements:

- ALC_FLR.2.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

5.2.4 Class ATE: Tests

5.2.4.1 ATE_COV.1 Evidence of coverage

Dependencies: ADV_FSP.2 Security-enforcing functional specification
 ATE_FUN.1 Functional testing

Developer action elements:

- ATE_COV.1.1D The developer shall provide evidence of the test coverage.

Content and presentation elements:

ATE_COV.1.1C The evidence of the test coverage shall show the correspondence between the tests in the test documentation and the TSFIs in the functional specification.

Evaluator action elements:

ATE_COV.1.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

5.2.4.2 ATE_FUN.1 Functional testing

Dependencies: ATE_COV.1 Evidence of coverage

Developer action elements:

ATE_FUN.1.1D The developer shall test the TSF and document the results.

ATE_FUN.1.2D The developer shall provide test documentation.

Content and presentation elements:

ATE_FUN.1.1C The test documentation shall consist of test plans, expected test results and actual test results.

ATE_FUN.1.2C The test plans shall identify the tests to be performed and describe the scenarios for performing each test. These scenarios shall include any ordering dependencies on the results of other tests.

ATE_FUN.1.3C The expected test results shall show the anticipated outputs from a successful execution of the tests.

ATE_FUN.1.4C The actual test results shall be consistent with the expected test results.

Evaluator action elements:

ATE_FUN.1.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

5.2.4.3 ATE_IND.2 Independent testing - sample

Dependencies: ADV_FSP.2 Security-enforcing functional specification
AGD_OPE.1 Operational user guidance
AGD_PRE.1 Preparative procedures
ATE_COV.1 Evidence of coverage

ATE_FUN.1 Functional testing

Developer action elements:

ATE_IND.2.1D The developer shall provide the TOE for testing.

Content and presentation elements:

ATE_IND.2.1C The TOE shall be suitable for testing.

ATE_IND.2.2C The developer shall provide an equivalent set of resources to those that were used in the developer's functional testing of the TSF.

Evaluator action elements:

ATE_IND.2.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

ATE_IND.2.2E The evaluator *shall execute* a sample of tests in the test documentation to verify the developer test results.

ATE_IND.2.3E The evaluator *shall test* a subset of the TSF to confirm that the TSF operates as specified.

5.2.5 Class AVA: Vulnerability assessment

5.2.5.1 AVA_VAN.2 Vulnerability analysis

Dependencies: ADV_ARC.1 Security architecture description
 ADV_FSP.1 Basic functional specification
 ADV_TDS.1 Basic design
 AGD_OPE.1 Operational user guidance
 AGD_PRE.1 Preparative procedures

Developer action elements:

AVA_VAN.2.1D The developer shall provide the TOE for testing.

Content and presentation elements:

AVA_VAN.2.1C The TOE shall be suitable for testing.

Evaluator action elements:

AVA_VAN.2.1E The evaluator *shall confirm* that the information provided meets all requirements for content and presentation of evidence.

- AVA_VAN.2.2E The evaluator *shall perform* a search of public domain sources to identify potential vulnerabilities in the TOE.
- AVA_VAN.2.3E The evaluator *shall perform* an independent vulnerability analysis of the TOE using the guidance documentation, functional specification, TOE design and security architecture description to identify potential vulnerabilities in the TOE.
- AVA_VAN.2.4E The evaluator *shall conduct* penetration testing, based on the identified potential vulnerabilities, to determine that the TOE is resistant to attacks performed by an attacker possessing Basic attack potential.

Application Note: The TOE version used as the basis for testing should include a reference to the specific signature set in place when this activity is conducted.

6 RATIONALE

83 This section provides the rationale for the selection of the IT security requirements, objectives, assumptions, and threats. In particular, it shows that the IT security requirements are suitable to meet the security objectives, which in turn are shown to be suitable to cover all aspects of the TOE security environment.

6.1 Rationale for TOE Security Objectives

Table 10 Rationale for TOE Security Objectives

Threat/Policy	Objectives Addressing the Threat/Policy	Rationale
T. ACCIDENTAL_ADMIN_ERROR An administrator may incorrectly install or configure the TOE resulting in ineffective security mechanisms.	O.ADMIN_GUIDANCE The TOE will provide administrators with the necessary information for secure management.	O.ADMIN_GUIDANCE helps to mitigate this threat by ensuring the TOE administrators have guidance that instructs them how to administer the TOE in a secure manner. Having this guidance helps to reduce the mistakes that an administrator might make that could cause the TOE to be configured in insecurely.

Threat/Policy	Objectives Addressing the Threat/Policy	Rationale
<p>T.MASQUERADE</p> <p>A user or process may masquerade as another entity in order to gain unauthorized access to data or TOE resources.</p>	<p>O.TOE_ACCESS</p> <p>The TOE will provide mechanisms that control a user's logical access to the TOE.</p>	<p>O.TOE_ACCESS mitigates this threat by controlling the logical access to the TOE and its resources. By constraining how and when authorized users can access the TOE, and by mandating the type and strength of the authentication mechanism this objective helps mitigate the possibility of a user attempting to login and masquerade as an authorized user. In addition, this objective provides the administrator the means to control the number of failed login attempts a user can generate before an account is locked out, further reducing the possibility of a user gaining unauthorized access to the TOE.</p>
<p>T.POOR_DESIGN</p> <p>Unintentional errors in requirements specification or design of the TOE may occur, leading to flaws that may be exploited by a casually mischievous user or program.</p>	<p>O.CONFIGURATION_IDENTIFICATION</p> <p>The configuration of the TOE is fully identified in a manner that will allow implementation errors to be identified and corrected with the TOE being redistributed promptly.</p>	<p>O.CONFIGURATION_IDENTIFICATION plays a role in countering this threat by requiring the developer to provide control of the changes made to the TOE's design.</p>
	<p>O.DOCUMENTED_DESIGN</p> <p>The design of the TOE is adequately and accurately documented.</p>	<p>O.DOCUMENTED_DESIGN ensures that the design of the TOE is documented, permitting detailed review by evaluators.</p>
	<p>O.VULNERABILITY_ANALYSIS</p> <p>The TOE will undergo some vulnerability analysis to demonstrate the design and implementation of the TOE does not contain any obvious flaws.</p>	<p>O.VULNERABILITY_ANALYSIS ensures that the design of the TOE is analyzed for design flaws.</p>

Threat/Policy	Objectives Addressing the Threat/Policy	Rationale
<p>T.POOR_IMPLEMENTATION</p> <p>Unintentional errors in implementation of the TOE design may occur, leading to flaws that may be exploited by a casually mischievous user or program.</p>	<p>O.CONFIGURATION_IDENTIFICATION</p> <p>The configuration of the TOE is fully identified in a manner that will allow implementation errors to be identified and corrected with the TOE being redistributed promptly.</p>	<p>O.CONFIGURATION_IDENTIFICATION plays a role in countering this threat by requiring the developer to provide control of the changes made to the TOE's design, although the previous three objectives help minimize the introduction of errors into the implementation.</p>
	<p>O.PARTIAL_FUNCTIONAL_TEST</p> <p>The TOE will undergo some security functional testing that demonstrates the TSF satisfies some of its security functional requirements.</p>	<p>O.PARTIAL_FUNCTIONAL_TEST increases the likelihood that any errors that do exist in the implementation (with respect to the functional specification, high-level, and low-level design) will be discovered through testing.</p>
	<p>O.VULNERABILITY_ANALYSIS</p> <p>The TOE will undergo some vulnerability analysis to demonstrate the design and implementation of the TOE does not contain any obvious flaws.</p>	<p>O.VULNERABILITY_ANALYSIS helps reduce errors in the implementation that may not be discovered during functional testing. Ambiguous design documentation and the fact that exhaustive testing of the external interfaces is not required may leave bugs in the implementation undiscovered in functional testing.</p>
<p>T.POOR_TEST</p> <p>Lack of or insufficient tests to demonstrate that all TOE security functions operate correctly (including in a fielded TOE) may result in incorrect TOE behavior being discovered thereby causing potential security vulnerabilities.</p>	<p>O.DOCUMENTED_DESIGN</p> <p>The design of the TOE is adequately and accurately documented.</p>	<p>O.DOCUMENTED_DESIGN helps to ensure that the TOE's documented design satisfies the security functional requirements. In order to ensure the TOE's design is correctly realized in its implementation, the appropriate level of functional testing of the TOE's security mechanisms must be performed during the evaluation of the TOE.</p>

Threat/Policy	Objectives Addressing the Threat/Policy	Rationale
	<p>O.PARTIAL_FUNCTIONAL_TEST</p> <p>The TOE will undergo some security functional testing that demonstrates the TSF satisfies some of its security functional requirements.</p>	<p>O.PARTIAL_FUNCTIONAL_TEST increases the likelihood that any errors that do exist in the implementation (with respect to the functional specification, high level, and low-level design) will be discovered through testing.</p>
	<p>O.VULNERABILITY_ANALYSIS</p> <p>The TOE will undergo some vulnerability analysis to demonstrate the design and implementation of the TOE does not contain any obvious flaws.</p>	<p>O.VULNERABILITY_ANALYSIS addresses this concern by requiring a vulnerability analysis be performed in conjunction with testing that goes beyond functional testing. This objective provides a measure of confidence that the TOE does not contain security flaws that may not be identified through functional testing.</p> <p>While these testing activities are a necessary activity for successful completion of an evaluation, this testing activity does not address the concern that the TOE continues to operate correctly and enforce its security policies once it has been fielded. Some level of testing must be available to end users to ensure the TOE's security mechanisms continue to operator correctly once the TOE is fielded.</p>
<p>T.RESIDUAL_DATA</p> <p>A user or process may gain unauthorized access to data through reallocation of TOE resources from one user or process to another.</p>	<p>O.RESIDUAL_INFORMATION</p> <p>The TOE will ensure that any information contained in a protected resource within its Scope of Control is not released when the resource is reallocated.</p>	<p>O.RESIDUAL_INFORMATION counters this threat by ensuring that TSF data and user data is not persistent when resources are released by one user/process and allocated to another user/process.</p>

Threat/Policy	Objectives Addressing the Threat/Policy	Rationale
<p>T.TSF_COMPROMISE</p> <p>A user or process may cause, through an unsophisticated attack, TSF data, or executable code to be inappropriately accessed (viewed, modified, or deleted).</p>	<p>O.RESIDUAL_INFORMATION</p> <p>The TOE will ensure that any information contained in a protected resource within its Scope of Control is not released when the resource is reallocated.</p>	<p>O.RESIDUAL_INFORMATION is necessary to mitigate this threat, because even if the security mechanisms do not allow a user to view TSF data, if TSF data were to reside inappropriately in a resource that was made available to a user, that user would be able to view the TSF data without authorization.</p>
	<p>O.PARTIAL_SELF_PROTECTION</p> <p>The TSF will maintain a domain for its own execution that protects itself and its resources from external interference, tampering, or unauthorized disclosure through its own interfaces.</p>	<p>O.PARTIAL_SELF_PROTECTION ensures the TOE is capable of protecting itself from attack.</p>
	<p>O.MANAGE</p> <p>The TOE will provide all the functions and facilities necessary to support the authorized administrators in their management of the security of the TOE, and restrict these functions and facilities from unauthorized use.</p>	<p>O.MANAGE is necessary because an access control policy is specified to control access to TSF data. This objective is used to dictate who is able to view and modify TSF data, as well as the behavior of TSF functions.</p>
	<p>O.INTERNAL_TOE_DOMAINS</p> <p>The TSF will maintain internal domains for separation of data and queries belonging to concurrent users.</p>	<p>O.INTERNAL_TOE_DOMAINS ensures the TOE will establish separate domains for data belonging to users.</p>

Threat/Policy	Objectives Addressing the Threat/Policy	Rationale
<p>T.UNAUTHORIZED_ACCESS</p> <p>A user may gain unauthorized access to user data for which they are not authorized according to the TOE security policy.</p>	<p>O.MEDIATE</p> <p>The TOE must protect user data in accordance with its security policy.</p>	<p>O.MEDIATE ensures that all accesses to user data are subject to mediation, unless said data has been specifically identifies as public data. The TOE requires successful authentication to the TOE prior to gaining access to any controlled-access content. By implementing strong authentication to gain access to these services, an attacker's opportunity to conduct a man-in-the-middle and/or password guessing attack successfully is greatly reduced. Lastly, the TSF will ensure that all configured enforcement functions (authentication, access control rules, etc.) must be invoked prior to allowing a user to gain access to TOE or TOE mediated services. The TOE restricts the ability to modify the security attributes associated with access control rules, access to authenticated and unauthenticated services, etc to the administrator. This feature ensures that no other user can modify the information flow policy to bypass the intended TOE security policy.</p>
	<p>O.ACCESS_HISTORY</p> <p>The TOE will store and retrieve information (to authorized users) related to previous attempts to establish a session.</p>	<p>O.ACCESS_HISTORY is important to mitigate this threat because it ensures the TOE will be able to store and retrieve the information that will advise the user of the last successful login attempt and performed actions without their knowledge.</p>

Threat/Policy	Objectives Addressing the Threat/Policy	Rationale
<p>T.UNIDENTIFIED_ACTIONS</p> <p>Failure of the authorized administrator to identify and act upon unauthorized actions may occur.</p>	<p>O.ADMIN_GUIDANCE</p> <p>The TOE will provide administrators with the necessary information for secure management.</p>	<p>The threat of an authorized administrator failing to know about malicious audit events produces the objectives of the authorized administrator having the facilities and knowing how to use them (O.ADMIN_GUIDANCE).</p>
	<p>O.MANAGE</p> <p>The TOE will provide all the functions and facilities necessary to support the authorized administrators in their management of the security of the TOE, and restrict these functions and facilities from unauthorized use.</p>	<p>The threat of an authorized administrator failing to know about malicious audit events produces the objectives of the authorized administrator having the capability to use the mechanisms (O.MANAGE) to review audit records.</p>
<p>P.ACCOUNTABILITY</p> <p>The authorized users of the TOE shall be held accountable for their actions within the TOE.</p>	<p>O.AUDIT_GENERATION</p> <p>The TOE will provide the capability to detect and create records of security relevant events associated with users.</p>	<p>O.AUDIT_GENERATION addresses this policy by providing the authorized administrator with the capability of configuring the audit mechanism to record the actions of a specific user, or review the audit trail based on the identity of the user. Additionally, the administrator's ID is recorded when any security relevant change is made to the TOE (e.g., access rule modification, start-stop of the audit mechanism, establishment of a trusted channel, etc.).</p>

Threat/Policy	Objectives Addressing the Threat/Policy	Rationale
	<p>O.TOE_ACCESS</p> <p>The TOE will provide mechanisms that control a user's logical access to the TOE.</p>	<p>O.TOE_ACCESS supports this policy by requiring the TOE to identify and authenticate all authorized users prior to allowing any TOE access or any TOE mediated access on behalf of those users.</p>
<p>P.ROLES</p> <p>The TOE shall provide an authorized administrator role for secure administration of the TOE. This role shall be separate and distinct from other authorized users.</p>	<p>O.ADMIN_ROLE</p> <p>The TOE will provide authorized administrator roles to isolate administrative actions.</p>	<p>The TOE has the objective of providing an authorized administrator role for secure administration. The TOE may provide other roles as well, but only the role of authorized administrator is required (O.ADMIN_ROLE).</p>

6.2 Rationale for the Security Objectives and Security Functional Requirements for the Environment

Table 11 Rational for IT Environmental Objectives

Assumption	Environmental Objective Addressing the Assumption	Rationale
<p>A.NO_EVIL</p> <p>Administrators are non-hostile, appropriately trained, and follow all administrator guidance.</p>	<p>OE.NO_EVIL</p> <p>Sites using the TOE shall ensure that authorized administrators are non-hostile, are appropriately trained and follow all administrator guidance.</p>	<p>All authorized administrators are trustworthy individuals, having background investigations commensurate with the level of data being protected, have undergone appropriate admin training, and follow all admin guidance.</p>

Assumption	Environmental Objective Addressing the Assumption	Rationale
<p>A.NO_GENERAL_PURPOSE</p> <p>There are no general-purpose computing or storage repository capabilities (e.g., compilers or user applications) available on DBMS servers, other than those services necessary for the operation, administration and support of the DBMS.</p>	<p>OE.NO_GENERAL_PURPOSE</p> <p>There will be no general-purpose computing capabilities (e.g., compilers or user applications) available on DMBS servers, other than those services necessary for the operation, administration and support of the DBMS.</p>	<p>The DBMS server must not include any general-purpose computing or storage capabilities. This will protect the TSF data from malicious processes.</p>
<p>A.PHYSICAL</p> <p>Physical security, commensurate with the value of the TOE and the data it contains, is assumed to be provided by the IT environment.</p>	<p>OE.PHYSICAL</p> <p>Physical security will be provided within the domain for the value of the IT assets protected by the TOE and the value of the stored, processed, and transmitted information.</p>	<p>The TOE, the TSF data, and protected user data is assumed to be protected from physical attack (e.g., theft, modification, destruction, or eavesdropping). Physical attack could include unauthorized intruders into the TOE environment, but it does not include physical destructive actions that might be taken by an individual that is authorized to access the TOE environment.</p>

6.3 Rationale for TOE Security Requirements

Table 12 Rationale for TOE Security Requirements

Objective	Requirements Addressing the Objective	Rationale
<p>O.ACCESS_HISTORY</p> <p>The TOE will store and retrieve information (to authorized users) related to previous attempts to establish a session.</p>	<p>FTA_TAH_(EXT).1</p>	<p>The TOE must be able to store and retrieve information about previous unauthorized login attempts and the number times the login was attempted every time the user logs into their account. The TOE must also store the last successful authorized login. This information will include the date, time, method, and location of the attempts. When appropriately displayed, this will allow the user to detect if another user is attempting to access their account. These records should not be deleted until after the user has been notified of their access history. (FTA_TAH_(EXT).1)</p>
<p>O.ADMIN_GUIDANCE</p> <p>The TOE will provide administrators with the necessary information for secure management.</p>	<p>ALC_DEL.1</p>	<p>ALC_DEL.1 ensures that the administrator is provided documentation that instructs them how to ensure the delivery of the TOE, in whole or in parts, has not been tampered with or corrupted during delivery. This requirement ensures the administrator has the ability to begin their TOE installation with a clean (e.g., malicious code has not been inserted once it has left the developer’s control) version of the TOE, which is necessary for secure management of the TOE.</p>

Objective	Requirements Addressing the Objective	Rationale
	AGD_PRE.1	AGD_PRE.1 ensures the administrator has the information necessary to install the TOE in the evaluated configuration. Often times a vendor's product contains software that is not part of the TOE and has not been evaluated. The Preparative User Guidance (AGD_PRE)documentation ensures that once the administrator has followed the installation and configuration guidance the result is a TOE in a secure configuration.
	AGD_OPE.1	AGD_OPE.1 mandates the developer provide the administrator with guidance on how to operate the TOE in a secure manner. This includes describing the interfaces the administrator uses in managing the TOE, security parameters that are configurable by the administrator, how to configure the TOE's rule set and the implications of any dependencies of individual rules. The documentation also provides a description of how to setup and review the auditing features of the TOE. The guidance must show the administrator how to use the functionality available, review the results of any tests and/or alerts, and act accordingly.
	AGD_OPE.1	AGD_OPE.1 is also intended for non-administrative users, but it could be used to provide guidance on security that is common to both administrators and non-administrators (e.g., password management guidelines).

Objective	Requirements Addressing the Objective	Rationale
	AGD_OPE.1 AGD_PRE.1	AGD_OPE.1 and AGD_PRE.1 analysis during evaluation will ensure that the guidance documentation is complete and consistent, and notes all requirements for external security measures.
<p>O.ADMIN_ROLE</p> <p>The TOE will provide authorized administrator roles to isolate administrative actions.</p>	FMT_SMR.1	The TOE will establish, at least, an authorized administrator role. The ST writer may choose to specify more roles. The authorized administrator will be given privileges to perform certain tasks that other users will not be able to perform. These privileges include, but are not limited to, access to audit information and security functions. (FMT_SMR.1)
<p>O.AUDIT_GENERATION</p> <p>The TOE will provide the capability to detect and create records of security relevant events associated with users.</p>	FAU_GEN.1-NIAP-0410	FAU_GEN.1-NIAP-0410 defines the set of events that the TOE must be capable of recording. This requirement ensures that the administrator has the ability to audit any security relevant events that takes place in the TOE. This requirement also defines the information that must be contained in the audit record for each auditable event. This requirement also places a requirement on the level of detail that is recorded on any additional security functional requirements an ST author adds to this PP.
	FAU_GEN_(EXT).2	FAU_GEN_(EXT).2 ensures that the audit records associate a user and/or group identity with the auditable event. In the case of authorized users, the association is accomplished with the user ID. In the case of authorized groups, the association is accomplished with the group ID.

Objective	Requirements Addressing the Objective	Rationale
	FAU_SEL.1-NIAP-0407	FAU_SEL.1-NIAP-0407 allows the administrator to configure which auditable events will be recorded in the audit trail. This provides the administrator with the flexibility in recording only those events that are deemed necessary by site policy, thus reducing the amount of resources consumed by the audit mechanism.
<p>O.CONFIGURATION_IDENTIFICATION</p> <p>The configuration of the TOE is fully identified in a manner that will allow implementation errors to be identified and corrected with the TOE being redistributed promptly.</p>	ALC_CMS.2	ALC_CMS.2 addresses this objective by requiring that there be a unique reference for the TOE, and that the TOE is labeled with that reference. It also requires that there be a CM system in place, and that the configuration items that comprise the TOE are uniquely identified. This provides a clear identification of the composition of the TOE.
	ALC_FLR.2	ALC_FLR.2 addresses this objective by requiring that there be a mechanism in place for identifying flaws subsequent to fielding, and for distributing those flaws to entities operating the system.
<p>O.DOCUMENTED_DESIGN</p> <p>The design of the TOE is adequately and accurately documented.</p>	ADV_FSP.2	ADV_FSP.2 requires that the interfaces to the TOE be documented and specified.
	ADV_TDS.1	ADV_HLD.1 requires the high-level design of the TOE be documented and specified and that said design be shown to correspond to the interfaces.
	ADV_TDS.1	ADV_TDS.1 requires that there be a correspondence between adjacent layers of the design decomposition.

Objective	Requirements Addressing the Objective	Rationale
<p>O.MANAGE</p> <p>The TOE will provide all the functions and facilities necessary to support the authorized administrators in their management of the security of the TOE, and restrict these functions and facilities from unauthorized use.</p>	FMT_MOF.1	FMT_MOF.1 requires that the ability to use particular TOE capabilities be restricted to the administrator.
	FMT_MSA.1	FMT_MSA.1 requires that the ability to perform operations on security attributes be restricted to particular roles.
	FMT_MSA_(EXT).3	FMT_MSA_(EXT).3 requires that default values used for security attributes are restrictive.
	FMT_MTD.1	FMT_MTD.1 requires that the ability to manipulate TOE content is restricted to administrators.
	FMT_REV.1(1) FMT_REV.1(2)	FMT_REV.1 restricts the ability to revoke attributes to the administrator.
	FMT_SMF.1	FMT_SMF.1 identifies the management functions that are available to the authorized administrator.
	FMT_SMR.1	FMT_SMR.1 defines the specific security roles to be supported.
<p>O.MEDIATE</p> <p>The TOE must protect user data in accordance with its security policy.</p>	FDP_ACC.1	<p>The FDP requirements were chosen to define the policies, the subjects, objects, and operations for how and when mediation takes place in the TOE.</p> <p>FDP_ACC.1 defines the Access Control policy that will be enforced on a list of subjects acting on the behalf of users attempting to gain access to a list of named objects. All the operation between subject and object covered are defined by the TOE's policy.</p>

Objective	Requirements Addressing the Objective	Rationale
	FDP_ACF.1-NIAP-0407	FDP_ACF.1-NIAP-0407 defines the security attribute used to provide access control to objects based on the TOE's access control policy.
	FPT_TRC_(EXT).1	Replicated TSF data that specifies attributes for access control must be consistent across distributed components of the TOE. The requirement is to maintain consistency of replicated TSF data.
<p>O.INTERNAL_TOE_DOMAINS</p> <p>The TSF will maintain internal domains for separation of data and queries belonging to concurrent users.</p>	ADV_ARC.1	ADV_ARC.1 provides the security architecture description of the security domains maintained by the TSF that are consistent with the SFRs. Since self-protection is a property of the TSF that is achieved through the design of the TOE and TSF, and enforced by the correct implementation of that design, self-protection will be achieved by that design and implementation.
<p>O.PARTIAL_FUNCTIONAL_TEST</p> <p>The TOE will undergo some security functional testing that demonstrates the TSF satisfies some of its security functional requirements.</p>	ATE_COV.1	ATE_COV.1 requires that there be a correspondence between the tests in the test documentation and the TSF as described in the functional specification.
	ATE_FUN.1	ATE_FUN.1 requires that the developer provide test documentation for the TOE, including test plans, test procedure descriptions, expected test results, and actual test results. These need to identify the functions tested, the tests performed, and test scenarios. There require that the developer run those tests, and show that the expected results were achieved.

Objective	Requirements Addressing the Objective	Rationale
	ATE_IND.2	ATE_IND.2 requires that the evaluators test a subset of the TSF to confirm correct operation, on an equivalent set of resources to those used by the developer for testing. These sets should include a subset of the developer run tests.
<p>O.PARTIAL_SELF_PROTECTION</p> <p>The TSF will maintain a domain for its own execution that protects itself and its resources from external interference, tampering, or unauthorized disclosure through its own interfaces.</p>	ADV_ARC.1	ADV_ARC.1 provides the security architecture description of the security domains maintained by the TSF that are consistent with the SFRs. Since self-protection is a property of the TSF that is achieved through the design of the TOE and TSF, and enforced by the correct implementation of that design, self-protection will be achieved by that design and implementation.
<p>O.RESIDUAL_INFORMATION</p> <p>The TOE will ensure that any information contained in a protected resource within its Scope of Control is not released when the resource is reallocated.</p>	FDP_RIP.1	FDP_RIP.1 is used to ensure the contents of resources are not available to subjects other than those explicitly granted access to the data.
<p>O.TOE_ACCESS</p> <p>The TOE will provide mechanisms that control a user's logical access to the TOE.</p>	FIA_ATD.1	FIA_ATD.1 defines the attributes of users, including a user ID that is used by the TOE to determine a user's identity and/or group memberships and enforce what type of access the user has to the TOE.
	FTA_MCS.1	FTA_MCS.1 ensures that users may only have a maximum of a specified number of active sessions open at any given time.
	FTA_TSE.1	FTA_TSE.1 allows the TOE to restrict access to the TOE based on certain criteria.

Objective	Requirements Addressing the Objective	Rationale
<p>O.VULNERABILITY_ANALYSIS</p> <p>The TOE will undergo some vulnerability analysis to demonstrate the design and implementation of the TOE does not contain any obvious flaws.</p>	<p>AVA_VAN.2</p>	<p>The AVA_VAN.2 component provides the necessary level of confidence that vulnerabilities do not exist in the TOE that could cause the security policies to be violated. AVA_VAN.2 requires the evaluator to perform a search for potential vulnerabilities in all the TOE deliverables. For those vulnerabilities that are not eliminated by the developer, a rationale must be provided that describes why these vulnerabilities cannot be exploited by a threat agent with a basic attack potential, which is in keeping with the desired assurance level of this TOE. This component provides the confidence that security flaws do not exist in the TOE that could be exploited by a threat agent of basic attack potential to violate the TOE's security policies.</p>

84 The following table includes the rationale for the IT Environment Requirements.

Table 13 Rationale for IT Environment Requirements

Environmental Objective	Requirements Addressing the Objective	Rationale

Environmental Objective	Requirements Addressing the Objective	Rationale
OE.NO_EVIL Sites using the TOE shall ensure that authorized administrators are non-hostile, are appropriately trained and follow all administrator guidance.	N/A	This objective does not contain any IT security requirements because it is a non-IT related objective. Thus, the CC does not mandate it map to any requirements.
OE.NO_GENERAL_PURPOSE There will be no general-purpose computing capabilities (e.g., compilers or user applications) available on DMBS servers, other than those services necessary for the operation, administration and support of the DBMS.	N/A	This objective does not contain any IT security requirements because it is a non-IT related objective. Thus, the CC does not mandate it map to any requirements.
OE.PHYSICAL Physical security will be provided within the domain for the value of the IT assets protected by the TOE and the value of the stored, processed, and transmitted information.	N/A	This objective does not contain any IT security requirements because it is a non-IT related objective. Thus, the CC does not mandate it map to any requirements.

6.4 Rationale for Assurance Requirements

- 85 This protection profile is developed for use by Commercial DBMS Security Software developers.
- 86 Flaw Remediation is the only requirement not included in any EAL level because it does not add any assurance to the current system, but to subsequent releases. Therefore, the PPRB decided to augment EAL2 with ALC_FLR.2 to instruct the vendors on proper flaw remediation techniques.

6.5 Rationale for Satisfying all Dependencies

Table 14 Functional Requirement Dependencies

Requirement	Dependency	Satisfied
-------------	------------	-----------

Requirement	Dependency	Satisfied
FAU_GEN.1-NIAP-0410	FPT_STM.1	This requirement must be satisfied by the IT environment because the DBMS is a software only TOE.
FAU_GEN_(EXT).2	FAU_GEN.1-NIAP-0410 FIA_UID.1	The dependency on FIA_UID.1 must be satisfied by the IT environment because the DBMS is a software only TOE.
FAU_SEL.1-NIAP-0407	FAU_GEN.1-NIAP-0410 FMT_MTD.1	Satisfied
FDP_ACC.1	FDP_ACF.1-NIAP-0407	Satisfied
FDP_ACF.1-NIAP-0407	FDP_ACC.1 FMT_MSA.3	The dependency on FMT_MSA.3 is satisfied by FMT_MSA_(EXT).3.
FDP_RIP.1	None	N/A
FIA_ATD.1	None	N/A
FMT_MOF.1	FMT_SMF.1 ¹ FMT_SMR.1	Satisfied
FMT_MSA.1	[FDP_ACC.1 or FDP_IFC.1] FMT_SMF.1 ¹ FMT_SMR.1	Dependency satisfied by FDP_ACC.1.
FMT_MSA_(EXT).3	FMT_MSA.1 FMT_SMR.1	Satisfied
FMT_MTD.1	FMT_SMF.1 ¹ FMT_SMR.1	Satisfied
FMT_REV.1(1)	FMT_SMR.1	Satisfied
FMT_REV.1(2)	FMT_SMR.1	Satisfied
FMT_SMF.1	None	N/A

¹ This list of dependency has been modified per CCIMB Interpretation 065.

Requirement	Dependency	Satisfied
FMT_SMR.1	FIA_UID.1	The dependency on FIA_UID.1 must be satisfied by the IT environment because the DBMS is a software only TOE.
FPT_TRC_(EXT).1	FPT_ITT.1	This dependency is satisfied by the IT environment due to lack of cryptography in the TOE and because the DBMS is a software only application.
FTA_MCS.1	FIA_UID.1	The dependency on FIA_UID.1 must be satisfied by the IT environment because the DBMS is a software only TOE.
FTA_TAH_(EXT).1	None	N/A
FTA_TSE.1	None	N/A

Table 15 Assurance Requirement Dependencies

Requirement	Dependency	Satisfied
ADV_ARC.1	ADV_FSP.1 ADV_TDS.1	Yes
ADV_FSP.2	ADV_TDS.1	N/A
ADV_TDS.1	ADV_FSP.2	Yes
AGD_OPE.1	ADV_FSP.1	Yes
AGD_PRE.1	None	Yes
ALC_CMC.2	ALC_CMS.1	Yes
ALC_CMS.2	None	N/A
ALC_DEL.1	None	N/A
ALC_FLR.2	None	N/A

Requirement	Dependency	Satisfied
ATE_COV.1	ADV_FSP.2	Yes
	ATE_FUN.1	Yes
ATE_FUN.1	ATE_COV.1	Yes
ATE_IND.2	ADV_FSP.2,	Yes
	AGD_OPE.1	Yes
	AGD_PRE.1	Yes
	ATE_COV.1	Yes
	ATE_FUN.1	Yes
AVA_VAN.2	ADV_ARC.1	Yes
	ADV_FSP.1	Yes
	ADV_TDS.1	Yes
	AGD_OPE.1	Yes
	AGD_PRE.1	Yes

6.6 Rationale for Extended Requirements

87 Table 16 presents the rationale for the inclusion of the extended functional and assurance requirements found in this PP. The extended requirements that are included as NIAP interpretations do not require a rationale for their inclusion per CCEVS management.

Table 16 Rationale for Extended Requirements

Extended Requirement	Identifier	Rationale
FAU_GEN_(EXT).2	User and/or group identity association	This requirement was needed to replace FAU_GEN.2.1-NIAP-0410 because this PP does not require the TOE to implement a user identity. It does require the TOE to implement a user identity and/or a group identity to satisfy the DAC policy. Therefore, this extended requirement was created to allow the audit function to use the user identity or the group identity or both.

Extended Requirement	Identifier	Rationale
FPT_TRC_(EXT).1	Internal TSF consistency	<p>FPT_TRC_(EXT).1 has been created to require timely consistency of replicated TSF data. Although there is a Common Criteria Requirement that attempts to address this functionality, it falls short of the needs of the environment in this protection profile.</p> <p>Specifically, FPT_TRC.1.1 states "The TSF shall ensure that TSF data is consistent when replicated between parts of the TOE." In the widely distributed environment of this PP's TOE, this is an infeasible requirement. For TOEs with a very large number of components, 100 percent TSF data consistency is not achievable and is not expected at any specific instant in time.</p> <p>Another concern lies in FPT_TRC.1.2 that states that when replicated parts of the TSF are "disconnected", the TSF shall ensure consistency of the TSF replicated data upon "reconnection". Upon first inspection, this seems reasonable, however, when applying this requirement it becomes clear that it dictates specific mechanisms to determine when a component is "disconnected" from the rest of the TSF and when it is "reconnected". This is problematic in this PP's environment in that it is not the intent of the authors to dictate that distributed TSF components keep track of connected/disconnected components.</p> <p>In general, to meet the needs of this PP, it is acceptable to only require a mechanism that provides TSF data consistency in a timely manner after it is determined that it is inconsistent.</p>
FTA_TAH_(EXT).1	TOE Access History	<p>This PP does not require the TOE to contain a client. Therefore, the PP cannot require the client to display a message. This requirement has been modified to require the TOE to store and retrieve the access history instead of displaying it.</p>

Extended Requirement	Identifier	Rationale
FMT_MSA_(EXT).3	Static attribute initialization	<p>The CC does not allow the PP author to specify restrictive values that are not modifiable. This extended requirement eliminates the element FMT_MSA.3.2 from the component FMT_MSA.3 and makes the component more secure by requiring the security attributes of the objects on creation to be restrictive and not allowing any user to be able of override the restrictive default values.</p>

7 APPENDICES

88 The following sections are the appendices for this Protection Profile.

A REFERENCES

- [1] Common Criteria Implementation Board, Common Criteria for Information Technology Security Evaluation, CCIB-98-026, Version 2.1, August 1999
 - [1a] Common Criteria Implementation Board, Common Criteria for Information Technology Security Evaluation, CCMB-2006-09, Version 3.1, September 2006
- [2] Department of Defense Chief Information Officer, Guidance and Policy for Department of Defense Information Assurance Memorandum No. 6-8510 dated 16 June 2000
 - [2a] Department of Defense Directive 8500.1, "Information Assurance," October 24, 2002
 - [2b] Department of Defense Instruction 8500.2, "Information Assurance," February 6, 2003
- [3] Department of Defense Standard, Department of Defense Trusted Computer System Evaluation Criteria (Orange Book), December 1985
- [4] Trusted Product Evaluation Program (TPEP) Trusted Computer System Evaluation Criteria (TCSEC) Interpretations
- [5] National Computer Security Center, Trusted Database Management System Interpretation of the Trusted Computer System Evaluation Criteria, NCSC-TG-021 Version-1, April 1991
- [6] Security Agency Information Assurance Solutions Technical Directors, Information Assurance Technical Framework, Release 3.1, September 2002

B GLOSSARY

Access – Interaction between an entity and an object that results in the flow or modification of data.

Access Control – Security service that controls the use of resources² and the disclosure and modification of data.³

Accountability – Property that allows activities in an IT system to be traced to the entity responsible for the activity.

Administrator – A user who has been specifically granted the authority to manage some portion or all of the TOE and whose actions may affect the TSP. Administrators may possess special privileges that provide capabilities to override portions of the TSP.

Assurance – A measure of confidence that the security features of an IT system are sufficient to enforce its' security policy.

Attack – An intentional act attempting to violate the security policy of an IT system.

Authentication – Security measure that verifies a claimed identity.

Authentication data – Information used to verify a claimed identity.

Authorization – Permission, granted by an entity authorized to do so, to perform functions and access data.

Authorized Administrator – The authorized person in contact with the Target of Evaluation who is responsible for maintaining its operational capability.

Authorized user – An authenticated user who may, in accordance with the TSP, perform an operation.

Availability – Timely⁴, reliable access to IT resources.

Compromise – Violation of a security policy.

Confidentiality – A security policy pertaining to disclosure of data.

Conformant Product – A Target of Evaluation that satisfied all the functional security requirements in Section 5.1 and satisfies all the TOE security assurance requirements in section 5.2 of this document.

² Hardware and software

³ Stored or communicated

⁴ According to a defined metric

Critical Security Parameters (CSP) – Security-related information (e.g., cryptographic keys, authentication data such as passwords and pins, and cryptographic seeds) appearing in plaintext or otherwise unprotected form and whose disclosure or modification can compromise the security of a cryptographic module or the security of the information protected by the module.

Database Management System (DBMS) – A suite of programs that typically manage large structured sets of persistent data, offering ad hoc query facilities to many users. They are widely used in business applications.

Defense-in-Depth (DID) – A security design strategy whereby layers of protection are utilized to establish an adequate security posture for an IT system.

Discretionary Access Control (DAC) – A means of restricting access to objects based on the identity of subjects and/or groups to which they belong. Those controls are discretionary in the sense that a subject with a certain access permission is capable of passing that permission (perhaps indirectly) on to any other subject.

Enclave – A collection of entities under the control of a single authority and having a homogeneous security policy. They may be logical, or may be based on physical location and proximity.

Entity – A subject, object, user or another IT device, which interacts with TOE objects, data, or resources.

External IT entity – Any trusted Information Technology (IT) product or system, outside of the TOE, which may, in accordance with the TSP, perform an operation.

Identity – A representation (e.g., a string) uniquely identifying an authorized user, which can either be the full or abbreviated name of that user or a pseudonym.

Integrity – A security policy pertaining to the corruption of data and TSF mechanisms.

Named Object – An object that exhibits all of the following characteristics:

- The object may be used to transfer information between subjects of differing user and/or group identities within the TSF.
- Subjects in the TOE must be able to require a specific instance of the object.
- The name used to refer to a specific instance of the object must exist in a context that potentially allows subjects with different user and/or group identities to require the same instance of the object.

Object – An entity within the TSC that contains or receives information and upon which subjects perform operations.

Operating Environment – The total environment in which a TOE operates. It includes the physical facility and any physical, procedural, administrative and personnel controls.

Public Object – An object for which the TSF unconditionally permits all entities “read” access. Only the TSF or authorized administrators may create, delete, or modify the public objects.

Secure State – Condition in which all TOE security policies are enforced.

Security attributes – TSF data associated with subjects, objects, and users that are used for the enforcement of the TSP.

Security level – The combination of a hierarchical classification and a set of non-hierarchical categories that represent the sensitivity of the information.

Sensitive information – Information that, as determined by a competent authority, must be protected because its unauthorized disclosure, alteration, loss, or destruction will at least cause perceivable damage to someone or something.

Subject – An entity within the TSC that causes operation to be performed.

Threat – Capabilities, intentions and attack methods of adversaries, or any circumstance or event, with the potential to violate the TOE security policy.

Threat Agent – Any human user or Information Technology (IT) product or system, which may attempt to violate the TSP and perform an unauthorized operation with the TOE.

Unauthorized user – A user who may obtain access only to system provided public objects if any exist.

User – Any entity (human user or external IT entity) outside the TOE that interacts with the TOE.

Vulnerability – A weakness that can be exploited to violate the TOE security policy.

C ACRONYMS

CC	Common Criteria
CCIMB	Common Criteria Interpretations Management Board
CM	Configuration Management
DoD	Department of Defense
EAL	Evaluation Assurance Level
IATF	Information Assurance Technical Framework
IT	Information Technology
NIAP	National Information Assurance Partnership
NIST	National Institute of Standards and Technology
NSA	National Security Agency
PP	Protection Profile
SFP	Security Functional Policies
SFR	Security Functional Requirement
ST	Security Target
TOE	Target of Evaluation
TSC	TOE Scope of Control
TSE	TOE Security Environment
TSF	TOE Security Functions
TSFI	TSF interfaces
TSP	TOE Security Policy
TTAP/CCEVS	Trust Technology Assessment Program/ Common Criteria Evaluation and Validation Scheme

D RESERVED

E REFINEMENTS

89 This section contains refinements where text was omitted. Omitted text is shown as bold text within parenthesis. The actual text of the functional requirements as presented in Section 5 has been retained.

FAU_SEL.1.1-NIAP-0407 **Refinement:** The TSF shall **(be able to) allow only the administrator** to include or exclude auditable events from the set of audited events based on the following attributes:

- a) *user identity and/or group identity,*
- b) *event type,*
- c) *object identity,*
- d) [selection: “subject identity”, “host identity”, “none”];
- e) [success of auditable security events;
- f) failure of auditable security events; and
- g) [selection: [assignment: list of additional criteria that audit selectivity is based upon], “no additional criteria”].]

FMT_MSA.1.1 **Refinement:** The TSF shall enforce the [Discretionary Access Control policy] to restrict the ability to [*manage*] **all** the security attributes to [authorized administrators] **including top-level objects (e.g., tables) and sub-level objects (e.g., rows, columns, cells).**

*Application Note: The ST author should ensure that all attributes identified in FIA_ATD.1 are adequately managed and protected **for top-level objects and sub-level objects.***