

Certification Report

BSI-DSZ-CC-0735-2011

for

Renesas RS47X integrated circuit version 01

from

Renesas Electronics Corporation

BSI - Bundesamt für Sicherheit in der Informationstechnik, Postfach 20 03 63, D-53133 Bonn
Phone +49 (0)228 99 9582-0, Fax +49 (0)228 9582-5477, Infoline +49 (0)228 99 9582-111



Deutsches IT-Sicherheitszertifikat

erteilt vom



Bundesamt für Sicherheit in der Informationstechnik

BSI-DSZ-CC-0735-2011

Renesas RS47X integrated circuit
version 01

from Renesas Electronics Corporation

PP Conformance: Security IC Platform Protection Profile, Version 1.0,
15 June 2007, BSI-CC-PP-0035-2007

Functionality: PP conformant plus product specific extensions
Common Criteria Part 2 extended

Assurance: Common Criteria Part 3 conformant
EAL 5 augmented by ALC_DVS.2 and AVA_VAN.5



Common Criteria
Recognition
Arrangement
for components up to
EAL 4



The IT product identified in this certificate has been evaluated at an approved evaluation facility using the Common Methodology for IT Security Evaluation (CEM), Version 3.1 extended by advice of the Certification Body for components beyond EAL 5 and guidance specific for the technology of the product for conformance to the Common Criteria for IT Security Evaluation (CC), Version 3.1.

This certificate applies only to the specific version and release of the product in its evaluated configuration and in conjunction with the complete Certification Report.

The evaluation has been conducted in accordance with the provisions of the certification scheme of the German Federal Office for Information Security (BSI) and the conclusions of the evaluation facility in the evaluation technical report are consistent with the evidence adduced.

This certificate is not an endorsement of the IT product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

Bonn, 21 July 2011

For the Federal Office for Information Security

Bernd Kowalski
Head of Department

L.S.



This page is intentionally left blank.

Preliminary Remarks

Under the BSIG¹ Act, the Federal Office for Information Security (BSI) has the task of issuing certificates for information technology products.

Certification of a product is carried out on the instigation of the vendor or a distributor, hereinafter called the sponsor.

A part of the procedure is the technical examination (evaluation) of the product according to the security criteria published by the BSI or generally recognised security criteria.

The evaluation is normally carried out by an evaluation facility recognised by the BSI or by BSI itself.

The result of the certification procedure is the present Certification Report. This report contains among others the certificate (summarised assessment) and the detailed Certification Results.

The Certification Results contain the technical description of the security functionality of the certified product, the details of the evaluation (strength and weaknesses) and instructions for the user.

¹ Act on the Federal Office for Information Security (BSI-Gesetz - BSIG) of 14 August 2009, Bundesgesetzblatt I p. 2821

Contents

A Certification.....	7
1 Specifications of the Certification Procedure.....	7
2 Recognition Agreements.....	7
2.1 European Recognition of ITSEC/CC – Certificates (SOGIS-MRA).....	7
2.2 International Recognition of CC – Certificates (CCRA).....	8
3 Performance of Evaluation and Certification.....	8
4 Validity of the Certification Result.....	9
5 Publication.....	9
B Certification Results.....	11
1 Executive Summary.....	12
2 Identification of the TOE.....	13
3 Security Policy.....	14
4 Assumptions and Clarification of Scope.....	14
5 Architectural Information.....	15
6 Documentation.....	15
7 IT Product Testing.....	15
8 Evaluated Configuration.....	16
9 Results of the Evaluation.....	17
9.1 CC specific results.....	17
9.2 Results of cryptographic assessment.....	18
10 Obligations and Notes for the Usage of the TOE.....	18
11 Security Target.....	19
12 Definitions.....	19
12.1 Acronyms.....	19
12.2 Glossary.....	20
13 Bibliography.....	21
C Excerpts from the Criteria.....	23
D Annexes.....	33

A Certification

1 Specifications of the Certification Procedure

The certification body conducts the procedure according to the criteria laid down in the following:

- BSI²
- BSI Certification Ordinance³
- BSI Schedule of Costs⁴
- Special decrees issued by the Bundesministerium des Innern (Federal Ministry of the Interior)
- DIN EN 45011 standard
- BSI certification: Procedural Description (BSI 7125) [3]
- Common Criteria for IT Security Evaluation (CC), Version 3.1⁵ [1]
- Common Methodology for IT Security Evaluation, Version 3.1 [2]
- BSI certification: Application Notes and Interpretation of the Scheme (AIS) [4]

2 Recognition Agreements

In order to avoid multiple certification of the same product in different countries a mutual recognition of IT security certificates - as far as such certificates are based on ITSEC or CC - under certain conditions was agreed.

2.1 European Recognition of ITSEC/CC – Certificates (SOGIS-MRA)

The SOGIS-Mutual Recognition Agreement (SOGIS-MRA) Version 3 became effective in April 2010. It defines the recognition of certificates for IT-Products at a basic recognition level and in addition at higher recognition levels for IT-Products related to certain technical domains only.

The basic recognition level includes Common Criteria (CC) Evaluation Assurance Levels EAL1 to EAL4 and ITSEC Evaluation Assurance Levels E1 to E3 (basic). For higher recognition levels the technical domain Smart card and similar Devices has been defined. It includes assurance levels beyond EAL4 resp. E3 (basic).

The new agreement was initially signed by the national bodies of Finland, France, Germany, The Netherlands, Norway, Spain, Sweden and the United Kingdom.

² Act on the Federal Office for Information Security (BSI-Gesetz - BSIG) of 14 August 2009, Bundesgesetzblatt I p. 2821

³ Ordinance on the Procedure for Issuance of a Certificate by the Federal Office for Information Security (BSI-Zertifizierungsverordnung, BSIZertV) of 07 July 1992, Bundesgesetzblatt I p. 1230

⁴ Schedule of Cost for Official Procedures of the Bundesamt für Sicherheit in der Informationstechnik (BSI-Kostenverordnung, BSI-KostV) of 03 March 2005, Bundesgesetzblatt I p. 519

⁵ Proclamation of the Bundesministerium des Innern of 12 February 2007 in the Bundesanzeiger dated 23 February 2007, p. 3730

Within the terms of this agreement the German Federal Office for Information Security (BSI) recognises

- for the basic recognition level certificates issued as of April 2010 by the national certification bodies of France, The Netherlands, Spain and the United Kingdom.
- for the higher recognition level in the technical domain Smart card and similar Devices certificates issued as of April 2010 by the national certification bodies of France, The Netherlands and the United Kingdom.

In addition, certificates issued for Protection Profiles based on Common Criteria are part of the recognition agreement.

The SOGIS-MRA logo printed on the certificate indicates that it is recognised under the terms of this agreement.

Historically, the first SOGIS-Mutual Recognition Agreement Version 1 (ITSEC only) became initially effective in March 1998. It was extended in 1999 to include certificates based on the Common Criteria (MRA Version 2). Recognition of certificates previously issued under these older versions of the SOGIS-Mutual Recognition Agreement is being continued.

2.2 International Recognition of CC – Certificates (CCRA)

An arrangement (Common Criteria Recognition Arrangement) on the mutual recognition of certificates based on the CC Evaluation Assurance Levels up to and including EAL 4 has been signed in May 2000 (CCRA). It includes also the recognition of Protection Profiles based on the CC.

As of January 2009 the arrangement has been signed by the national bodies of: Australia, Austria, Canada, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, India, Israel, Italy, Japan, Republic of Korea, Malaysia, The Netherlands, New Zealand, Norway, Pakistan, Republic of Singapore, Spain, Sweden, Turkey, United Kingdom, United States of America. The current list of signatory nations and approved certification schemes can be seen on the web site: <http://www.commoncriteriaportal.org>

The Common Criteria Recognition Arrangement logo printed on the certificate indicates that this certification is recognised under the terms of this agreement.

This evaluation contains the components ADV_FSP.5, ADV_INT.2, ADV_TDS.4, ALC_CMS.5, ALC_DVS.2, ALC_TAT.2, ATE_DPT.3 and AVA_VAN.5 that are not mutually recognised in accordance with the provisions of the CCRA. For mutual recognition the EAL4 components of these assurance families are relevant.

3 Performance of Evaluation and Certification

The certification body monitors each individual evaluation to ensure a uniform procedure, a uniform interpretation of the criteria and uniform ratings.

The product Renesas RS47X integrated circuit version 01 has undergone the certification procedure at BSI. This is a re-certification based on BSI-DSZ-CC-0697-2011. Specific results from the evaluation process BSI-DSZ-CC-0697-2011 were re-used.

The evaluation of the product Renesas RS47X integrated circuit version 01 was conducted by T-Systems GEI GmbH. The evaluation was completed on 13 July 2011. The T-Systems GEI GmbH is an evaluation facility (ITSEF)⁶ recognised by the certification body of BSI.

⁶ Information Technology Security Evaluation Facility

For this certification procedure the sponsor and applicant is: Renesas Electronics Corporation

The product was developed by: Renesas Electronics Corporation

The certification is concluded with the comparability check and the production of this Certification Report. This work was completed by the BSI.

4 Validity of the Certification Result

This Certification Report only applies to the version of the product as indicated. The confirmed assurance package is only valid on the condition that

- all stipulations regarding generation, configuration and operation, as given in the following report, are observed,
- the product is operated in the environment described, where specified in the following report and in the Security Target.

For the meaning of the assurance levels please refer to the excerpts from the criteria at the end of the Certification Report.

The Certificate issued confirms the assurance of the product claimed in the Security Target at the date of certification. As attack methods evolve over time, the resistance of the certified version of the product against new attack methods needs to be re-assessed. Therefore, the sponsor should apply for the certified product being monitored within the assurance continuity program of the BSI Certification Scheme (e.g. by a re-certification). Specifically, if results of the certification are used in subsequent evaluation and certification procedures, in a system integration process or if a user's risk management needs regularly updated results, it is recommended to perform a re-assessment on a regular e.g. annual basis.

In case of changes to the certified version of the product, the validity can be extended to the new versions and releases, provided the sponsor applies for assurance continuity (i.e. re-certification or maintenance) of the modified product, in accordance with the procedural requirements, and the evaluation does not reveal any security deficiencies.

5 Publication

The product Renesas RS47X integrated circuit version 01 has been included in the BSI list of the certified products, which is published regularly (see also Internet: <https://www.bsi.bund.de> and [5]). Further information can be obtained from BSI-Infoline +49 228 9582-111.

Further copies of this Certification Report can be requested from the developer⁷ of the product. The Certification Report may also be obtained in electronic form at the internet address stated above.

⁷ Renesas Electronics Corporation
5-20-1 Jousuihon-cho, Kodaira-shi
Tokyo 187-8588
Japan

This page is intentionally left blank.

B Certification Results

The following results represent a summary of

- the Security Target of the sponsor for the Target of Evaluation,
- the relevant evaluation results from the evaluation facility, and
- complementary notes and stipulations of the certification body.

1 Executive Summary

The Target of Evaluation (TOE) is the Renesas RS47X integrated circuit version 01. The RS47X is an integrated circuit (IC) providing a hardware platform to a smart card operating system and smart card application software.

The TOE is intended for use in a range of high security applications, including high speed security authentication, data encryption or electronic signature. Several security features independently implemented in hardware or controlled by software will be provided to ensure proper operation and integrity and confidentiality of stored data. This includes for example measures for memory protection, leakage protection and sensors to allow operations only under specified conditions.

The Security Target [6] is the basis for this certification. It is based on the certified Protection Profile Security IC Platform Protection Profile, Version 1.0, 15 June 2007, BSI-CC-PP-0035-2007 [7].

The TOE Security Assurance Requirements (SAR) are based entirely on the assurance components defined in Part 3 of the Common Criteria (see part C or [1], Part 3 for details). The TOE meets the assurance requirements of the Evaluation Assurance Level EAL 5 augmented by ALC_DVS.2 and AVA_VAN.5.

The TOE Security Functional Requirements (SFR) relevant for the TOE are outlined in the Security Target [6] and [8], chapter 6.1. They are selected from Common Criteria Part 2 and some of them are newly defined. Thus the TOE is CC Part 2 extended.

The TOE Security Functional Requirements are implemented by the following TOE Security Functionalities:

TOE Security Functionality	Addressed issue
SF.HWProtect	Hardware protection/ protection against physical manipulation
SF.LeakProtect	Leak protection
SF.RNG	Random Number Generator
SF.DES	Tripple-DES function
SF.AES	AES function
SF.ESFunctions	Control of operating conditions
SF.TestModeControl	Protection of test mode functions
SF.Inject	Secure data injection

Table 1: TOE Security Functionalities

For more details please refer to the Security Target [6] and [8], chapter 7.1.

The assets to be protected by the TOE are defined in the Security Target [6] and [8], chapter 3.1. Based on these assets the TOE Security Problem is defined in terms of Assumptions, Threats and Organisational Security Policies. This is outlined in the Security Target [6] and [8], chapter 3.2 to 3.4.

This certification covers the following configurations of the TOE: RS47X integrated circuit version 01 with and without the optional modules of the hardware. For details refer to chapter 8.

The vulnerability assessment results as stated within this certificate do not include a rating for those cryptographic algorithms and their implementation suitable for encryption and decryption (see BSI Section 9, Para. 4, Clause 2).

The certification results only apply to the version of the product indicated in the certificate and on the condition that all the stipulations are kept as detailed in this Certification Report. This certificate is not an endorsement of the IT product by the Federal Office for Information Security (BSI) or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT product by BSI or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

2 Identification of the TOE

The Target of Evaluation (TOE) is called:

Renesas RS47X integrated circuit version 01

The following table outlines the TOE deliverables:

No	Type	Identifier	Release	Form of Delivery
1	HW	Renesas RS47X integrated circuit	version 01	Wafer or packaged module
2	SW	IC Dedicated Test Software Test ROM Software	20981	Included in RS47X ROM
3	SW	RNG on-line test software	1.3	Hardcopy provided as a part of [11]
4	SW	AES/DES library for RS-4 consists of RS4_LL.lib, RS4_LL.txt, and RS4_LL.h	4658 4658 4658	Electronic Data
5	DOC	Hardware Manual [13]	1.10	Electronic Data/Hardcopy
6	DOC	User Guidance [11]	1.4	Electronic Data/Hardcopy
7	DOC	Option List [12]	1.1, Rev. 14985	Electronic Data/Hardcopy

Table 2: Deliverables of the TOE

The hardware platform is labelled according to the availability of the optional contactless protocols Type-B and Type-F and considering the selection of the built-in capacitance between both antenna contact pads (LA-LB) that are optional modules selected in [25] by the user.

The security functionality of the TOE is not influenced by the delivery forms.

The commercial type name is the name of the TOE along with the selected contactless protocols option, the package code, and with the customer specific ROM code (the Security IC Embedded Software) of the TOE. The commercial type name is built as shown in Table 3:

Product Name	Type-A or Type-F	ROM code	Package code	Built-in capacitance
RS47X	A for Type-A C for Type-F	A number between 0 – 99 (unique for each ROM)	package code (two or three ASCII characters)	1 or space

Table 3: Meaning of the commercial type names of the TOE

The requirements for the delivery of the TOE are described in the Option List for Smart Card Microcomputer (for RS47X) [12]. The TOE is delivered to the customer by Renesas with special protective measures. The DES/AES Library of RS-4 is delivered in electronic form.

The TOE documentation ([11], [12], and [13]) is delivered as hard copy as well as in electronic form.

The TOE is identified with the information stored at the first 20 bytes of the EEPROM address range. The Option List for Smart Card Microcomputer (for RS47X) describes the information for identification of the TOE. In addition the hardware version can be identified by the nameplate on the surface of the die.

3 Security Policy

The security policy of the TOE is to provide basic security functions to be used by the smart card operating system and the smart card application thus providing an overall smart card system security. Therefore, the TOE will implement a symmetric cryptographic block cipher algorithm to ensure the confidentiality of plain text data by encryption and to support secure authentication protocols and it will provide a random number generation of appropriate quality.

As the TOE is a hardware security platform, the security policy of the TOE is also to provide protection against leakage of information (e.g. to ensure the confidentiality of cryptographic keys during cryptographic functions performed by the TOE), against physical probing, against malfunctions, against physical manipulations and against abuse of functionality. Hence the TOE shall:

- maintain the integrity and the confidentiality of data stored in the memory of the TOE and
- maintain the integrity, the correct operation and the confidentiality of security functions (security mechanisms and associated functions) provided by the TOE.

4 Assumptions and Clarification of Scope

The Assumptions defined in the Security Target and some aspects of Threats and Organisational Security Policies are not covered by the TOE itself. These aspects lead to specific Security Objectives to be fulfilled by the TOE-Environment. The following topics are of relevance:

- Usage of Hardware Platform
- Treatment of User Data
- Protection during composite product manufacturing
- Injected Data Support

Details can be found in the Security Target [6] and [8] chapter 4.2.

5 Architectural Information

The Renesas Renesas RS47X integrated circuit version 01 is an integrated circuit providing a hardware platform for a Security IC Embedded Software. A top level block diagram and a list of subsystems can be found within the TOE description of the “RS47X Version 01 Security Target”, [6] and [8]. The complete hardware description and the complete instruction set of the Renesas Renesas RS47X integrated circuit version 01 can be found in the “RS47X User’s Manual”, [13] and is publicly available in “H8S/2600 Series, H8S/2000 Series Software Manual, Revision 4.00”, [14].

The implementation of the TOE Security Functionality is based on the components 32-bit CPU, DES/3DES coprocessor, AES coprocessor, Random Number Generator, system control logic, and security circuitry implemented in the analogue circuitry as well as in the random logic circuitries, that includes security sensors. The contactless interface detects the related contactless communication protocols automatically. The security measures for physical protection are realized within the layout of the whole circuitry.

Beside the security functionalities, the TOE is equipped with the CRC coprocessor, the contactless interface circuitry, the UART, the interval timers, the pseudo-random number generator, the modular multiplication coprocessor, and optional the watchdog timer. The security of the TOE does not depend on those modules.

The smart card embedded support software “DES/AES Library of RS-4” is delivered as object code to the customer, who has to use the library when triple-DES or AES are required.

6 Documentation

The evaluated documentation as outlined in table 2 is being provided with the product to the customer. This documentation contains the required information for secure usage of the TOE in accordance with the Security Target.

Additional obligations and notes for secure usage of the TOE as outlined in chapter 10 of this report have to be followed.

7 IT Product Testing

The tests performed by the developer can be divided into the following categories:

- Tests which are performed in a simulation environment with different tools for the analogue circuitries and for the digital parts of the TOE,
- Characterisation and verification tests to release the hardware platform for production including tests with different operating conditions as well as special verification tests for security features of the hardware,
- Functional tests at the end of the production process using IC Dedicated Test Software. These tests are executed for every chip to check its correct functionality as a last step of phase 3,
- Design tool checks (layout versus schematic), and

- Verification tests carried out to verify the functionality and quality of the related property (statistical tests, side-channel analysis, FIB tests etc.).

The developer tests cover all TSFIs as identified in the functional specification as well as in the test documentation.

The evaluators were able to repeat the tests of the developer. A test protocol of the tests provided by the developer was verified. The tests of the developer were repeated by sampling. In addition the evaluators performed independent tests to supplement, augment and to verify the tests performed by the developer. The tests of the evaluators comprise special tests and examination of the hardware platform using open samples.

The evaluation provides evidence that the actual version of the TOE provides the TOE Security Functionality as specified by the developer. The test results confirm the correct implementation of the TOE Security Functionality.

For penetration testing the evaluators took all TOE Security Functionality into consideration. Extensive penetration testing was performed to test the security mechanisms used to provide the Security Functions. The tests for the hardware platform comprise the use of bespoke equipment and expert knowledge. The penetration tests considered both the physical tampering of the hardware platform and attacks which do not modify the hardware platform physically. Also the support of attacks by reverse engineering was considered. The test of the hardware platform comprises attacks that must be averted by the combination of the hardware platform and the Security IC combination of the hardware platform and the Security IC Embedded Software as well as attacks against the hardware platform directly. In addition side channel analysis was performed for the DES/3DES and AES coprocessor including the supporting software DES/AES Library for RS-4.

8 Evaluated Configuration

This certification covers the following configurations of the TOE:

The Renesas RS47X integrated circuit version 01 can be delivered with or without the optional modules of the hardware. These modules are the Watchdog Timer, the EEPROM protect bit mode function, and the available contactless communication protocols, as well as the availability of the 35pF internal capacitor between the antenna contact pads. Although the WDT and EEPROM protect bit mode functions could add further features for the implementation of a secure application, the security of the TOE is not decreased when they were disabled by the ordered product. Note that the TOE is equipped with these modules, however their functionality can be made available to the user by settings in test ROM.

Furthermore the internal capacitance is connected directly to the contact pads for antenna, which could also be connected or supported by the external capacitors, which can be ordered by the customer for COT delivery (refer to [12]). The availability of the modules can not be modified in the user mode. Therefore there is only one name and configuration for the TOE.

Except for the availability of the modules selected by the user, the Renesas RS47X integrated circuit version 01 has only one configuration. The Renesas RS47X integrated circuit version 01 is tested during the evaluation along with the optional modules. Beside the functionality of the optional devices are enabled/disabled in the test mode, there are no other differences. Since the optional modules are not security functionalities and non of the

security functionalities depends on the functions of the optional modules, the availability of the optional modules does not effect the security of the TOE.

9 Results of the Evaluation

9.1 CC specific results

The Evaluation Technical Report (ETR) [9] was provided by the ITSEF according to the Common Criteria [1], the Methodology [2], the requirements of the Scheme [3] and all interpretations and guidelines of the Scheme (AIS) [4] as relevant for the TOE.

The Evaluation Methodology CEM [2] was used for those components up to EAL5 extended by advice of the Certification Body for components beyond EAL 5 and guidance specific for the technology of the product [4] (AIS 34).

The following guidance specific for the technology were used:

- Supporting Document – Mandatory Technical Document, The Application of CC to Integrated Circuits
- Supporting Document – Mandatory Technical Document, Application of Attack Potential to Smartcards
- Supporting Document - Guidance, Smartcard Evaluation

(see [4], AIS 25, AIS 26, AIS 37).

For RNG assessment the scheme interpretations AIS 31 was used (see [4]).

To support composite evaluations according to AIS 36 the document ETR for composite evaluation [10] was provided and approved. This document provides details of this platform evaluation that have to be considered in the course of a composite evaluation on top.

The assurance refinements outlined in the Security Target were followed in the course of the evaluation of the TOE.

As a result of the evaluation the verdict PASS is confirmed for the following assurance components:

- All components of the EAL 5 package including the class ASE as defined in the CC (see also part C of this report)
- The components ALC_DVS.2 and AVA_VAN.5 augmented for this TOE evaluation.

As the evaluation work performed for this certification procedure was carried out as a re-evaluation based on the certificate BSI-DSZ-CC-0697-2011 some re-use of specific evaluation tasks was possible.

The evaluation has confirmed:

- PP Conformance: Security IC Platform Protection Profile, Version 1.0, 15 June 2007, BSI-CC-PP-0035-2007 [10]
- for the Functionality: PP conformant plus product specific extensions Common Criteria Part 2 extended
- for the Assurance: Common Criteria Part 3 conformant
EAL 5 augmented by ALC_DVS.2 and AVA_VAN.5

For specific evaluation results regarding the development and production environment see annex B in part D of this report.

The results of the evaluation are only applicable to the TOE as defined in chapter 2 and the configuration as outlined in chapter 8 above.

9.2 Results of cryptographic assessment

The vulnerability assessment results as stated within this certificate do not include a rating for those cryptographic algorithms and their implementation suitable for encryption and decryption (see BSIG Section 9, Para. 4, Clause 2). This holds for:

- the TOE Security functionality SF.DES, SF.AES and
- for other usage of encryption and decryption within the TOE.

The strength of the cryptographic algorithms was not rated in the course of this certification procedure (see BSIG Section 4, Para. 3, Clause 2). But Cryptographic Functionalities with a security level of 80 bits or lower can no longer be regarded as secure against attacks with high attack potential without considering the application context. Therefore for this functionalities it shall be checked whether the related crypto operations are appropriate for the intended system. Some further hints and guidelines can be derived from the 'Technische Richtlinie BSI TR-02102' (<https://www.bsi.bund.de>).

The Cryptographic Functionality 2-key Triple DES (2TDES), provided by the TOE achieves a security level of maximum 80 Bits (in general context).

10 Obligations and Notes for the Usage of the TOE

The documents as outlined in table 2 contain necessary information about the usage of the TOE and all security hints therein have to be considered. In addition all aspects of assumptions, threats and policies as outlined in the Security Target not covered by the TOE itself need to be fulfilled by the operational environment of the TOE.

The customer or user of the product shall consider the results of the certification within his system risk management process. In order for the evolution of attack methods and techniques to be covered, he should define the period of time until a re-assessment for the TOE is required and thus requested from the sponsor of the certificate.

The limited validity for the usage of cryptographic algorithms as outlined in chapter 9 has to be considered by the user and his system risk management process.

Some security measures are partly implemented in the hardware and require additional configuration or control or measures to be implemented by the IC Dedicated Support Software or Embedded Software.

For this reason the TOE includes guidance documentation (see table 2) which contains guidelines for the developer of the IC Dedicated Support Software and Embedded Software on how to securely use the microcontroller chip and which measures have to be implemented in the software in order to fulfil the security requirements of the Security Target of the TOE.

In the course of the evaluation of the composite product or system it must be examined if the required measures have been correctly and effectively implemented by the software. Additionally, the evaluation of the composite product or system must also consider the evaluation results as outlined in the document ETR for composite evaluation [10].

11 Security Target

For the purpose of publishing, the Security Target [8] of the Target of Evaluation (TOE) is provided within a separate document as Annex A of this report. It is a sanitised version of the complete Security Target [6] used for the evaluation performed. Sanitisation was performed according to the rules as outlined in the relevant CCRA policy (see AIS 35 [4])

12 Definitions

12.1 Acronyms

3DES	Triple Data Encryption Standard
AES	Advanced Encryption Standard
AIS	Application Notes and Interpretations of the Scheme
BSI	Bundesamt für Sicherheit in der Informationstechnik / Federal Office for Information Security, Bonn, Germany
BSIG	BSI-Gesetz / Act on the Federal Office for Information Security
CCRA	Common Criteria Recognition Arrangement
CC	Common Criteria for IT Security Evaluation
CEM	Common Methodology for Information Technology Security Evaluation
COT	Chip on Tape
CPU	Central processing unit
DES	Data Encryption Standard
EAL	Evaluation Assurance Level
EEPROM	Electrically Erasable Programmable Read-Only Memory
ETR	Evaluation Technical Report
HW	Hardware
IC	Integrated circuit
IT	Information Technology
ITSEF	Information Technology Security Evaluation Facility
PP	Protection Profile
ROM	Read-Only Memory
SAR	Security Assurance Requirement
SFP	Security Function Policy
SFR	Security Functional Requirement
ST	Security Target
TOE	Target of Evaluation
TSF	TOE Security Functionalities
TSFI	TSF Interface

WDT Watchdog Timer

12.2 Glossary

Augmentation - The addition of one or more requirement(s) to a package.

Extension - The addition to an ST or PP of functional requirements not contained in part 2 and/or assurance requirements not contained in part 3 of the CC.

Formal - Expressed in a restricted syntax language with defined semantics based on well-established mathematical concepts.

Informal - Expressed in natural language.

Object - An passive entity in the TOE, that contains or receives information, and upon which subjects perform operations.

Protection Profile - An implementation-independent statement of security needs for a TOE type.

Security Target - An implementation-dependent statement of security needs for a specific identified TOE.

Semiformal - Expressed in a restricted syntax language with defined semantics.

Subject - An active entity in the TOE that performs operations on objects.

Target of Evaluation - A set of software, firmware and/or hardware possibly accompanied by guidance.

TOE Security Functionality - combined functionality of all hardware, software, and firmware of a TOE that must be relied upon for the correct enforcement of the SFRs

13 Bibliography

- [1] Common Criteria for Information Technology Security Evaluation, Version 3.1, Part 1: Introduction and general model, Revision 3, July 2009
Part 2: Security functional components, Revision 3, July 2009
Part 3: Security assurance components, Revision 3, July 2009
- [2] Common Methodology for Information Technology Security Evaluation (CEM), Evaluation Methodology, Version 3.1, Rev. 3, July 2009
- [3] BSI certification: Procedural Description (BSI 7125)
- [4] Application Notes and Interpretations of the Scheme (AIS) as relevant for the TOE⁸.
- [5] German IT Security Certificates (BSI 7148), periodically updated list published also in the BSI Website
- [6] RS47X Version 01 Security Target, Revision 5076, Renesas Electronics Corporation, 29 March 2011
- [7] Security IC Platform Protection Profile, Version 1.0, 15 June 2007, BSI-CC-PP-0035-2007
- [8] RS47X Version 01 Security Target -Public Version-, Revision 1.2, Renesas Electronics Corporation, 15 July 2011
- [9] Evaluation Technical Report BSI-DSZ-CC-0735, Version 1.0, 15 July 2011, Renesas RS47X integrated circuit version 01, T-Systems GEI GmbH, (confidential document)
- [10] ETR for composite evaluation according to AIS 36 for the Product Renesas RS47X integrated circuit, Version 01, BSI-DSZ-CC-0735, 15 July 2011, Version 1.1, T-Systems GEI GmbH (confidential document)
- [11] RS-4 dual-way Series User Guidance Manual, Revision 1.4, Renesas Electronics Corporation, July, 2011
- [12] Option List for Smart Card Microcomputer (for RS47X), Revision 1.1, Rev. 14985, Renesas Electronics Corporation, 24 June 2011

⁸specifically

- AIS 20, Version 1, 2. December 1999, Funktionalitätsklassen und Evaluationsmethodologie für deterministische Zufallszahlengeneratoren
- AIS 25, Version 6, 7 September 2009, Anwendung der CC auf Integrierte Schaltungen including JIL Document and CC Supporting Document
- AIS 26, Version 7, 3 August 2010, Evaluationsmethodologie für in Hardware integrierte Schaltungen including JIL Document and CC Supporting Document
- AIS 31, Version 1, 25 Sept. 2001 Funktionalitätsklassen und Evaluationsmethodologie für physikalische Zufallszahlengeneratoren
- AIS 32, Version 6, 3 August 2010, CC-Interpretationen im deutschen Zertifizierungsschema
- AIS 34, Version 3, 3 September 2009, Evaluation Methodology for CC Assurance Classes for EAL5+ (CCv2.3 & CCv3.1) and EAL6 (CCv3.1)
- AIS 35, Version 2.0, 12 November 2007, Öffentliche Fassung des Security Targets (ST-Lite) including JIL Document and CC Supporting Document and CCRA policies
- AIS 38, Version 2.0, 28 September 2007, Reuse of evaluation results

- [13] RS47X User's Manual: Hardware, Renesas Secure Microcomputer RS-4 Series, Rev. 1.10, Renesas Electronics Corporation, September 14, 2010
- [14] H8S/2600 Series, H8S/2000 Series Software Manual, Revision 4.00, Renesas Technology Corp., 24 February 2006
- [15] RS47X Document Version for the Common Criteria, Revision 5176, Renesas Electronics Corporation, 15 July, 2011 (confidential document)

C Excerpts from the Criteria

CC Part1:

Conformance Claim (Release 3 = chapter 10.4)

"The conformance claim indicates the source of the collection of requirements that is met by a PP or ST that passes its evaluation. This conformance claim contains a CC conformance claim that:

- describes the version of the CC to which the PP or ST claims conformance.
- describes the conformance to CC Part 2 (security functional requirements) as either:
 - **CC Part 2 conformant** - A PP or ST is CC Part 2 conformant if all SFRs in that PP or ST are based only upon functional components in CC Part 2, or
 - **CC Part 2 extended** - A PP or ST is CC Part 2 extended if at least one SFR in that PP or ST is not based upon functional components in CC Part 2.
- describes the conformance to CC Part 3 (security assurance requirements) as either:
 - **CC Part 3 conformant** - A PP or ST is CC Part 3 conformant if all SARs in that PP or ST are based only upon assurance components in CC Part 3, or
 - **CC Part 3 extended** - A PP or ST is CC Part 3 extended if at least one SAR in that PP or ST is not based upon assurance components in CC Part 3.

Additionally, the conformance claim may include a statement made with respect to packages, in which case it consists of one of the following:

- **Package name Conformant** - A PP or ST is conformant to a pre-defined package (e.g. EAL) if:
 - the SFRs of that PP or ST are identical to the SFRs in the package, or
 - the SARs of that PP or ST are identical to the SARs in the package.
- **Package name Augmented** - A PP or ST is an augmentation of a predefined package if:
 - the SFRs of that PP or ST contain all SFRs in the package, but have at least one additional SFR or one SFR that is hierarchically higher than an SFR in the package.
 - the SARs of that PP or ST contain all SARs in the package, but have at least one additional SAR or one SAR that is hierarchically higher than an SAR in the package.

Note that when a TOE is successfully evaluated to a given ST, any conformance claims of the ST also hold for the TOE. A TOE can therefore also be e.g. CC Part 2 conformant.

Finally, the conformance claim may also include two statements with respect to Protection Profiles:

- **PP Conformant** - A PP or TOE meets specific PP(s), which are listed as part of the conformance result.
- **Conformance Statement (Only for PPs)** - This statement describes the manner in which PPs or STs must conform to this PP: strict or demonstrable. For more information on this Conformance Statement, see Annex D."

CC Part 3:

Class APE: Protection Profile evaluation (chapter 10)

“Evaluating a PP is required to demonstrate that the PP is sound and internally consistent, and, if the PP is based on one or more other PPs or on packages, that the PP is a correct instantiation of these PPs and packages. These properties are necessary for the PP to be suitable for use as the basis for writing an ST or another PP.

Assurance Class	Assurance Components
Class APE: Protection Profile evaluation	APE_INT.1 PP introduction
	APE_CCL.1 Conformance claims
	APE_SPD.1 Security problem definition
	APE_OBJ.1 Security objectives for the operational environment APE_OBJ.2 Security objectives
	APE_ECD.1 Extended components definition
	APE_REQ.1 Stated security requirements APE_REQ.2 Derived security requirements

APE: Protection Profile evaluation class decomposition”

Class ASE: Security Target evaluation (chapter 11)

“Evaluating an ST is required to demonstrate that the ST is sound and internally consistent, and, if the ST is based on one or more PPs or packages, that the ST is a correct instantiation of these PPs and packages. These properties are necessary for the ST to be suitable for use as the basis for a TOE evaluation.”

Assurance Class	Assurance Components
Class ASE: Security Target evaluation	ASE_INT.1 ST introduction
	ASE_CCL.1 Conformance claims
	ASE_SPD.1 Security problem definition
	ASE_OBJ.1 Security objectives for the operational environment ASE_OBJ.2 Security objectives
	ASE_ECD.1 Extended components definition
	ASE_REQ.1 Stated security requirements ASE_REQ.2 Derived security requirements
	ASE_TSS.1 TOE summary specification ASE_TSS.2 TOE summary specification with architectural design summary

ASE: Security Target evaluation class decomposition

Security assurance components (chapter 7)

“The following Sections describe the constructs used in representing the assurance classes, families, and components.”

“Each assurance class contains at least one assurance family.”

“Each assurance family contains one or more assurance components.”

The following table shows the assurance class decomposition.

Assurance Class	Assurance Components
ADV: Development	ADV_ARC.1 Security architecture description
	ADV_FSP.1 Basic functional specification ADV_FSP.2 Security-enforcing functional specification ADV_FSP.3 Functional specification with complete summary ADV_FSP.4 Complete functional specification ADV_FSP.5 Complete semi-formal functional specification with additional error information ADV_FSP.6 Complete semi-formal functional specification with additional formal specification
	ADV_IMP.1 Implementation representation of the TSF ADV_IMP.2 Implementation of the TSF
	ADV_INT.1 Well-structured subset of TSF internals ADV_INT.2 Well-structured internals ADV_INT.3 Minimally complex internals
	ADV_SPM.1 Formal TOE security policy model
	ADV_TDS.1 Basic design ADV_TDS.2 Architectural design ADV_TDS.3 Basic modular design ADV_TDS.4 Semiformal modular design ADV_TDS.5 Complete semiformal modular design ADV_TDS.6 Complete semiformal modular design with formal high- level design presentation

Assurance Class	Assurance Components	
AGD:	AGD_OPE.1 Operational user guidance	
Guidance documents	AGD_PRE.1 Preparative procedures	
ALC: Life cycle support	ALC_CMC.1 Labelling of the TOE ALC_CMC.2 Use of a CM system ALC_CMC.3 Authorisation controls ALC_CMC.4 Production support, acceptance procedures and automation ALC_CMC.5 Advanced support	
	ALC_CMS.1 TOE CM coverage ALC_CMS.2 Parts of the TOE CM coverage ALC_CMS.3 Implementation representation CM coverage ALC_CMS.4 Problem tracking CM coverage ALC_CMS.5 Development tools CM coverage	
	ALC_DEL.1 Delivery procedures	
	ALC_DVS.1 Identification of security measures ALC_DVS.2 Sufficiency of security measures	
	ALC_FLR.1 Basic flaw remediation ALC_FLR.2 Flaw reporting procedures ALC_FLR.3 Systematic flaw remediation	
	ALC_LCD.1 Developer defined life-cycle model ALC_LCD.2 Measurable life-cycle model	
	ALC_TAT.1 Well-defined development tools ALC_TAT.2 Compliance with implementation standards ALC_TAT.3 Compliance with implementation standards - all parts	
	ATE: Tests	ATE_COV.1 Evidence of coverage ATE_COV.2 Analysis of coverage ATE_COV.3 Rigorous analysis of coverage
		ATE_DPT.1 Testing: basic design ATE_DPT.2 Testing: security enforcing modules ATE_DPT.3 Testing: modular design ATE_DPT.4 Testing: implementation representation
		ATE_FUN.1 Functional testing ATE_FUN.2 Ordered functional testing
ATE_IND.1 Independent testing – conformance ATE_IND.2 Independent testing – sample ATE_IND.3 Independent testing – complete		
AVA: Vulnerability assessment	AVA_VAN.1 Vulnerability survey AVA_VAN.2 Vulnerability analysis AVA_VAN.3 Focused vulnerability analysis AVA_VAN.4 Methodical vulnerability analysis AVA_VAN.5 Advanced methodical vulnerability analysis	

Assurance class decomposition

Evaluation assurance levels (chapter 8)

“The Evaluation Assurance Levels (EALs) provide an increasing scale that balances the level of assurance obtained with the cost and feasibility of acquiring that degree of assurance. The CC approach identifies the separate concepts of assurance in a TOE at the end of the evaluation, and of maintenance of that assurance during the operational use of the TOE.

It is important to note that not all families and components from CC Part 3 are included in the EALs. This is not to say that these do not provide meaningful and desirable assurances. Instead, it is expected that these families and components will be considered for augmentation of an EAL in those PPs and STs for which they provide utility.”

Evaluation assurance level (EAL) overview (chapter 8.1)

“Table 1 represents a summary of the EALs. The columns represent a hierarchically ordered set of EALs, while the rows represent assurance families. Each number in the resulting matrix identifies a specific assurance component where applicable.

As outlined in the next Section, seven hierarchically ordered evaluation assurance levels are defined in the CC for the rating of a TOE's assurance. They are hierarchically ordered inasmuch as each EAL represents more assurance than all lower EALs. The increase in assurance from EAL to EAL is accomplished by substitution of a hierarchically higher assurance component from the same assurance family (i.e. increasing rigour, scope, and/or depth) and from the addition of assurance components from other assurance families (i.e. adding new requirements).

These EALs consist of an appropriate combination of assurance components as described in Chapter 7 of this CC Part 3. More precisely, each EAL includes no more than one component of each assurance family and all assurance dependencies of every component are addressed.

While the EALs are defined in the CC, it is possible to represent other combinations of assurance. Specifically, the notion of “augmentation” allows the addition of assurance components (from assurance families not already included in the EAL) or the substitution of assurance components (with another hierarchically higher assurance component in the same assurance family) to an EAL. Of the assurance constructs defined in the CC, only EALs may be augmented. The notion of an “EAL minus a constituent assurance component” is not recognised by the standard as a valid claim. Augmentation carries with it the obligation on the part of the claimant to justify the utility and added value of the added assurance component to the EAL. An EAL may also be augmented with extended assurance requirements.

Assurance Class	Assurance Family	Assurance Components by Evaluation Assurance Level						
		EAL1	EAL2	EAL3	EAL4	EAL5	EAL6	EAL7
Development	ADV_ARC		1	1	1	1	1	1
	ADV_FSP	1	2	3	4	5	5	6
	ADV_IMP				1	1	2	2
	ADV_INT					2	3	3
	ADV_SPM						1	1
	ADV_TDS		1	2	3	4	5	6
Guidance Documents	AGD_OPE	1	1	1	1	1	1	1
	AGD_PRE	1	1	1	1	1	1	1
Life cycle Support	ALC_CMC	1	2	3	4	4	5	5
	ALC_CMS	1	2	3	4	5	5	5
	ALC_DEL		1	1	1	1	1	1
	ALC_DVS			1	1	1	2	2
	ALC_FLR							
	ALC_LCD			1	1	1	1	2
	ALC_TAT				1	2	3	3
Security Target Evaluation	ASE_CCL	1	1	1	1	1	1	1
	ASE_ECD	1	1	1	1	1	1	1
	ASE_INT	1	1	1	1	1	1	1
	ASE_OBJ	1	2	2	2	2	2	2
	ASR_REQ	1	2	2	2	2	2	2
	ASE_SPD		1	1	1	1	1	1
	ASE_TSS	1	1	1	1	1	1	1
Tests	ATE_COV		1	2	2	2	3	3
	ATE_DPT			1	1	3	3	4
	ATE_FUN		1	1	1	1	2	2
	ATE_IND	1	2	2	2	2	2	3
Vulnerability assessment	AVA_VAN	1	2	2	3	4	5	5

Table 1: Evaluation assurance level summary”

Evaluation assurance level 1 (EAL1) - functionally tested (chapter 8.3)

“Objectives

EAL1 is applicable where some confidence in correct operation is required, but the threats to security are not viewed as serious. It will be of value where independent assurance is required to support the contention that due care has been exercised with respect to the protection of personal or similar information.

EAL1 requires only a limited security target. It is sufficient to simply state the SFRs that the TOE must meet, rather than deriving them from threats, OSPs and assumptions through security objectives.

EAL1 provides an evaluation of the TOE as made available to the customer, including independent testing against a specification, and an examination of the guidance documentation provided. It is intended that an EAL1 evaluation could be successfully conducted without assistance from the developer of the TOE, and for minimal outlay.

An evaluation at this level should provide evidence that the TOE functions in a manner consistent with its documentation.”

Evaluation assurance level 2 (EAL2) - structurally tested (chapter 8.4)

“Objectives

EAL2 requires the co-operation of the developer in terms of the delivery of design information and test results, but should not demand more effort on the part of the developer than is consistent with good commercial practise. As such it should not require a substantially increased investment of cost or time.

EAL2 is therefore applicable in those circumstances where developers or users require a low to moderate level of independently assured security in the absence of ready availability of the complete development record. Such a situation may arise when securing legacy systems, or where access to the developer may be limited.”

Evaluation assurance level 3 (EAL3) - methodically tested and checked (chapter 8.5)

“Objectives

EAL3 permits a conscientious developer to gain maximum assurance from positive security engineering at the design stage without substantial alteration of existing sound development practises.

EAL3 is applicable in those circumstances where developers or users require a moderate level of independently assured security, and require a thorough investigation of the TOE and its development without substantial re-engineering.”

Evaluation assurance level 4 (EAL4) - methodically designed, tested, and reviewed
(chapter 8.6)**“Objectives**

EAL4 permits a developer to gain maximum assurance from positive security engineering based on good commercial development practises which, though rigorous, do not require substantial specialist knowledge, skills, and other resources. EAL4 is the highest level at which it is likely to be economically feasible to retrofit to an existing product line.

EAL4 is therefore applicable in those circumstances where developers or users require a moderate to high level of independently assured security in conventional commodity TOEs and are prepared to incur additional security-specific engineering costs.”

Evaluation assurance level 5 (EAL5) - semiformally designed and tested (chapter 8.7)**“Objectives**

EAL5 permits a developer to gain maximum assurance from security engineering based upon rigorous commercial development practises supported by moderate application of specialist security engineering techniques. Such a TOE will probably be designed and developed with the intent of achieving EAL5 assurance. It is likely that the additional costs attributable to the EAL5 requirements, relative to rigorous development without the application of specialised techniques, will not be large.

EAL5 is therefore applicable in those circumstances where developers or users require a high level of independently assured security in a planned development and require a rigorous development approach without incurring unreasonable costs attributable to specialist security engineering techniques.”

Evaluation assurance level 6 (EAL6) - semiformally verified design and tested
(chapter 8.8)**“Objectives**

EAL6 permits developers to gain high assurance from application of security engineering techniques to a rigorous development environment in order to produce a premium TOE for protecting high value assets against significant risks.

EAL6 is therefore applicable to the development of security TOEs for application in high risk situations where the value of the protected assets justifies the additional costs.”

Evaluation assurance level 7 (EAL7) - formally verified design and tested (chapter 8.9)

"Objectives

EAL7 is applicable to the development of security TOEs for application in extremely high risk situations and/or where the high value of the assets justifies the higher costs. Practical application of EAL7 is currently limited to TOEs with tightly focused security functionality that is amenable to extensive formal analysis."

Class AVA: Vulnerability assessment (chapter 16)

"The AVA: Vulnerability assessment class addresses the possibility of exploitable vulnerabilities introduced in the development or the operation of the TOE."

Vulnerability analysis (AVA_VAN) (chapter 16.1)

"Objectives

Vulnerability analysis is an assessment to determine whether potential vulnerabilities identified, during the evaluation of the development and anticipated operation of the TOE or by other methods (e.g. by flaw hypotheses or quantitative or statistical analysis of the security behaviour of the underlying security mechanisms), could allow attackers to violate the SFRs.

Vulnerability analysis deals with the threats that an attacker will be able to discover flaws that will allow unauthorised access to data and functionality, allow the ability to interfere with or alter the TSF, or interfere with the authorised capabilities of other users."

This page is intentionally left blank

D Annexes

List of annexes of this certification report

- Annex A: Security Target provided within a separate document.
- Annex B: Evaluation results regarding development and production environment

This page is intentionally left blank.

Annex B of Certification Report BSI-DSZ-CC-0735-2011

Evaluation results regarding development and production environment



The IT product Renesas RS47X integrated circuit version 01 (Target of Evaluation, TOE) has been evaluated at an approved evaluation facility using the Common Methodology for IT Security Evaluation (CEM), Version 3.1 extended by advice of the Certification Body for components beyond EAL 5 and guidance specific for the technology of the product for conformance to the Common Criteria for IT Security Evaluation (CC), Version 3.1.

As a result of the TOE certification, dated 21 July 2011, the following results regarding the development and production environment apply. The Common Criteria assurance requirements ALC – Life cycle support (i.e. ALC_CMC.4, ALC_CMS.5, ALC_DEL.1, ALC_DVS.2, ALC_LCD.1, ALC_TAT.2)

are fulfilled for the development and production sites of the TOE listed below:

- a) Renesas Electronics Corporation, 5-20-1, Jousuihon-cho, Kodaira-shi, Tokyo 187-8588, Japan (development and customer support)
- b) Renesas Electronics Europe Ltd., Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5FH, U.K. (development, testing and customer support)
- c) Renesas Electronics Corporation Naka Factory, 751 Horiguchi, Hitachinaka-shi, Ibaraki 312-0034, Japan (semiconductor factory)
- d) Dai Nippon Printing Co., Ltd., 2-2-1 Fukuoka, Fujimino-shi, Saitama 356-8507, Japan (mask shop)
- e) Renesas Electronics Corporation – Kofu site, 4617 Nishiyahata, Kai-shi, Yamanashi 400-0117, Japan (test center)
- f) Toyo Electronics Co., Ltd., 2781-1, Shimosone-cho, Kofu-shi, Yamanashi, 400-1508, Japan (test center)
- g) Renesas Musashi Engineering Service Co., Ltd., 5-22-1 Jousuihon-cho, Kodaira-shi, Tokyo 187-8522, Japan (ROM handling)
- h) MTEX Matsumura Corp., 2-2-2 Kitamachi, Obanazawa-shi, Yamagata 999-4231, Japan (module assembly)
- i) The Apollo Electronics Co., Ltd., 610 Shimoimasuwa, Minami-alps-shi, Yamanashi, 400-0212, Japan (back grinding)
- j) Enzan Factory Co., Ltd., 276 Enzanshimoozo, Kosu-shi, Yamanashi, 404-0043, Japan (wafer dicing)
- k) Renesas Electronics Europe GmbH, Karl-Hammerschmidt-Str. 42, 85609 Aschheim-Dornach, Germany (development and test site for DES/AES library for RS4)

For the sites listed above, the requirements have been specifically applied in accordance with the Security Target [6]). The evaluators verified, that the threats, security objectives and requirements for the TOE life cycle phases up to delivery (as stated in the Security Target [6] and [8]) are fulfilled by the procedures of these sites.