Certification Report

BSI-DSZ-CC-0918-V2-2021

for

CONEXA 3.0 Version 1.1

from

Theben AG

BSI - Bundesamt für Sicherheit in der Informationstechnik, Postfach 20 03 63, D-53133 Bonn Phone +49 (0)228 99 9582-0, Fax +49 (0)228 9582-5477, Infoline +49 (0)228 99 9582-111

Certification Report V1.0 CC-Zert-327 V5.41





BSI-DSZ-CC-0918-V2-2021 (*)

Smart Meter Gateway

CONEXA 3.0, Version 1.1

from Theben AG

PP Conformance: Protection Profile for the Gateway of a Smart

Metering System, Version 1.3, 31 March 2014, BSI-

CC-PP-0073-2014

Functionality: PP conformant

Common Criteria Part 2 extended

Assurance: Common Criteria Part 3 conformant

EAL 4 augmented by ALC FLR.2, AVA VAN.5

SOGIS
IT SECURITY CERTIFIED

SOGIS
Recognition Agreement
for components up to
EAL 4



The IT Product identified in this certificate has been evaluated at an approved evaluation facility using the Common Methodology for IT Security Evaluation (CEM), Version 3.1 extended by Scheme Interpretations and by advice of the Certification Body for components beyond EAL 5 for conformance to the Common Criteria for IT Security Evaluation (CC), Version 3.1. CC and CEM are also published as ISO/IEC 15408 and ISO/IEC 18045.

(*) This certificate applies only to the specific version and release of the product in its evaluated configuration and in conjunction with the complete Certification Report and Notification. For details on the validity see Certification Report part A chapter 5.

The evaluation has been conducted in accordance with the provisions of the certification scheme of the German Federal Office for Information Security (BSI) and the conclusions of the evaluation facility in the evaluation technical report are consistent with the evidence adduced.

This certificate is not an endorsement of the IT Product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT Product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

Bonn, 1 July 2021

For the Federal Office for Information Security



Common Criteria Recognition Arrangement recognition for components up to EAL 2 and ALC_FLR only

Matthias Internann Head of Branch L.S.



This page is intentionally left blank.

Contents

A. Certification	6
 Preliminary Remarks Specifications of the Certification Procedure Recognition Agreements Performance of Evaluation and Certification Validity of the Certification Result Publication 	6 8 8
B. Certification Results	10
 Executive Summary. Identification of the TOE. Security Policy. Assumptions and Clarification of Scope. Architectural Information. Documentation. IT Product Testing. Evaluated Configuration. Results of the Evaluation. Obligations and Notes for the Usage of the TOE. Security Target. Definitions. Bibliography. 	
C. Excerpts from the Criteria	24
D. Annexes	25

A. Certification

1. Preliminary Remarks

Under the BSIG¹ Act, the Federal Office for Information Security (BSI) has the task of issuing certificates for information technology products.

Certification of a product is carried out on the instigation of the vendor or a distributor, hereinafter called the sponsor.

A part of the procedure is the technical examination (evaluation) of the product according to the security criteria published by the BSI or generally recognised security criteria.

The evaluation is normally carried out by an evaluation facility recognised by the BSI or by BSI itself.

The result of the certification procedure is the present Certification Report. This report contains among others the certificate (summarised assessment) and the detailed Certification Results.

The Certification Results contain the technical description of the security functionality of the certified product, the details of the evaluation (strength and weaknesses) and instructions for the user.

2. Specifications of the Certification Procedure

The certification body conducts the procedure according to the criteria laid down in the following:

- Act on the Federal Office for Information Security¹
- BSI Certification and Approval Ordinance²
- BMI Regulations on Ex-parte Costs³
- Special decrees issued by the Bundesministerium des Innern (Federal Ministry of the Interior)
- DIN EN ISO/IEC 17065 standard
- BSI certification: Scheme documentation describing the certification process (CC-Produkte) [3]
- BSI certification: Scheme documentation on requirements for the Evaluation Facility, its approval and licencing process (CC-Stellen) [3]

Act on the Federal Office for Information Security (BSI-Gesetz - BSIG) of 14 August 2009, Bundesgesetzblatt I p. 2821

Ordinance on the Procedure for Issuance of Security Certificates and approval by the Federal Office for Information Security (BSI-Zertifizierungs- und -Anerkennungsverordnung - BSIZertV) of 17 December 2014, Bundesgesetzblatt 2014, part I, no. 61, p. 2231

BMI Regulations on Ex-parte Costs - Besondere Gebührenverordnung des BMI für individuell zurechenbare öffentliche Leistungen in dessen Zuständigkeitsbereich (BMIBGebV), Abschnitt 7 (BSI-Gesetz) - dated 2 September 2019, Bundesgesetzblatt I p. 1365

 Common Criteria for IT Security Evaluation (CC), Version 3.1⁴[1] also published as ISO/IEC 15408.

- Common Methodology for IT Security Evaluation (CEM), Version 3.1 [2] also published as ISO/IEC 18045
- BSI certification: Application Notes and Interpretation of the Scheme (AIS) [4]

3. Recognition Agreements

In order to avoid multiple certification of the same product in different countries a mutual recognition of IT security certificates - as far as such certificates are based on ITSEC or CC - under certain conditions was agreed.

3.1. European Recognition of CC – Certificates (SOGIS-MRA)

The SOGIS-Mutual Recognition Agreement (SOGIS-MRA) Version 3 became effective in April 2010. It defines the recognition of certificates for IT-Products at a basic recognition level and, in addition, at higher recognition levels for IT-Products related to certain SOGIS Technical Domains only.

The basic recognition level includes Common Criteria (CC) Evaluation Assurance Levels EAL 1 to EAL 4. For "Smartcards and similar devices" a SOGIS Technical Domain is in place. For "HW Devices with Security Boxes" a SOGIS Technical Domains is in place, too. In addition, certificates issued for Protection Profiles based on Common Criteria are part of the recognition agreement.

The current list of signatory nations and approved certification schemes, details on recognition, and the history of the agreement can be seen on the website at https://www.sogis.eu.

The SOGIS-MRA logo printed on the certificate indicates that it is recognised under the terms of this agreement by the related bodies of the signatory nations. A disclaimer beneath the logo indicates the specific scope of recognition.

This certificate is recognized according to the rules of SOGIS-MRA, i.e. up to and including CC part 3 EAL 4 components. The evaluation contained the components AVA_VAN.5 that is not mutually recognised in accordance with the provisions of the SOGIS MRA. For mutual recognition the EAL 4 components of these assurance families are relevant.

3.2. International Recognition of CC – Certificates (CCRA)

The international arrangement on the mutual recognition of certificates based on the CC (Common Criteria Recognition Arrangement, CCRA-2014) has been ratified on 08 September 2014. It covers CC certificates based on collaborative Protection Profiles (cPP) (exact use), CC certificates based on assurance components up to and including EAL 2 or the assurance family Flaw Remediation (ALC_FLR) and CC certificates for Protection Profiles and for collaborative Protection Profiles (cPP).

The current list of signatory nations and approved certification schemes can be seen on the website: https://www.commoncriteriaportal.org.

The Common Criteria Recognition Arrangement logo printed on the certificate indicates that this certification is recognised under the terms of this agreement by the related bodies

Proclamation of the Bundesministerium des Innern of 12 February 2007 in the Bundesanzeiger dated 23 February 2007, p. 3730

of the signatory nations. A disclaimer beneath the logo indicates the specific scope of recognition.

This certificate is recognized according to the rules of CCRA-2014, i. e. up to and including CC part 3 EAL 2+ ALC_FLR components.

4. Performance of Evaluation and Certification

The certification body monitors each individual evaluation to ensure a uniform procedure, a uniform interpretation of the criteria and uniform ratings.

The product CONEXA 3.0, Version 1.1 has undergone the certification procedure at BSI. This is a re-certification based on BSI-DSZ-CC-0918-2020. Specific results from the evaluation process BSI-DSZ-CC-0918-2020 were re-used.

The evaluation of the product CONEXA 3.0, Version 1.1 was conducted by TÜV Informationstechnik GmbH. The evaluation was completed on 30 June 2021. TÜV Informationstechnik GmbH is an evaluation facility (ITSEF)⁵ recognised by the certification body of BSI.

For this certification procedure the sponsor and applicant is: Theben AG.

The product was developed by: Theben AG.

The certification is concluded with the comparability check and the production of this Certification Report. This work was completed by the BSI.

5. Validity of the Certification Result

This Certification Report applies only to the version of the product as indicated. The confirmed assurance package is valid on the condition that

- all stipulations regarding generation, configuration and operation, as given in the following report, are observed,
- the product is operated in the environment described, as specified in the following report and in the Security Target.

For the meaning of the assurance components and assurance levels please refer to CC itself. Detailed references are listed in part C of this report.

The Certificate issued confirms the assurance of the product claimed in the Security Target at the date of certification. As attack methods evolve over time, the resistance of the certified version of the product against new attack methods needs to be re-assessed. Therefore, the sponsor should apply for the certified product being monitored within the assurance continuity program of the BSI Certification Scheme (e.g. by a re-assessment or re-certification). Specifically, if results of the certification are used in subsequent evaluation and certification procedures, in a system integration process or if a user's risk management needs regularly updated results, it is recommended to perform a re-assessment on a regular e.g. annual basis.

In order to avoid an indefinite usage of the certificate when evolved attack methods would require a re-assessment of the products resistance to state of the art attack methods, the maximum validity of the certificate has been limited. The certificate issued on 1 July 2021 is valid until 30 June 2029. Validity can be re-newed by re-certification.

⁵ Information Technology Security Evaluation Facility

The owner of the certificate is obliged:

 when advertising the certificate or the fact of the product's certification, to refer to the Certification Report as well as to provide the Certification Report, the Security Target and user guidance documentation mentioned herein to any customer of the product for the application and usage of the certified product,

- 2. to inform the Certification Body at BSI immediately about vulnerabilities of the product that have been identified by the developer or any third party after issuance of the certificate.
- 3. to inform the Certification Body at BSI immediately in the case that security relevant changes in the evaluated life cycle, e.g. related to development and production sites or processes, occur, or the confidentiality of documentation and information related to the Target of Evaluation (TOE) or resulting from the evaluation and certification procedure where the certification of the product has assumed this confidentiality being maintained, is not given any longer. In particular, prior to the dissemination of confidential documentation and information related to the TOE or resulting from the evaluation and certification procedure that do not belong to the deliverables according to the Certification Report part B, or for those where no dissemination rules have been agreed on, to third parties, the Certification Body at BSI has to be informed.
- 4. to monitor the resistance of the certified product against new attack methods and to provide a qualified confirmation by applying for a re-certification or re-assessment process on a regular basis every two years starting from the issuance of the certificate.
- 5. to make sure that over the complete lifetime of the certificate a security module with a valid CC certificate is used.

In case of changes to the certified version of the product, the validity can be extended to the new versions and releases, provided the sponsor applies for assurance continuity (i.e. re-certification or maintenance) of the modified product, in accordance with the procedural requirements, and the evaluation does not reveal any security deficiencies.

6. Publication

The product CONEXA 3.0, Version 1.1 has been included in the BSI list of certified products, which is published regularly (see also Internet: https://www.bsi.bund.de and [5]). Further information can be obtained from BSI-Infoline +49 228 9582-111.

Further copies of this Certification Report can be requested from the developer⁶ of the product. The Certification Report may also be obtained in electronic form at the internet address stated above.

Theben AG
 Hohenbergstraße 32
 72401 Haigerloch

B. Certification Results

The following results represent a summary of

- the Security Target of the sponsor for the Target of Evaluation,
- the relevant evaluation results from the evaluation facility, and
- complementary notes and stipulations of the certification body.

1. Executive Summary

The Target of Evaluation (TOE) is the Smart Meter Gateway (SMGW) CONEXA 3.0, Version 1.1.

It is an electronic unit comprising hardware, software and firmware used for collection, storage and provision of meter data from one or more meters of one or multiple commodities.

The gateway connects a wide area network (WAN) with a network of devices of one or more smart metering devices (local metrological network, LMN) and the consumer home area network (HAN), which hosts controllable local systems (CLS).

The security functionality of the TOE comprises protection of confidentiality, authenticity, integrity of data and information flow control mainly to protect the privacy of consumers, to ensure a reliable billing process and to protect the Smart Metering System and a corresponding large scale infrastructure of the smart grid.

Besides a certified security module the hardware device also includes hard-wired communication adapters which both are not part of the TOE but which are always inseparable parts of the delivered entity.

The Security Target [6] is the basis for this certification. It is based on the certified Protection Profile for the Gateway of a Smart Metering System, Version 1.3, 31 March 2014, BSI-CC-PP-0073-2014 [8].

The TOE Security Assurance Requirements (SAR) are based entirely on the assurance components defined in Part 3 of the Common Criteria (see part C or [1], Part 3 for details). The TOE meets the assurance requirements of the Evaluation Assurance Level EAL 4 augmented by ALC_FLR.2, AVA_VAN.5.

The TOE Security Functional Requirements (SFR) relevant for the TOE are outlined in the Security Target [6], chapters 6.1 – 6.10. They are selected from Common Criteria Part 2 and one of them is newly defined. Thus the TOE is CC Part 2 extended.

The TOE Security Functional Requirements are implemented by the following TOE Security Functions:

TOE Security Functionality	Addressed issue	
SF.AU: Audit	The TOE maintains three kinds of logs: system log, consumer log, calibration log.	
	The purpose of the system log is to inform the gateway adminis (GWA) and the service technician about the system status of Meter Gateway. The consumer log informs authorized consumption about all information flows to the WAN, available processing probilling relevant and other meter data. Within the calibration log calibration relevant information is stored.	
SF.CR: Cryptography	The TOE implements the following cryptographic functions:	
	 TLS 1.2 protected connections between the TOE and entities in the WAN, LMN or HAN. 	
	 AES-CBC for encryption and decryption and AES-CMAC for integrity protection for unidirectional communication with wireless meters 	
	 CMS encryption, MAC protection and signature for meter data sended to the WAN 	

TOE Security Functionality	Addressed issue	
	AES-CBC for TSF and user data encryption	
SF.UD: User Data Protection	The TOE is attached to the three separated networks HAN, WAN and LMN. The interfaces to the different networks are physically separated. This TSF controls the access of all external entities in WAN, HAN and LMN to any information that is sent to, from or via the TOE or that is stored within the TOE.	
SF.IA: Identification & Authentication	Each user who communicates with the TOE or receives data from the TOE shall be identified and authenticated before any action on behalf of that user, including receiving of data sent from the gateway.	
SF.SM: Security Management	The TOE offers a set of functions to manage and configure the TSF. Those functions comprise management of devices in LMN and HAN, client management, maintenance of processing profiles, key- and certificate-management, firmware update, wake-up configuration, monitoring, resetting of the TOE (restart), audit log configuration.	
SF.PR: Privacy	This SF assures the privacy of the Consumer by ensuring that authorized external entities can only obtain data that is absolutely relevant for billing processes and the secure operation of the grid.	
SF.SP: Self-protection	The TOE provides a set of self-protection mechanisms that in particular comprises the self-test of the TOE, detection of replay and physical attacks and the failure with preservation of a secure state.	

Table 1: TOE Security Functionalities

For more details please refer to the Security Target [6], chapter 7.

The assets to be protected by the TOE are defined in the Security Target [6], chapter 3.2. Based on these assets the TOE Security Problem is defined in terms of Assumptions, Threats and Organisational Security Policies. This is outlined in the Security Target [6], chapter 3.3 - 3.5.

This certification covers the configurations of the TOE as outlined in chapter 8.

The vulnerability assessment results as stated within this certificate do not include a rating for those cryptographic algorithms and their implementation suitable for encryption and decryption (see BSIG Section 9, Para. 4, Clause 2).

The certification results only apply to the version of the product indicated in the certificate and on the condition that all the stipulations are kept as detailed in this Certification Report. This certificate is not an endorsement of the IT product by the Federal Office for Information Security (BSI) or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT product by BSI or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

2. Identification of the TOE

The Target of Evaluation (TOE) is called:

CONEXA 3.0, Version 1.1

The following table outlines the TOE deliverables:

No	Type	Identifier	Release	Form of Delivery
1	HW	CONEXA 3.0 Hardware	HW V01.00	Secure delivery process as described below table

No	Туре	Identifier	Release	Form of Delivery		
2	SW	CONEXA 3.0 Software	v3.40.0-cc	Pre-Installed on HW		
3	3 DOC	Handbuch CONEXA 3.0 für	Version 2.8.2	Download from https secured webpage		
		den Gateway Administrator [10]	SHA-256 Hash: 627793299a81877745fcfc766610d6703 ed8f3cd7fcaebc45f6ce3dfa3786bc3			
4	DOC	Handbuch CONEXA 3.0 für	Version 2.9	Download from https		
		den Service-Techniker [11]	SHA-256 Hash: a439e7d1a7372de518529540b9fd650b 0f7f9632bffc6ac3b8ac4fffe445ca82	secured webpage		
5	DOC	Handbuch CONEXA 3.0 für	Version 2.7.1	Download from https		
	den Letztverbraucher [12]		SHA-256 Hash: 01669c6de518d9b582378441dac92c72 e5597a0c3e28f28fac2cf39c336f2937	secured webpage		
6	DOC		Version 2.9	Download from https		
		Profilbeschreibungen [13]	SHA-256 Hash: ca52056d87762bcd1be772f14df49583c 58ad4614045112dd0ae0bee77f42e17	secured webpage		
7	DOC	COSEM HTTP-Webservice	Version 2.2	Download from https		
		[14]	SHA-256 Hash: 8abbabcaff546dbfc060d0100bd2fd6a5b 99988af99d9b97c759b22626dea8dd	secured webpage		
8	DOC	Conexa 3.0 Logmeldungen	Version 1.7.0	Download from https		
		[15]	SHA-256 Hash: 483af9a3b89be8ea76e2779e43ec7aa2 2ec8a12ba905ef864a2c1b4cca8488c5	secured webpage		
9	DOC		Version 1.4	Download from https		
		IF_GW_CON [16]	SHA-256 Hash: 26c821592d7245e29ce91fc25c5dacc0c 3310f2885fa9e1baff30d7e97103221	secured webpage		
10	DOC	1	Version 1.4	Download from https		
		IF_GW_SRV [17]	SHA-256 Hash: ec094d7ff046c387e921bfdd2d49443308 3030745cc22cdf20824dc5f5feab99	secured webpage		

Table 2: Deliverables of the TOE

The Smart Meter Gateways are delivered within a special and secure transport box (Pylocx Box) by a standard transportation service. The secure transport box can only be opened by authorized individuals by using a special key pad and a valid one time PIN. Due to the mandatory instructions of the developer it is not allowed to remove SMGW from the secure transport box outside a secure storage room (e.g. at the premise of the energy company) or at the place of installation at the consumers premise where it is installed by a service technician. All places where SMGW will be stored during the delivery need to provide a basic protection against possible attackers (e.g. concrete walls, doors need to be locked, and a physical inventory needs to be performed). Thereby it is ensured that no manipulation of the SMGW can take place on the complete track of delivery (starting with the manufacturer, through the different stages of storages to the final place of installation).

The TOE thereby consists of the main circuit board of the Smart Meter Gateway, the case and the seal. The correct hardware of the TOE can be identified by the identifier "HWV01.00", which can be found on a laser engraving on the TOE.

The firmware and software is pre-installed on the hardware and therefore also part of the physical delivery. It can be uniquely identified by all users by connecting to the TOE and using the commands described in the relevant guidance document.

The guidance documents mentioned in table 2 can be downloaded by a https secured website. The corresponding users can uniquely identified the guidance by checking the hash sum which is included in table 2 of this report and in the Security Target (which both are published on the website of the BSI).

3. Security Policy

The Security Policy is expressed by the set of Security Functional Requirements and implemented by the TOE. It covers the following issues:

Security audit, communication, cryptographic support, user data protection, identification and authentication, security management, privacy, protection of the TSF, trusted channels.

4. Assumptions and Clarification of Scope

The Assumptions defined in the Security Target and some aspects of Threats and Organisational Security Policies are not covered by the TOE itself. These aspects lead to specific security objectives to be fulfilled by the TOE-Environment. The following topics are of relevance:

- Trustworthy authorised and authenticated external entities
- Trustworthy and well-trained gateway administrators and service technicians
- Basic level of physical protection by installation in a non-public environment within the premises of the consumer
- Processing profiles are obtained from a trustworthy and reliable source only
- Usage of certified Security Module for specific cryptographic services
- Certification of firmware updates prior to installation in the SMGW
- Reliability and availability of WAN network connections, trustworthiness and availability of time sources, assumptions on LMN and HAN network connections
- Secure generation of ECC key pair and secure transmission to SMGW by the GWA

Details can be found in the Security Target [6], chapter 4.2.

5. Architectural Information

The TOE is subdivided into the following subsystems:

Hardware:

Includes the case of the SMGW, the seals and the electronic parts of the TOE and provides the physical basement as well as the passive physical protection for the TOE

OS:

Includes the underlying operating system and provides the filesystem encryption, firewall functionality and mandatory access control

SMPF:

Implements parts of the SMGW software and provides the functionality for system initialisation after the boot process, authentication of external entities, management of processing profiles and logging

Crypto:

Implements parts of the SMGW software and provides the cryptographic functions of the TOE and the interface to the Security Module

Services:

Implements parts of the SMGW software and provides the webserver for the requests send by the gateway administrator, service technician and consumer

WAN:

Implements parts of the SMGW software and provides the wake-up-service, the communication channels for the GWA and the external entities.

HAN:

Implements parts of the SMGW software and provides the communication channels to the external entities at the HAN interface

Calibration:

Implements parts of the SMGW software and provides the communication channels to the meters at the LMN interface as well as the processing of the received meter data

6. Documentation

The evaluated documentation as outlined in table 2 is being provided with the product to the customer. This documentation contains the required information for secure usage of the TOE in accordance with the Security Target.

Additional obligations and notes for secure usage of the TOE as outlined in chapter 10 of this report have to be followed.

7. IT Product Testing

7.1. TOE Test Configuration

All tests in the context of the evaluation have been conducted using multiple TOE samples in mainly two different configurations:

- Final TOE with factory setting (cmp. Table 2)
- Instrumentalised TOE with SSH access for TOE manipulations and for firewall tests on the TOE

7.2. Developer Testing

The developer's testing approach was to test the TSFI systematically next to a deeper consideration of TOE subsystems, internal interactions and concrete SFR tests.

The developer testing covered each TSFI, the case with its seals, the subsystem behaviour and interactions as well as all SFRs.

The actual test results of the developer tests matched the expected results. Therefore developer's testing effort demonstrated that the security functionality and TSFI perform as specified.

7.3. Independent Evaluator Testing

For the repetition of the developer tests the evaluation body chose to repeat a defined subset with the intent to cover the existing interfaces and the implemented security functionality in order to verify the correctness of the developer testing.

For the independent tests the evaluation body chose to broadly cover all existing TSFI, whereby the focus was set to the WAN interface.

The tests of the evaluation body are mainly performed on a stand-alone test equipment (Exceeding Solutions), containing approx. 3000 automated test cases in about 150 test suites developed by the lab, partitioned according to the SF established in the ST [6], Chapter 7. Using this environment, every necessary role with corresponding rights (Gateway Administrator, Service Technicians, Consumers and Meters) might be emulated at the appropriate interface.

The overall test result is that no deviations were found between the expected and the actual test results.

7.4. Penetration Testing

The evaluation body conducted penetration testing based on functional areas of concern derived from SFRs and architectural mechanisms.

The penetration testing activities were performed as tests and as analytical tasks. Whenever an analysis was estimated to yield better results, the evaluators chose the analytical approach. Analytical activities were especially applied in the areas secure boot, self-protection, domain separation, kernel and system hardening as well as non-bypassability. Combined approaches were also applied.

Furthermore, all differences between the certified SW version of the TOE during the baseline certification (BSI-DSZ-CC-0918) and the actual one under evaluation (BSI-DSZ-CC-0918-V2) were analysed by a detailed source code analyses discussed without further indication of potential vulnerabilities.

The overall test result is that no deviations were found between the expected and the actual test results. No attack scenario with the attack potential *High* was actually successful in the TOE's operational environment.

8. Evaluated Configuration

The TOE as identified in table 2 has been evaluated. There is only one configuration as the different variants of the communication adapters that are outside of the TOE scope run with the same HW and SW configuration of the TOE.

9. Results of the Evaluation

9.1. CC specific results

The Evaluation Technical Report (ETR) [7] was provided by the ITSEF according to the Common Criteria [1], the Methodology [2], the requirements of the Scheme [3] and all interpretations and guidelines of the Scheme (AIS) [4] as relevant for the TOE.

The Evaluation Methodology CEM [2] was used for those components up to EAL 5 extended by advice of the Certification Body for components beyond EAL 5 [4] (AIS 34) and guidance specific for the technology of the product [4] (AIS 46, AIS 48).

As a result of the evaluation the verdict PASS is confirmed for the following assurance components:

- All components of the EAL 4 package including the class ASE as defined in the CC (see also part C of this report)
- The components ALC FLR.2, AVA VAN.5 augmented for this TOE evaluation.

As the evaluation work performed for this certification procedure was carried out as a reevaluation based on the certificate BSI-DSZ-CC-0918-2020, re-use of specific evaluation tasks was possible. The changes to the basis evaluation are reported in [18]. The developer provided the evaluation body with a complete set of documentation. The evaluator also produces evaluation technical reports for all evaluation aspects. A complete list of all evaluation documents is given in Section 5.

In addition, the evaluation body used the Site Certification DSZ-CC-S-0176, therefore all work units inside the ALC SER significantly changed, with the exception of ALC_DEL, which was not covered by the Site Certification DSZ-CC-S-0176-2021.

The evaluation has confirmed:

- PP Conformance: Protection Profile for the Gateway of a Smart Metering System, Version 1.3, 31 March 2014, BSI-CC-PP-0073-2014 [8]
- for the Functionality: PP conformant Common Criteria Part 2 extended
- for the Assurance: Common Criteria Part 3 conformant

EAL 4 augmented by ALC FLR.2, AVA VAN.5

The results of the evaluation are only applicable to the TOE as defined in chapter 2 and the configuration as outlined in chapter 8 above.

9.2. Results of cryptographic assessment

The following table gives an overview of the cryptographic functionalities inside the TOE to enforce the security policy and outlines the standard of application where its specific appropriateness is stated.

Purpose	Cryptographic Mechanism	Standard of Implementation	Key Size in Bits	Standard of Application	Validity Period
TLS cipher suite (key establishment,	TLS_ECDHE_ ECDSA_WITH _AES_128_CB	Cipher Suite: [RFC 5289], [RFC 5246]	AES: 128bit, 256bit	TR03109-1 [18]	2026+

Purpose	Cryptographic Mechanism	Standard of Implementation	Key Size in Bits	Standard of Application	Validity Period
record layer encryption and integrity, peer authentication)	C_SHA256, TLS_ECDHE_ ECDSA_WITH _AES_256_CB C_SHA384, TLS_ECDHE_ ECDSA_WITH _AES_128_GC M_SHA256, TLS_ECDHE_ ECDSA_WITH _AES_256_GC M_SHA384	AES: [FIPS 197] CBC: [NIST SP800-38A] HMAC: [RFC 2104] GCM: [NIST SP800-38D] brainpoolPxxxr1: [RFC 5639] secpxxxr1: [RFC 5114] SHA: [FIPS 180-4]	EC: secp256r1, secp384r1, brainpoolP256r1, brainpoolP384r1, brainpoolP512r1		
Key generation for CMS containers	Key generation: ECKA-EG Key wrap: id-aes128- wrap	Key generation: [TR 03111] Key wrap: [RFC 3394]	128bit	TR03109-1 [18]	2026+
Encryption / decryption /integrity of CMS container	id-aes128- gcm, id-aes-CBC- CMAC-128	AES: [FIPS 197] GCM: [RFC 5084], [NIST SP800-38D] CMAC: [RFC 4493] CBC: [NIST SP800-38A]	128bit	TR03109-1 [18]	2026+
Key generation for meter data	AES-CMAC	AES: [FIPS 197] AES-CMAC: [RFC 4493]	128bit	TR03109-1 [18]	2026+
Encryption/ decryption, integrity of meter data	Encryption: AES-CBC Integrity protection: AES-CMAC	AES: [FIPS 197] CBC: [NIST SP800-38A] AES-CMAC: [RFC 4493]	128bit	TR03109-1 [18]	2026+
Hashing for signatures	SHA-256, SHA-384, SHA-512	SHA: [FIPS 180-4]	_	TR-02102-1 [20]	2026+

Purpose	Cryptographic Mechanism	Standard of Implementation	Key Size in Bits	Standard of Application	Validity Period
Encryption / decryption, integrity of TSFI	AES-128-CBC ESSIV:SHA25 6	AES: [FIPS 197] CBC: [NIST SP800-38A] SHA:	128bit	TR-02102-1 [20]	2026+
		FIPS 180-4]			

Table 3: TOE cryptographic functionality

The strength of the these cryptographic algorithms was not rated in the course of this certification procedure (see BSIG Section 9, Para. 4, Clause 2).

According to R-03109-3 [19] or TR-02102-1 [20], respectively, the algorithms are suitable for Smart Metering Systems.

10. Obligations and Notes for the Usage of the TOE

The documents as outlined in table 2 contain necessary information about the usage of the TOE and all security hints therein have to be considered. In addition all aspects of Assumptions, Threats and OSPs as outlined in the Security Target not covered by the TOE itself need to be fulfilled by the operational environment of the TOE.

The customer or user of the product shall consider the results of the certification within his system risk management process. In order for the evolution of attack methods and techniques to be covered, he should define the period of time until a re-assessment of the TOE is required and thus requested from the sponsor of the certificate.

The limited validity for the usage of cryptographic algorithms as outlined in chapter 9 has to be considered by the user and his system risk management process, too.

If available, certified updates of the TOE should be used. If non-certified updates or patches are available the user of the TOE should request the sponsor to provide a recertification. In the meantime a risk management process of the system using the TOE should investigate and decide on the usage of not yet certified updates and patches or take additional measures in order to maintain system security.

11. Security Target

For the purpose of publishing, the Security Target [6] of the Target of Evaluation (TOE) is provided within a separate document as Annex A of this report.

12. Definitions

12.1. Acronyms

AIS Application Notes and Interpretations of the Scheme

BSI Bundesamt für Sicherheit in der Informationstechnik / Federal Office for

Information Security, Bonn, Germany

BSIG BSI-Gesetz / Act on the Federal Office for Information Security

CCRA Common Criteria Recognition ArrangementCC Common Criteria for IT Security Evaluation

CEM Common Methodology for Information Technology Security Evaluation

CLS Controllable Local Systems

CMS Cryptographic Message Syntax

EAL Evaluation Assurance Level
EMA Electro-Magnetic Analysis
ETR Evaluation Technical Report

GWA Gateway Administrator

HAN Home Area Network

HTTP Hypertext Transfer Protocol

HTTPS Hypertext Transfer Protocol Secure

IP Internet Protocol

IT Information Technology

ITSEF Information Technology Security Evaluation Facility

LMN Local Metrological Network

MAC Message Authentication Code

NTP Network Time Protocol

PP Protection Profile

SAR Security Assurance Requirement

SF Security Function

SFP Security Function Policy

SFR Security Functional Requirement

SMGW Smart Meter Gateway

SMPF Smart Metering Platform Framework

ST Security Target

TOE Target of Evaluation

TSF TOE Security Functionality

WAN Wide Area Network

12.2. Glossary

Augmentation - The addition of one or more requirement(s) to a package.

Collaborative Protection Profile - A Protection Profile collaboratively developed by an International Technical Community endorsed by the Management Committee.

Extension - The addition to an ST or PP of functional requirements not contained in CC part 2 and/or assurance requirements not contained in CC part 3.

Formal - Expressed in a restricted syntax language with defined semantics based on well-established mathematical concepts.

Informal - Expressed in natural language.

Object - A passive entity in the TOE, that contains or receives information, and upon which subjects perform operations.

Package - named set of either security functional or security assurance requirements

Protection Profile - A formal document defined in CC, expressing an implementation independent set of security requirements for a category of IT Products that meet specific consumer needs.

Security Target - An implementation-dependent statement of security needs for a specific identified TOE.

Semiformal - Expressed in a restricted syntax language with defined semantics.

Subject - An active entity in the TOE that performs operations on objects.

Target of Evaluation - An IT Product and its associated administrator and user guidance documentation that is the subject of an Evaluation.

TOE Security Functionality - Combined functionality of all hardware, software, and firmware of a TOE that must be relied upon for the correct enforcement of the SFRs.

13. Bibliography

- [1] Common Criteria for Information Technology Security Evaluation, Version 3.1, Part 1: Introduction and general model, Revision 5, April 2017 Part 2: Security functional components, Revision 5, April 2017 Part 3: Security assurance components, Revision 5, April 2017 https://www.commoncriteriaportal.org
- [2] Common Methodology for Information Technology Security Evaluation (CEM), Evaluation Methodology, Version 3.1, Rev. 5, April 2017, https://www.commoncriteriaportal.org
- [3] BSI certification: Scheme documentation describing the certification process (CC-Produkte) and Scheme documentation on requirements for the Evaluation Facility, approval and licencing (CC-Stellen), https://www.bsi.bund.de/zertifizierung
- [4] Application Notes and Interpretations of the Scheme (AIS) as relevant for the TOE⁷ https://www.bsi.bund.de/AIS
- [5] German IT Security Certificates (BSI 7148), periodically updated list published also on the BSI Website, https://www.bsi.bund.de/zertifizierungsreporte
- [6] Security Target BSI-DSZ-CC-0918-V2-2021, Version 1.91.1, 01.06.2021, CONEXA 3.0 Security Target, Theben AG

⁷specifically

- AIS 34, Version 3, Evaluation Methodology for CC Assurance Classes for EAL 5+ (CCv2.3 & CCv3.1) and EAL 6 (CCv3.1)
- AIS 46, Version 3, Informationen zur Evaluierung von kryptographischen Algorithmen und ergänzende Hinweise für die Evaluierung von Zufallszahlengeneratoren
- AIS 48, Version 1.0, Anforderungen an die Prüfung von Sicherheitsetiketten

[7] Evaluation Technical Report, Version 2, 28.06.2021, ETR Summary V2 – CONEXA 1.1, TÜV Informationstechnik GmbH, (confidential document)

- [8] Protection Profile for the Gateway of a Smart Metering System, Version 1.3, 31 March 2014, BSI-CC-PP-0073-2014
- [9] Configuration list for the TOE, Version 1.1, 09.06.2021, ALC_CMS.4 Konfigurationsliste Smart Meter Gateway CONEXA 3.0 (confidential document)
- [10] Handbuch CONEXA 3.0 für den Gateway Administrator, Version 2.8.2, 20.05.2021 Theben AG
- [11] Handbuch CONEXA 3.0 für den Service-Techniker, Version 2.9, 20.05.2021, Theben AG
- [12] Handbuch CONEXA 3.0 für den Letztverbraucher, Version 2.7.1, 12.04.2021, Theben AG
- [13] Conexa 3.0 Profilbeschreibungen, Version 2.9, 24.03.2021, Theben AG
- [14] COSEM HTTP-Webservice, Version 2.2, 27 March 2020, Theben AG
- [15] Conexa 3.0 Logmeldungen, Version 1.7.0, 13.04.2021, Theben AG
- [16] Schnittstellenbeschreibung IF_GW_CON, Version 1.4, 04 April 2020, Theben AG
- [17] Schnittstellenbeschreibung IF_GW_SRV, Version 1.4, 04 April 2020, Theben AG
- [18] Impact Analysis Report Release 1, Version 1.0, 12.05.2021, Theben AG (confidential document)
- [19] Technische Richtlinie BSI TR-03109-1 Anforderungen an die Interoperabilität der Kommunikationseinheit eines intelligenten Messsystems, Version 1.0, 18 March 2013, Federal Office for Information Security
- [20] Technische Richtlinie TR-03109-3 Kryptographische Vorgaben für die Infrastruktur von intelligenten Messsystemen, Version 1.1, 17 April 2014, Federal Office for Information Security
- [21] Technische Richtlinie BSI TR-02102-1 Kryptographische Verfahren: Empfehlungen und Schlüssellängen, Version 2020-01, 04 March 2020, Federal Office for Information Security
- [22] Standard of Implementation:
 - BSI TR-03111, Elliptic Curve Cryptography (ECC), Version 2.10, 2018
 - [FIPS 180-4] NIST FIPS PUB 180-4: Secure Hash Standard (SHS). NIST, 2015.
 - [FIPS 197] NIST FIPS PUB 197: Announcing the ADVANCED ENCRYPTION STANDARD (AES). NIST, 2001.
 - [NIST SP800-38A] NIST SP800-38A: Recommendation for Block Cipher Modes of Operation: Methods and Techniques. NIST, 2001.
 - [NIST SP800-38B] NIST SP800-38B: Recommendation for Block Cipher Modes of Operation: The CMAC Mode for Authentication. NIST, 2005.
 - [NIST SP800-38D] NIST SP800-38D: Recommendation for Block Cipher Modes of Operation: Galois/Counter Mode (GCM) and GMAC. NIST, 2007.
 - [RFC 2104] Network Working Group RFC 2104, H. Krawczyk et al.: HMAC: Keyed-Hashing for Message Authentication. Network Working Group, Feb. 1997.

[RFC 3394] IETF RFC 3394, J. Schaad, R. Housley: Advanced Encryption Standard(AES) Key Wrap Algorithm. IETF, 2002.

[RFC 4493] IETF RFC 4493, J. H. Song, J. Lee, T. Iwata: The AES-CMAC-Algorithm. IETF, 2006.

[RFC 5084] IETF RFC 5084, R. Housley: Using AES-CCM and AES-GCM Authenticated Encryption in the Cryptographic Message Syntax (CMS). IETF, 2007.

[RFC 5114] IETF RFC 5114, M. Lepinski, S. Kent: Additional Diffie-Hellman Groups for Use with IETFStandards, 2008

[RFC5246] RFC 5246 - The Transport Layer Security (TLS) Protocol, Version 1.2, Dierks & Rescorla - Standard Track, August 2008

[RFC 5289] IETF RFC 5289, E. Rescorla: TLS Elliptic Curve Cipher Suites with SHA-256/384 and AES Galois Counter Mode (GCM). IETF, 2008.

[RFC 5639] IETF RFC 5639, M. Lochter, J. Merkle: Elliptic Curve Cryptography(ECC) Brainpool Standard Curves and Curve Generation. IETF, 2010.

C. Excerpts from the Criteria

For the meaning of the assurance components and levels the following references to the Common Criteria can be followed:

- On conformance claim definitions and descriptions refer to CC part 1 chapter 10.5
- On the concept of assurance classes, families and components refer to CC Part 3 chapter 7.1
- On the concept and definition of pre-defined assurance packages (EAL) refer to CC Part 3 chapters 7.2 and 8
- On the assurance class ASE for Security Target evaluation refer to CC Part 3 chapter 12
- On the detailed definitions of the assurance components for the TOE evaluation refer to CC Part 3 chapters 13 to 17
- The table in CC part 3 , Annex E summarizes the relationship between the evaluation assurance levels (EAL) and the assurance classes, families and components.

The CC are published at https://www.commoncriteriaportal.org/cc/

D. Annexes

List of annexes of this certification report

Annex A: Security Target provided within a separate document.