



# **Certification Report**

Buheita Fujiwara, Chairman Information-technology Promotion Agency, Japan

# **Target of Evaluation**

inger of hvaluation	
Application date/ID	2007-07-09 (ITC-7160)
Certification No.	C0118
Sponsor	Konica Minolta Business Technologies, Inc.
Name of TOE	Japan: bizhub PRO C5500 / ineo+5500 Gazou
	Seigyo Program
	Overseas: bizhub PRO C5500 / ineo+5500
	Image Control Program
Version of TOE	A0E70Y0-00I1-G00-10
PP Conformance	None
Conformed Claim	EAL3
Developer	Konica Minolta Business Technologies, Inc.
Evaluation Facility	Mizuho Information & Research Institute, Inc.
	Center for Evaluation of Information Security

This is to report that the evaluation result for the above TOE is certified as follows.

2007-09-27

Haruki Tabuchi, Technical Manager Information Security Certification Office IT Security Center

**Evaluation Criteria, etc.:** This TOE is evaluated in accordance with the following criteria prescribed in the "IT Security Evaluation and Certification Scheme".

- Common Criteria for Information Technology Security Evaluation Version 2.3 (ISO/IEC 15408:2005)
- Common Methodology for Information Technology Security Evaluation Version 2.3 (ISO/IEC 18045:2005)

#### Evaluation Result: Pass

"Japan: bizhub PRO C5500 / ineo+5500 Gazou Seigyo Program, Overseas: bizhub PRO C5500 / ineo+5500 Image Control Program, version: A0E70Y0-00I1-G00-10" has been evaluated in accordance with the provision of the "IT Security Certification Procedure" by Information-technology Promotion Agency, Japan, and has met the specified assurance requirements.

Notice:

This document is the English translation version of the Certification Report published by the Certification Body of Japan Information Technology Security Evaluation and Certification Scheme.

# Table of Contents

1. Executive Summary	1
1.1 Introduction	1
1.2 Evaluated Product	1
1.2.1 Name of Product	1
1.2.2 Product Overview	1
1.2.3 Scope of TOE and Overview of Operation	2
1.2.4 TOE Functionality	3
1.3 Conduct of Evaluation	5
1.4 Certification	6
1.5 Overview of Report	6
1.5.1 PP Conformance	6
1.5.2 EAL	6
1.5.3 SOF	6
1.5.4 Security Functions	6
1.5.5 Threat	9
1.5.6 Organizational Security Policy	9
1.5.7 Configuration Requirements	9
1.5.8 Assumptions for Operational Environment	10
1.5.9 Documents Attached to Product	10
2. Conduct and Results of Evaluation by Evaluation Facility	12
2.1 Evaluation Methods	12
2.2 Overview of Evaluation Conducted	12
2.3 Product Testing	12
2.3.1 Developer Testing	12
2.3.2 Evaluator Testing	
2.4 Evaluation Result	15
3. Conduct of Certification	16
4. Conclusion	
4.1 Certification Result	
4.2 Recommendations	17
5. Glossary	
6. Bibliography	20

# 1. Executive Summary

# 1.1 Introduction

This Certification Report describes the content of certification result in relation to IT Security Evaluation of "Japan: bizhub PRO C5500 / ineo+5500 Gazou Seigyo Program, Overseas: bizhub PRO C5500 / ineo+5500 Image Control Program, version: A0E70Y0-00I1-G00-10" (hereinafter referred to as "the TOE") conducted by Mizuho Information & Research Institute, Inc. Center for Evaluation of Information Security (hereinafter referred to as "Evaluation Facility"), and it reports to the sponsor, Konica Minolta Business Technologies, Inc.

The reader of the Certification Report is advised to read the corresponding ST and manuals (please refer to "1.5.9 Documents Attached to Product" for further details) attached to the TOE together with this report. The assumed environment, corresponding security objectives, security functional and assurance requirements needed for its implementation and their summary specifications are specifically described in ST. The operational conditions and functional specifications are also described in the document attached to the TOE.

Note that the Certification Report presents the certification result based on assurance requirements conformed to the TOE, and does not certify individual IT product itself.

Note: In this Certification Report, IT Security Evaluation Criteria and IT Security Evaluation Method prescribed by IT Security Evaluation and Certification Scheme are named CC and CEM, respectively.

#### 1.2 Evaluated Product

#### 1.2.1 Name of Product

The target product	t by this Certificate is as follows:
Name of Product	Japan: bizhub PRO C5500 / ineo+5500 Gazou Seigyo Program
	Overseas: bizhub PRO C5500 / ineo+5500 Image Control Program
Version:	A0E70Y0-00I1-G00-10
Developer:	Konica Minolta Business Technologies, Inc.

#### 1.2.2 Product Overview

This product (Hereinafter referred to as "bizhub PRO C5500 Image Control Program"\*1), that is installed on digital MFP (Hereinafter referred to as "bizhub PRO C5500 Series") manufactured by Konica Minolta Business Technologies, Inc., is a software product for the purpose of reducing the risk for disclosure of document data in bizhub PRO C5500 Series.

bizhub PRO C5500 Image Control Program prevents document data in bizhub PRO C5500 Series from disclosing during the use of functions such as copier and printer. It offers the protective function\*2 with password lock system against the risk of reading

<sup>\*1:</sup> shows "bizhub PRO C5500 / ineo+5500 Gazou Seigyo Program" for Japan and "bizhub PRO C5500 / ineo+5500 Image Control Program" for overseas.

<sup>\*2:</sup> HDD has the password so that it cannot be removed and read in another equipment. HDD lock password is set in the HDD lock function.

data out illegally from HDD (Hard Disk Drive) which is a medium for storing temporarily document data.

Figure 1-1 shows the expected operating environment with bizhub PRO 5500 Series in office.




Figure 1-1 Operating Environment of bizhub PRO C5500 Series

bizhub PRO C5500 Series including the TOE is connected with an internal network and a public telephone line network as shown in Figure 1-1. When an external network is connected, it is connected through a firewall in order to protect each of equipments in the internal network.

# 1.2.3 Scope of TOE and Overview of Operation

Figure 1-2 shows the structure of bizhub PRO C5500 Series including the TOE.




Figure 1-2 TOE Structure

bizhub PRO C5500 Series consists of hardware, OS and bizhub PRO C5500 Image Control Program. The hardware includes bizhub PRO C5500 Series main unit, DRAM/HDD section, operation panel, network card, and various interfaces. The HDD is an optional unit (not equipped as standard). The DRAM/HDD section stores temporarily document data. The DRAM is not accessed from outside and the temporary stored data in DRAM is deleted by turning the power off. bizhub PRO C5500 Image Control Program operates on OS.

The hatching parts in Figure 1-2 show the control range of TOE, namely, each function provided by the TOE and the storage area of document data controlled by the TOE.

# 1.2.4 TOE Functionality

The TOE consists of "basic function" that executes copying/printing/scanning of document data, "management function" that sets the TOE by the administrator, and "CE function" that executes the initial setting of TOE (Administrator registration and TOE installation) by the CE \*3.

# 1.2.4.1 Basic function of TOE

Basic functions are scan function and print function. By these functions combination, copy function, printer function and scanner function are provided for the user.

In copy function, the document data (digitized data) scanned from paper document is

<sup>\*3</sup> Customer Engineer: belongs to the company undertaken to maintain bizhub PRO C5500 Series, and executes maintenance of bizhub PRO 5500 Series.

once stored into the temporary storage area of DRAM/HDD and then printing is performed after reading out from there. In printer function, the document data from client PC is converted by the external print controller and is entered to bizhub PRO C5500 Series. It is once stored into the temporary storage area of DRAM/HDD and then printing is performed after reading out from there. The document data stored into the temporary storage DRAM is deleted by turning the power off. In scanner function, the digitized data scanned from paper document is transmitted to the external print controller without temporarily storing. Figure 1-3 shows the processing overview of basic functions.




Figure 1-3 Processing Architecture of Basic Function

The following shows user functions and basic functions provided for the user.

No	User function	Basic function
1	Copy function	Scan function and Print function
2	Printer function	Print function
3	Scanner function	Scan function

The followings are the details of each basic function.

(1) Scan function

The information of paper document that is requested through the operation panel by general user, is scanned and converted to digitized data. It is stored on the temporary storage area in copy function, and is directly transmitted to the external print controller in scan function.

#### (2) Print function

The document data stored on the temporary storage DRAM/HDD is printed out.

# 1.2.4.2 Management function

The administrator uses management function to execute administrator password change, security strengthen mode setting<sup>\*</sup>4, TOE network information setting and operation setting of functions provided by the TOE. In addition, management function controls information related to operation of digital MFP, such as printing audit information, controlling the number of prints, troubleshooting, and checking toner shortage.

# 1.2.4.3 CE function

The following functions are provided so that the CE can execute the initial setting and the maintenance for the TOE.

- Service setting mode

The CE executes registration and change of administrator password through the operation panel.

- CSRS (CS Remote Care)

The CE gets information for the hardware maintenance such as the number of prints, jam frequency, and toner shortage through a computer connected to public line network or Internet.

# 1.3 Conduct of Evaluation

Based on the IT Security Evaluation/Certification Program operated by the Certification Body, TOE functionality and its assurance requirements are being evaluated by evaluation facility in accordance with those publicized documents such as "IT Security Evaluation and Certification Scheme"[2], "IT Security Certification Procedure"[3] and "Evaluation Facility Approval Procedure"[4].

Scope of the evaluation is as follow.

- Security design of the TOE shall be adequate;
- Security functions of the TOE shall be satisfied with security functional requirements described in the security design;
- This TOE shall be developed in accordance with the basic security design;
- Above mentioned three items shall be evaluated in accordance with the CC Part 3 and CEM.

More specific, the evaluation facility examined "Multi functional printer (digital copier) bizhub PRO C5500 / ineo<sup>+</sup> 5500 Series Version 2" as the basis design of security functions for the TOE (hereinafter referred to as "the ST")[1], the evaluation deliverables in relation to development of the TOE and the development, manufacturing and shipping sites of the TOE. The evaluation facility evaluated if the TOE is satisfied both Annex B of CC Part 1 (either of [5], [8] or [11]) and Functional Requirements of CC Part 2 (either of [6], [9] or [12]) and also evaluated if the development, manufacturing and shipping environments for the TOE is also satisfied with Assurance Requirements of CC Part 3 (either of [7], [10] or [13]) as its rationale. Such evaluation procedure and its result are presented in "Multi functional printer (digital copier) bizhub PRO C5500 / ineo<sup>+</sup> 5500 Series Evaluation Technical Report"

<sup>\*4</sup> Security strengthen mode is enabled so as to make functions provided by the TOE more secure condition. In a state of effective security strengthen mode, HDD lock password is set not to be read/written data. At the time of bizhub PRO C5500 Series power on, the TOE commands HDD to authenticate and unlock by using the lock password. The HDD confirms to be the valid TOE and unlocks so as to make reading/writing data possible.

(hereinafter referred to as "the Evaluation Technical Report") [17]. Further, evaluation methodology should comply with the CEM (either of [14], [15] or [16]).

# 1.4 Certification

The Certification Body verifies the Evaluation Technical Report prepared by the evaluation facility and evaluation evidence materials, and confirmed that the TOE evaluation is conducted in accordance with the prescribed procedure. Certification review is also prepared for those concerns found in the certification process. Evaluation is completed with the Evaluation Technical Report dated 2007-09 submitted by the evaluation facility and those problems pointed out by the Certification Body are fully resolved and confirmed that the TOE evaluation is appropriately conducted in accordance with CC and CEM. The Certification Body prepared this Certification Report based on the Evaluation Technical Report submitted by the evaluation facility and concluded fully certification activities.

# 1.5 Overview of Report

# 1.5.1 PP Conformance

There is no PP to be conformed.

# 1.5.2 EAL

Evaluation Assurance Level of TOE defined by this ST is EAL3 conformance.

#### 1.5.3 SOF

This ST claims "SOF-basic" as its minimum strength of function.

This TOE assumes the attack capability of attacker to be low level. It assumes to be operated under the condition secured adequate security in terms of physical and human aspect. Therefore, the security strength satisfies SOF-Basic that is able to resist sufficiently the attack from the threat agent with low level attack capability.

#### 1.5.4 Security Functions

Security functions of the TOE are as follow.

# (1) Identification and authentication.

Function title	Specification of security function	
IA.ADM_ADD	IA.ADM_ADD registers the administrator in the	
Administrator	TOE. Only the CE operates IA.ADM_ADD. The CE	
registration	registers the administrator password.	
	IA.ADM_ADD provides an interface for	

	<ul> <li>administrator registration. The administrator registration interface requests password entry for registering the administrator.</li> <li>For the password entered by the administrator, the permitted value is verified according to the following rules.</li> <li>A password shall be 8 characters.</li> <li>A password shall be composed of alphabetic capital letters, small letters, and numerals. (All is one-byte characters.)</li> <li>A password shall not be identical to the previous password used.</li> <li>In the verification of permitted value, the previous password used.</li> </ul>
	administrator is registered if the rules are obeyed,
IA.ADM_AUTH	and it is rejected if not so. Before the operator can use the TOE,
Administrator	Before the operator can use the TOE, IA.ADM_AUTH identifies that he/she is the
identification and	registered administrator in the TOE and
authentication	authenticates that he/she is the administrator.
	<ul> <li>IA.ADM_AUTH does not permit any operation of the management functions before identification and authentication of the administrator. The interface for administrator identification and authentication requests to enter the password registered by IA.ADM_ADD and the password changed by IA.PASS. IA.ADM_AUTH identifies that he/she is the administrator through the interface display for administrator identification and authentication, and it authenticates that he/she is the administrator by the entered password. When the administrator enters the password, dummy characters (*) are displayed instead of the entered password.</li> <li>When the authentication is unsuccessful, the interface for administrator identification and authentification and authentication and authentication is provided after five seconds.</li> </ul>
IA.CE_AUTH	Before the operator can use the TOE, IA.CE_AUTH
CE identification	identifies that he/she is the registered CE in the

and authentication	TOE and authenticates that he/she is the CE.
	IA.CE_AUTH does not permit any operate of the CE functions before identification and authentication of the CE. It requests to enter the password changed by IA.PASS. IA.CE_AUTH identifies that he/she is the CE through the interface display for CE identification and authentication, and it authenticates that he/she is the CE by the entered password. When the CE enters the password, dummy characters (*) are displayed instead of the entered password.
	When the authentication is unsuccessful, the interface for CE identification and authentication is provided after five seconds.
IA.PASS	IA.PASS changes the administrator password or CE
Password change	password that is the authentication information for administrator or CE.
	<ul> <li>IA.PASS provides an interface for password change and requests to enter a new password.</li> <li>The following shows the password available to change depending on the type of user.</li> <li>CE : CE password, Administrator password</li> <li>Administrator : Administrator password</li> <li>For the password entered by the product-related persons, the permitted value is verified according to the following rules.</li> <li>A password shall be 8 characters.</li> <li>A password shall be composed of alphabetic capital letters, small letters, and numerals. (All is one-byte characters.)</li> <li>A password shall not be identical to the previous password used.</li> <li>In the verification of permitted value, the password is changed if the rules are obeyed.</li> </ul>

Function title	Specification of security function
MNG.MODE	MNG.MODE permits and executes only for the
Setting of security	administrator to enable or disable the security
strengthen mode	strengthen mode.
MNG.HDD	MNG.HDD permits and executes only for the
HDD lock password	administrator the following processing.
function	- Change of HDD lock password
	For the HDD lock password entered by the
	administrator, the permitted value is verified
	according to the following rules.
	- A password shall be 8 to 32 characters.
	- A password shall be composed of alphabetic capital
	letters, small letters, and numerals. (All is
	one-byte characters.)
	In the verification of permitted value, the HDD lock
	password is set or changed in the HDD device if the
	rules are obeyed, and the change is rejected if not
	so.

# 1.5.5 Threat

This TOE assumes such threats presented in Table 1-1 and provides functions for countermeasure to them.

Table	1-1	Assumed	Threats
-------	-----	---------	---------

Identifier	Threat
T.HDDACCESS	When a general user changes the setting on
(Unauthorized access	security strengthen mode and connects the HDD
to the HDD)	with an illegal device, the document data is read
	out.

# 1.5.6 Organizational Security Policy

There is no required security policy of the organization upon use of the TOE.

# 1.5.7 Configuration Requirements

The TOE is a software product installed on bizhub PRO C5500 Series. The TOE is installed as a security function at time of bizhub PRO C5500 Series.

# 1.5.8 Assumptions for Operational Environment

Assumptions required in environment using this TOE presents in the Table 1-2. The effective performance of the TOE security functions are not assured unless these preconditions are satisfied.

Identifier	Assumptions
ASM.SECMOD (Operating setting condition for the security strengthen mode)	<ul> <li>The administrator enables the security strengthen mode.</li> <li>bizhub PRO C5500 Series mounts an optional HDD.</li> </ul>
ASM.NET (Setting condition for the internal network)	- When the internal network with bizhub PRO C5500 Series including the TOE is connected to the external network, bizhub PRO C5500 Series cannot be accessed by the external network.
ASM.ADMIN (Reliable administrator)	- The administrator shall not carry out an illegal act.
ASM.CE (Personal condition for the CE)	- The CE shall not carry out an illegal act.
ASM.SECRET (Operational condition on the confidential information)	<ul> <li>When the TOE is used, the administrator password and HDD lock password shall not be disclosed by the administrator.</li> <li>The CE password shall not be disclosed by the CE.</li> </ul>

#### Table 1-2 Assumptions in Use of the TOE

#### 1.5.9 Documents Attached to Product

Documents attached to the TOE are listed below.

#### · Japanese version

<Manuals for CE>

- bizhub PRO C5500 Installation Manual A0E7956000
- bizhub PRO C6500 / C6500P / C5500 Service Manual Field Service CCA0E7-M-FJ2-0000

<Manuals for Administrator>

- bizhub PRO C5500 User's Guide Copier A0E7955000
- bizhub PRO C5500 User's Guide POD Administrator's Reference A0E7957000
- bizhub PRO C5500 User's Guide Security A0E7955500
- $\cdot$  Overseas version

<Manuals for CE>

- bizhub PRO C5500 INSTALLATION MANUAL A0E7956200
- bizhub PRO C6500 / C6500P / C5500 SERVICE MANUAL Field Service CCA0E7-M-FE2-0000
- COLOR MFP 55ppm INSTALLATION MANUAL A0E7956300

<Manuals for Administrator>

- bizhub PRO C5500 User's Guide Copier A0E7955100
- bizhub PRO C5500 User's Guide POD Administrator's Reference A0E7957100
- bizhub PRO C5500 User's Guide Security A0E7955600
  ineo+5500 User's Guide [Copier] A0E7959500
- ineo+5500 User's Guide [POD Administrator's Reference] A0E7959700
- ineo+5500 User's Guide [Security] A0E7959600

# 2. Conduct and Results of Evaluation by Evaluation Facility

# 2.1 Evaluation Methods

Evaluation was conducted by using the evaluation methods prescribed in CEM in accordance with the assurance requirements in CC Part 3. Details for evaluation activities are report in the Evaluation Technical Report. It described the description of overview of the TOE, and the contents and verdict evaluated by each work unit prescribed in CEM.

# 2.2 Overview of Evaluation Conducted

The history of evaluation conducted was present in the Evaluation Technical Report as follows.

Evaluation has started on 2007-07 and concluded by completion the Evaluation Technical Report dated 2007-09. The evaluation facility received a full set of evaluation deliverables necessary for evaluation provided by developer, and examined the evidences in relation to a series of evaluation conducted. Additionally, the evaluation facility directly visited the development and manufacturing sites on 2007-08 and examined procedural status conducted in relation to each work unit for configuration management, delivery and operation and lifecycle by investigating records and staff hearing. Further, the evaluation facility executed sampling check of conducted testing by developer and evaluator testing by using developer testing environment at developer site on 2007-08.

Concerns found in evaluation activities for each work unit were all issued as Observation Report and were reported to developer. These concerns were reviewed by developer and all problems were solved eventually.

As for concerns indicated during evaluation process by the Certification Body, the certification review was sent to the evaluation facility. These were reflected to evaluation after investigation conducted by the evaluation facility and the developer.

#### 2.3 Product Testing

Overview of developer testing evaluated by evaluator and evaluator testing conducted by evaluator are as follows.

#### 2.3.1 Developer Testing

 Developer Test Environment Test configuration performed by the developer is showed in the Figure 2-1.

# CRP-C0118-01




Figure 2-1 Configuration of Developer Testing

2) Outlining of Developer Testing

Outlining of the testing performed by the developer is as follow.

a. Test configuration

Test configuration performed by the developer is showed in the Figure 2-1. Developer testing was performed at the same TOE testing environment with the TOE configuration identified in ST.

- Test machine bizhub PRO C5500 / ineo+5500 More than one unit is prepared for a part of test.
- Test environment

Network: Connected to Ethernet environment (10Base-T) Client PC: WindowsXP (Japanese version/English version) Application: Internet Explorer (Ver.6) Mail server: Connected to internal network Print controller: IC-408 (built-in type) (Print controller is not essential because it does not relate to this test.)

#### b. Testing Approach

For the testing, following approach was used.

- 1. The operation of security functions is confirmed by the operation of TSFI.
- 2. If testing of TSFI and subsystem interface cannot be performed by the operation through the external interface directly connected to bizhub PRO C5500 Series, it is performed with methods by indirectly stimulating the interface.
- 3. For the observation of test behavior, the direct confirmation is performed if it can be confirmed by the external TSFI, the behavior of test results is confirmed by using a measuring equipment if it can not be observed.

- 4. By comparing the expected behavior with the actual test results obtained at test execution, whether the test objects are achieved or not, are determined.
- c. Scope of Testing Performed

Testing is performed 22 items by the developer.

The coverage analysis is conducted and it is verified that all the security functions and external interfaces stipulated in the function specifications are satisfactorily tested. The depth analysis is conducted and it is verified that all the subsystems and subsystem interfaces stipulated in the high level design are satisfactorily tested.


d. Result


The evaluator confirmed consistencies between the expected test results and the actual test results provided by the developer. The evaluator confirmed the execution method of the developer test and the legitimacy of the executed items, and confirmed that the execution method and execution results are consistent with those shown in the test plan.

#### 2.3.2 Evaluator Testing

#### 1) Evaluator Test Environment

Test configuration performed by the evaluator is showed in the Figure 2-2.





Test configuration performed by the evaluator differs from the configuration in the ST, however it is judged to be equivalence them for the following reason.

There is no function that accesses the TOE by the internal network in a state of effective security strengthen mode, thus, whether to connect with the network does not affect the test. Therefore, it can be judged that the configuration performed by the evaluator without network connection is equivalence TOE configuration identified in ST.

- 2) Outlining of Evaluator Testing Outlining of testing performed by the evaluator is as follow.
  - a. Test configuration Test configuration performed by the evaluator is showed in the Figure 2-2. The

evaluator test is performed for the TOE configured following bizhub PRO C5500 Installation Manual.

b. Testing Approach

For the testing, following approach was used.

- 1. The operation of security functions is confirmed by the operation of TSFI.
- 2. If testing of TSFI and subsystem interface cannot be performed by the operation through the external interface directly connected to bizhub PRO C5500 Series, it is performed with methods by indirectly stimulating the interface.
- 3. For the observation of test behavior, the direct confirmation is performed if it can be confirmed by the external TSFI, the behavior of test results is confirmed by using a measuring equipment if it can not be observed.
- 4. By comparing the expected behavior with the actual test results obtained at test execution, whether the test objects are achieved or not, are determined.
- c. Scope of Testing Performed

The evaluator performed 20 tests in total: 5 independent tests, 8 sampled developer tests and 7 intrusion tests. As the selection criteria of the test item, the followings are taken into account.

<Independent test>

- 1. Security function that enters security parameter.
- 2. Function used from Web interface found by the examination of guidance and functional specifications.
- 3. Security function about the effectiveness of HDD lock password.

<Sampled developer test>

- 1. Exceed 20% of the total developer test items.
- 2. Cover all security functions without specifying any security function.
- 3. Include function needed to operate prior to security strengthen mode on.

<Intrusion test>

- 1. Function that should be made invalid in security strengthen mode.
- 2. Measure to make security strengthen mode invalid.
- 3. Occurrence of unsecured condition by operating security strengthen mode on/off.
- 4. Occurrence of unsecured condition by pressing Reset button on the operation panel.
- 5. Occurrence of unsecured condition by intruding from network.
- 6. Start-up at unsecured condition by installing HDD that is not set lock password on MFP activated security strengthen mode.
- d. Result

All evaluator testing conducted is completes correctly and could confirm the behavior of the TOE. The evaluator also confirmed that all the test results are consistent with the behavior.

#### 2.4 Evaluation Result

The evaluator had the conclusion that the TOE satisfies all work units prescribed in CEM by submitting the Evaluation Technical Report.

# 3. Conduct of Certification

The following certification was conducted based on each materials submitted by evaluation facility during evaluation process.

- 1. Contents pointed out in the Observation Report shall be adequate.
- 2. Contents pointed out in the Observation Report shall properly be reflected.
- 3. Evidential materials submitted were sampled, its contents were examined, and related work units shall be evaluated as presented in the Evaluation Technical Report.

# 4. Conclusion

# 4.1 Certification Result

The Certification Body verified the Evaluation Technical Report, the Observation Report and the related evaluation evidential materials submitted and confirmed that all evaluator action elements required in CC Part 3 are conducted appropriately to the TOE. The Certification Body verified the TOE is satisfied the EAL3 assurance requirements prescribed in CC Part 3.

# 4.2 Recommendations

None

# 5. Glossary

The abbreviations used in this report are listed below.

CC:	Common Criteria for Information Technology Security Evaluation		
CE:	Customer Engineer		
CEM:	Common Methodology for Information Technology Security Evaluation		
CSRC:	CS Remote Care		
DRAM:	Dynamic Random Access Memory		
EAL:	Evaluation Assurance Level		
HDD:	Hard Disk Drive		
OS:	Operating System		
PD:	Protection Profile		
SOF:	Strength of Function		
ST:	Security Target		
TOE:	Target of Evaluation		
TSF:	TOE Security Functions		

The glossaries used in this report are listed below.

- Administrator: Administrator belongs to the organization that introduces bizhub PRO C5500 Series, and performs the operational management of bizhub PRO C5500 Series.
- Centronics interface: Interface to connect with maintenance computer when setting and creating the TOE.
- Document data: Digitized information data such as characters and figures.
- External network: Network (e.g. Internet and so on) except the internal network.
- HDD lock function: HDD has the password so that it cannot be removed and read in another equipment.

HDD lock password: HDD lock password is set in the HDD lock function.

Internal network: LAN in an organization that introduces bizhub PRO C5500 Series. Connected with the client PC and several servers such as Mail server and FTP server.

- Operation panel: Touch panel display and operation buttons integrated into main frame of bizhub PRO C5500 Series.
- Paper document: Paper-based document with information such as characters and figures.
- RS232C interface: Interface to connect with Public Telephone Line Network through modem.
- Service port interface: Interface to connect with maintenance computer when setting and creating the TOE.

Temporary storage: Input document data is stored temporarily into DRAM/HDD until it is printed as paper document.

# 6. Bibliography

- Multi functional printer (digital copier) bizhub PRO C5500 / ineo+5500 Series Security Target Version 2 (August 10, 2007) Konica Minolta Business Technologies, Inc.
- [2] IT Security Evaluation and Certification Scheme, May 2007, Information-technology Promotion Agency, Japan CCS-01
- [3] IT Security Certification Procedure, May 2007, Information-technology Promotion Agency, Japan CCM-02
- [4] Evaluation Facility Approval Procedure, May 2007, Information-technology Promotion Agency, Japan CCM-03
- [5] Common Criteria for Information Technology Security Evaluation Part 1: Introduction and general model Version 2.3 August 2005 CCMB-2005-08-001
- [6] Common Criteria for Information Technology Security Evaluation Part 2: Security functional requirements Version 2.3 August 2005 CCMB-2005-08-002
- [7] Common Criteria for Information Technology Security Evaluation Part 3: Security assurance requirements Version 2.3 August 2005 CCMB-2005-08-003
- [8] Common Criteria for Information Technology Security Evaluation Part 1: Introduction and general model Version 2.3 August 2005 CCMB-2005-08-001 (Translation Version 1.0 December 2005)
- [9] Common Criteria for Information Technology Security Evaluation Part 2: Security functional requirements Version 2.3 August 2005 CCMB-2005-08-002 (Translation Version 1.0 December 2005)
- [10] Common Criteria for Information Technology Security Evaluation Part 3: Security assurance requirements Version 2.3 August 2005 CCMB-2005-08-003 (Translation Version 1.0 December 2005)
- [11] ISO/IEC 15408-1:2005 Information Technology Security techniques -Evaluation criteria for IT security - Part 1: Introduction and general model
- [12] ISO/IEC 15408-2:2005 Information technology Security techniques -Evaluation criteria for IT security - Part 2: Security functional requirements
- [13] ISO/IEC 15408-3:2005 Information technology Security techniques -Evaluation criteria for IT security - Part 3: Security assurance requirements
- [14] Common Methodology for Information Technology Security Evaluation: Evaluation Methodology Version 2.3 August 2005 CCMB-2005-08-004
- [15] Common Methodology for Information Technology Security Evaluation: Evaluation Methodology Version 2.3 August 2005 CCMB-2005-08-004 (Translation Version 1.0 December 2005)
- [16] ISO/IEC 18045:2005 Information technology Security techniques Methodology for IT security evaluation

 [17] Multi functional printer (digital copier) bizhub PRO C5500 / ineo+5500 Series Evaluation Technical Report Version 1.0, September 11, 2007, Mizuho Information & Research Institute, Inc. Center for Evaluation of Information Security